



COOPERTIRES

ZEON RS3

Maximum Performance



UTQG 220 AA

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
275/40ZR18 99W	02020	(9.5) 9.0-11.0	51	1709	26.64	11.12	10.0	778	9.5	7.5	30	\$
275/35R20XL 102W	02021	(9.5) 9.0-11.0	50	1874	27.57	10.70	9.66	752	9.5	7.5	28	



Special Features

- The Cooper Zeon RS3 is a maximum performance, dry traction tire, developed in conjunction with ROUSH Performance, to provide ultimate grip, handling and excitement.
- The Cooper Zeon RS3 is perfectly balanced to blend the needs of a track day tire with the requirements of an everyday tire.

ZEON 2XS

Premium, Ultra-High Performance



UTQG V-Rated 280 A A Others 280 AA A

FREE 45-Day Road Test!

Y/W/V-Speed Design Directional Design

Special Features

- The Cooper Zeon 2XS is a premium, (ZR) ultra-high performance summer tire.
- The V-, W- and Y-rated 2XS is designed to provide excellent cornering ability and steering response along with optimum wet and dry traction and high-speed capability.
- As a summer tire, the Cooper Zeon 2XS is not intended to be driven in snow or ice.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL Y-RATED												
215/45R17 87Y	01200	(7.0) 7.0-8.0	51	1201	24.73	8.30	7.96	838	10	7.9	23	\$
225/45R17 91Y	01201	(7.5) 7.0-8.5	51	1356	24.88	9.03	8.19	833	10	7.9	23	
235/45R17 94Y	01202	(8.0) 7.5-9.0	51	1477	25.32	9.30	8.59	819	10	7.9	25	
245/40R17 91Y	01205	(8.5) 8.0-9.5	51	1356	24.69	9.84	9.07	840	10	7.9	24	
255/40R17 94Y	01206	(9.0) 8.5-10.0	51	1477	25.00	10.31	9.39	829	10	7.9	26	
225/40R18RE 92Y	01207	(8.0) 7.5-9.0	50	1389	25.07	9.03	8.44	827	10	7.9	23	
235/40R18 91Y	01208	(8.5) 8.0-9.5	51	1356	25.37	9.55	8.75	817	10	7.9	25	
245/40R18XL 97Y	01209	(8.5) 8.0-9.5	50	1609	25.69	9.85	9.07	807	10	7.9	26	
235/35ZR19XL 91Y	01211	(8.5) 8.0-9.5	50	1356	25.37	9.60	8.75	817	10	7.9	24	
255/35ZR19XL 96Y	01215	(9.0) 8.5-10.0	50	1565	25.97	10.06	9.31	798	10	7.9	26	
BLACKWALL W-RATED												
205/55ZR16 91W	+01224	(6.5) 5.5-7.5	51	1356	24.85	8.49	7.42	834	10	7.9	22	
215/55ZR16 93W	+01225	(7.0) 6.0-7.5	51	1433	25.24	8.90	7.67	821	10	7.9	23	
225/55ZR16 95W	+01226	(7.0) 6.0-8.0	51	1521	25.71	9.02	7.93	806	10	7.9	26	
205/50ZR17XL 93W	01257	(6.5) 5.5-7.5	50	1433	25.08	8.34	7.35	827	10	7.9	23	
205/45ZR17XL 88W	+01258	(7.0) 6.5-7.5	50	1235	24.21	8.12	7.39	856	10	7.9	21	
215/45ZR17 87W	+01233	(7.0) 7.0-8.0	51	1201	24.73	8.30	7.96	838	10	7.9	23	
245/45R17 95W	01236	(8.0) 7.5-9.0	51	1521	25.62	9.61	8.91	809	10	7.9	26	
255/45R17 98W	01237	(8.5) 8.0-9.5	51	1653	26.03	10.12	9.35	796	10	7.9	29	
205/40R17RE 84W	01238	(7.5) 7.0-8.0	50	1102	23.42	8.49	7.80	885	10	7.9	19	
275/40R17 98W	01243	(9.5) 9.0-11.0	51	1653	25.64	11.06	10.02	809	10	7.9	28	
285/40ZR17 100W	01259	(10.0) 9.5-11.0	51	1764	25.95	11.61	10.50	799	10	7.9	32	
225/45R18RE 95W	01250	(7.5) 7.0-8.5	50	1521	25.89	9.03	8.19	801	10	7.9	24	
245/45R18RE 100W	01251	(8.0) 7.5-9.0	50	1764	26.62	9.61	8.91	779	10	7.9	27	
275/40ZR18 99W	01261	(9.5) 9.0-11.0	51	1709	26.64	11.06	10.04	778	10	7.9	29	
215/35ZR18RE 84W	+01247	(7.5) 7.0-8.5	50	1102	23.86	8.56	7.95	869	10	7.9	21	
255/35ZR18XL 94W	01268	(9.0) 8.5-10.0	50	1477	24.96	10.06	9.31	831	10	7.9	25	
265/35ZR18 93W	+01248	(9.5) 9.0-10.5	51	1433	25.28	10.50	9.71	820	10	7.9	26	
255/40ZR19XL 100W	+01260	(9.0) 8.5-10.0	50	1764	27.01	10.31	9.39	768	10	7.9	28	
225/35ZR19XL 88W	+01265	(8.0) 7.5-9.0	50	1235	25.18	9.13	8.35	823	10	7.9	22	
275/30ZR19XL 96W	+01256	(9.5) 9.0-10.0	50	1565	25.52	10.84	10.18	813	10	7.9	27	
245/35ZR20XL 95W	01262	(8.5) 8.0-9.5	50	1521	26.76	9.68	8.91	775	10	7.9	26	
255/35ZR20XL 97W	01267	(9.0) 8.5-10.0	50	1609	26.97	10.06	9.31	769	10	7.9	27	
275/30ZR20XL 97W	+01255	(9.5) 9.0-10.0	50	1609	26.52	10.79	10.18	782	10	7.9	28	
285/30ZR20XL 99W	+01253	(10.0) 9.5-10.5	50	1709	26.74	11.26	10.66	775	10	7.9	29	

+ Discontinued - Limited Availability



ZEON SPORT A/S

Ultra-High Performance



UTQG
W-Rated 400 AA AA
V-Rated 400 A A
FREE 45-Day
Road Test!
W/V-Speed Design
Directional Design
M+S Rated

Special Features

- The Cooper Zeon Sport A/S is a premium W-speed rated, ultra-high performance all-season line designed for drivers who want year-round traction with commendable handling and high-speed capabilities.
- The Cooper Zeon Sport A/S is an excellent original equipment replacement for a wide range of vehicles including luxury touring cars, performance cars and crossovers (CUV).

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL W-RATED												
205/55ZR16 91W	25501	(6.5) 5.5-7.5	51	1356	24.87	8.49	7.38	834	10.0	7.9	22	\$
215/55ZR16 93W	25515	(7.0) 6.0-7.5	51	1433	25.27	8.90	7.63	821	10.0	7.9	24	
225/55ZR16 95W	25502	(7.0) 6.0-8.0	51	1521	25.79	9.02	7.89	804	10.0	7.9	27	
225/50ZR16 92W	25505	(7.0) 6.0-8.0	51	1389	24.91	9.12	8.32	832	10.0	7.9	27	
245/50ZR16 97W	25516	(7.5) 7.0-8.5	51	1609	25.66	9.86	8.96	808	10.0	7.9	29	
215/55ZR17 94W	25518	(7.0) 6.0-7.5	51	1477	26.29	8.90	7.63	789	10.0	7.9	25	
225/55ZR17 97W	25526	(7.0) 6.0-8.0	51	1609	26.74	9.11	7.95	775	10.5	8.3	29	
235/55ZR17 99W	25503	(7.5) 6.5-8.5	51	1709	27.13	9.67	8.52	764	10.0	7.9	30	
205/50ZR17XL 93W	25520	(6.5) 5.5-7.5	50	1433	25.11	8.34	7.37	826	10.0	7.9	23	
215/50ZR17 91W	25504	(7.0) 6.0-7.5	51	1356	25.50	8.82	7.77	813	10.0	7.9	25	
225/50ZR17 94W	25506	(7.0) 6.0-8.0	51	1477	25.90	9.12	8.34	801	10.0	7.9	29	
235/50ZR17 96W	25507	(7.5) 6.5-8.5	51	1565	26.29	9.55	8.60	789	10.0	7.9	30	
205/45ZR17 84W	25521	(7.0) 6.5-7.5	51	1102	24.24	8.12	7.40	855	10.0	7.9	21	
215/45ZR17XL 91W	25522	(7.0) 7.0-8.0	50	1356	24.75	8.30	7.97	838	10.0	7.9	23	
225/45ZR17XL 94W	25510	(7.5) 7.0-8.5	50	1477	24.91	9.03	8.20	832	10.0	7.9	24	
235/45ZR17 94W	25512	(8.0) 7.5-9.0	51	1477	25.35	9.30	8.60	818	10.0	7.9	25	
245/45ZR17 95W	25508	(8.0) 7.5-9.0	51	1521	25.65	9.61	8.92	808	10.0	7.9	26	
275/40ZR17 98W	25525	(9.5) 9.0-11.0	51	1653	25.66	11.06	10.04	808	10.0	7.9	31	
235/55ZR18 100W	25519	(7.5) 6.5-8.5	51	1764	28.13	9.67	8.52	737	10.0	7.9	31	
225/45ZR18 91W	25511	(7.5) 7.0-8.5	51	1356	25.91	9.03	8.20	800	10.0	7.9	25	
245/45ZR18 96W	25509	(8.0) 7.5-9.0	51	1565	26.65	9.81	8.92	778	10.0	7.9	28	
255/45ZR18XL 103W	25523	(8.5) 8.0-9.5	50	1929	27.03	9.80	9.36	767	10.0	7.9	29	
225/40ZR18XL 92W	25514	(8.0) 7.5-9.0	50	1389	25.07	9.19	8.44	827	10.0	7.9	24	
235/40ZR18XL 95W	25524	(8.5) 8.0-9.5	50	1521	25.36	9.33	8.00	817	10.0	7.9	25	
245/40ZR18XL 97W	25513	(8.5) 8.0-9.5	50	1609	25.72	9.84	9.08	806	10.0	7.9	26	
275/40ZR18 99W	25517	(9.5) 9.0-11.0	51	1709	26.66	11.06	10.04	778	10.0	7.9	30	
245/45ZR20 99W	25528	(8.0) 7.5-9.0	51	1709	28.61	9.59	8.86	725	10.5	8.3	30	
BLACKWALL V-RATED												
265/50R20XL 111V	25530	(8.5) 7.5-9.5	50	2403	30.42	10.73	9.44	682	10.5	8.3	37	



ZEON ZPT

Premium All-Season



UTQG 380 A A
FREE 45-Day
Road Test!
H-Speed Design
Directional Design
M+S Rated

Special Features

- The Cooper Zeon ZPT is a premium all-season, H-rated high performance tire targeted to the growing "tuner" market.
- The Cooper Zeon ZPT provides an ultra-high performance "look" at the more affordable H-rated price. It is especially suited for foreign and domestic compacts that have undergone tire/wheel "plus fitment" upgrades.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
195/50R15 82H	01852	(6.0) 5.5-7.0	44	1047	22.77	7.95	7.26	911	10.0	7.9	19	\$
205/50R15 86H	01853	(6.5) 5.5-7.5	44	1168	23.15	8.34	7.37	896	10.0	7.9	20	
205/50R16 87H	01857	(6.5) 5.5-7.5	44	1201	24.06	8.34	7.35	862	10.0	7.9	21	
225/50R16 92H	01859	(7.0) 6.0-8.0	44	1389	24.98	9.12	8.32	830	10.0	7.9	26	
245/50R16 97H	01861	(7.5) 7.0-8.5	44	1609	25.74	9.86	8.95	805	10.0	7.9	29	
205/45R16 83H	01860	(7.0) 6.5-7.5	44	1074	23.29	8.12	7.39	890	10.0	7.9	20	
215/45R17 87H	01863	(7.0) 7.0-8.0	44	1201	24.75	8.30	7.97	838	10.0	7.9	23	
225/45R17 91H	01864	(7.5) 7.0-8.5	44	1356	24.91	9.03	8.20	832	10.0	7.9	25	
235/45R17 94H	01865	(8.0) 7.5-9.0	44	1477	25.35	9.30	8.60	818	10.0	7.9	26	
245/45R17 95H	01866	(8.0) 7.5-9.0	44	1521	25.65	9.61	8.92	808	10.0	7.9	26	
205/40R17RE 84H	01868	(7.5) 7.0-8.0	50	1102	23.45	8.43	7.81	884	10.0	7.9	20	
215/40R17 83H	01869	(7.5) 7.0-8.5	44	1074	23.77	8.51	8.12	872	10.0	7.9	20	
215/45R18 89H	01878	(7.0) 7.0-8.0	44	1279	25.67	8.30	7.99	801	10.5	8.3	23	
225/40R18 88H	01874	(8.0) 7.5-9.0	44	1235	25.07	9.03	8.44	827	10.0	7.9	24	
235/40R18 91H	01875	(8.5) 8.0-9.5	44	1356	25.40	9.55	8.76	816	10.0	7.9	26	
245/40R18RE 97H	01876	(8.5) 8.0-9.5	50	1609	25.72	9.84	9.08	806	10.0	7.9	27	
215/35R18RE 84H	01877	(7.5) 7.0-8.5	50	1102	23.88	8.56	7.96	868	10.0	7.9	21	



CS4 TOURING (V, H & T)

Premium Luxury Touring



UTQG
V-Rated 520 A A
H-Rated 560 A A

60,000 Mile
Treadwear Protection
Limited Warranty

FREE 45-Day
Road Test!

V/H-Speed Rated
M+S Rated

Special Features

- The CS4 Touring is Cooper's premium luxury touring tire designed for drivers who want optimum ride comfort, sporty handling, all-season traction and attractive styling in a touring tire.

UTQG
14" 620 A
Others 780 A

80,000 Mile
Treadwear Protection
Limited Warranty

FREE 45-Day
Road Test!

T-Speed Rated
M+S Rated

Special Features

- The CS4 Touring is Cooper's premium luxury touring tire designed for drivers who want optimum ride comfort, sporty handling, all-season traction and attractive styling in a touring tire.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL V-RATED												
205/65R15 94V	22506	(6.0) 5.5-7.5	44	1477	25.41	8.37	6.46	817	11	8.7	22	\$
195/55R15 85V	22507	(6.0) 5.5-7.0	44	1135	23.43	7.92	6.52	887	11	8.7	21	
205/60R16 92V	22501	(6.0) 5.5-7.5	44	1389	25.65	8.40	6.55	809	11	8.7	24	
215/60R16 95V	22502	(6.5) 6.0-7.5	44	1521	26.10	8.95	7.13	795	11	8.7	24	
225/60R16 98V	22503	(6.5) 6.0-8.0	44	1653	26.56	9.15	7.16	782	11	8.7	27	
235/60R16 100V	22505	(7.0) 6.5-8.5	44	1764	27.10	9.52	7.55	766	11	8.7	27	
225/55R16 95V	22509	(7.0) 6.0-8.0	44	1521	25.77	9.36	7.59	806	11	8.7	27	
225/50R16 92V	22513	(7.0) 6.0-8.0	44	1389	24.89	9.15	7.69	835	11	8.7	23	
215/55R17 94V	22508	(7.0) 6.0-7.5	44	1477	26.31	8.90	7.32	789	11	8.7	27	
225/55R17 97V	22510	(7.0) 6.0-8.0	44	1609	26.79	9.31	7.40	774	11	8.7	27	
235/55R17 99V	22511	(7.5) 6.5-8.5	44	1709	27.15	9.75	8.01	765	11	8.7	29	
225/50R17 94V	22514	(7.0) 6.0-8.0	44	1477	25.89	9.66	7.69	802	11	8.7	23	
235/50R17 96V	22515	(7.5) 6.5-8.5	44	1565	26.30	9.91	8.09	790	11	8.7	23	
225/60R18 100V	22504	(6.5) 6.0-8.0	44	1764	28.62	9.01	7.19	725	11	8.7	28	
BLACKWALL H-RATED												
185/65R14 86H	11407	(5.5) 5.0-6.5	44	1168	23.45	7.64	5.75	885	11	8.7	19	
185/60R14 82H	11401	(5.5) 5.0-6.5	44	1047	22.73	7.48	5.90	914	11	8.7	18	
195/60R14 86H	11402	(6.0) 5.5-7.0	44	1168	23.20	7.97	6.29	894	11	8.7	20	
185/65R15 88H	11408	(5.5) 5.0-6.5	44	1235	24.45	7.83	5.75	849	11	8.7	20	
195/65R15 91H	11409	(6.0) 5.5-7.0	44	1356	24.97	8.05	6.13	831	11	8.7	25	
205/65R15 94H	11410	(6.0) 5.5-7.5	44	1477	25.41	8.34	6.46	817	11	8.7	22	
215/65R15 96H	11411	(6.5) 6.0-7.5	44	1565	26.04	8.69	6.76	780	11	8.7	24	
195/60R15 88H	11403	(6.0) 5.5-7.0	44	1235	24.20	8.03	6.29	858	11	8.7	21	
205/60R15 91H	11404	(6.0) 5.5-7.5	44	1356	24.65	8.29	6.55	841	11	8.7	20	
215/60R15 94H	11405	(6.5) 6.0-7.5	44	1477	25.10	8.82	6.93	828	11	8.7	23	
225/60R15 96H	11406	(6.5) 6.0-8.0	44	1565	25.56	8.97	7.16	813	11	8.7	26	
205/60R16 92H	11417	(6.0) 5.5-7.5	44	1389	25.65	8.40	6.55	809	11	8.7	23	
215/60R16 95H	11418	(6.5) 6.0-7.5	44	1521	26.10	8.95	7.13	795	11	8.7	25	
225/60R16 98H	11419	(6.5) 6.0-8.0	44	1653	26.56	9.15	7.16	782	11	8.7	26	
205/55R16 91H	11413	(6.5) 5.5-7.5	44	1356	24.86	8.59	7.17	836	11	8.7	23	
215/55R16 93H	11414	(7.0) 6.0-7.5	44	1433	25.27	8.87	7.17	822	11	8.7	23	
225/55R16 95H	11415	(7.0) 6.0-8.0	44	1521	25.77	9.29	7.79	806	11	8.7	27	
205/50R16 87H	11416	(6.5) 5.5-7.5	44	1201	24.09	8.32	7.05	862	11	8.7	23	
235/65R17 104H	11412	(7.0) 6.5-8.5	44	1984	29.09	10.06	7.36	715	11	8.7	30	
P255/65R18 109H	11420	(7.5) 7.0-9.0	44	2271	31.02	10.20	8.33	670	11	8.7	37	
P255/60R19 108H	11421	(7.5) 7.0-9.0	44	2205	31.02	10.20	8.53	671	11	8.7	36	
BLACKWALL T-RATED												
185/70R14 88T	11144	(5.5) 4.5-6.0	44	1235	24.15	7.44	5.67	860	12	9.5	19	
195/70R14 91T	11145	(6.0) 5.0-6.5	44	1356	24.80	8.05	6.03	840	12	9.5	21	
185/65R14 86T	11130	(5.5) 5.0-6.5	44	1168	23.51	7.64	5.82	885	12	9.5	20	
205/70R15 96T	11146	(6.0) 5.0-7.0	44	1565	26.28	8.23	6.27	791	12	9.5	22	
215/70R15 98T	11147	(6.5) 5.5-7.0	44	1653	26.85	8.70	6.63	775	12	9.5	24	
185/65R15 88T	11131	(5.5) 5.0-6.5	44	1235	24.51	7.83	5.82	849	12	9.5	21	
195/65R15 91T	11132	(6.0) 5.5-7.0	44	1356	25.03	8.05	6.18	831	12	9.5	24	
205/65R15 94T	11133	(6.0) 5.5-7.5	44	1477	25.47	8.34	6.43	817	12	9.5	22	
215/65R15 96T	11134	(6.5) 6.0-7.5	44	1565	26.04	8.69	6.76	780	12	9.5	24	
185/60R15 84T	11120	(5.5) 5.0-6.5	44	1102	23.73	7.44	5.96	876	12	9.5	20	
195/60R15 88T	11121	(6.0) 5.5-7.0	44	1235	24.26	8.03	6.34	858	12	9.5	22	
205/60R15 91T	11122	(6.0) 5.5-7.5	44	1356	24.71	8.29	6.59	841	12	9.5	23	
215/60R15 94T	11124	(6.5) 6.0-7.5	44	1477	25.16	8.82	6.97	828	12	9.5	25	
225/70R16 103T	11150	(6.5) 6.0-7.5	44	1929	28.49	9.60	6.89	730	12	9.5	27	
215/65R16 98T	11135	(6.5) 6.0-7.5	44	1653	27.10	8.70	6.80	770	12	9.5	26	
225/65R16 100T	11119	(6.5) 6.0-8.0	44	1764	27.50	9.10	7.07	757	12	9.5	28	
235/65R16 103T	11138	(7.0) 6.5-8.5	44	1929	27.93	9.56	7.39	744	12	9.5	27	
205/60R16 92T	11123	(6.0) 5.5-7.5	44	1389	25.71	8.40	6.59	809	12	9.5	25	
215/60R16 95T	11125	(6.5) 6.0-7.5	44	1521	26.16	8.95	6.97	795	12	9.5	25	
225/60R16 98T	11127	(6.5) 6.0-8.0	44	1653	26.62	9.15	7.19	782	12	9.5	28	
235/60R16 100T	11129	(7.0) 6.5-8.5	44	1764	27.16	9.52	7.57	766	12	9.5	28	
205/55R16 91T	11140	(6.5) 5.5-7.5	44	1356	24.92	8.59	7.00	836	12	9.5	24	
215/65R17 99T	11136	(6.5) 6.0-7.5	44	1709	27.98	8.93	6.80	743	12	9.5	28	
225/65R17 102T	11137	(6.5) 6.0-8.0	44	1874	28.40	8.98	7.00	732	12	9.5	29	
215/60R17 96T	11126	(6.5) 6.0-7.5	44	1565	27.11	9.03	6.97	767	12	9.5	27	
225/60R17 99T	11128	(6.5) 6.0-8.0	44	1709	27.56	9.14	7.19	754	12	9.5	29	
235/60R17 102T	11149	(7.0) 6.5-8.5	44	1873	28.16	10.07	7.64	736	12	9.5	33	
225/55R17 97T	11141	(7.0) 6.0-8.0	44	1609	26.85	9.31	7.61	774	12	9.5	28	
235/55R17 99T	11143	(7.5) 6.5-8.5	44	1709	27.21	9.75	8.01	765	12	9.5	30	
235/65R18 106T	11139	(7.0) 6.5-8.5	44	2094	29.93	10.06	7.38	695	12	9.5	32	
225/55R18 98T	11142	(7.0) 6.0-8.0	44	1653	27.85	9.11	7.60	747	12	9.5	29	
WHITWALL T-RATED												
225/60R16 98T	11148	(6.5) 6.0-8.0	44	1653	26.62	9.15	7.19	782	12	9.5	28	



LIFELINE GLS (V, H & T)

All-Season Touring



UTQG
V/H-Rated 440 A A
45,000 Mile
Treadwear Protection
Limited Warranty
V/H-Speed Rated
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE
BLACKWALL V-RATED											
205/60R16 92V	01655	(6.0) 5.5-7.5	44	1389	25.65	8.22	6.22	811	10.5 8.3	24	\$
215/60R16 95V	01656	(6.5) 6.0-7.5	44	1521	26.11	8.82	6.65	796	10.5 8.3	27	
215/55R17 94V	01657	(7.0) 6.0-7.5	44	1477	26.25	8.75	7.04	792	10.5 8.3	27	
215/50R17XL 95V	01658	(7.0) 6.0-7.5	50	1521	25.46	8.72	7.04	817	10.5 8.3	26	
225/50R17 94V	01659	(7.0) 6.0-8.0	44	1477	25.83	8.99	7.25	805	10.5 8.3	27	
BLACKWALL H-RATED											
195/65R15 91H	01683	(6.0) 5.5-7.0	44	1356	24.96	8.09	5.87	833	10.5 8.3	22	
205/65R15 94H	01684	(6.0) 5.5-7.5	44	1477	25.40	8.42	6.03	819	10.5 8.3	23	
195/60R15 88H	01680	(6.0) 5.5-7.0	44	1235	24.16	8.10	5.98	861	10.5 8.3	21	
205/60R15 91H	01681	(6.0) 5.5-7.5	44	1356	24.64	8.40	6.22	844	10.5 8.3	22	
225/60R16 98H	01682	(6.5) 6.0-8.0	44	1653	26.55	9.11	6.78	783	10.5 8.3	25	
205/55R16 91H	01685	(6.5) 5.5-7.5	44	1356	24.85	8.59	6.67	837	10.5 8.3	23	
215/55R16 93H	01686	(7.0) 6.0-7.5	44	1433	25.24	8.92	7.04	824	10.5 8.3	24	
225/55R16 95H	01654	(7.0) 6.0-8.0	44	1521	25.76	8.88	7.08	807	10.5 8.3	26	



UTQG
T-Rated 540 A B
60,000 Mile
Treadwear Protection
Limited Warranty
T-Speed Rated
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE
BLACKWALL											
175/70R13 82T	01611	(5.0) 4.5-6.0	44	1047	22.68	6.89	5.10	914	10.0 7.9	15	\$
175/70R14 84T	01612	(5.0) 4.5-6.0	44	1102	23.68	6.89	5.10	876	10.0 7.9	16	
185/70R14 88T	01613	(5.5) 4.5-6.0	44	1235	24.23	7.40	5.30	856	10.0 7.9	17	
195/70R14 91T	01614	(6.0) 5.0-6.5	44	1356	24.78	7.80	5.60	837	10.0 7.9	18	
175/65R14 82T	01603	(5.0) 5.0-6.0	44	1047	22.95	6.85	5.20	903	10.0 7.9	16	
185/65R14 86T	01604	(5.5) 5.0-6.5	44	1168	23.40	7.35	5.55	886	10.0 7.9	17	
185/65R15 88T	01605	(5.5) 5.0-6.5	44	1235	24.40	7.35	5.55	852	10.0 7.9	18	
195/65R15 91T	01606	(6.0) 5.5-7.0	44	1356	24.90	7.80	5.85	832	10.0 7.9	20	
205/65R15 94T	01607	(6.0) 5.5-7.5	44	1477	25.26	8.16	6.05	821	10.5 8.3	21	
215/65R15 96T	01608	(6.5) 6.0-7.5	44	1565	25.81	8.65	6.50	803	10.5 8.3	23	
185/60R15 84T	01690	(5.5) 5.0-6.5	44	1102	23.59	7.18	5.62	881	10.0 7.9	17	
215/60R15 94T	01691	(6.5) 6.0-7.5	44	1477	24.94	8.54	6.57	834	10.5 8.3	21	
215/65R16 98T	01609	(6.5) 6.0-7.5	44	1653	26.81	8.65	6.50	773	10.5 8.3	25	
235/65R16 103T	01693	(7.0) 6.5-8.5	44	1929	27.79	9.37	7.10	748	10.5 8.3	26	
215/60R16 95T	01601	(6.5) 6.0-7.5	44	1521	25.93	8.55	6.55	800	10.5 8.3	24	
225/60R16 98T	01602	(6.5) 6.0-8.0	44	1653	26.50	8.80	6.80	782	10.5 8.3	24	
205/55R16 91T	01610	(6.5) 5.5-7.5	44	1356	24.64	8.30	7.00	841	10.0 7.9	23	
225/60R17 99T	01692	(6.5) 6.0-8.0	44	1709	27.38	8.81	6.78	759	10.5 8.3	25	
WHITEWALL (.65")											
205/70R14 95T	01615	(6.0) 5.0-7.0	44	1521	25.28	8.11	5.80	822	10.5 8.3	20	
215/70R14 96T	01616	(6.5) 5.5-7.0	44	1565	25.78	8.58	6.10	804	10.5 8.3	22	
WHITEWALL (.75")											
205/70R15 96T	01617	(6.0) 5.0-7.0	44	1565	26.18	8.11	5.80	792	10.5 8.3	21	
215/70R15 98T	01618	(6.5) 5.5-7.0	44	1653	26.68	8.58	6.10	777	10.5 8.3	22	



Special Features

- The Lifeline GLS is Cooper's first line all-season touring tire designed for consumers looking for touring performance in a moderately-priced tire.
- It is ideally suited as a replacement set of tires on the vehicle.
- The Lifeline GLS fits a wide range of automobiles requiring a speed rated touring tire, both foreign and domestic.

GFE

Low Resistance



UTQG 540 A B
60,000 Mile
Treadwear Protection
Limited Warranty
FREE 45-Day
Road Test!
T-Speed Rated
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE
BLACKWALL											
175/65R14 82T	02403	(5.0) 5.0-6.0	44	1047	22.95	6.85	5.20	903	10.0 7.9	15	\$
185/65R14 86T	02404	(5.5) 5.0-6.5	44	1168	23.40	7.35	5.55	886	10.0 7.9	16	
185/65R15 88T	02405	(5.5) 5.0-6.5	44	1235	24.40	7.35	5.55	852	10.0 7.9	18	
195/65R15 91T	02406	(6.0) 5.5-7.0	44	1356	24.90	7.80	5.85	832	10.0 7.9	18	
205/65R15 94T	02407	(6.0) 5.5-7.5	44	1477	25.26	8.16	6.05	821	10.5 8.3	20	
215/65R16 98T	02408	(6.5) 6.0-7.5	44	1653	26.81	8.65	6.50	773	10.5 8.3	23	
215/60R16 95T	02401	(6.5) 6.0-7.5	44	1521	25.93	8.55	6.55	800	10.5 8.3	22	
225/60R16 98T	02402	(6.5) 6.0-8.0	44	1653	26.50	8.80	6.80	782	10.5 8.3	24	



Special Features

- The GFE is a low rolling resistant tire designed to provide your fuel efficient vehicle even better gas mileage.
- Size range is focused on small fuel efficient vehicles, but also includes larger, popular sizes.

COBRA RADIAL G/T

All-Season Performance



UTQG
50 Series 440 A C
Others 440 A B
50,000 Mile
Treadwear Protection
Limited Warranty
T/S-Speed Rated
M+S Rated

Special Features

- The Cobra Radial G/T is Cooper's all-season cosmetic performance tire that is targeted to buyers who prefer raised white-letter styling in an all-season tire.
- Available in a wide range of standard and low profile sizes, the Cobra Radial G/T is especially popular with drivers of older domestic "muscle cars" who still want to retain the characteristic "look" of their vehicles.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
P185/60R14 82T	39620	(5.5) 5.0-6.5	44	1047	22.80	7.15	6.00	912	10.5	8.3	17	\$
P205/50R15 84S	39618	(6.5) 5.5-7.5	35	1113	23.15	8.18	6.85	898	10.5	8.3	20	
P235/55R16 96T	39650	(7.5) 6.5-8.5	44	1565	26.15	9.65	7.95	793	10.5	8.3	24	
RAISED WHITE LETTER												
P215/70R14 96T	39633	(6.5) 5.5-7.0	44	1554	25.76	8.66	7.00	807	10.5	8.3	22	
P225/70R14 98T	39634	(6.5) 6.0-7.5	44	1675	26.27	8.92	7.20	792	10.5	8.3	24	
P215/60R14 91T	39606	(6.5) 6.0-7.5	44	1345	24.16	8.42	7.00	861	10.5	8.3	21	
P235/60R14 96T	39608	(7.0) 6.5-8.5	44	1565	25.06	9.11	7.60	830	10.5	8.3	24	
P215/70R15 97T	39635	(6.5) 5.5-7.0	44	1620	26.71	8.71	7.00	778	10.5	8.3	23	
P225/70R15 100T	39636	(6.5) 6.0-7.5	44	1753	27.37	9.10	7.20	760	10.5	8.3	25	
P235/70R15 102T	39637	(7.0) 6.0-8.0	44	1896	27.90	9.46	7.60	745	10.5	8.3	27	
P255/70R15 108T	39638	(7.5) 6.5-8.5	44	2183	28.95	10.40	8.20	718	10.5	8.3	31	
P215/65R15 95T	39616	(6.5) 6.0-7.5	44	1510	26.00	8.38	6.80	799	10.5	8.3	22	
P235/60R15 98T	39612	(7.0) 6.5-8.5	44	1642	26.11	9.15	7.60	796	10.5	8.3	25	
P245/60R15 100T	39613	(7.0) 7.0-8.5	44	1753	26.55	9.47	8.00	783	10.5	8.3	27	



TRENDSETTER SE

All-Season



UTQG 440 A B
40,000 Mile
Treadwear Protection
Limited Warranty
M+S Rated

Special Features

- The Trendsetter SE is Cooper's entry level all-season tire line targeted to the value-oriented consumer.
- The affordably priced Trendsetter SE is available in sizes that fit a wide range of older to later model automobiles – those that require the use of 75-series whitewall sizes.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
P175/70R13 82S	02907	(5.0) 4.5-6.0	35	1036	22.68	6.89	4.90	914	10.0	7.9	14	\$
P185/70R13 85S	02908	(5.5) 4.5-6.0	35	1135	23.23	7.40	5.10	893	10.0	7.9	15	
P175/70R14 84S	02926	(5.0) 4.5-6.0	35	1102	23.18	6.89	4.90	896	10.0	7.9	16	
P185/70R14 87S	02909	(5.5) 4.5-6.0	35	1201	24.23	7.40	5.10	856	10.0	7.9	17	
P195/70R14 90S	02910	(6.0) 5.0-6.5	35	1312	24.78	7.80	5.40	837	10.0	7.9	17	
P205/70R14 93S	02914	(6.0) 5.0-7.0	35	1433	25.28	8.11	5.60	822	10.0	7.9	18	
P175/65R14 81S	02918	(5.0) 5.0-6.0	35	1019	22.90	6.85	5.00	907	10.0	7.9	15	
P185/65R14 85S	02919	(5.5) 5.0-6.5	35	1124	23.35	7.35	5.35	889	10.0	7.9	16	
P205/70R15 95S	02911	(6.0) 5.0-7.0	35	1499	26.28	8.11	5.60	790	10.0	7.9	20	
P195/65R15 89S	02915	(6.0) 5.5-7.0	35	1279	24.90	7.80	5.70	839	10.0	7.9	18	
P205/65R15 92S	02916	(6.0) 5.5-7.5	35	1400	25.25	8.16	5.85	823	10.0	7.9	20	
P215/65R15 95S	02917	(6.5) 6.0-7.5	35	1510	25.88	8.65	6.38	807	10.0	7.9	22	
P215/60R16 94S	02935	(6.5) 6.0-7.5	35	1477	26.10	8.55	6.40	801	10.0	7.9	22	
P225/60R16 97S	02936	(6.5) 6.0-8.0	35	1609	26.52	8.80	6.60	788	10.0	7.9	23	
P205/55R16 89S	02932	(6.5) 5.5-7.5	35	1279	24.75	8.30	7.10	844	10.0	7.9	22	
WHITEWALL (.50")												
P155/80R13 STD	01301	(4.5) 4.0-5.0	35	959	22.75	6.10	3.90	911	9.5	7.5	13	
WHITEWALL (.65")												
P185/75R14 STD	01305	(5.0) 4.5-6.0	35	1290	24.80	7.20	4.60	836	10.0	7.9	17	
P195/75R14 STD	01306	(5.5) 5.0-6.5	35	1400	25.40	7.60	4.90	816	10.0	7.9	18	
P205/75R14 95	01307	(5.5) 5.0-7.0	35	1532	25.95	7.95	5.10	799	10.5	8.3	19	
P215/75R14 98S	01308	(6.0) 5.5-7.0	35	1664	26.55	8.40	5.40	781	10.5	8.3	20	
P215/70R14 96S	02904	(6.5) 5.5-7.0	35	1554	25.78	8.58	5.90	804	10.0	7.9	21	
WHITEWALL (.75")												
P205/75R15 97S	01310	(5.5) 5.0-7.0	35	1598	26.98	8.03	5.10	769	10.5	8.3	20	
P215/75R15 100S	01311	(6.0) 5.5-7.0	35	1742	27.55	8.40	5.40	753	10.5	8.3	22	
P225/75R15 102S	01312	(6.0) 6.0-7.5	35	1874	28.05	8.70	5.60	739	10.5	8.3	24	
P235/75R15 105S	01313	(6.5) 6.0-8.0	35	2028	28.65	9.10	5.90	724	11.0	8.7	25	
P205/70R15 95S	02905	(6.0) 5.0-7.0	35	1499	26.28	8.11	5.60	790	10.0	7.9	20	
P215/70R15 97S	02906	(6.5) 5.5-7.0	35	1620	26.78	8.58	5.90	774	10.0	7.9	22	
P225/70R15 100S	02912	(6.5) 6.0-7.5	35	1753	27.28	8.85	6.15	760	10.0	7.9	24	





SUV SIZES
UTQG 520 A B
S-Speed Rated
SUV &
Light Truck Sizes
M+S Rated

Special Features

- The Cooper Zeon LTZ was developed as a hybrid between a sport truck tire and an all-terrain tire.
- The aggressiveness of the Cooper Zeon LTZ can tame any road surface while providing excellent ride and handling capabilities.

SUV SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
285/60R18 XL 120S	01401	(8.5) 8.0-10.0	50	3086	31.48	11.43	9.46	660	14	11.1	49	\$
275/60R20 XL 119S	01403	(8.0) 7.5-9.5	50	2998	33.03	11.06	9.00	629	14	11.1	53	
275/55R20 XL 117S	01405	(8.5) 7.5-9.5	50	2833	31.93	11.22	9.30	652	14	11.1	52	
285/50R20 XL 116S	01409	(9.0) 8.0-10.0	50	2756	31.29	11.63	9.73	664	14	11.1	49	
305/50R20 XL 120S	01407	(9.5) 8.5-11.0	50	3086	32.18	12.14	10.37	646	14	11.1	53	
275/45R20 XL 110S	01411	(9.0) 8.5-10.5	50	2337	29.82	10.87	9.25	695	14	11.1	45	
305/40R22 XL 114S	01402	(11.0) 10.0-12.0	50	2601	31.64	12.71	11.01	657	14	11.1	47	
305/35R24 XL 112S	01404	(11.0) 10.0-12.0	50	2469	32.48	12.71	11.13	640	14	11.1	49	



LIGHT TRUCK SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL														
LT305/55R20 E 121/118S	01408	(9.5) 8.5-11.0	65	2910	3195	33.2	12.44	10.2	14.5	626	16	12.7	60	\$
OUTLINE WHITE LETTER														
LT265/75R16 E 123/120R	01430	(7.5) 7.0-8.0	80	3085	3415	31.60	10.63	7.8	12.2	659	16.5	13.1	47	
LT265/70R17 E 121/118R	01412	(8.0) 7.0-8.5	80	2910	3195	31.60	10.90	8.5	12.4	659	16.5	13.1	50	
LT275/70R18 E 125/122S	01420	(8.0) 7.0-8.5	80	3305	3640	33.15	11.11	9.0	12.8	627	16.0	12.7	56	



ZEON XST^A

Premium Sport Truck



UTQG 420 A A
FREE 45-Day Road Test!
V/H-Speed Rated
Asymmetrical Design
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
V-RATED												
235/65R17 104V	06020	(7.0) 6.5-8.5	44	1984	29.20	9.65	7.70	712	12	9.5	34	\$
255/55R18XL 109V	06061	(8.0) 7.0-9.0	50	2271	29.00	10.30	8.60	698	12	9.5	42	
275/45R22XL 112V	06097	(9.0) 8.5-10.0	50	2469	31.70	10.80	9.40	657	12	9.5	46	
285/45R22XL 114V	06076	(9.5) 9.0-11.0	50	2601	32.00	11.30	9.90	609	12	9.5	48	
305/45R22XL 118V	06088	(10.0) 9.5-11.0	50	2910	32.70	12.00	10.40	636	12	9.5	52	
305/40R22XL 114V	06089	(11.0) 10.0-12.0	50	2601	31.60	12.50	10.80	657	12	9.5	48	
245/35R22XL 97V	06078	(8.5) 8.0-9.5	50	1609	28.70	9.90	9.40	722	12	9.5	32	
265/35R22XL 102V	06077	(9.5) 9.0-10.0	50	1874	29.30	10.90	9.60	708	12	9.5	36	
255/30R22XL 95V	06063	(9.0) 8.5-9.5	50	1521	28.07	10.30	8.70	739	10	7.9	29	
295/35R24XL 110V	06096	(10.0) 10.0-12.0	50	2337	32.10	11.90	10.20	611	12	9.5	48	
305/35R24XL 112V	06094	(11.0) 10.0-12.0	50	2469	32.40	12.50	10.90	644	12	9.5	48	



Special Features

- The Cooper Zeon XST^A is a premium sport truck tire that utilizes an asymmetrical tread design to combine ride comfort with all-season traction.
- The Cooper Zeon XST^A size range provides coverage from plus applications to OE sizes.

ZEON XST

Premium All-Season Sport Truck



UTQG 420 A A
FREE 45-Day Road Test!
V-Speed Rated
Directional Design
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
285/60R18 116V	+04058	(8.5) 8.0-10.0	44	2756	31.33	11.73	9.66	644	12	9.5	45	\$
285/55R18 113V	+04066	(9.0) 8.0-10.0	44	2535	30.23	11.93	9.94	667	12	9.5	44	
285/50R20XL 116V	04071	(9.0) 8.0-10.0	50	2756	31.13	11.92	9.93	648	12	9.5	49	

+ Discontinued - Limited Availability



Special Features

- The Cooper Zeon XST is a premium all-season sport truck tire designed for drivers who want to upgrade their vehicles' looks and handling by replacing the original equipment wheels and tires.
- The Cooper Zeon XST size range provides "plus fits" for a wide range of pickups, SUVs and crossovers (CUV).

DISCOVERER H/T PLUS

Light Truck Touring



UTQG 460 A B
T-Speed Rated
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
265/60R18XL 114T	19931	(8.0) 7.5-9.5	50	2601	30.39	10.92	8.99	664	12	9.5	44	\$
285/60R18 116T	19930	(8.5) 8.0-10.0	44	2756	31.33	11.73	9.66	644	12	9.5	44	
255/55R18XL 109T	19934	(8.0) 7.0-9.0	50	2271	28.99	10.36	8.85	698	12	9.5	41	
275/60R20XL 119T	19932	(8.0) 7.5-9.5	50	2998	32.95	11.00	9.30	632	12	9.5	48	
275/55R20XL 117T	19935	(8.5) 7.5-9.5	50	2833	31.95	11.00	9.50	652	12	9.5	47	
285/50R20XL 116T	19937	(9.0) 8.0-10.0	50	2756	31.13	11.92	9.93	648	12	9.5	47	
305/50R20XL 120T	19936	(9.5) 8.5-11.0	50	3086	32.05	12.44	10.57	648	12	9.5	52	
275/45R20XL 110T	19939	(9.0) 8.5-10.0	50	2337	29.75	10.75	9.25	680	12	9.5	41	



Special Features

- The Discoverer H/T Plus is an extension of Cooper's Discoverer H/T SUV / light truck touring line that features sport truck and original equipment sizing in a non-directional, T-rated platform.
- It provides an excellent replacement for the 20-inch original equipment fitments on full-size pickups and SUVs as well as "plus fitments" for drivers seeking to upgrade the looks and handling of their vehicles.

DISCOVERER CTS

Premium Luxury Touring



UTQG 700 A B
SUV Sizes
70,000 Mile Treadwear Protection Limited Warranty
FREE 45-Day Road Test!
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL												
255/65R16 109T	04601	(7.5) 7.0-9.0	44	2271	29.11	10.16	8.23	714	12.0	9.5	34	\$
235/70R17XL 111T	04602	(7.0) 6.0-8.0	50	2403	30.01	9.47	7.43	692	13.0	10.3	36	
255/70R18 113T	04603	(7.5) 6.5-8.5	44	2535	32.13	10.25	8.08	647	13.5	10.7	40	
235/65R18 106T	04604	(7.0) 6.5-8.5	44	2094	30.09	9.37	7.58	690	12.0	9.5	34	
245/60R18 105T	04605	(7.0) 7.0-8.5	44	2039	29.68	9.55	8.00	700	12.0	9.5	32	
275/55R20XL 117T	04606	(8.5) 7.5-9.5	50	2833	31.94	10.95	9.17	650	12.0	9.5	41	
OUTLINE WHITE LETTER												
225/75R16 104T	04607	(6.0) 6.0-7.5	44	1984	29.13	8.64	6.40	713	13.0	10.3	29	
245/75R16 111T	04608	(7.0) 6.5-8.0	44	2403	30.31	9.60	7.07	685	13.5	10.7	34	
265/75R16 116T	04609	(7.5) 7.0-9.0	44	2756	31.56	10.50	7.77	658	13.5	10.7	39	
215/70R16 100T	04610	(6.5) 5.5-7.0	44	1764	27.73	8.70	6.89	749	13.0	10.3	28	
235/70R16 106T	04611	(7.0) 6.0-8.0	44	2094	28.83	9.41	7.43	721	13.0	10.3	3	
245/70R16 107T	04612	(7.0) 6.5-8.0	44	2149	29.43	9.75	7.66	706	13.0	10.3	34	
255/70R16 111T	04613	(7.5) 6.5-8.5	44	2403	30.03	10.24	7.97	692	13.5	10.7	36	
265/70R16 112T	04614	(8.0) 7.0-9.0	44	2469	30.40	10.80	8.29	683	13.5	10.7	38	
245/70R17 110T	04615	(7.0) 6.5-8.0	44	2337	30.48	9.68	7.75	682	13.0	10.3	36	
265/70R17 115T	04616	(8.0) 7.0-9.0	44	2679	31.43	10.68	8.30	661	13.5	10.7	39	
245/65R17 107T	04617	(7.0) 7.0-8.5	44	2149	29.55	9.53	7.75	703	12.0	9.5	34	
255/65R17 110T	04618	(7.5) 7.0-9.0	44	2337	30.11	10.09	8.23	690	12.0	9.5	37	
265/65R17 112T	04619	(8.0) 7.5-9.5	44	2469	30.58	10.60	8.56	679	12.0	9.5	38	
265/70R18 116T	04620	(8.0) 7.0-9.0	44	2756	32.63	10.72	8.43	637	13.5	10.7	42	



Special Features

- The Discoverer CTS is a premium luxury touring tire designed to deliver higher levels of wet traction, ride comfort and appearance.
- It is especially suited for "body on frame" sport utility vehicles (SUV), crossovers (CUV) and late model light duty trucks.

SRM II RADIAL LT

Premium All-Season Light Truck



Light Truck Sizes
***M+S Rated.**

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL														
LT215/85R16 E 115/112N	64311	(6.0) 5.5-7.0	80	2470	2680	30.26	8.21	5.93	9.9	683	14	11.1	39	\$
LT235/85R16 E 120/116N	64310	(6.5) 6.0-7.0	80	2778	3042	31.70	9.21	6.69	10.8	656	14	11.1	42	
LT225/75R16 E 115/112N	64316	(6.0) 6.0-7.0	80	2470	2680	29.18	8.60	6.60	10.2	711	14	11.1	39	
LT245/75R16 E 120/116N	64307	(7.0) 6.5-7.0	80	2778	3042	30.46	9.35	6.98	11.3	680	14	11.1	44	
LT265/75R16 E 123/120N	64312	(7.5) 7.0-8.0	80	3085	3415	31.65	10.50	8.00	12.2	663	14	11.1	47	
7.50R16LT D 112/107N	64301	(6.0) 5.5-7.0	65	2150	2470	31.80	8.35	6.13	10.0	652	14	11.1	38	
8.75R16.SLT D 111/106N	64303	(6.75) 6.0-6.75	65	2095	2405	29.42	8.70	6.75	9.9	704	14	11.1	39	
9.50R16.SLT D 117/112N	64304	(6.75) 6.75-8.25	65	2470	2835	30.43	9.15	7.15	10.7	681	14	11.1	40	

* Four-Rib Tread Design - Not M+S Rated



Special Features

- The SRM II Radial LT is Cooper's premium all-season light truck rib tire geared toward drivers of work and commercial vehicles.
- The solid shoulder design allows the SRM II to be especially suited in applications where tire rotations are infrequent or as a companion tire used on the steer axles of vehicles that use a traction tire on the drive axle.



UTQG
H-Rated 440 A A
Other 520 A B

SUV Sizes

H-Rated 40,000 Mile
Treadwear Protection
Limited Warranty

T/S-Rated 60,000 Mile
Treadwear Protection
Limited Warranty

M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Pass. Max. Load	L.T. Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL H-RATED													
235/65R17 104H	50501	(7.0) 6.5-8.5	44	1984	1804	29.06	9.45	7.65	715	12.0	9.5	31	\$
BLACKWALL S-RATED													
265/70R15 112S	50525	(8.0) 7.0-9.0	35	2469	2245	29.43	10.45	8.00	707	14.0	11.1	35	
225/75R16 104S	50539	(6.0) 6.0-7.5	35	1984	1804	29.15	8.65	6.40	711	13.0	10.3	30	
215/70R16 100S	50545	(6.5) 5.5-7.0	35	1764	1604	27.75	8.80	7.20	753	13.0	10.3	29	
245/70R16 107S	50546	(7.0) 6.5-8.0	35	2149	1954	29.40	9.90	7.70	705	13.0	10.3	33	
275/65R17 115S	50504	(8.0) 7.5-9.5	44	2679	2435	30.90	11.20	9.30	672	12.0	9.5	39	
OUTLINE WHITE LETTER T-RATED													
235/75R15XL 109T	50502	(6.5) 6.0-8.0	50	2271	2065	29.00	9.40	6.85	717	13.0	10.3	33	
235/70R16 106T	50503	(7.0) 6.0-7.5	44	2094	1904	28.85	9.40	7.40	719	12.5	9.9	33	
OUTLINE WHITE LETTER S-RATED													
P205/75R15 97S	50510	(5.5) 5.0-6.5	35	1598	1453	27.05	8.10	5.70	764	13.0	10.3	24	
P215/75R15 100S	50511	(6.0) 5.5-7.0	35	1742	1584	27.60	8.60	5.95	750	13.0	10.3	26	
P225/75R15 102S	50512	(6.0) 6.0-7.0	35	1874	1704	28.20	8.95	6.20	735	13.0	10.3	27	
P235/75R15 105S	50513	(6.5) 6.0-7.5	35	2028	1844	28.85	9.30	6.45	719	13.5	10.7	29	
P265/75R15 112S	50517	(7.5) 7.0-8.5	35	2469	2245	30.50	10.65	7.60	680	14.0	11.1	37	
P225/70R15 100S	50521	(6.5) 6.0-7.0	35	1753	1594	27.25	9.10	7.00	761	12.0	9.5	27	
P235/70R15 102S	50522	(7.0) 6.0-7.5	35	1896	1724	27.80	9.65	7.40	746	12.0	9.5	29	
255/70R15 108S	50530	(7.5) 6.5-8.0	44	2205	2005	29.00	10.40	8.00	715	12.0	9.5	33	
225/75R16 104S	50518	(6.0) 6.0-7.5	35	1984	1804	29.15	8.65	6.40	711	13.0	10.3	31	
P235/75R16 106S	50526	(6.5) 6.0-8.0	35	2094	1904	29.70	9.30	6.90	700	13.5	10.7	33	
P245/75R16 109S	50527	(7.0) 6.5-7.5	35	2271	2065	30.35	9.60	7.00	683	13.5	10.7	35	
P265/75R16 114S	50529	(7.5) 7.0-8.5	35	2601	2365	31.50	10.60	7.60	658	14.0	11.1	40	
P225/70R16 101S	50532	(6.5) 6.0-7.0	35	1819	1654	28.30	9.00	7.00	733	13.0	10.3	30	
245/70R16 107S	50534	(7.0) 6.5-8.0	35	2149	1954	29.40	9.90	7.70	705	13.0	10.3	34	
P255/70R16 109S	50535	(7.5) 6.5-8.0	35	2271	2065	29.95	10.30	8.00	692	13.5	10.7	36	
265/70R16 112S	50536	(8.0) 7.0-9.0	35	2469	2245	30.40	10.80	8.00	682	13.5	10.7	38	
275/70R16 114S	50528	(8.0) 7.0-9.0	44	2601	2365	31.20	11.00	8.92	669	13.0	10.3	40	
255/65R16 109S	50520	(7.5) 7.0-9.0	35	2271	2065	29.06	10.24	8.25	715	12.0	9.5	32	
245/70R17 110S	50531	(7.0) 6.5-8.0	44	2337	2125	30.43	9.96	8.16	662	13.0	10.3	35	
P265/70R17 113S	50538	(8.0) 7.0-9.0	35	2535	2305	31.40	10.65	8.30	660	13.5	10.7	40	
235/65R17 104S	50519	(7.0) 6.5-8.5	35	1984	1804	29.06	9.45	7.65	715	12.0	9.5	31	
245/65R17 107S	50537	(7.0) 7.0-8.5	35	2149	1954	29.45	9.62	7.85	685	12.0	9.5	33	
275/60R17 110S	50516	(8.0) 7.5-9.5	35	2337	2125	29.88	11.00	9.00	675	12.0	9.5	37	



LIGHT TRUCK SIZES

UTQG 700 A B
Light Truck Sizes
60,000 Mile
Treadwear Protection
Limited Warranty
M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Rev. Per Mile	Dual Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL														
LT215/85R16 E 115/112Q	50595	(6.0) 5.5-7.0	80	2470	2680	30.26	8.21	6.13	9.9	683	16	12.7	39	\$
LT235/85R16 E 120/116Q	50597	(6.5) 6.0-7.0	80	2778	3042	31.65	9.31	6.77	10.8	654	16	12.7	43	
LT225/75R16 E 115/112Q	50506	(6.0) 6.0-7.0	80	2470	2680	29.39	8.95	6.60	10.2	710	16	12.7	39	
LT245/75R16 E 120/116Q	50580	(7.0) 6.5-7.5	80	2778	3042	30.44	9.57	7.45	11.3	680	16	12.7	45	
LT245/70R17 E 119/116R	50589	(7.0) 6.5-8.0	80	2755	3000	30.60	9.56	7.45	11.3	679	16	12.7	46	
OUTLINE WHITE LETTER														
LT235/75R15 C 104/101Q	50551	(6.5) 6.0-7.0	50	1820	1985	28.83	9.00	6.61	10.8	719	16	12.7	34	
31X10.50R15LT C 109Q	50553	(8.5) 7.0-9.0	50	---	2270	30.27	11.06	8.50	---	684	16	12.7	40	
LT245/75R16 C 108/104Q	50564	(7.0) 6.5-7.5	50	2006	2205	30.44	9.57	7.45	11.3	680	16	12.7	42	
LT265/75R16 C 112/109Q	50567	(7.5) 7.0-8.5	50	2270	2470	31.60	10.33	7.65	12.2	654	16	12.7	44	
LT265/75R16 E 123/120Q	50569	(7.5) 7.0-8.0	80	3085	3415	31.61	10.40	7.60	12.2	654	16	12.7	48	
LT235/80R17 E 120/117R	50586	(6.5) 6.0-8.0	80	2835	3085	31.65	9.40	6.85	10.8	652	16	12.7	44	
LT245/75R17 E 121/118S	50554	(7.0) 6.5-8.0	80	2910	3195	31.60	9.59	7.65	11.3	657	16	12.7	46	
LT265/70R17 E 121/118R	50592	(8.0) 7.0-8.5	80	2910	3195	31.60	10.65	8.50	12.4	656	16	12.7	51	
LT275/65R18 E 123/120S	50555	(8.0) 7.5-9.5	80	3085	3415	32.09	10.90	8.80	12.8	645	18	14.3	54	



Special Features

- The Discoverer H/T is Cooper's premium touring SUV/light truck original equipment replacement tire.
- It is designed for drivers who want ride comfort, all-season traction and a premium warranty in a highway touring tire.
- The Discoverer H/T is suitable for a wide range of vehicles including SUVs, crossovers (CUV), light trucks and vans up to 1 ton.

DISCOVERER ATR

Premium All Terrain



UTQG 500 A B

SUV Sizes

**50,000 Mile
Treadwear Protection
Limited Warranty**

M+S Rated

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Pass. Max. Load	L.T. Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
OUTLINE													
WHITE LETTER													
225/70R14 99S	05564	(6.5) 6.0-7.0	44	1709	1554	26.45	8.90	7.05	795	12.5	9.9	26	\$
205/75R15 97S	05565	(5.5) 5.0-6.5	44	1609	1463	27.10	7.90	6.00	771	13.5	10.7	24	
215/75R15 100S	05566	(6.0) 5.5-7.0	44	1764	1604	27.60	8.40	6.40	757	13.5	10.7	26	
225/75R15 102S	05567	(6.0) 6.0-7.0	44	1874	1704	28.33	8.70	6.65	737	13.5	10.7	27	
235/75R15 105S	05568	(6.5) 6.0-7.5	44	2039	1854	28.90	9.23	7.00	723	14.0	11.1	30	
235/75R15XL 109S	05569	(6.5) 6.0-8.0	41	2271	2065	28.90	9.20	7.00	723	14.0	11.1	32	
265/75R15 112S	05558	(7.5) 7.0-8.5	44	2469	2245	30.69	10.50	8.00	681	14.5	11.5	37	
205/70R15 96T	05570	(6.0) 5.0-7.0	44	1565	1423	26.40	8.44	6.50	790	13.5	10.7	24	
225/70R15 100S	05571	(6.5) 6.0-7.5	44	1764	1604	27.45	9.00	7.05	763	12.5	9.9	27	
235/70R15 103S	05572	(7.0) 6.0-8.0	44	1929	1754	27.99	9.45	7.40	747	12.5	9.9	29	
255/70R15 108S	05559	(7.5) 6.5-8.5	44	2205	2005	29.05	10.50	8.05	715	14.0	11.1	34	
265/70R15 112S	05560	(8.0) 7.0-9.0	44	2469	2245	29.60	10.60	8.45	706	14.0	11.1	36	
225/75R16 104S	05573	(6.0) 6.0-7.5	44	1984	1804	29.25	8.71	6.65	712	13.5	10.7	30	
235/75R16 108S	05574	(6.5) 6.0-8.0	44	2205	2005	29.84	9.25	7.00	700	14.0	11.1	33	
245/75R16 111S	05575	(7.0) 6.5-7.5	44	2403	2185	30.52	9.65	7.40	685	14.0	11.1	34	
265/75R16 116S	05557	(7.5) 7.0-9.0	44	2756	2505	31.65	10.51	8.00	658	14.5	11.5	38	
215/70R16 100S	05576	(6.5) 5.5-7.0	44	1764	1604	27.87	8.70	6.85	750	13.5	10.7	29	
225/70R16 103S	05577	(6.5) 6.0-7.0	44	1929	1704	28.40	8.90	7.05	736	13.5	10.7	30	
235/70R16 106T	05578	(7.0) 6.0-8.0	44	2094	1904	28.99	9.46	7.43	720	13.5	10.7	33	
245/70R16 107S	05579	(7.0) 6.5-8.0	44	2149	1954	29.59	9.79	7.70	707	13.5	10.7	33	
255/70R16 111S	05561	(7.5) 6.5-8.5	44	2403	2185	30.10	10.24	8.00	695	14.0	11.1	36	
265/70R16 112T	05555	(8.0) 7.0-9.0	44	2469	2245	30.45	10.90	8.45	682	14.0	11.1	37	
235/70R17RE 111S	05554	(7.0) 6.0-8.0	41	2403	2185	29.99	9.46	7.43	697	14.0	11.1	35	
245/70R17 110S	05580	(7.0) 6.5-8.0	44	2337	2125	30.40	10.10	7.70	683	14.0	11.1	33	
255/70R17 112S	05581	(7.5) 6.5-8.5	44	2469	2246	31.10	10.24	8.00	671	14.0	11.1	38	
265/70R17 115S	05556	(8.0) 7.0-9.0	44	2679	2435	31.60	10.70	8.45	662	14.0	11.1	40	
235/65R17 104T	05562	(7.0) 6.5-8.5	44	1984	1804	29.10	9.54	7.65	716	13.5	10.7	33	
245/65R17 107S	05551	(7.0) 7.0-8.5	44	2149	1954	29.63	9.59	8.00	704	13.5	10.7	34	
255/65R17 110S	05552	(7.5) 7.0-9.0	44	2337	2125	30.05	9.88	8.45	695	13.5	10.7	36	
265/65R17 112T	05563	(8.0) 7.5-9.5	44	2470	2245	30.55	10.71	8.75	682	13.5	10.7	38	
235/60R17 102T	05582	(7.0) 6.5-8.5	44	1874	1705	28.40	9.54	7.65	734	14.0	11.1	33	
265/70R18 116S	05550	(8.0) 7.0-9.0	44	2756	2508	32.60	10.70	8.45	636	14.0	11.1	42	
265/65R18 114T	05584	(8.0) 7.5-9.5	44	2601	2367	31.50	10.52	8.86	658	13.5	10.7	41	
265/60R18 110T	05583	(8.0) 7.5-9.5	44	2337	2127	30.46	10.52	9.05	680	13.5	10.7	40	
275/55R20RE .117S	05553	(8.5) 7.5-9.5	50	2833	2575	31.92	11.18	9.40	654	13.0	10.3	45	



LIGHT TRUCK SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Wt.	PRICE	
BLACKWALL														
LT215/85R16 E 115/112R	05510	(6.0) 5.5-7.0	80	2470	2680	30.30	8.42	6.00	9.9	686	16.5	13.1	38	\$
LT235/85R16 E 120/116R	05502	(6.5) 6.0-7.0	80	2778	3042	31.78	9.36	6.70	10.8	660	16.5	13.1	42	
LT225/75R16 E 115/112R	05511	(6.0) 6.0-7.0	80	2470	2680	29.39	8.92	6.90	10.2	713	16.5	13.1	38	
LT245/75R16 E 120/116R	05501	(7.0) 6.5-7.5	80	2778	3042	30.37	9.26	7.40	11.3	684	16.5	13.1	42	
OUTLINE WHITE LETTER														
LT235/75R15 C 104/101R	05520	(6.5) 6.0-7.0	50	1820	1985	28.90	9.15	7.00	10.8	723	16.0	12.7	35	
30X9.50R15LT C 104R	05518	(7.5) 6.5-8.5	50	1985	2930	9.60	7.30	---	711	16.5	13.1	36		
31X10.50R15LT C 109R	05519	(8.5) 7.0-9.0	50	2270	3030	10.70	8.20	---	688	16.5	13.1	40		
LT235/85R16 E 120/116R	05521	(6.5) 6.0-7.0	80	2778	3042	31.78	9.36	6.70	10.8	660	16.5	13.1	43	
LT245/75R16 C 108/104R	05522	(7.0) 6.5-7.5	50	2006	2205	30.52	9.62	7.40	11.3	688	16.5	13.1	42	
LT245/75R16 E 120/116R	05523	(7.0) 6.5-7.5	80	2778	3042	30.37	9.26	7.40	11.3	684	16.5	13.1	43	
LT265/75R16 C 112/109R	05512	(7.5) 7.0-8.0	50	2270	2470	31.60	10.49	7.80	12.2	657	16.5	13.1	46	
LT265/75R16 E 123/120R	05506	(7.5) 7.0-8.0	80	3085	3415	31.60	10.63	7.80	12.2	657	16.5	13.1	48	
LT285/75R16 D 122/119R	05507	(8.0) 7.5-9.0	65	3000	3305	32.60	11.47	8.80	13.1	637	17.0	13.5	51	
LT315/75R16 D 121R	05513	(8.5) 8.0-10.0	50	3195	345	12.43	9.80	---	603	17.0	13.5	62		
LT255/70R16 C 108/104R	05514	(7.5) 6.5-8.0	50	1985	2205	30.08	10.38	8.10	12.3	692	16.5	13.1	43	
LT305/70R16 D 118/115R	05504	(9.0) 8.0-9.5	50	2680	2910	32.95	12.24	9.70	14.2	638	17.0	13.5	55	
LT235/80R17 E 120/117R	05508	(6.5) 6.0-7.5	80	2835	3085	31.78	9.23	6.70	10.8	654	16.5	13.1	43	
LT245/75R17 E 121/118S	05527	(7.0) 6.5-7.5	80	2910	3195	31.50	9.95	7.65	11.3	660	15.5	12.3	46	
LT265/70R17 C 112/109R	05515	(8.0) 7.0-8.5	50	2270	2470	31.58	10.61	8.50	12.4	662	16.5	13.1	48	
LT265/70R17 E 121/118R	05503	(8.0) 7.0-8.5	80	2910	3195	31.60	10.90	8.50	12.4	659	16.5	13.1	50	
LT275/70R17 C 114/110R	05505	(8.0) 7.0-8.5	50	2335	2600	32.20	11.10	8.65	12.8	647	16.5	13.1	49	
LT285/70R17 D 121/118R	05516	(8.5) 7.5-9.0	65	2910	3195	32.76	11.69	9.00	13.4	636	17.0	13.5	52	
LT315/70R17 D 121/118R	05509	(9.5) 8.5-10.0	50	2910	3195	34.35	12.65	9.90	14.8	606	17.0	13.5	61	
LT275/70R18 E 125/122S	05526	(8.0) 7.0-8.5	80	3305	3640	33.15	11.11	9.00	12.8	627	15.5	12.3	54	
LT275/65R18 C 113/110S	05524	(8.0) 7.5-9.5	50	2335	2535	32.10	11.05	8.80	12.8	647	16.0	12.7	50	
LT275/65R18 E 123/120S	05525	(8.0) 7.5-9.5	80	3085	3415	32.10	11.07	8.80	12.8	647	15.5	12.3	52	



Light Truck Sizes
50,000 Mile
Treadwear Protection
Limited Warranty
M+S Rated

Special Features

- The Discoverer ATR is Cooper's premium all-terrain SUV and light truck tire designed as an original equipment replacement for drivers who want increased traction without sacrificing ride comfort and quiet ride.
- The Discoverer ATR is suitable for a wide range of SUVs, crossovers (CUV), light trucks and vans up to 1 ton.



Light Truck Sizes M+S Rated

Special Features

- The Discoverer STT is Cooper's premium high void off-road light truck traction tire designed for drivers who want the utmost in off-road traction.
- It is offered in a wide range of commercial and large diameter flotation sizes and is designed for use on pickups, SUVs and off-road vehicles

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	Dual PSI	Single Max. Load	Max. Load	Overall Diameter	Section Width	Tread Width	Min. Space Chains	Dual w/o Mile	Rev. Per (32nds)	Tread Depth (mm)	Wt.	PRICE
BLACKWALL														
LT235/85R16 E 120/116Q	76104	(6.5) 6.0-7.0	80	2778	3042	31.80	9.70	7.30	10.8	652	18.0	14.3	49	\$
LT325/80R16 D 124/121Q	76113	(9.0) 8.5-11.0	50	3195	3525	36.78	13.10	10.80	14.8	565	20.5	16.3	85	
LT245/75R16 E 120/116Q	76103	(7.0) 6.5-7.0	80	2778	3042	30.70	9.45	7.60	11.3	675	18.0	14.3	47	
LT245/70R17 E 119/116Q	76102	(7.0) 6.5-8.0	80	2755	3000	30.70	9.60	7.60	11.3	676	18.0	14.3	47	
LT295/70R17 D 121/118Q	76139	(8.5) 7.5-10.0	65	2910	3195	33.45	11.80	9.40	13.7	623	20.5	16.3	63	
37X12.50R17LT D 124P	76101	(10.0) 8.5-11.0	50	-----	3525	36.90	13.10	10.00	-----	563	23.0	18.3	83	
LT275/70R18 E 125/122Q	76134	(8.0) 7.0-9.0	80	3305	3640	33.35	11.00	8.80	12.8	623	20.5	16.3	60	
LT325/65R18 E 127/124N	76132	(9.5) 9.0-12.0	65	3525	3860	34.75	13.50	10.80	14.8	598	23.0	18.3	78	
LT305/60R18 E 121/118Q	76136	(9.0) 8.5-11.0	65	2910	3195	32.64	12.09	9.80	14.2	636	20.5	16.3	65	
LT325/60R18 E 124/121N	76133	(9.0) 9.0-12.0	65	3195	3525	33.22	13.30	10.80	14.8	625	23.0	18.3	75	
33X12.50R20LT E 114Q	76128	(10.0) 8.5-11.0	65	-----	2600	32.66	12.49	9.80	-----	636	20.5	16.3	65	
35X12.50R20LT E 121Q	76130	(10.0) 8.5-11.0	65	-----	3195	34.66	12.50	9.80	-----	599	20.5	16.3	70	
35X13.50R20LT E 122N	76131	(11.0) 8.5-11.0	65	-----	3305	34.65	13.65	10.50	-----	599	21.0	16.7	77	
OUTLINE WHITE LETTER														
LT235/75R15 C 104/101Q	76125	(6.5) 6.0-7.0	50	1820	1985	29.09	9.45	7.00	10.8	718	18.0	14.3	39	
30X9.50R15LT C 104Q	76107	(7.5) 6.5-8.5	50	-----	1985	29.70	9.80	7.80	-----	708	20.0	15.9	43	
31X10.50R15LT C 109Q	76105	(8.5) 7.0-9.0	50	-----	2270	30.75	10.85	8.30	-----	681	20.0	15.9	47	
32X11.50R15LT C 113Q	76117	(9.0) 8.0-10.0	50	-----	2535	31.76	11.40	9.00	-----	657	20.0	15.9	49	
33X12.50R15LT C 108Q	76115	(10.0) 8.5-11.0	35	-----	2205	32.76	12.08	9.70	-----	637	20.5	16.3	56	
35X12.50R15LT C 113Q	76118	(10.0) 8.5-11.0	35	-----	2535	34.76	12.20	10.00	-----	600	20.5	16.3	67	
LT225/75R16 E 115/112Q	76124	(6.0) 6.0-7.0	80	2470	2680	29.53	8.70	6.70	10.2	703	17.5	13.9	43	
LT265/75R16 E 123/120Q	76111	(7.5) 7.0-8.0	80	3085	3415	32.00	10.10	8.25	12.2	655	18.0	14.3	53	
LT285/75R16 D 122/119Q	76112	(8.0) 7.5-9.0	65	3000	3305	33.10	11.30	8.85	13.7	646	18.0	14.3	56	
LT315/75R16 D 121Q	76126	(8.5) 8.0-10.0	50	-----	3195	34.47	11.92	9.80	-----	620	20.0	15.9	67	
LT255/70R16 C 108/104Q	76122	(7.5) 6.5-8.0	50	1985	2205	30.31	10.56	8.00	12.3	685	17.5	13.9	46	
LT265/70R16 C 110/107Q	76120	(8.0) 7.0-8.5	50	2150	2335	30.86	10.94	8.40	12.4	673	18.5	14.7	49	
LT305/70R16 D 118/115Q	76121	(9.0) 8.0-9.5	50	2680	2910	33.07	12.00	9.80	13.3	628	19.0	15.1	61	
LT265/70R17 E 121/118Q	76109	(8.0) 7.0-8.5	80	2910	3195	31.90	10.80	8.25	12.4	652	18.0	14.3	53	
LT285/70R17 D 121/118Q	76110	(8.5) 7.5-9.5	65	2910	3195	33.00	11.50	8.85	13.4	646	18.0	14.3	57	
33X12.50R17LT D 114Q	76116	(10.0) 8.5-11.0	50	-----	2600	32.76	12.54	9.80	-----	634	20.5	16.3	63	
35X12.50R17LT D 119Q	76119	(10.0) 8.5-11.0	50	-----	3000	34.76	12.67	9.80	-----	598	20.5	16.3	68	
LT275/65R18 C 113/110Q	76108	(8.0) 7.5-9.0	50	2335	2535	32.32	10.98	8.45	12.8	643	18.0	14.3	56	
35X12.50R18LT E 123Q	76127	(10.0) 8.5-11.0	65	-----	3415	34.76	12.50	10.00	-----	598	20.0	15.9	68	



COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222



BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-283-0416 • Fax 503-240-3342
Toll Free: 1-866-977-8473

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78218
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

PHOENIX

601 South 65th Avenue, Suite 6
Phoenix, AZ 85043
Local 623-474-4660 • Fax 623-474-4661
Toll Free: 1-855-825-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO/MICHIGAN

14801 TR 212
Findlay, OH 45840
Local 419-425-6508 • Fax 419-425-6514
Toll Free: 1-877-309-1972



**Studdable
M+S Rated**

Special Features

- The Discoverer S/T is Cooper's premium all-purpose SUV/light truck traction tire that is a hybrid of three designs – all-terrain, high void and commercial traction.
- The Discoverer S/T fits a wide range of SUVs and light trucks up to 1 ton, but it is especially suitable for high-powered, high-torque light trucks where optimum wear and traction are required.

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.


SUV SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Stud Size	Wt.	PRICE	
BLACKWALL														
275/60R20RE 119S	73420	(8.5) 8.0-9.5	50	2998	2725	33.05	12.69	9.10	629	15.0	11.9	13	51	\$
OUTLINE WHITE LETTER S-RATED														
235/75R15 105S	73406	(6.5) 6.0-8.0	35	2039	1854	29.00	9.40	7.40	717	15.0	11.9	13	32	
235/75R15RE 109S	73405	(6.5) 6.0-7.5	41	2271	2065	29.00	9.40	7.40	717	15.0	11.9	13	3	
245/75R16 111S	73409	(7.0) 6.5-8.0	35	2403	2185	30.40	9.65	7.60	683	15.0	11.9	13	35	
265/75R16 116S	73410	(7.5) 7.0-9.0	35	2756	2505	31.55	10.55	8.30	658	15.0	11.9	13	40	
235/70R16 106S	73412	(7.0) 6.0-8.0	35	2094	1904	28.90	9.50	7.40	719	15.0	11.9	13	33	
255/70R16 111S	73413	(7.5) 6.5-8.5	35	2403	2185	30.10	10.15	7.80	691	15.0	11.9	13	36	
265/70R16 112S	73414	(8.0) 7.0-9.0	44	2469	2245	30.63	10.71	8.40	684	15.0	11.9	13	38	
245/70R17 110S	73416	(7.0) 6.5-8.0	44	2337	2125	30.43	9.96	7.60	683	15.0	11.9	13	36	



LIGHT TRUCK SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Stud Size	Wt.	PRICE	
BLACKWALL															
LT215/85R16 E 115/112N	73430	(6.0) 5.5-7.0	80	2470	2680	30.48	8.41	6.10	9.9	684	18	14.3	15	41	\$
LT235/85R16 E 120/116N	73432	(6.5) 6.0-7.0	80	2778	3042	31.90	9.29	7.00	10.8	654	18	14.3	15	45	
LT225/75R16 E 115/112N	73433	(6.0) 6.0-7.0	80	2470	2680	29.35	8.54	6.60	10.2	710	18	14.3	15	40	
LT245/75R16 E 120/116N	73434	(7.0) 6.5-7.5	80	2778	3042	30.53	9.76	7.45	11.3	680	18	14.3	15	46	
OUTLINE WHITE LETTER															
LT235/75R15 C 104/101Q	73422	(6.5) 6.0-7.0	50	1820	1985	28.62	9.14	7.20	10.8	715	18	14.3	15	37	
30X9.50R15LT C 104Q	73446	(7.5) 6.5-8.5	50	---	1985	29.35	9.63	7.40	---	708	18	14.3	15	37	
31X10.50R15LT C 109Q	73447	(8.5) 7.0-9.0	50	---	2270	30.47	10.71	8.20	---	687	18	14.3	15	41	
33X12.50R15LT C 108Q	73448	(10.0) 8.5-11.0	35	---	2205	32.63	12.36	9.80	---	640	20	15.9	17	53	
35X12.50R15LT C 113Q	73449	(10.0) 8.5-11.0	35	---	2535	34.88	12.87	10.20	---	613	20	15.9	17	64	
LT255/85R16 D 119/116N	73440	(7.0) 6.5-8.0	65	2755	3000	33.21	10.04	7.20	11.7	628	18	14.3	15	48	
LT265/75R16 C 112/109N	73443	(7.5) 7.0-8.0	50	2270	2470	31.64	10.50	8.10	12.2	654	18	14.3	15	47	
LT265/75R16 E 123/120N	73444	(7.5) 7.0-8.0	80	3085	3415	31.76	10.59	8.10	12.2	654	18	14.3	15	52	
LT285/75R16 D 122/119N	73445	(8.0) 7.5-9.0	65	3000	3305	32.80	11.30	9.20	13.3	628	20	15.9	17	56	
LT315/75R16 D 121N	73455	(8.5) 8.0-10.0	50	---	3195	34.60	12.87	10.00	---	615	20	15.9	17	65	
LT305/70R16 D 118/115N	73461	(9.0) 8.0-9.5	50	2680	2910	32.81	12.29	10.00	13.3	626	18	14.3	15	56	
LT235/80R17 E 120/117Q	73481	(6.5) 6.0-8.0	80	2835	3085	31.85	9.40	7.00	10.8	652	18	14.3	15	47	
LT245/75R17 E 121/118Q	73468	(7.0) 6.5-8.0	80	2910	3195	31.75	9.59	7.67	11.3	654	18	14.3	15	49	
LT245/70R17 E 119/116Q	73471	(7.0) 6.5-8.0	80	2755	3000	30.45	10.07	7.45	11.3	679	18	14.3	15	46	
LT265/70R17 C 112/109Q	73473	(8.0) 7.0-8.5	50	2270	2470	31.65	10.71	8.40	12.4	656	18	14.3	15	47	
LT265/70R17 E 121/118Q	73475	(8.0) 7.0-8.5	80	2910	3195	31.65	11.03	8.40	12.4	656	18	14.3	15	52	
LT275/70R17 C 114/110Q	73478	(8.0) 7.0-9.0	50	2335	2600	32.20	11.32	8.80	12.8	645	18	14.3	15	50	
LT285/70R17 D 121/118Q	73480	(8.5) 7.5-9.5	65	2910	3195	32.80	11.35	9.10	13.4	634	18	14.3	15	55	
33X12.50R17LT D 114Q	73450	(10.0) 8.5-11.0	50	---	2600	32.63	12.36	9.80	---	640	20	15.9	17	58	
35X12.50R17LT D 119Q	73451	(10.0) 8.5-11.0	50	---	3000	34.88	12.87	10.20	---	613	20	15.9	17	66	
LT275/70R18 E 125/122Q	73484	(8.0) 7.0-9.0	80	3305	3640	33.30	10.95	8.80	12.8	624	18	14.3	15	56	
LT275/65R18 E 123/120Q	73424	(8.0) 7.5-9.5	80	3085	3415	32.30	10.90	8.80	12.8	643	18	14.3	15	55	



**Studdable
M+S Rated**

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Stud Size	Wt.	PRICE	
BLACKWALL															
LT235/85R16 E 120/116N	52032	(6.5) 6.0-7.0	80	2778	3042	31.90	9.29	7.00	10.8	654	18	14.3	15	45	\$
LT245/75R16 E 120/116N	52034	(7.0) 6.5-7.5	80	2778	3042	30.53	9.76	7.45	11.3	680	18	14.3	15	45	
OUTLINE WHITE LETTER															
LT265/75R16 E 123/120N	52044	(7.5) 7.0-8.0	80	3085	3415	31.76	10.59	8.10	12.2	654	18	14.3	15	50	
NEW LT265/70R17 E 121/118Q	52043	(8.0) 7.0-8.5	80	2910	3195	31.65	11.03	8.40	12.4	656	18	14.3	15	51	

Special Features

- The Discoverer S/T-C is Cooper's premium all-purpose light truck traction tire that utilizes a special cut and chip resistance tread compound.
- A hybrid of three designs – all-terrain, high void and commercial traction – the Discoverer S/T-C is especially suited for off-road applications where cutting and chipping of the tread that leads to reduced mileage is of primary concern.





**SUV & Light Truck Sizes
Studdable
M+S Rated**

Special Features

- The Discoverer M+S is Cooper's premium studdable winter SUV/light truck tire designed for drivers looking for excellent traction on snow and ice.
- The Discoverer M+S line fits a wide range of SUVs and light trucks, foreign and domestic.

For optimum safe and satisfactory performance, winter tires should be used in sets of four.

Only new tires should be fitted with studs. On vehicles with front wheel drive, adverse handling characteristics can be introduced by mounting studded snow tires on front wheels only. Studded tires can be sold for use only where use is not prohibited by law.

SUV SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Pass. Max. Load	L. T. Max. Load	Overall Diameter	Section Width	Tread Width	Rev. Per Mile	Tread Depth (32nds mm)	Stud Size	Wt.	PRICE	
BLACKWALL														
225/70R14 99S	50471	(6.5) 6.0-7.5	35	1709	1554	26.25	9.10	7.00	790	15	11.9	13	27	\$
235/75R15 105S	50444	(6.5) 6.0-8.0	35	2039	1854	29.00	9.60	7.20	717	15	11.9	13	32	
235/75R15 RE 109S	50445	(6.5) 6.0-7.5	41	2271	2065	29.00	9.40	7.20	717	15	11.9	13	33	
265/75R15 112S	50447	(7.5) 7.0-9.0	35	2469	2245	30.60	10.65	8.10	679	15	11.9	13	37	
235/70R15 103S	50475	(7.0) 6.0-7.5	35	1929	1754	28.00	9.65	7.40	746	15	11.9	13	30	
265/70R15 112S	50478	(8.0) 7.0-9.0	35	2469	2245	29.43	10.45	8.00	707	15	11.9	13	35	
225/75R16 104S	50448	(6.0) 6.0-7.5	35	1984	1804	29.18	8.65	6.80	713	15	11.9	13	31	
235/75R16 108S	50449	(6.5) 6.0-8.0	35	2205	2005	29.85	9.30	7.00	697	15	11.9	13	34	
245/75R16 111S	50450	(7.0) 6.5-8.0	35	2403	2185	30.40	9.60	7.40	683	15	11.9	13	35	
265/75R16 116S	50451	(7.5) 7.0-9.0	35	2756	2505	31.60	10.60	8.10	658	15	11.9	13	39	
215/70R16 100S	50480	(6.5) 5.5-7.0	35	1764	1604	27.75	8.80	7.20	753	15	11.9	13	30	
225/70R16 103S	50481	(6.5) 6.0-7.5	35	1929	1704	28.30	9.00	7.00	733	15	11.9	13	30	
235/70R16 106S	50482	(7.0) 6.0-7.5	35	2094	1904	28.85	9.40	7.40	719	15	11.9	13	32	
245/70R16 107S	50483	(7.0) 6.5-8.0	35	2149	1954	29.50	9.85	7.70	705	15	11.9	13	34	
255/70R16 111S	50484	(7.5) 6.5-8.0	35	2403	2185	29.90	10.30	8.00	693	15	11.9	13	35	
265/70R16 112S	50485	(8.0) 7.0-9.0	35	2469	2245	30.40	10.80	8.00	682	15	11.9	13	39	
245/70R17 110S	50486	(7.0) 6.5-8.0	44	2337	2125	30.50	9.85	7.70	681	14	11.1	13	35	
265/70R17 115S	50488	(8.0) 7.0-9.0	35	2679	2435	31.40	10.65	8.30	660	15	11.9	13	40	
255/60R17 106S	50495	(7.5) 7.0-9.0	44	2094	1904	29.06	10.29	8.80	715	14	11.1	13	36	
255/65R18 RE 109S	50498	(8.0) 7.0-9.0	50	2271	2065	29.12	10.36	8.90	713	14	11.1	13	41	
275/60R20 RE 97S	50499	(8.5) 8.0-9.5	50	2998	2725	33.08	12.69	9.22	628	14	11.1	13	50	
OUTLINE WHITE LETTER														
255/65R16 109S	50490	(7.5) 7.0-9.0	35	2271	2065	29.18	10.24	8.25	718	14	11.1	13	36	
235/65R17 104S	50493	(7.0) 6.5-8.5	35	1984	1804	29.11	9.45	7.65	716	14	11.1	13	33	
245/65R17 107S	50494	(7.0) 7.0-8.5	35	2149	1954	29.52	9.82	9.27	708	14	11.1	13	36	
275/60R17 110S	50496	(8.0) 7.5-9.5	35	2337	2125	30.10	11.20	9.02	699	14	11.1	13	39	



LIGHT TRUCK SIZES

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Tread Width	Min. Dual Space w/o Chains	Rev. Per Mile	Tread Depth (32nds mm)	Stud Size	Wt.	PRICE	
BLACKWALL															
LT235/75R15 C 104/101Q	50410	(6.5) 6.0-7.0	50	1820	1985	28.82	9.00	7.20	10.8	715	17	13.5	15	34	\$
31X10.50R15LT C 109Q	50414	(8.5) 7.0-9.0	50	---	2270	30.25	10.50	8.20	---	685	19	15.1	15	40	
LT215/85R16 E 115/112Q	50422	(6.0) 5.5-7.0	80	2470	2680	30.28	9.10	5.90	9.9	684	17	13.5	15	38	
LT235/85R16 E 120/116Q	50424	(6.5) 6.0-7.0	80	2778	3042	31.78	9.31	6.94	10.8	654	17	13.5	15	43	
LT225/75R16 E 115/112Q	50431	(6.0) 6.0-7.0	80	2470	2680	29.30	8.95	6.70	10.2	710	17	13.5	15	39	
LT245/75R16 C 108/104Q	50434	(7.0) 6.5-7.5	50	2006	2205	30.44	9.57	7.45	11.3	680	17	13.5	15	41	
LT245/75R16 E 120/116Q	50432	(7.0) 6.5-7.5	80	2778	3042	30.44	9.57	7.45	11.3	680	18	14.3	15	45	
LT265/75R16 C 112/109Q	50435	(7.5) 7.0-8.0	50	2270	2470	31.54	10.33	8.14	12.2	654	17	13.5	15	44	
LT265/75R16 E 123/120Q	50437	(7.5) 7.0-8.5	80	3085	3415	31.54	10.50	8.14	12.2	654	17	13.5	15	49	
LT235/80R17 E 120/117Q	50419	(6.5) 6.0-8.0	80	2835	3085	31.85	9.40	7.00	10.8	652	17	13.5	15	45	
LT245/70R17 E 119/116Q	50416	(7.0) 6.5-8.0	80	2755	3000	30.45	10.07	7.45	11.3	679	17	13.5	15	44	
LT265/70R17 E 121/118Q	50417	(8.0) 7.0-8.5	80	2910	3195	31.65	11.03	8.40	12.4	656	17	13.5	15	50	
LT275/70R17 C 114/110Q	50418	(8.0) 7.0-9.0	50	2335	2600	32.20	11.32	8.80	12.8	645	17	13.5	15	48	
LT275/70R18 E 125/122R	50411	(8.0) 7.0-9.0	80	3305	3640	33.15	10.95	9.00	12.8	626	17	13.5	15	55	

