



Hankook

PERFORMANCE TIRES

HANKOOK VENTUS V12 es K110 High Performance Radial



UTQG 340 A A

- The Hankook K106 is a high performance radial designed for serious driving excitement.
- The radical V-shaped tread pattern efficiently disperse water without compromising speed or handling.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
245/40R17 95Y	1008163	8.5	7.0-8.5	50	1521	24.7	9.8	8.4	10	840	\$
255/40R17 98Y	1008213	9	8.5-10.0	50	1653	25	10.2	8.7	10	830	
205/45R17 88W	1008164	7	6.5-7.5	50	1235	24.3	8.1	7	10	857	
215/45R17 91W	1008656	7	7.0-8.0	50	1356	24.6	8.4	10	10	843	
225/45R17 94Y	1008404	7.5	7.0-8.5	50	1477	25	8.9	7.7	10	832	
235/45R17 97Y	1008165	8	7.5-9.0	50	1609	25.4	9.3	8.1	10	819	
245/45R17 99Y	1008215	8	7.5-9.0	50	1709	25.7	9.6	8.4	10	809	
205/50R17 93Y	1008166	6.5	5.5-7.5	50	1433	25.1	8.4	6.8	10	827	
215/50R17 95W	1008172	7	6.0-7.5	50	1521	25.5	8.9	7.1	10	814	
285/30R18 97Y	1009504	10	9.5-10.5	50	1609	24.8	11.4	10.1	10	839	
295/30R18 98Y	1009505	10.5	10.0-11.0	50	1653	25	11.9	10.5	10	831	
245/35R18 92Y	1008209	8.5	8.0-9.5	50	1389	24.8	8.8	8.4	10	839	
255/35R18 94Y	1008210	9	8.5-10.0	50	1477	25	10.2	8.7	10	831	
265/35R18 97Y	1008211	9.5	9.0-10.5	50	1609	25.3	10.7	9.1	10	821	
275/35R18 99Y	1008212	9.5	9.0-11.0	50	1709	25.6	10.9	9.4	10	813	
285/35R18 101Y	1008657	10	9.5-11.0	50	1819	25.9	11.4	9.8	10	803	
215/40R18 89Y	1008214	7.5	7.0-8.5	50	1279	24.8	8.6	7.4	10	839	
225/40R18 92Y	1008405	8	7.5-9.0	50	1389	25.1	9.1	7.7	10	828	
235/40R18 95Y	1008167	8.5	8.0-9.5	50	1521	25.4	9.5	8.1	10	818	
245/40R18 97Y	1008168	8.5	8.0-9.5	50	1609	25.7	9.8	8.4	10	808	
255/40R18 99Y	1008658	9	8.5-10.0	50	1709	26	10.2	8.7	10	798	
265/40R18 101Y	1009506	9.5	9.0-10.5	50	1819	26.3	10.7	9.1	10	789	
275/40R18 103Y	1008659	9.5	9.0-11.0	50	1929	26.7	10.9	9.4	10	779	
215/45R18 93Y	1008976	7	7.0-8.0	50	1433	25.6	8.4	7.4	10	811	
225/45R18 95Y	1008977	7.5	7.0-8.5	50	1521	25.9	8.9	7.7	10	801	
245/45R18 100Y	1008216	8	7.5-9.0	50	1764	26.7	9.6	8.4	10	779	
255/45R18 103Y	1009507	8.5	8.0-9.5	50	1929	27.1	10	8.7	10	768	
265/30R19 93Y	1008207	9.5	9.0-10.0	50	1433	25.3	10.7	9.4	10	821	
275/30R19 96Y	1008208	9.5	9.0-10.0	50	1565	25.6	10.9	9.7	10	813	
285/30R19 98Y	1008978	10	9.5-10.5	50	1653	25.8	11.4	10.1	10	806	
295/30R19 100Y	1009508	10.5	10.0-11.0	50	1764	26	11.9	10.5	10	798	
305/30R19 102Y	1009509	11	10.5-11.5	50	1874	26.3	12.3	10.8	10	791	
225/35R19 88Y	1009510	8	7.5-9.0	50	1235	25.2	9.1	7.7	10	823	
215/35ZR19XL 85Y	1009775	8		50	1135	24.9	8.50		10		
235/35R19 91Y	1008169	8.5	8.0-9.5	50	1356	25.5	9.5	8.1	10	816	
245/35R19 93Y	1008170	8.5	8.0-9.5	50	1433	25.8	9.8	8.4	10	806	
255/35R19 96Y	1008979	9	8.5-10.0	50	1565	26	10.2	8.7	10	798	
275/35R19 100Y	1008980	9.5	9.0-10.0	50	1764	26.6	10.9	9.4	10	782	
285/35R19 99Y	1008981	10	9.5-11.0	51	1709	26.9	11.4	9.8	10	773	
225/40R19 93Y	1008982	8	7.5-9.0	50	1433	26.1	9.1	7.7	10	796	
245/40R19 98Y	1008983	8.5	8.0-9.5	50	1653	26.7	9.8	8.4	10	777	
255/40R19 100Y	1009065	9	8.5-10.0	50	1764	27.1	10.2	8.7	10	768	
275/40R19 105Y	1009066	9.5	9.0-10.0	50	2039	27.7	10.9	9.4	10	751	
225/45ZR19XL 96Y	1009776	7.5		50	1565	27.00	8.90		10		
245/45R19 102Y	1009067	8	7.5-9.0	50	1874	27.7	9.6	8.4	10	751	
305/25R20 97Y	1009514	11	10.5-11.5	50	1609	26	12.3	10.8	10	800	
225/30R20 85Y	1009515	8	8	50	1135	25.4	9.1	8	10	819	
235/30R20 88Y	1009068	8.5	8.5	50	1235	25.6	9.5	8.3	10	812	
255/30R20 92Y	1009070	9	8.5-9.5	50	1389	26.1	10.2	9	10	797	
275/30R20 97Y	1009071	9.5	9.5	50	1609	26.5	10.9	9.7	10	783	
285/30R20 99Y	1009072	10	9.5-10.5	50	1709	26.8	11.4	10.1	10	776	
225/35ZR20XL 90Y	1009777	7.5		50	1323	26.3	8.90		10		
245/35R20 95Y	1009073	8.5	8.0-9.5	50	1521	26.8	9.8	8.4	10	776	
255/35R20 97Y	1009074	9	8.5-10.0	50	1609	27	10.2	8.7	10	769	
275/35R20 102Y	1009075	9.5	9.0-11.0	50	1874	27.6	10.9	9.4	10	754	
245/40R20 99Y	1009076	8.5	8.0-9.5	50	1709	27.7	9.8	8.4	10	750	
245/45R20 103Y	1009171	8	7.5-9.0	50	1929	28.7	9.6	8.4	10	725	
255/45R20 105Y	1009172	8.5	8.0-9.5	50	2039	29.1	10	8.7	10	715	
285/30R21 100Y	1009517	10	9.5-10.5	50	1764	27.8	11.4	10.1	10	748	
245/35R21 96Y	1009516	8.5	8.0-9.5	50	1565	27.8	9.8	8.4	10	748	

HANKOOK VENTUS V4 es H105 Ultra-High Performance Radial



UTQG 420 A A ROAD HAZARD WARRANTY

- The superb wet and dry handling is competitive with some of the best UHP summer tires available, but the Ventus V4 ES also gets twice the winter performance of the typical summer UHP tire.
- The best technological advances in profile design, construction, tread pattern and tread compound have been applied together in one state-of-the-art tire.
- The result is a sophisticated tire that provides excellent handling in all weather conditions, along with an advanced, cutting-edge appearance.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
205/50R16 91V	1005271	6.5	5.5-7.5	50	1,356	24.1	8.3	6.8	11.0	862	\$
225/50R16 96V	1005274	7.0	6.0-8.0	50	1,565	24.9	9.1	7.7	11.0	834	
175/55R15 77T	1009669	5.5	5.0-6.0	51	908	22.6	7.2	6.0	10.0	921	
195/55R16 87V	1009500	6.0	5.5-7.0	51	1,201	24.4	7.9	6.1	11.0	851	
205/55R16 94V	1005280	6.5	5.5-7.5	50	1,477	24.9	8.3	6.5	11.0	834	
215/55R16 97V	1005281	7.0	6.0-7.5	50	1,609	25.3	8.8	6.8	10.5	821	
225/55R16 99V	1005282	7.0	6.0-8.0	50	1,709	25.9	9.1	7.1	10.5	802	
215/35R17 79H	1009670	7.5	7.0-8.5	51	963	22.9	8.6	7.4	10.0	907	
205/40R17 84W	1005267	7.5	7.0-8.0	50	1,102	23.5	8.3	7.0	10.5	884	
245/40R17 95W	1005993	8.5	8.0-9.5	50	1,521	24.7	9.8	8.4	10.5	841	
275/40R17 99W	1004891	9.5	9.0-11.0	51	1,653	25.6	10.7	9.4	10.5	812	
215/45R17 91W	1005264	7.0	7.0-8.0	50	1,356	24.6	8.5	7.4	10.5	844	
225/45R17 94W	1005265	7.5	7.0-8.5	50	1,477	25.0	8.9	7.7	11.0	831	
235/45R17 97W	1005268	8.0	7.5-9.0	50	1,609	25.4	9.3	8.0	10.5	818	
245/45R17 99W	1005270	8.0	7.5-9.0	50	1,709	25.7	9.6	8.4	11.0	808	
255/45R17 98W	1009501	8.5	8.0-9.5	51	1,653	26.1	10.0	8.7	11.0	797	
205/50R17 93W	1009496	6.5	5.5-7.5	50	1,433	25.1	8.4	7.0	11.0	827	
215/50R17 91W	1005810	7.0	6.0-7.5	51	1,356	25.5	8.9	7.1	11.0	815	
225/50R17 98W	1005994	7.0	6.0-8.0	50	1,653	25.9	9.1	7.4	10.5	802	
235/50R17 98W	1005995	7.5	6.5-8.5	50	1,565	26.3	9.6	7.8	10.5	790	
215/55R17 94W	1006710	7.0	6.0-7.5	50	1,477	26.3	8.9	7.4	10.5	790	
225/55R17 101W	1005996	7.0	6.0-8.0	50	1,819	26.8	9.2	7.4	10.5	775	
235/50R17 99W	1008400*	7.5	6.5-8.5	51	1,709	23.2	9.6	8.0	10.5	895	
215/35R18 84W	1005263	7.5	7.0-8.5	50	1,102	23.9	8.6	7.4	10.5	869	
225/40R18 92W	1004426	8.0	7.5-9.0	50	1,389	25.1	9.1	7.7	11.0	828	
235/40R18 95W	1005272	8.5	8.0-9.5	50	1,521	25.4	9.5	8.0	11.0	818	
245/40R18 97W	1005276	8.5	8.0-9.5	50	1,609	25.7	9.6	8.4	11.0	808	
225/45R18 95W	1007112	7.5	7.0-8.5	50	1,521	25.9	8.9	7.7	11.0	802	
235/45R18 98W	1007870	8.0	7.5-9.0	50	1,653	26.3	9.3	8.0	11.0	789	
245/45R18 100W	1005997	8.5	7.5-9.0	50	1,764	26.7	9.6	8.4	10.5	778	
255/45R18 99W	1005811	8.5	8.0-9.5	51	1,709	27.0	10.0	8.7	11.0	769	
225/50R18 95W	1008402*	7.0	6.0-8.0	51	1,521	26.9	9.2	7.5	10.5	772	
235/50R18 97W	1008403*	7.5	6.5-8.5	51	1,609	27.3	9.6	7.8	10.5	761	
245/50R18 100W	1009503	7.5	7.0-8.5	51	1,764	27.7	10.0	8.4	10.5	751	
215/35R19 85W	1005735	7.5	7.0-8.5	50	1,135	24.9	8.5	7.4	10.5	834	
235/35R19 91W	1005812	8.5	8.0-9.5	50	1,358	25.5	9.4	8.0	11.0	815	
225/35R20 90W	1005737	8.0	7.5-9.0	50	1,323	26.3	8.9	7.7	10.5	790	
235/35R20 92W	1007871	8.5	8.0-9.5	50	1,389	26.5	9.5	8.0	11.0	785	
245/35R20 95W	1005813	8.5	8.0-9.5	50	1,521	26.8	9.6	8.0	11.0	775	
255/35R20 97W	1005814	9.0	8.5-10.0	50	1,609	27.0	10.2	8.8	11.0	769	
285/25R22 95W	1009498	10.5	10.5	50	1,521	27.6	11.6	10.1	10.5	753	
295/25R22 97W	1009497	10.5	10.0-11.0	50	1,609	27.8	11.9	10.5	10.5	746	
235/30R22 90W	1009499	8.5	8.5	50	1,323	27.6	9.5	8.0	10.5	753	
245/30R22 92W	1006543	8.5	8.0-9.0	50	1,389	27.7	9.8	8.7	11.0	750	
255/30R22 95W	1006107	9.0	8.5-9.5	50	1,521	27.9	10.4	9.1	10.5	746	
265/30R22 97W	1009493	9.5	9.0-10.0	50	1,609	28.3	10.7	9.3	10.5	734	
265/35R22 102W	1005992	9.5	9.0-10.5	50	1,874	29.1	10.8	9.3	10.5	714	
255/30R24 97W	1009494	9.0	8.5-9.5	50	1,609	30.1	10.2	9.1	10.5	691	
275/30R24 101W	1009495	9.5	9.0-10.0	50	1,819	30.6	10.9	9.4	10.5	680	

HANKOOK VENTUS ST RH06

SUV Sport Radial



UTQG 280 AA A ROAD HAZARD WARRANTY

- Designed specifically for the high performance, luxury SUV market. Controlled footprint shape ensures maximum contact.
- Remarkable performance and road handling in all weather conditions.
- Outstanding performance, minimal treadwear, long tread life and a quiet, comfortable ride.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
255/50R17 101W	1004322	8.0	7.0-9.0	51	1,819	27.1	10.3	8.8	11.0	767	\$
275/60R17 110V	1003968	8.0	7.5-9.5	44	2,337	30.0	10.8	9.4	12.5	692	
295/45R18 108V	1004324	10.0	9.5-11.0	51	2,205	28.5	11.5	9.8	11.0	729	
275/40R20 106W	1004328	9.5	9.0-10.5	50	2,094	28.7	10.8	9.5	11.0	724	
275/45R20 109V	1004296	9.0	8.5-10.0	50	2,271	29.8	10.6	9.2	11.0	697	
295/45R20 114V	1004231	10.0	9.5-11.0	50	2,601	30.5	11.7	9.8	11.0	681	
265/50R20 112W	1004912	8.5	7.5-9.5	50	2,469	30.5	10.8	8.8	11.0	681	
285/50R20 112V	1003971	9.0	8.0-10.0	51	2,469	31.3	11.2	9.5	11.0	664	
275/55R20 117V	1004295	8.5	7.5-9.5	50	2,833	31.9	11.1	9.2	11.0	651	
265/35R22 102W	1004914	9.5	9.0-10.5	50	1,874	29.3	10.6	8.8	11.0	709	
285/35R22 102W	1004915	10.0	9.5-11.0	51	1,874	29.9	11.2	9.5	11.0	695	
265/40R22 106V	1007457	9.5	9.0-10.5	50	2,094	30.4	10.6	8.8	11.0	683	
305/40R22 114V	1005412	11.0	10.0-12.0	50	2,601	31.6	12.2	10.5	11.0	645	
275/45R22 112V	1008409	9.0	8.5-10.5	50	2,469	31.8	10.7	9.2	11.0	654	
285/45R22 114V	1007301	9.5	9.0-10.5	50	2,601	32.1	11.2	9.5	11.0	633	
305/45R22 118V	1004712	10.0	9.5-11.0	50	2,910	32.8	11.8	10.6	11.0	575	
285/35R23 107V	1008410	10.0	9.5-11.0	50	2,149	30.9	11.4	9.8	11.0	673	
305/35R24 114V	1004714	11.0	10.0-12.0	50	2,601	32.5	12.0	10.6	11.0	624	
305/30R26 111V	1005223	11.0	10.5-11.5	50	2,403	33.2	12.3	10.6	11.0	579	
315/40R26 121V	1006376	11.0		50	3,197	35.9	12.6		11.0		

HANKOOK VENTUS AS RH07

SUV/Sport Truck Radial



UTQG 420 A A

ROAD HAZARD WARRANTY

- Ventus AS is designed as a suitable replacement O.E. Y inch up tire to provide a comfortable, quiet ride plus all-season traction.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
255/65R16 109H	1007213	7.5	6.5-8.0	44	2,271	29.1	10.2	8.5	12.0	714	\$
235/55R17 103H	1007304	7.5	6.5-8.5	50	1,929	27.2	9.6	7.9	11.0	765	
275/55R17 109V	1007771	8.5	7.5-9.5	44	2,271	28.9	11.2	9.2	11.0	719	
235/60R17 102H	1008988	7.0	6.5-8.5	44	1,874	28.2	9.4	7.9	11.0	737	
255/60R17 106V	1007320	7.5	7.0-9.0	44	2,094	29.1	10.2	8.4	12.0	715	
225/65R17 102H	1008553	6.5	6.0-8.0	44	1,874	28.5	9.0	6.9	11.0	729	
235/65R17 108H	1006933	7.0	6.5-8.5	50	2,205	29.1	9.4	7.8	12.0	714	
245/65R17 107H	1006934	7.0	7.0-8.5	44	2,149	29.5	9.8	8.1	12.0	704	
235/55R18 104V	1007305	7.5	6.5-8.5	50	1,984	28.1	9.6	7.9	11.0	738	
255/55R18 109V	1006928	8.0	7.0-9.0	50	2,271	29.0	10.4	8.5	11.0	742	
275/55R18 114H	1007306	8.5	7.5-9.5	50	2,601	29.9	11.2	9.2	11.0	695	
235/60R18 107V	1007313	7.0	6.5-8.5	50	2,150	29.1	9.4	7.8	12.0	714	
255/60R18 108V	1007324	7.5	7.5-9.0	44	2,205	30.2	10.0	8.5	12.0	688	
265/60R18 110V	1006929	8.0	7.0-8.5	44	2,337	30.5	10.7	6.0	12.0	681	
275/60R18 113H	1007215	8.0	7.5-9.5	44	2,535	31.0	11.0	9.1	12.0	671	
235/65R18 103H	1006932	7.0	6.5-8.5	44	2,094	30.0	9.4	7.8	12.0	692	
255/65R18 109H	1009592	7.5	7.0-9.0	44	2,271	31.1	10.2	8.5	12.0	668	
265/65R18 112H	1009593	8.0	7.5-9.5	44	2,469	31.5	10.7	8.9	12.0	660	
275/65R18 116H	1006930	8.0	7.5-9.5	44	2,756	31.1	11.0	9.1	12.0	668	
285/45R19 107W	1008539	9.5	9.0-10.5	51	2,149	29.1	11.2	9.5	11.0	714	
255/50R19 103W	1008538	8.0	7.0-9.0	51	1,929	29.1	10.4	8.5	11.0	714	
235/55R19 105V	1009844	7.5	6.5-8.5	50	2,039	29.2	9.6	7.9	11.0	712	
P255/60R19 108H	1009594	7.5	7.0-9.0	44	2,205	31.1	10.2	8.5	12.0	668	
245/55R19 103H	1011112	7.5	7.0-8.5	51	1,929	29.6	10.0	8.1	11.0	701.0	
255/55R19 111V	1008594	8.0	7.0-9.0	50	2,403	30.0	10.4	8.5	11.0	692	
275/55R19 111H	1009747	8.5	7.5-9.5	51	2,403	30.9	11.2	9.1	11.0	672	
275/40R20 106V	1007773	9.5	9.0-11.0	50	2,094	28.7	10.9	9.2	11.0	725	
255/45R20 105V	1007873	8.5	8.0-9.5	50	2,039	29.1	10.0	8.5	11.0	715	
265/45R20 104V	1008544	9.0	8.5-10.0	51	1,984	29.4	10.5	8.9	11.0	707	
275/45R20 110V	1006563	9.0	8.0-10.0	50	2,337	29.8	10.7	9.2	11.0	697	
245/50R20 102V	1009595	7.5	7.0-8.5	50	1,874	29.7	10.0	8.1	11.0	699	
255/50R20 109V	1007874	8.0	7.0-9.0	50	2,271	30.1	10.4	8.5	11.0	691	
265/50R20 112V	1007774	8.5	7.5-9.5	50	2,469	30.5	10.9	8.9	11.0	682	
285/50R20 116H	1006923	9.0	8.0-10.0	50	2,756	31.3	11.7	9.5	11.0	664	
275/55R20 117H	1006926	8.5	7.5-9.5	50	2,833	31.9	11.2	9.2	11.0	651	
275/60R20 119H	1006927	8.0	7.5-9.5	50	2,998	33.0	11.0	9.1	12.0	630	

HANKOOK VENTUS HR II H405

High Performance Radial



UTQG 340 A A

ROAD HAZARD WARRANTY

- The Ventus HR II is an ultra-low profile radial with a wide footprint for aggressive handling on tight turns and better performance on wet roads.
- The stylish unidirectional grooves enhance steering stability, improve drainage, and reduced rolling resistance.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
195/50R15 82H	1003621	6.0	5.5-7.0	44	1,047	22.8	7.8	6.1	10.0	911	\$
205/50R15 86H	1003622	6.5	5.5-7.5	44	1,168	23.1	8.3	6.7	10.0	899	
205/40R16 83H	1002098	7.5	7.0-8.0	50	1,074	22.4	8.4	7.0	10.0	927	
215/40R16 82H	1002106	7.5	7.0-8.5	44	1,047	22.7	8.5	7.4	10.0	915	
205/45R16 86H	1004769	7.0	6.5-7.5	44	1,168	23.2	8.1	7.0	10.0	895	
205/50R16 87H	1004433	6.5	5.5-7.5	50	1,202	24.1	8.3	6.7	10.0	862	
215/50R16 90H	1002182	7.0	6.0-7.5	50	1,323	24.5	8.8	6.8	10.0	848	
225/50R16 92H	1003624	7.0	6.0-8.0	50	1,389	24.9	9.0	7.1	10.0	834	
245/50R16 96H	1003625	7.5	7.0-8.5	50	1,576	25.7	9.8	7.7	10.5	808	
205/55R16 90H	1003737	6.5	5.5-7.5	50	1,356	25.0	8.3	6.5	10.5	831	
215/55R16 93H	1003179	7.0	6.0-7.5	50	1,433	25.3	8.9	6.8	10.5	821	
225/55R16 95H	1003626	7.0	6.0-7.5	50	1,521	25.7	9.1	7.1	10.0	808	
205/40R17 80H	1002108	7.5	7.0-8.0	50	992	23.5	8.3	7.0	10.0	884	
215/40R17 83H	1002096	7.5	7.0-8.5	50	1,074	23.7	8.5	7.4	10.0	877	
235/40R17 90H	1002109	8.5	8.0-9.5	50	1,323	24.3	9.5	8.0	10.0	855	
245/40R17 91H	1003011	8.5	8.0-9.5	50	1,356	24.8	9.7	8.5	10.0	838	
255/40R17 94H	1002094	9.0	8.5-10.0	50	1,477	25.1	10.2	8.7	10.0	828	
275/40R17 98H	1003013	9.5	9.0-11.0	50	1,653	25.7	10.9	9.4	10.0	808	
215/45R17 87H	1002099	7.0	7.0-8.0	50	1,201	24.5	8.4	7.4	10.0	848	
225/45R17 94H	1004847	7.5	7.0-8.5	44	1,477	24.8	8.9	7.7	10.0	838	
235/45R17 93H	1002107	8.0	7.5-9.0	50	1,433	25.2	9.3	8.0	10.0	824	
245/45R17 95H	1002097	8.0	7.5-9.0	50	1,521	25.7	9.6	8.4	10.0	808	
255/45R17 98H	1002095	8.5	8.0-9.5	50	1,653	26.0	10.1	8.7	10.0	799	
215/50R17 91H	1002091	7.0	6.0-7.5	50	1,356	25.4	8.9	6.8	10.5	818	
225/50R17 94H	1004089	7.0	6.0-8.0	50	1,477	25.9	9.1	7.7	10.0	802	
225/55R17 97H	1004246	7.0	6.0-8.0	50	1,609	26.8	9.1	7.1	10.0	775	
235/55R17 99H	1004435	7.5	6.5-8.5	50	1,709	27.2	9.6	8.0	10.5	764	
225/40R18 88H	1003008	8.0	7.5-9.0	50	1,235	25.1	9.1	7.6	10.0	828	
235/40R18 93H	1004768	8.5	8.0-9.5	44	1,433	25.4	9.4	8.0	10.0	818	
245/40R18 93H	1003012	8.0	8.0-9.5	50	1,433	25.7	9.7	8.3	10.0	808	

HANKOOK VENTUS H101

High Performance Radial



UTQG 400 A B

50,000 Mile

Tread Life Warranty

ROAD HAZARD WARRANTY

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
RAISED WHITE LETTERS											
P265/50R15 99S	1000934	8.5	7.5-9.5	44	1,720	25.4	10.7	9.1	10.5	.818 \$
P295/50R15 105S	1000935	9.5	8.0-10.0	44	2,061	26.6	12.0	10.2	11.0	.781
P275/60R15 107S	1000941	8.0	7.5-9.5	44	2,149	27.9	10.8	8.9	11.0	.745

- A 50/60 series All-Season high performance tire with excellent handling and traction without sacrificing treadwear.
- Tread pattern has wide grooves and kerfs provide good all-season performance. Computer optimized tread pattern ensures a smooth, quiet ride.

HANKOOK RADIAL K106

High Performance Radial



UTQG 340 A A

- The Hankook K106 is high performance radial designed for serious driving excitement.
- The radical V-shaped tread pattern efficiently disperses water without compromising speed or handling.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
195/50R15 87H	1005882	6.0	5.5-7.0	44	1,047	22.8	7.8	6.1	10.0	.911 \$
205/50R15 86V	1006206	6.5	5.5-7.5	44	1,168	23.1	8.4	6.7	10.0	.899
195/55R15 85V	1006207	6.0	5.5-7.0	44	1,135	23.5	7.9	6.1	10.0	.884
205/55R15 88V	1006208	6.5	5.5-7.0	44	1,235	23.9	8.4	6.5	10.0	.869
205/45R16 87V	1005192	7.0	6.5-7.5	50	1,201	23.2	8.1	7.0	10.0	.895
205/50R16 87V	1005150	6.5	5.5-7.5	44	1,201	24.2	8.3	6.8	10.0	.858
225/50R16 92V	1005149	7.0	6.0-8.0	44	1,389	24.8	9.1	7.1	10.5	.838
205/55R16 91V	1005151	6.5	5.5-7.5	44	1,356	25.0	8.4	6.5	10.5	.831
215/55R16 93V	1005164	7.0	6.0-7.5	44	1,433	25.2	9.0	6.8	10.5	.824
225/55R16 95V	1003490	7.0	6.0-8.0	44	1,524	25.7	9.3	7.1	10.5	.808
205/40R17 80H	1005323	7.5	7.0-8.0	44	.992	23.6	8.3	7.0	10.5	.880
215/45R17 87H	1005324	7.0	7.0-8.0	44	1,201	24.7	8.3	7.4	10.5	.841
225/45R17 91H	1005322	7.5	7.0-8.5	44	1,356	25.0	8.8	7.7	10.5	.831
215/50R17 91H	1005325	7.0	6.0-7.5	44	1,356	25.4	8.9	7.4	10.5	.818
215/35R18 80H	1005327	7.5	7.0-8.5	44	.992	23.9	8.5	7.4	10.5	.869
225/40R18 88H	1005326	8.0	7.5-9.0	44	1,235	25.1	8.9	7.7	10.5	.828

HANKOOK OPTIMO H724

Standard Touring All-Season



UTQG 500 A B

70,000 Mile

Tread Life Warranty

- **Center Rib Block**
The center rib improves handling and stability during lane change maneuvers.
- **Pitch Design Technology**
5 pitch technology reduces tire noise for a quieter ride.
- **Variable Lateral Groove**
Variable groove widths maximize water discharge and minimize the potential for hydroplaning.
- **Multi-Kerf with Optimal Radius**
Computer optimized multi-kerf (sipe) design improves ride comfort and provides enhanced traction in rainy driving conditions.
- **4 Optimized Circumferential Grooves**
Groove width and positions are optimized to deliver improved stability on wet road surfaces.

Tire Size	Code No.	Meas. Rim	Rim Width Range	Overall Diameter	Section Width	Tread Width	Tread Depth	Revs/ Miles	MAX Air Load	PRICE
P175/70R13 82T	1010983	5	4.5-5.5	22.7	7	4.6	9.5	916	44 1,036 \$
P185/60R14 82T	1011704	5.5	5.0-6.5	22.8	7.4	5.2	9.5	913	44 1,047
P195/60R14 85T	1011706	6	5.5-7.0	23.2	7.9	5.4	10	894	44 1,135
P175/65R14 81T	1010987	5	5.0-6.0	23	7	4.9	9.5	903	44 1,019
P185/65R14 85T	1010986	5.5	5.0-6.5	23.5	7.4	5.2	9.5	885	44 1,124
P175/70R14 84T	1011694	5	4.5-6.0	23.7	7	4.6	9.5	876	44 1,102
P185/70R14 87T	1010985	5.5	4.5-6.0	24.3	7.4	4.8	10	857	44 1,201
P195/70R14 90T	1010999	6	5.0-6.5	24.8	7.9	5.1	10	838	44 1,312
P205/70R14 93T	1011733	6	5.0-7.0	25.4	8.2	5.3	10	819	44 1,433
P215/70R14 96T	1011004	6.5	5.5-7.0	25.9	8.7	5.6	10	802	44 1,554
P185/75R14 89S	1011005	5	4.5-6.0	25	7.2	4.6	10	832	44 1,290
P195/75R14 92S	1011010	5.5	5.0-6.5	25.5	7.7	4.8	10	814	44 1,400
P205/75R14 95S	1010991	5.5	5.0-7.0	26.1	8	5	10	795	44 1,532
P215/75R14 98S	1011002	6	5.5-7.0	26.7	8.5	5.3	10	778	44 1,664
P185/60R15 84T	1011696	5.5	5.0-6.5	23.7	7.4	5.2	9.5	875	44 1,102
P195/60R15 87T	1010993	6	5.5-7.0	24.2	7.9	5.4	10	858	44 1,190
P205/60R15 90T	1011709	6	5.5-7.5	24.7	8.2	5.7	10	842	44 1,301
P215/60R15 93T	1011697	6.5	6.0-7.5	25.2	8.7	6	10	826	44 1,411
P185/65R15 86T	1011707	5.5	5.0-6.5	24.4	7.4	5.2	9.5	850	44 1,168
P195/65R15 89T	1010997	6	5.5-7.0	25	7.9	5.4	10	831	44 1,279
P205/65R15 92T	1011006	6	5.5-7.5	25.5	8.2	5.7	10	816	44 1,400
P215/65R15 95T	1011710	6.5	6.0-7.5	26	8.7	6	10	798	44 1,510
P205/70R15 95T	1011001	6	5.0-7.0	26.3	8.2	5.3	10	789	44 1,499
P215/70R15 97T	1010989	6.5	5.5-7.0	26.9	8.7	5.6	10	773	44 1,620
P225/70R15 100T	1011008	6.5	6.0-7.5	27.4	9	5.9	10.5	757	44 1,753
P205/75R15 97S	1010990	5.5	5.0-7.0	27.1	8	5	10	766	44 1,598
P215/75R15 100S	1010992	6	5.5-7.0	27.7	8.5	5.3	10	751	44 1,742
P225/75R15 102S	1011009	6	6.0-7.5	28.3	8.8	5.6	10.5	734	44 1,874
P235/75R15 108S XL	1010988	6.5	6.0-8.0	28.9	9.3	5.8	10.5	720	50 2,183
P205/60R16 91T	1011000	6	5.5-7.5	25.7	8.2	5.7	10	809	44 1,356
P215/60R16 94T	1011003	6.5	6.0-7.5	26.1	8.7	6	10	795	44 1,477
P225/60R16 97T	1011011	6.5	6.0-8.0	26.6	9	6.3	10.5	781	44 1,609
P235/60R16 99T	1011699	7	6.5-8.5	27.1	9.4	6.6	10.5	767	44 1,709
P205/65R16 94T	1011698	6	5.5-7.5	26.5	8.2	5.7	10	785	44 1,477
P215/65R16 96T	1011007	6.5	6.0-7.5	27	8.7	6	10	769	44 1,565
P235/65R16 101T	1011700	7	6.5-8.5	28	9.4	6.6	10.5	741	44 1,819
P215/60R17 95T	1011701	6.5	6.0-7.5	27.2	8.7	6	10	765	44 1,521
P225/60R17 98T	1011703	6.5	6.0-8.0	27.6	9	6.3	10.5	752	44 1,653
P215/65R17 98T	1011702	6.5	6.0-7.5	28	8.7	6	10	741	44 1,653

HANKOOK OPTIMO H418

Passenger Radial



UTQG 440 A A

- The Optimo H418 is a H & V rated, all-season tire that delivers the perfect balance of comfort and technical performance for today's touring sports cars and luxury performance sedans.
- While the solid central rib aids in handling, the high-angle diagonal grooves channel water away from the center.
- The interlocking shoulder rib ensures flexibility for wet traction.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P185/60R14 82H	1003768	5.5	5.0-6.5	44	1,047	22.7	7.4	5.8	10.0	915	\$
P195/60R14 85H	1003769	6.0	5.5-7.0	44	1,135	23.2	7.8	6.1	10.0	895	
P175/65R14 81H	1003771	5.0	5.0-6.0	44	1,019	23.0	7.0	5.4	10.0	903	
P185/65R14 85H	1004493	5.5	5.0-6.5	44	1,124	23.4	7.4	5.6	10.0	888	
P195/65R14 88H	1003766	6.0	5.5-7.0	44	1,235	24.0	7.9	5.9	10.0	866	
P195/60R15 87H	1003647	6.0	5.5-7.0	44	1,190	24.2	7.8	5.5	10.5	858	
P205/60R15 90H	1003758	6.0	5.5-7.5	44	1,301	24.6	8.1	6.5	10.5	844	
P215/60R15 93H	1003759	6.5	6.0-7.5	44	1,411	25.1	8.6	6.8	10.5	828	
P225/60R15 95H	1003760	6.5	6.0-8.0	44	1,521	25.6	8.9	7.1	10.5	812	
P185/65R15 86H	1003761	6.0	5.0-6.5	44	1,168	25.0	7.6	5.3	10.5	831	
P195/65R15 89H	1003762	6.0	5.5-7.0	44	1,279	25.0	7.9	5.9	10.0	831	
P205/65R15 92H	1004625	6.0	5.5-7.5	44	1,400	25.4	8.2	5.8	10.0	818	
P215/65R15 95H	1003764	6.5	6.0-7.5	44	1,521	26.0	8.7	6.6	10.5	799	
P205/50R16 86H	1004835	6.5	5.5-7.5	44	1,168	24.1	8.3	6.4	10.0	862	
P225/50R16 91H	1004836	7.0	6.0-8.0	44	1,367	24.8	9.0	6.8	10.0	838	
P205/55R16 89H	1003911	6.5	5.5-7.5	44	1,279	24.8	8.3	6.3	10.0	838	
P215/55R16 91H	1004833	7.0	6.0-7.5	44	1,356	25.2	8.7	6.6	10.0	824	
P225/55R16 94H	1004834	7.0	6.0-8.0	44	1,477	25.7	9.0	6.7	10.0	808	
P235/55R16 96H	1005983	7.5	6.5-8.5	44	1,565	26.1	9.5	7.5	10.0	796	
P205/60R16 91H	1004626	6.0	5.5-7.5	44	1,356	25.6	8.4	6.5	10.0	812	
P205/60R16 91V	1006915	6.0	5.5-7.5	44	1,356	25.7	8.1	6.5	10.5	808	
P215/60R16 94H	1003765	6.5	6.0-7.5	44	1,477	26.2	8.6	6.8	10.5	793	
P215/60R16 94V	1006914	6.5	6.0-7.5	44	1,477	26.2	8.6	6.8	10.5	793	
P225/60R16 97H	1003112	6.5	6.0-8.0	44	1,609	26.7	9.0	6.7	10.5	778	
P235/60R16 99H	1003767	7.0	6.5-8.5	44	1,709	27.2	9.3	7.4	10.5	764	
P225/65R16 99H	1007869	6.5	6.0-8.0	44	1,709	27.5	9.0	6.7	10.5	755	
P215/50R17 90V	1004627	6.5	6.0-7.5	44	1,323	25.6	8.5	6.5	9.7	812	
P215/55R17 93V	1008238	7.0	6.0-7.5	44	1,433	26.3	8.9	7.1	10.0	790	
P215/55R17 93V	1008239*	7.0	6.0-7.5	44	1,433	26.3	8.9	7.1	10.0	790	
P225/55R17 95V	1008238*	7.0	6.0-8.0	44	1,521	26.8	9.2	7.5	10.0	776	
P235/55R17 98H	1008237*	7.5	6.5-8.5	44	1,609	27.2	9.6	7.8	10.0	765	
P225/60R18 99H	1007328	6.5	6.0-8.0	44	1,709	28.6	9.0	6.7	10.5	726	

HANKOOK OPTIMO H727

Premium Radial



UTQG 700 A B

**100,000 Mile
Tread Life Warranty
ROAD HAZARD WARRANTY**

- The Optimo H727 is a touring tire specifically designed for today's luxury sedans.
- The computer calculated tread design, featuring CCT (Carbon Compounding Technology) and FSO (Footprint Shape Optimization) affords the driver a quiet, comfortable ride along with uniform wear and long life.
- Hundreds of "sipes" and open grooves assures outstanding traction on rain soaked or dry roads... especially in tight turns.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P185/65R14 85T	1006111	5.5	5.0-6.5	44	1,124	23.4	7.4	6.2	11.5	888	\$
P195/70R14 90T	1006104	6.0	5.0-6.5	44	1,312	24.7	8.0	6.5	11.5	842	
P185/60R15 84T	1006836	5.5	5.0-6.5	44	1,102	23.7	7.4	6.4	11.5	875	
P195/60R15 87T	1006117	6.0	5.5-7.0	44	1,190	24.2	7.8	6.7	11.5	858	
P205/60R15 90T	1006118	6.0	5.5-7.5	44	1,301	24.7	8.1	7.1	11.5	840	
P195/65R15 89T	1006112	6.0	5.5-7.0	44	1,279	25.0	7.9	6.5	11.5	831	
P205/65R15 92T	1006113	6.0	5.5-7.5	44	1,400	25.5	8.1	6.9	12.0	816	
P205/70R15 95T	1006105	6.0	5.0-7.0	44	1,499	26.3	8.2	6.9	12.0	789	
P215/70R15 97T	1006106	6.5	5.5-7.0	44	1,620	26.9	8.8	7.2	12.0	773	
P235/75R15 108T	1006103	6.5	6.0-8.0	50	2,183	28.9	9.4	7.7	12.0	720	
P205/55R16 89T	1006123	6.5	5.5-7.5	44	1,279	24.9	8.3	7.1	11.5	834	
P205/60R16 91T	1006120	6.0	5.5-7.5	44	1,356	25.7	8.1	7.1	11.5	807	
P215/60R16 94T	1005468	6.5	6.0-7.5	44	1,477	26.2	8.6	7.4	11.5	792	
P225/60R16 97T	1006121	6.5	6.0-8.0	44	1,609	26.7	8.9	8.0	12.0	779	
P235/60R16 99T	1006122	7.0	6.5-8.5	44	1,709	27.2	9.3	8.1	12.0	765	
P205/65R16 94T	1006115	6.0	5.5-7.5	44	1,477	26.5	8.2	6.9	12.0	785	
P215/65R16 96T	1006116	6.5	6.0-7.5	44	1,565	27.1	8.6	7.2	12.0	768	
P225/65R16 100T	1011822	6.5	6.0-8.0	44	1,279	24.9	8.3	7.0	11.5	834	
P235/65R16 101T	1006837	7.0	6.5-8.5	44	1,819	28.1	9.5	7.9	12.5	739	
P225/55R17 95T	1006840	7.0	6.0-8.0	44	1,521	26.8	9.2	7.8	12.0	776	
P215/60R17 95T	1007265	6.5	6.0-7.5	44	1,521	27.2	8.7	7.2	12.0	764	
P225/60R17 98T	1006839	6.5	6.0-8.0	44	1,653	27.6	9.0	7.8	12.0	752	
P215/65R17 98T	1006838	6.5	6.0-7.5	44	1,653	28.0	8.7	7.2	12.0	741	
PP225/50R18 94T	1009492	7.0	6.0-8.0	44	1,477	26.9	9.2	7.8	12.0	772	
P215/55R18 94T	1009490	7.0	6.0-7.5	44	1,477	27.3	8.9	7.2	12.0	761	
P225/55R18 97T	1007787	7.0	6.0-8.0	44	1,609	27.8	9.2	7.8	12.0	747	

HANKOOK MILEAGE PLUS II H725 Premium All-Season Radial



UTQG 620 A B
80,000 Mile
Tread Life Warranty
ROAD HAZARD WARRANTY

- The Mileage Plus II is a premium all-season radial that combines quality with value.
- Extremely low pattern noise is achieved through new advancements in pattern arrangement and computer optimization.
- Computer modeling profile design improves handling.
- The Mileage Plus II handles superbly in all seasons and provides a comfortable quiet ride.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
WHITE LETTERS											
P175/70R14 84S	1004558	5.0	4.5-6.0	44	1,102	23.7	6.9	5.1	10.5	877	\$
P185/70R14 85S	1004559	5.5	4.5-6.0	44	1,201	24.2	7.4	5.4	10.5	858	
P225/70R14 98S	1004858	6.5	6.0-7.5	44	1,675	26.3	8.9	6.6	11.0	790	
P185/75R14 89S	1004568	5.0	4.5-6.0	44	1,290	24.9	7.3	5.2	11.0	834	
P195/75R14 92S	1004569	5.5	5.0-6.5	44	1,400	25.4	7.8	5.5	11.0	818	
P205/75R14 95S	1004570	5.5	5.0-7.0	44	1,532	26.0	8.0	5.8	11.0	799	
P215/75R14 98S	1004574										
P207/70R15 95S	1004565	6.0	5.0-7.0	44	1,499	26.3	8.1	6.0	11.0	790	
P215/70R15 97S	1004567	6.5	5.5-7.0	44	1,620	26.8	8.7	6.3	11.0	775	
P225/70R15 100S	1003953	6.5	6.0-7.5	44	1,753	27.4	8.9	6.6	11.0	758	
P235/70R15 102S	1004572	7.0	6.0-8.0	44	1,896	27.9	9.4	6.9	11.0	745	
P205/75R15 97S	1004573	5.5	5.0-7.0	44	1,598	27.0	8.0	5.8	11.0	769	
P215/75R15 100S	1004575	6.0	5.5-7.0	44	1,742	27.6	8.4	6.1	11.0	753	
P225/75R15 102S	1005335	6.0	6.0-7.5	44	1,874	28.2	8.8	6.4	11.0	737	
P235/75R15 105S	1004576	6.5	6.0-8.0	44	2,028	28.7	9.4	6.7	11.0	724	
BLACK LETTERS											
P175/65R14 81S	1004553	5.0	5.0-6.0	44	1,019	23.0	6.9	5.3	10.0	903	
P185/65R14 86S	1004554	5.5	5.0-6.5	44	1,124	23.5	7.4	5.6	10.5	884	
P195/65R14 88S	1004556	6.0	5.5-7.0	44	1,235	23.9	7.8	5.9	10.5	869	
P195/70R14 90S	1004563	6.0	5.0-6.5	44	1,312	24.7	7.9	5.7	10.5	841	
P205/60R15 90S	1004550	6.0	5.5-7.5	44	1,301	24.6	8.1	6.4	10.5	844	
P215/60R15 93S	1004551	6.5	6.0-7.5	44	1,411	25.1	8.6	6.7	10.5	828	
P185/65R15 86S	1004555	5.5	5.0-6.5	44	1,168	24.4	7.4	5.6	10.5	851	
P195/65R15 89S	1004560	6.0	5.5-7.0	44	1,279	25.0	7.8	5.9	10.5	832	
P205/65R15 92S	1004561	6.0	5.5-7.5	44	1,400	25.4	8.1	6.2	10.5	818	
P215/65R15 95S	1004562	6.5	6.0-7.5	44	1,510	25.9	8.5	6.5	10.5	802	
P205/55R16 89S	1004549	6.5	5.5-7.5	44	1,279	24.8	8.2	6.6	10.5	838	
P205/60R16 91S	1005336	6.0	5.5-7.5	44	1,356	25.6	8.1	6.4	10.5	812	
P215/60R16 94S	1004552	6.5	6.0-7.5	44	1,477	26.1	8.6	6.7	10.5	796	
P225/60R16 97S	1004557	6.5	6.0-8.0	44	1,609	26.6	8.8	7.0	11.0	781	

HANKOOK RA08

Passenger Radial



Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
185R14 102Q	2000179	5.5	8.0	S 65	1,874	25.6	7.4	5.1	11.5	812	\$
				D 65	1,764						
195R14 106R	2000180	5.5	8.0	S 65	2,094	26.3	7.6	5.5	11.0	790	
				D 65	1,984						

- All-Season and all position radial for vans and transporters.
- Wider footprint and aggressive kerfs with zig-zag grooves contribute to better wear resistance and wet traction.

HANKOOK H406

O.E. Radial



UTQG 340 A A
50,000 Mile
Tread Life Warranty
ROAD HAZARD

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P175/70R13 82T	1001042	5.0	4.5-6.0	44	1,036	22.7	6.9	5.0	10.0	915	\$
P185/60R14 82H	1001010	5.5	5.0-6.5	44	1,047	22.8	7.4	5.8	9.5	911	

- A 60/65/70 series Original Equipment tire for select imports from Hyundai and Kia automobile manufacturers.

HANKOOK H411

O.E. Radial



UTQG 380 A A

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
205/55R16 89V	1002424	6.5	5.5-7.5	44	1279	25	8.5	6.2	11	831	\$

- The Optimo H411 is original equipment for the Hyundai Tiburon.

HANKOOK RADIAL H714 3 GROOVE

Passenger Radial



UTQG 380 A B

3 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
175/70R13 82T	1003466	5.0	4.5-6.0	44	1,047	22.7	6.9	4.9	9.5	915	\$
185/70R13 86T	1003469	5.5	4.5-6.0	44	1,168	23.2	7.4	5.1	9.5	895	
185/60R14 82H	1003467	5.5	5.0-6.5	44	1,047	22.6	7.4	5.2	9.5	919	
195/60R14 86H	1003471	6.0	5.5-7.0	44	1,168	23.2	7.8	5.4	9.5	895	
175/65R14 82T	1003465	5.0	5.0-6.0	44	1,047	23.0	6.9	4.9	9.5	903	
185/65R14 86H	1003468	5.5	5.0-6.5	44	1,168	23.3	7.4	5.2	9.5	892	
185/70R14 88T	1003470	5.5	4.5-6.0	44	1,235	24.3	7.4	5.1	9.5	855	
195/70R14 91T	1003473	6.0	5.0-6.5	44	1,356	24.7	7.9	5.4	9.5	841	
205/70R14 95T	1003474	6.0	5.0-7.0	44	1,521	25.3	8.2	5.7	9.5	821	
195/60R15 88H	1005932	6.0	5.5-7.0	44	1,234	24.0	7.8	6.1	9.5	866	
205/60R15 90H	1002998	6.0	5.5-7.5	44	1,356	24.7	8.2	6.5	10.0	841	
195/65R15 91H	1003472	6.0	5.5-7.0	44	1,356	24.9	7.8	5.4	9.5	834	

- An all-season performance radial, the H714 is available in 3 or 4 groove designs.
- The unique tread pattern disperses water to the sides of the tire while the extra-wide grooves enhance wet handling and braking.

HANKOOK RADIAL H714 4 GROOVE

Passenger Radial



UTQG 380 A B

4 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
WHITE WALL											
P155/80R13 89S	1003475	4.5	4.0-5.0	44	959	22.6	6.2	3.8	9.0	919	\$
P185/80R13 90S	1003477	5.0	4.5-6.0	44	1,301	24.4	7.3	4.6	9.5	851	
P185/70R14 87S	1003476	5.5	4.5-6.0	44	1,201	24.1	7.4	4.8	9.5	862	
P195/70R14 90S	1003478	6.0	5.0-6.5	44	1,312	24.6	7.9	5.0	9.5	846	
P205/70R14 93S	1003479	6.0	5.0-7.0	44	1,433	25.2	8.1	5.3	10.0	824	
P215/70R14 96S	1003483	6.5	5.5-7.0	44	1,554	25.7	8.7	5.6	10.0	808	
P185/75R14 89S	1001270	5.0	4.5-6.0	44	1,290	24.8	7.3	4.6	9.5	838	
P195/75R14 92S	1001274	5.5	5.0-6.5	44	1,400	25.3	7.8	4.8	9.5	821	
P205/75R14 95S	1003481	6.0	5.0-7.0	44	1,532	25.9	8.1	5.0	10.0	802	
P215/75R14 98S	1003485	6.0	5.5-7.0	44	1,664	26.5	8.6	5.3	10.0	784	
P205/70R15 95S	1003480	6.0	5.0-7.0	44	1,499	26.2	8.1	5.3	10.0	793	
P215/70R15 97S	1003484	6.5	5.5-7.0	44	1,620	26.7	8.7	5.6	10.0	778	
P225/70R15 100S	1003487	6.5	6.0-7.5	44	1,753	27.3	8.9	5.8	10.0	761	
P205/75R15 97S	1003482	6.5	5.0-7.0	44	1,598	26.9	8.0	5.0	10.0	772	
P215/75R15 100S	1003486	6.0	5.5-7.0	44	1,742	27.4	8.6	5.3	10.0	758	
P225/75R15 102S	1003488	6.0	6.0-7.5	44	1,874	28.0	8.8	5.6	10.0	742	
P235/75R15 105S	1003489	6.5	6.0-8.0	44	2,028	28.6	9.4	5.8	10.0	726	
BLACK WALL											
P205/60R15 90T	1005261	6.0	5.5-7.5	44	1,301	24.5	8.1	5.7	10.0	848	
P215/60R15 93T	1005266	6.5	6.0-7.5	44	1,411	25.0	8.7	5.9	10.0	831	
P215/60R15 93H	1006502	6.5	6.0-7.5	44	1,411	25.0	8.7	5.9	10.0	831	
P205/65R15 92T	1005262	6.0	5.5-7.5	44	1,400	25.4	8.3	5.7	10.0	818	
205/65R15 92H	1005422	6.0	5.5-7.5	44	1,477	25.4	8.0	5.8	10.0	818	
215/65R15 95H	1005423	6.5	6.0-7.5	44	1,565	25.9	8.6	6.6	10.0	802	
P205/60R16 91H	1006498	6.0	5.5-7.5	44	1,356	25.7	8.1	6.5	10.0	808	
P215/60R16 94T	1005275	6.5	6.0-7.5	44	1,477	26.0	8.6	5.9	10.0	799	
P215/60R16 94H	1006499	6.5	6.0-7.5	44	1,477	26.0	8.6	5.9	10.0	799	
P225/60R16 97T	1005278	6.5	6.0-8.0	44	1,609	26.5	9.0	6.3	10.0	784	
P225/60R16 97H	1006500	6.5	6.0-8.0	44	1,609	26.5	9.0	6.3	10.0	784	
P235/60R16 99H	1006501	7.0	6.5-8.5	44	1,709	26.9	9.6	6.6	10.0	772	
P205/65R16 94T	1005273	6.0	5.5-7.5	44	1,477	26.4	8.3	5.7	10.0	787	
P215/65R16 96T	1005277	6.5	6.0-7.5	44	1,565	26.9	8.7	5.9	10.0	772	

- An all-season performance radial, the H714 is available in 3 or 4 groove designs.
- The unique tread pattern disperses water to the sides of the tire while the extra-wide grooves enhance wet handling and braking.

HANKOOK RADIAL H431

All Season

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
225/45R18V XL	1010086		7.5	50	1521	25.9	8.9		11		\$

UTQG 480 A A

HANKOOK OPTIMO H420

O.E. Radial



Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P185/60R14 82H	1003450	5.5	5.0-6.5	44	1,047	22.8	7.4	5.8	9.5	911	\$
P205/55R16 98H	1003796										

• A 55/60/65 series Original Equipment tire for the Kia Rio, Chevrolet Aveo, Suzuki Forenza and Suzuki Verona.

UTQG 420 A A

50,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H417

O.E. Radial



Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P225/60R16 97H	1007900	6.5	6.0-8.0	44	1,609	26.6	8.8	7.0	10.0	781	\$
P225/60R16 97V	1007042	6.5	6.0-8.0	44	1,609	26.6	8.8	7.0	10.0	781	
P235/55R17 98V	1007752	6.5	6.5-8.5	44	1,653	27.2	9.0	6.9	10.0	770	

• A 55/60/65 series Original Equipment for select imports from Suzuki, Hyundai and Kia automobile manufacturers.

UTQG 380 A A

50,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H418 2 GROOVE

O.E. Radial



2 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P175/70R14 84T	1004492	5.0	4.5-6.0	44	1,102	23.7	7.0	4.8	10.0	877	\$
P185/65R14 85H	1004493	5.5	5.0-6.5	44	1,124	23.4	7.4	5.1	10.0	888	
P195/60R15 87H	1003647	6.0	5.5-7.0	44	1,190	24.2	7.8	5.5	10.0	858	
P235/60R16 99T	1005668	7.0	6.5-8.5	44	1,709	26.9	9.2	6.9	11.0	772	
P215/65R16 96T	1004440	6.5	6.0-7.5	44	1,565	27.1	8.7	6.9	11.0	768	

• The Optimo H418 is Original Equipment for the selected models from Chevrolet, Hyundai, and Kia automobile manufacturers.

UTQG 440 A A

60,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H418 3 GROOVE

O.E. Radial



3 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
185/55R15 82V	1009127	6.0	5.0-6.5	44	1,047	23.1	7.6	5.4	10.0	899	\$
P195/55R15 84V	1004706	6.0	5.5-7.0	44	1,102	23.4	7.6	5.7	10.0	888	
P205/65R15 92H	1004625	6.0	5.5-7.5	44	1,400	25.4	8.2	5.8	10.0	818	
P205/60R16 91H	1004626	6.0	5.5-7.5	44	1,356	25.6	8.4	6.5	10.0	812	
225/70R16 102T	1005834	6.5	6.0-7.5	44	1,874	28.3	9.1	6.7	11.0	734	
235/60R17 102T	1005836	11.0	6.5-8.5	44	1,874	28.1	9.4	6.9	11.0	739	

• The Optimo H418 is Original Equipment for the selected models from Chevrolet, Hyundai, and Kia automobile manufacturers.

UTQG 440 A A

60,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H426 3 GROOVE

O.E. Radial



3 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P185/65R14 85H	1007474	5.5	5.0-6.5	44	1,124	23.4	7.4	5.2	10.0	883	\$

• The Optimo H426 is Original Equipment for the selected imports from Hyundai.

UTQG 380 A A
50,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H426 4 GROOVE

O.E. Radial



4 Groove type

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P195/55R15 84V	1007475	5.5	5.0-5-7	44	1,102	23.4	7.6	5.8	10.0	885	\$
P195/65R15 89T	1009168	5.5	5.0-6.5	44	1,279	25.0	7.7	5.8	10.0	836	
P195/65R15 89S	1010208	6.0		44	1,279	25.00	7.70		10.0		
P195/50R16 84H	1011165	6.0		50	1,102	23.70	7.91				
P205/55R16 89H	1009169	6.0	5.5-7.5	44	1,279	25.1	8.0	6.3	10.0	831	
P215/45R17 91V	1005930	7.0	7.0-8.0	50	1,356	24.8	8.3	7.2	10.0	840	
P225/50R17 93H	1010878	7.0		44	1,434	25.91	9.17		11.0		
P215/55R17 93V	1007623	7.0	6.0-7.5	44	1,433	26.1	8.3	6.5	10.0	801	
P225/45R18 91V	1010211	7.5		44	1,356	25.90	8.90		10.0		
P255/45R20 101V	1010281	8.5		50	1,819	29.06	10.04				

• The Optimo is Original Equipment for the selected imports from Hyundai.

UTQG 380 A A
50,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H725

O.E. Radial



Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P195/60R15 87T	1005508	6.0	5.5-7.0	44	1,190	24.4	8.2	6.4	9.5	851	\$
P235/60R17 100T	1006957	7.0	6.5-8.5	44	1,742	28.1	9.5	7.9	10.0	739	
P235/55R18 99H	1006986*	7.5	6.5-8.5	44	1,709	28.0	9.3	7.9	8.5	741	
P235/55R18 99T	1010731	7.5	6.5-8.5	44	1,709	28.0	9.3	7.9	11.0	741	
P235/55R19 101H	1007237	7.5	6.5-8.5	44	1,819	29.2	9.7	7.9	10.0	711	
P235/55R19 101H	1008187	7.5	6.5-8.5	44	1,819	29.2	9.7	7.9	11.0	711	

• Optimo H725 is Original Equipment tire for the selected models from Ford and Saturn.

UTQG 620 B B
***UTQG 620 A B**
80,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK OPTIMO H725A

O.E. Radial



Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
Type A											
205/55R16 91H	1007836	6.5	5.5-7.5	44	1,356	24.9	8.4	6.9	11.0	835	\$
P225/45R17 90H	1009277	7.5	7.0-8.5	44	1,323	25.1	8.6	8.2	10.0	828	
P225/50R17 93S	1007078	7.0	6.0-8.0	44	1,433	25.9	9.4	7.1	11.0	802.1	
Type B											
P205/55R16 89H	1006653	6.5	5.5-7.5	44	1,279	24.7	8.7	6.6	11.0	841	

• Optimo H725A is Original Equipment tire for the selected models from Saturn, Chevrolet, and Pontiac.

UTQG 340 A A
50,000 Mile
Tread Life Warranty
ROAD HAZARD

HANKOOK RA07

O.E. Radial



UTQG 440 A B
50,000 Mile
Tread Life Warranty

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
225/75R16 104T	1005039	6.0	6.0-7.5	44	1,984	29.3	8.8	6.4	11.0	709	
245/70R17 108T	1008264	7.0	6.5-8.0	44	2,205	30.6	9.8	6.9	11.0	679	
265/60R18 109T	1009964	8.0	7.5-9.5	44	2,271	30.5	10.7	7.5	11.0	681	

- An H & T-rated premium radial for all-season PCR types 4x4s ensures superior traction and handling with exceptional on-and-off-road performance.
- Wide tread design yields precise steering response, while multi-kerfs provide the smooth, comfortable ride of a passenger tire.
- Extra-strong bead filler coupled with a nylon edge cover combine to create precision steering and stability.

HANKOOK DYNAPRO HP RA23

O.E. Radial



UTQG 500 A A

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P225/70R16 101T	1007288	6.5	6.0-7.5	44	1,819	28.4	9.0	6.5	11.0	731	\$
P245/65R17 105T	1007374	7.0	7.0-8.5	44	2,039	29.4	9.7	7.1	11.0	706	
P245/60R18 104T	1007375	7.0	7.0-8.5	44	1,984	29.4	9.7	7.3	11.0	707	

50,000 Mile Tread Life Warranty
ROAD HAZARD

- Dynapro HP is Original Equipment tire for the Hyundai Vera Cruz.

HANKOOK DYNAPRO AS RH03

O.E. Radial



UTQG 440 B A

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
P235/65R17 103T	1005421	7.0	6.5-8.5	44	1,929	29.0	10.0	7.6	11.5	716	\$
P235/70R17 108S	1003240	7.0	6.0-8.0	41	2,205	30.0	9.4	7.2	12.0	692	
LT245/75R16/10	2000801	7.0	6.5-8.0	44	2,205	30.4	9.8	7.2	14.0	683	

50,000 Mile Tread Life Warranty
ROAD HAZARD

- All-Season rib designed to match OEM performance.
- A solid shoulder rib provides responsive handling and even wear.
- The interlocking intermediate ribs and high sipe density provide a smooth and quiet ride with great traction
- Premium tread compound yields excellent wear and traction performance.

HANKOOK DYNAPRO AS RH03

All-Season Highway Rib



UTQG 440 A B
50,000 Mile
Tread Life Warranty
ROAD HAZARD

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
OUTLINE WHITE LETTERS											
P225/70R15 100S	1006758	6.5	6.0-7.5	44	1,753	27.4	8.9	6.7	12.0	758	\$
P235/70R15 102S	1006754	7.0	6.0-8.0	44	1,896	28.0	9.4	7.0	12.0	742	
P255/70R15 108S	1006755	7.5	6.5-8.5	44	2,183	29.1	10.2	7.6	12.5	714	
P225/75R15 102S	1006757	6.0	6.0-7.5	44	1,874	28.3	8.7	6.5	12.0	734	
P235/75R15 105S	1006649	6.5	6.0-8.0	44	2,028	28.9	9.2	6.8	12.0	719	
P265/75R15 112S	1006759	7.5	7.0-9.0	44	2,469	30.6	10.6	7.7	12.5	679	
P215/70R16 99S	1006949	6.5	5.5-7.0	44	1,709	27.8	8.7	6.4	12.0	747	
P225/70R16 104S	1006760	6.5	6.0-7.5	41	1,984	28.4	8.9	6.7	12.0	732	
P235/70R16 104S	1006764	7.0	6.0-8.0	44	1,984	28.0	9.4	7.0	12.0	742	
P245/70R16 107S	1005425	7.0	6.5-8.0	44	2,094	29.5	9.7	7.3	12.0	704	
P255/70R16 109S	1005426	7.5	6.5-8.5	44	2,271	30.1	10.2	7.6	12.5	690	
P265/70R16 111S	1005427	8.0	7.0-9.0	44	2,403	30.6	10.7	7.8	13.0	679	
P275/70R16 114S	1006950	8.0	7.0-9.0	44	2,601	31.0	11.1	8.2	12.5	670	
P215/75R16 101S	1007883	6.0	5.5-7.0	44	1,819	28.7	8.5	6.4	12.0	724	
P225/75R16 104S	1006762	6.0	6.0-7.5	44	1,984	29.3	8.8	6.5	12.0	709	
P235/75R16 106S	1006948	6.5	6.0-8.0	44	2,094	29.8	9.3	6.8	12.0	697	
P245/75R16 109S	1006647	7.0	6.0-8.0	44	2,271	30.4	9.8	7.1	12.0	683	
P245/65R17 105S	1006952	7.0	7.0-8.5	44	2,039	29.5	9.9	7.5	12.0	704	
P255/70R17 108S	1006765	7.5	7.0-9.0	44	2,205	30.2	10.5	7.8	12.0	688	
P265/65R17 113S	1006953	8.0	7.5-9.5	44	2,337	30.6	10.9	8.1	12.0	679	
P245/70R17 108S	1006951	7.0	6.5-8.0	44	2,205	30.5	9.7	7.3	12.0	681	
P265/70R17 113S	1006648	8.0	7.0-9.0	44	2,535	31.9	10.7	7.8	13.0	651	
BLACK LETTERS											
P235/60R17 103S	1007034	7.0	6.5-8.5	50	1,929	28.1	9.5	7.4	12.0	739	
P275/60R17 110S	1006763	8.0	8.0-8.5	44	2,337	30.0	10.9	8.6	12.0	692	
P255/70R18 112S	1007032	7.5	6.5-8.5	44	2,469	32.1	10.2	7.6	12.5	647	
P265/70R18 114S	1007033	8.0	7.0-9.0	44	2,601	32.6	10.7	7.9	12.5	637	

- P & LT Metrick light truck/SUV tire with all-season, all-terrain applications.
- Computerized tread pattern created for optimal performance on all road surfaces and in all seasons.
- Tread design created for optimal handling and a quiet, comfortable ride.
- Robust footprint shape ensures even pressure distribution, precise handling, even treadwear and long life.

HANKOOK DYNAPRO AS RH03

Highway All-Season



**40,000 Mile
Tread Life Warranty**

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Single Max Load	Single Dual Max Load	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
OUTLINE WHITE LETTERS													
LT215/75R15/6	2000905	6.0	5.5-7.0	50	1,765	50	1,610	27.6	8.5	6.3	14.5	753	\$
LT235/75R15/6	2000910	6.5	6.0-7.0	50	1,985	50	1,820	28.8	9.3	6.9	15.5	721	
BLACK LETTERS													
LT225/75R16/10	2000908	6.0	6.0-7.0	80	2,680	80	2,470	29.3	8.8	6.7	14.5	709	
LT265/75R16/10	2000923	7.5	7.0-8.0	80	3,415	80	3,085	31.6	10.5	7.9	16.5	657	
LT215/85R16/10	2000906	6.0	5.5-7.0	80	2,680	80	2,470	30.3	8.5	6.1	14.5	686	
LT235/85R16/10	2000911	6.5	6.0-7.5	80	3,042	80	2,778	31.8	9.4	6.6	15.5	653	
LT235/80R17/10	2001291	6.5	6.0-7.5	80	3,085	80	2,835	31.7	9.5	6.7	16.5	655	
LT245/70R17/10	2001314	7.0	6.5-8.0	80	3,000	80	2,755	30.5	9.8	7.2	16.5	681	
LT265/70R17/10	2000921	8.0	7.0-8.5	80	3,195	80	2,910	31.6	10.7	7.8	16.5	657	
LT245/75R17/10	2000919	7.0	6.0-7.5	80	3,195	80	2,910	31.5	9.8	7.2	16.5	660	

*O.E. Ford E-350

HANKOOK DYNAMIC AT RF08

P-metric Light Truck / SUV



**UTQG 450 B A
50,000 Mile
Tread Life Warranty
ROAD HAZARD**

- A P-Metric light truck/SUV tire with all-season, all-terrain applications.
- Computerized tread pattern created for optimal performance on all road surfaces and in all seasons.
- Tread design created for optimal handling and a quiet, comfortable ride.
- Robust footprint shape ensures even pressure distribution, precise handling, even treadwear and long life.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	PSI	Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
OUTLINE BLACK LETTERS											
P235/70R15 102S	1006511	7.0	6.0-8.0	44	1,896	28.0	9.4	6.9	12.5	742	
P265/70R15 110S	1006504	8.0	7.0-9.0	44	2,337	29.6	10.6	7.8	13.0	702	
P215/75R15 100S	1006512	6.0	5.5-7.0	44	1,742	27.6	8.5	6.2	12.5	753	
P235/75R15 108S	1006509	6.5	6.0-8.0	50	2,183	28.9	9.3	6.8	12.5	719	
P255/65R16 106S	1006516	7.5	7.0-8.0	44	2,094	29.0	10.2	7.8	13.0	716	
P225/70R16 101S	1006518	6.5	6.0-7.5	44	1,819	28.4	8.9	6.7	12.5	732	
P235/70R16 106S	1006508	7.0	6.0-8.0	44	1,984	28.9	9.4	6.9	12.5	719	
P245/70R16 106S	1006506	7.0	6.5-8.0	44	2,094	29.5	9.7	7.2	12.5	704	
P255/70R16 109S	1006503	7.5	6.5-8.0	44	2,271	30.1	10.2	7.6	13.5	690	
P265/70R16 112S	1006505	8.0	7.0-8.5	44	2,403	30.6	10.7	7.8	13.0	679	
P245/75R16 109S	1006510	7.0	6.5-8.0	44	2,271	30.4	9.9	7.0	13.0	683	
P265/75R16 112S	1006513	7.5	7.0-9.0	44	2,601	31.6	10.6	7.6	13.0	657	
P275/60R17 110S	1006521	8.0	8.0-8.5	44	2,337	30.0	10.9	8.6	13.0	692	
P235/65R17 103S	1006522	7.0	6.5-8.5	44	1,929	29.2	9.4	7.2	12.5	711	
P255/70R17 110S	1006523	7.5	6.5-8.5	44	2,205	31.3	10.3	7.5	13.0	664	
P235/75R17 108S	1002438*	6.5	6.5-8.0	35	2,205	30.9	9.4	7.2	13.0	672	

*O.E. Ford F-150

COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222



BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-283-0416 • Fax 503-240-3342
Toll Free: 1-866-977-8473

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78218
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

PHOENIX

601 South 65th Avenue, Suite 6
Phoenix, AZ 85043
Local 623-474-4660 • Fax 623-474-4661
Toll Free: 1-855-825-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO/MICHIGAN

14801 TR 212
Findlay, OH 45840
Local 419-425-6508 • Fax 419-425-6514
Toll Free: 1-877-309-1972



HANKOOK

155



- Premium Aggressive all-terrain tire for light truck, van and sport utility vehicles.
- Innovative tread and sidewall design to enhance the style of your vehicle. Developed for high powered pickups.
- The Dynapro ATm offers the best grip and acceleration both on-and off-road.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
OUTLINE WHITE LETTER													
P255/65R16	1008665	7.5	7.0-9.0	44	2,094			29.1	10.2	7.9	13.0	714	\$
P225/70R16	1008666	6.5	6.0-7.5	44	1,819			28.4	9.0	7.0	13.0	732	
P235/70R16	1008717	7.0	6.0-8.0	50	2,149			29.0	9.5	7.3	13.0	716	
P245/70R16	1008668	7.0	6.5-8.0	44	2,094			29.5	9.8	7.6	13.0	704	
P255/70R16	1008669	7.5	6.5-8.5	44	2,271			30.1	10.2	7.9	13.0	690	
P265/70R16	1009326	8.0	7.0-9.0	44	2,403			30.6	10.7	8.2	13.0	679	
225/75R16	1008718	6.0	6.0-7.5	50	2,094			29.3	8.8	7.0	13.0	709	
P235/75R16	1008719	6.5	6.0-8.0	50	2,271			29.8	9.3	7.3	13.0	697	
P245/75R16	1008672	7.0	6.5-8.0	44	2,271			30.5	9.8	7.6	13.0	681	
P265/75R16	1008708	7.5	7.0-9.0	44	2,601			31.7	10.5	8.2	13.0	655	
P235/65R17	1008720	7.0	6.5-8.5	44	1,929			29.1	9.5	7.3	13.0	714	
P245/65R17	1008673	7.0	7.0-8.5	44	2,028			29.5	9.8	7.6	13.0	704	
P255/65R17	1008674	7.5	7.0-9.0	44	2,205			30.1	10.2	7.9	13.0	690	
P265/65R17	1008675	8.0	7.5-9.5	44	2,337			30.6	10.7	8.2	13.0	679	
P245/70R17	1008676	7.0	6.5-8.0	44	2,205			30.6	9.8	7.6	13.0	679	
P255/70R17	108677	7.5	6.5-8.5	44	2,337			31.1	10.2	7.9	13.0	668	
P265/70R17	1008678	8.0	7.0-9.0	44	2,535			31.7	10.7	8.2	13.0	655	
P235/75R17	1009328	6.5	6.0-8.0	44	2,205			30.9	9.3	7.3	13.0	672	
P245/75R17	1009518	7.0	6.5-8.0	44	2,337			31.5	9.8	7.6	13.0	659	
P255/75R17	1009519	7.0	6.5-8.5	44	2,535			32.1	10.0	7.9	13.0	647	
P255/60R18 107T	1009659	7.5	7.0-9.0	44	2,149			30.0	10.2	7.9	13.0	692	
P265/60R18	1008681	8.0	7.5-8.5	44	2,271			30.5	10.7	8.2	13.0	681	
P265/65R18	1009521	8.0	7.5-9.5	44	2,469			31.5	10.7	8.2	13.0	659	
P275/65R18	1009329	8.0	7.5-9.5	44	2,601			32.1	11.0	8.6	13.0	647	
P255/70R18	1009520	7.5	6.5-8.5	44	2,601			32.1	10.2	7.9	13.0	647	
P265/70R18	1009330	8.0	7.0-9.0	44	2,601			32.6	10.7	8.2	13.0	637	
305/50R20	1009331	9.5	8.5-11.0	50	3,086			32.1	12.4	9.5	13.0	648	
275/55R20	1009332	8.5	7.5-9.5	50	2,833			31.9	11.2	8.6	13.0	651	
275/60R20	1009333	8.0	7.5-9.5	44	2,601			33.0	11.0	8.6	13.0	630	
305/45R22	1009334	10.0	9.5-11.5	50	2,910			32.8	11.9	9.5	13.0	633	
BLACK LETTER													
LT235/75R15/6	2001372	6.5	6.0-7.0	50	1,985	50	1,820	28.9	9.3	7.1	16.5	716.0	
30X9.50R15/6	2001369	7.5	6.5-8.5	50	1,990			29.5	9.4	7.2	16.5	699.5	
31X10.50R15/6	2001370	8.5	7.0-9.0	50	2,250			30.5	10.6	8.1	16.5	676.9	
33x12.50R15/6	2001371	10.0	9.0-11.0	35	2,205			32.5	12.5	9.6	16.5	635.1	
LT265/70R16/8	2001373	7.5	7.0-8.0	50	2,335	50	2,150	30.6	10.7	8.0	16.5	674.3	
LT305/70R16/10	2001403	9.0	8.0-9.5	65	3,525	65	3,195	32.8	12.3	9.3	16.5	632.5	
LT225/75R16/10	2001375	6.0	5.5-7.0	80	2,680	80	2,470	29.3	8.8	6.9	16.0	705.1	
LT245/75R16/10	2001376	7.0	6.5-7.5	80	3,042	80	2,778	30.5	9.8	7.2	16.5	677.8	
LT265/75R16/10	2001312	7.5	7.0-8.0	80	3,415	80	3,085	31.7	10.5	8.1	16.5	652.5	
LT285/75R16/10	2001378	8.0	7.5-9.0	80	3,805	80	3,460	32.8	11.4	8.6	16.5	632.7	
LT315/75R16/8	2001404	8.5	8.0-10.0	50	3,195			34.6	12.4	9.6	16.5	600.8	
LT215/85R16/10	2001380	6.0	5.5-7.0	80	2,680	80	2,470	30.4	8.5	6.5	16.0	679.5	
LT235/85R16/10	2001381	6.5	6.0-7.0	80	3,042	80	2,778	31.7	9.3	7.0	16.5	650.9	
LT245/70R17/10	2001382	7.0	6.5-8.0	80	3,000	80	2,775	30.6	9.8	7.4	16.5	679.9	
LT265/70R17/10	2001383	8.0	7.0-8.5	80	3,195	80	2,910	31.7	10.6	8.0	16.0	656.3	
LT285/70R17/10	2001405	8.5	7.5-9.0	80	3,750	80	3,415	32.8	11.6	8.7	16.5	634.2	
LT295/70R17/10	2001588	8.5	7.5-10.0	80	3,195	80	2,910	33.3	11.7	9.0	16.5	624.0	
LT315/70R17/8	2001402	9.5	8.5-10.0	50	3,195	50	2,910	34.4	12.4	9.6	16.5	603.7	
LT245/75R17/10	2001386	7.0	6.5-7.5	80	3,195	80	2,910	31.5	9.8	7.4	16.0	659.5	
LT235/80R17/10	2001387	6.5	6.0-7.5	80	3,085	80	2,835	31.8	9.3	7.1	16.5	653.0	
LT325/60R18/10	2001427	9.5	9.0-12.0	65	3,525	65	3,195	33.3	13.0	9.8	16.0	622.8	
LT275/65R18/10	2001406	8.0	7.5-9.0	80	3,415	80	3,085	32.1	11.0	8.3	16.4	647.4	
LT285/65R18/8	2001418	8.5	8.0-10.0	65	3,195	65	2,910	32.6	11.5	8.7	16.0	619.4	
LT325/65R18/10	2001428	9.5	9.0-10.0	65	3,860	65	3,525	34.6	13.0	9.9	16.0	600.1	
LT275/70R18/10	2001419	8.0	7.0-8.5	80	3,640	80	3,305	33.2	11.0	8.3	16.0	607.7	
LT285/55R20/10	2001432	9.0	8.0-10.0	65	2,835	80	2,600	32.4	11.7	8.7	16.0	641.8	
LT305/55R20/10	2001433	9.5	8.5-11.0	65	3,195	65	2,910	33.2	12.4	9.2	16.0	625.0	
LT325/60R20/10	2001429	9.5	9.0-12.0	65	3,750	65	3,415	35.4	13.0	9.8	16.0	587.5	
LT275/65R20/10	2001431	8.0	7.5-9.0	80	3,750	80	3,415	32.6	11.0	8.3	16.0	636.3	
LT325/50R22/10	2001430	10.0	9.0-12.0	65	3,305	65	3,085	36.1	13.2	9.8	16.0	575.3	

visit us at:



OPEN 24 HRS / 7 DAYS A WEEK

HANKOOK DYNAPRO AS RT03

Mud Terrain



- The Dynapro MT RT03 is a rugged tire designed for "true off-road drivers".
- The "V" shaped tread blocks are tapered for better grip in mud or sand and you should see them perform in snow.
- There are "ejectors" built into the tread grooves to prevent stones from penetrating.
- Specifically designed shoulders keep dirt from building up and to help prevent damage from impacts.

Tire Size	Code No.	Measuring Rim	Approved Rim Width	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T
OUTLINE WHITE LETTERS														
LT305/70R16/8	2001220	8.0	8.0-9.5	50	2,910	50	2,680	33.1	12.2	9.4	19.0	628	\$	
LT265/75R16/10	2001027	7.5	7.0-8.0	80	3,415	80	3,085	31.9	10.8	8.2	18.0	652		
LT285/75R16/10	2001028	8.0	7.5-9.0	80	3,750	80	3,415	33.0	11.6	8.7	18.5	629		
LT295/75R16/8	2001219	8.0	7.5-9.0	65	3,415	65	3,085	33.6	11.6	9.0	19.0	618		
LT315/75R16/10	2001295	8.5	8.0-10.0	65	3,860			34.8	12.3	9.4	20.0	597		
35X12.50R15LT/6	2001270	10.0	8.5-11.0	65	2,535			34.8	12.9	9.8	19.0	597		
BLACK LETTERS														
LT215/75R15/6	2000981	6.0	5.5-7.0	50	1,765	50	1,610	27.9	8.4	6.8	17.0	745		
LT235/75R15/6	2000978	6.5	6.0-7.0	50	1,985	50	1,820	29.1	9.1	7.2	18.5	714		
LT225/75R16/10	2001285	6.0	6.0-7.0	80	2,680	80	2,470	29.4	8.9	6.9	16.5	705		
LT245/75R16/10	2001283	7.0	6.5-8.0	80	3,042	80	2,778	30.7	9.9	7.7	16.5	676		
LT215/85R16/10	2001286	6.0	5.5-7.0	80	2,680	80	2,470	30.6	8.8	6.8	17.0	678		
LT235/85R16/10	2001287	6.5	6.0-7.5	80	3,042	80	2,778	32.0	9.5	7.2	16.5	650		
LT265/70R17/10	2001269	7.5	7.0-8.0	80	3,195	80	2,910	31.9	10.7	8.3	18.5	651		
LT285/70R17/8	2001222	8.5	7.5-9.0	65	3,195	65	2,910	33.0	11.5	8.9	18.5	630		
LT315/70R17/8	2001223	9.5	8.5-10.0	50	3,195	50	2,910	34.6	12.7	9.7	20.0	600		
LT255/75R17	2001560	7.0	6.5-8.5	80	3,195	80	2,910	32.1	10.0	7.8	18.5	647		
LT325/60R18/10	2001227	9.5	9.5-10.5	65	3,525	65	3,195	33.6	13.0	10.1	20.0	618		
LT275/65R18/10	2001300	8.0	7.5-9.0	80	3,415	80	3,085	32.3	11.0	8.7	18.5	643		
LT325/65R18/10	2001226	9.5	9.0-10.0	65	3,860	65	3,525	34.8	13.0	10.1	20.0	597		
30X9.50R15LT/6	2000976	7.5	6.0-8.5	50	1,985			29.8	9.5	7.6	18.5	697		
31X10.50R15LT/6	2000789	8.5	7.0-9.0	50	2,270			30.7	10.6	8.4	19.0	677		
32X11.50R15LT/6	2000980	9.0	8.0-10.0	50	2,535			31.8	10.8	9.1	19.0	653		
33X12.50R15LT/6	2000977	10.0	8.0-11.0	50	2,225			32.8	12.2	9.8	19.0	633		
35X12.50R17LT/10	2001297	10.0	8.5-11.0	65	3,525			34.8	12.9	9.8	20.0	597		
37X12.50R17LT/10	2001301	10.0	8.5-11.0	65	4,080			36.8	12.9	9.8	21.0	565		
33X12.50R18LT/10	2001558	10.0	8.5-11.0	65	2,910			32.5	12.5	7.8	18.5	639		
35X12.50R18LT/10	2001298	10.0	8.5-11.0	65	3,415			34.8	12.9	9.8	20.0	597		
37X12.50R18LT/8	2001275	10.0	8.5-11.0	50	3,415			36.8	12.9	9.8	20.5	565		
33X12.50R20LT/10	2001559	10.0	8.5-11.0	65	2,600			32.5	12.5	10.4	18.5	639		
35X12.50R20LT/10	2001277	10.0	8.5-11.0	65	3,195			34.8	12.9	9.8	20.5	597		
37X13.50R20LT/10	2001276	11.0	8.5-11.0	50	3,860			36.8	13.6	10.9	21.0	565		
38X15.50R20LT/8	2001281	12.0	11.0-13.0	50	3,640			37.8	15.4	12.3	21.0	550		
37X13.50R22LT/10	2001278	11.0	8.5-11.0	50	3,420			36.8	13.6	10.9	21.0	565		
40X15.50R22LT/8	2001279	12.0	11.0-13.0	50	3,860			39.8	15.4	12.3	21.0	522		

HANKOOK DYNAMIC RF04

All-Terrain



Tire Size	Code No.	Measuring Rim	Approved Rim Width	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
OUTLINE WHITE LETTER													
LT235/75R15/6	2001160	6.5	6.0-7.0	50	1,985	50	1,820	29.0	9.3	6.9	16.5	716	\$
LT265/75R16/6	2001170	7.5	7.0-8.0	50	2,470	50	2,270	31.7	10.5	7.9	16.5	655	
LT235/85R16/10	2001168	6.5	6.0-7.5	80	3,042	80	2,778	31.8	9.4	6.7	16.5	653	
30X9.50R15/6	2001156	7.5	6.5-8.5	50	1,990			29.4	9.7	7.1	16.5	707	
31X10.50R15/6	2001157	8.5	7.0-9.0	50	2,250			30.5	10.8	7.9	16.5	681	
BLACK LETTERS													
LT245/75R16/10	2001164	7.0	6.5-7.5	80	3,042	80	2,778	30.5	9.7	7.2	16.5	681	
LT215/85R16/10	2001159	6.0	5.5-7.0	80	2,680	80	2,470	30.4	8.5	6.1	16.0	683	

- Designed for on and off-road performance.
- Computer optimized profile and construction offer superior shock dampening and durability.
- Tightly linked shoulder elements aid responsive handling and resistance to irregular wear while still providing all-terrain grip.
- Optimized sipe density and premium tread compound combine to offer superb wear and traction.

HANKOOK F19

Highway Rib



Tire Size	Code No.	Measuring Rim	Approved Rim Width	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE
7.50R16LT/14	2000863	6.0	5.5-7.0	105	3,330	105	3,175	31.9	8.4	5.9	14.5	651	\$

- Bold tread design provides excellent driving stability.
- Asymmetric groove angles reduce groove cracks to a minimum.
- Uneven abrasion is diminished by the insertion of kerf on the shoulder area.
- Four straight grooves channel water for superior traction.

HANKOOK AL07

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
11R22.5/14	.3001538	.8.25	.105	.6,175	.105	.5,840	.41.4	.11.1	.8.4	.18	.502\$
11R24.5/14	.3001540	.8.25	.105	.6,610	.105	.6,005	.43.5	.11.0	.8.5	.18	.478
295/75R22.5/14	.3001544	.9.00	.110	.6,175	.110	.5,675	.40.2	.11.6	.8.4	.18	.517
285/75R24.5/14	.3001542	.8.25	.110	.6,175	.110	.5,675	.41.4	.10.9	.8.5	.18	.502

Long Haul Steering

- Designed with Hankook's UMS technology, the AL07 revolutionizes long haul applications.
- UMS optimizes the tire plyline, giving the lowest possible belt edge stress.
- The tire deflection is precisely engineered for maximum performance.
- This advanced construction also yields outstanding footprint pressure distribution - the key to long and even wear.

HANKOOK DL01

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
11R24.5/14	.3000829						.44.1	.11.2	.8.2	.30.0	.496\$
11R22.5/16	.3000957	.8.25	.120	.6,610	.120	.6,005	.42.1	.11.2	.8.2	.30.0	.496
295/75R22.5/14	.3000598						.41.0			.30.0	
11R24.5/16	.3000958	.8.25	.120	.7,160	.120	.6,610	.44.1	.11.0	.8.2	.30.0	.471

Long Distance Drive Axle Tire

- Extra deep tread, exceptional traction and high mileage are all built in to the DL01.
- Designed to provide a new level of performance in all driving conditions, the DL01 features casing profile technology for higher durability and easy retreading.

HANKOOK DL07

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
285/75R24.5/14	.3001587	.8.25	.110	.6,175	.110	.5,675	.42.2	.11.3	.9.3	.31	.492\$

Developed with an aggressive block pattern, the DL07 will provide superior traction for line-haul applications. The wider, deeper grooves with enhanced stone ejector platforms will prevent stone drilling and maximize removal mileage. Advanced tread design and carcass construction provides even wear patterns, equal weight/torque distribution, reduced heat buildup, and increased fuel efficiency.

HANKOOK TL01

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
11R22.5/14	.3001450	.8.3	.105	.6,175	.105	.5,840	.41.0	.11.0	.8.3	.12.0	.501\$
11R24.5/14	.3001451	.8.3	.105	.6,610	.105	.6,005	.43.0	.11.0	.8.3	.12.0	.483
285/75R24.5/14	.3001452	.8.25	.105	.6,175	.105	.5,675	.41.2	.11.1	.8.3	.12.0	.501
295/75R22.5/14	.3001158	.9.00	.110	.6,175	.110	.5,675	.39.8	.11.1	.8.2	.12.0	.505

HANKOOK AH12

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
255/70R22.5/16	.3001014	.7.50	.120	.5,510	.120	.5,070	.36.6	.9.8	.7.8	.17	.568\$
10R22.5/14	.3000952	.7.50	.115	.5,675	.115	.5,355	.40.1	.10.2	.7.1	.16	.518
11R22.5/14	.3001518	.8.25	.105	.6,175	.105	.5,840	.41.5	.11.1	.8.3	.19	.501
11R22.5/16	.3001519	.8.25	.120	.6,610	.120	.6,005	.41.5	.11.1	.8.3	.19	.501
11R24.5/14	.3001533	.8.25	.105	.6,610	.105	.6,005	.43.4	.11.0	.8.2	.18	.479
11R24.5/16	.3001534	.8.25	.120	.7,160	.120	.6,610	.43.4	.11.0	.8.2	.18	.479
295/75R22.5/14	.3000947	.9.00	.110	.6,175	.110	.5,675	.40.2	.11.5	.8.6	.18	.517
285/75R24.5/14	.3000949	.8.25	.110	.6,175	.110	.5,675	.41.4	.11.3	.8.7	.18	.502
275/70R22.5/16	.3001054	.8.25	.131	.6,945	.131	.6,395	.37.9	.10.9	.8.1	.19	.548

HANKOOK AM06

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
10.00R20/16 TT	3000860	7.50	120	6,610	120	6,005	41.6	11.1	8.4	23	500	\$
12.00R20/18 TT	3000915	8.50	120	8,270	120	7,610	44.3	12.2	9.4	23	469	
11R22.5/16 TL	3000836						41.7			23		
12R22.5/16 TL	3000478						43.0			23		
12.00R24/18 TT	3001002	8.50	120	9,370	120	8,540	48.1	12.2	8.5	21	432	
11R24.5/16	3000994	8.25	120	7,160	120	6,610	43.7	11.1	8.3	23	475	
315/80R22.5/20	3001310	9.00	130	10,000	130	9,090	42.8	12.4	9.4	23	485	

HANKOOK AH11

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
215/75R17.5/12	3000771	6.00	100	3,750	100	3,530	30.5	8.2	6.7	16	681	\$
235/75R17.5/14	3000896	6.75	110	4,410	110	4,190	31.7	9.4	8.0	17	655	
8R19.5/12	3000869	6.00	110	3,525	110	3,305	33.6	7.9	5.3	16	618	
225/70R19.5/12	3001466	6.75	95	3,640	95	3,415	32.2	8.9	7.0	16	645	
245/70R19.5/14	3001059	7.50	110	4,540	110	4,300	33.2	9.6	8.0	17	625	
265/70R19.5/14	3001060	7.50	110	5,070	110	4,675	34.3	10.2	8.3	17	607	
9.00R20/14 TT	3000797	7.00	115	5,675	115	5,355	40.2	10.1	6.9	17	517	
10.00R20/16 TT	3000791	7.50	120	6,610	120	6,005	41.5	11.1	8.4	20	500	
11.00R20/16 TT	3000793	8.00	120	7,390	120	6,780	42.7	11.8	8.3	20	487	
12R22.5/16 TT	3000792	9.00	120	7,390	120	6,780	42.8	11.8	8.3	20	486	
11R24.5/16 TT	3001091	8.25	120	7,160	120	6,610	43.5	11.1	8.7	20	478	
315/80R22.5/20TT	3001453	9.00	130	9,000	130	8,255	42.5	12.4	9.5	21	489	

HANKOOK AH10

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
385/65R22.5/18	3001016	11.75	120	9,370			42.3	15.0	11.3	21	491	\$
425/65R22.5/20	3001018	13.00	125	11,400			44.3	16.3	12.1	21	469	

HANKOOK AM02

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
385/65R22.5/18	3000082	11.75	120	9,370			42.3	15.0	11.3	21	491	\$
425/65R22.5/20	3001389	13.00	125	11,400			44.3	16.7	12.4	21	469	
445/65R22.5/20	3000808	14.00	130	12,800			45.8	17.7	13.9	23	454	

HANKOOK TH10

Medium Truck Radial



Tire Size	Code No.	Measuring Rim	Single PSI	Single Max Load	Dual PSI	Dual Max Load	Overall Dia. (In.)	Section Wid. (In.)	Tread Width (32/In)	Tread Depth	Revs/ Mile	PRICE	F.E.T.
215/75R17.5/16	3001529	6.00	125	4,805	125	4,540	30.4	8.3	6.8	16	683	\$
235/75R17.5/16	3001530	6.75	125	6,005	125	5,675	31.4	9.4	7.9	15	662	
245/70R17.5/16	3001531	7.50	125	6,005	125	5,675	31.4	9.8	8.0	15	662	