



HERCULES TIRES®

RIDE ON OUR STRENGTH.

ULTRA TOURING



UTQG 620 AB

Designed for long treadlife and a quiet ride. Sizes that complement today's original equipment fits. Noise tests prove this is one of the quietest tires you can get.

**70,000 Mile
Tread Life
Warranty**

**1st 50%
Free Replacement
Warranty**

TR

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
WHITEWALL									
205/70R15 96T	.02542	6.0	1565	44	21.5	11.0	26.34	8.23	\$
215/70R15 98T	.02544	6.5	1653	44	23.2	11.0	26.89	8.70	
235/70R15 103T	.02545	7.0	1929	44	27.0	11.0	27.99	9.55	
225/60R16 98T	.02540	6.5	1653	44	25.3	11.0	26.61	8.98	
225/60R17 99T	.02561	6.5	1709	44	27.0	11.0	27.62	9.14	
BLACKWALL									
185/70R14 88T	.02576	5.5	1235	44	18.2	11.0	24.25	7.44	
195/70R14 91T	.02578	6.0	1356	44	19.9	11.0	24.80	8.05	
205/70R15 96T	.02580	6.0	1565	44	21.5	11.0	26.34	8.23	
215/70R15 98T	.02582	6.5	1653	44	23.0	11.0	26.89	8.70	
185/65R14 86T	.02562	5.5	1168	44	18.6	11.0	23.46	7.44	
185/65R15 88T	.02566	5.5	1235	44	19.6	11.0	24.45	7.44	
195/65R15 91T	.02568	6.0	1356	44	20.6	11.0	25.00	7.91	
205/65R15 94T	.02570	6.0	1477	44	21.4	11.0	25.47	8.23	
215/65R15 96T	.02572	6.5	1565	44	23.1	11.0	26.02	8.70	
205/65R16 95T	.02573	6.0	1521	44	23.0	11.0	26.47	8.30	
215/65R16 98T	.02574	6.5	1653	44	25.5	11.0	27.01	8.70	
235/65R16 103T	.02575	7.0	1929	44	27.0	11.0	27.93	9.56	
215/65R17 99T	.02563	6.5	1709	44	26.0	11.0	27.14	9.03	
185/60R15 84T	.02549	5.5	1102	44	20.0	11.0	23.76	7.44	
195/60R15 88T	.02550	6.0	1235	44	20.5	11.0	24.21	7.91	
205/60R15 91T	.02552	6.0	1356	44	21.5	11.0	24.69	8.23	
215/60R15 94T	.02554	6.5	1477	44	21.7	11.0	25.16	8.70	
215/60R16 95T	.02556	6.5	1521	44	23.5	11.0	26.14	8.70	
225/60R16 98T	.02558	6.5	1653	44	25.3	11.0	26.61	8.98	
215/60R17 96T	.02559	6.5	1565	44	26.0	11.0	27.14	9.03	
235/60R17 102T	.02577	7.0	1874	44	28.3	11.0	28.09	9.53	
205/55R16 90T	.02546	6.5	1356	44	22.7	11.0	24.88	8.56	
225/55R17 97T	.02548	7.0	1609	44	28.3	11.0	26.76	9.20	

30 DAY
"TRUST OUR RIDE"
 TEST DRIVE



UTQG 420 AA

**50,000 Mile
Tread Life
Warranty**

**1st 50%
Free Replacement
Warranty**



UTQG 360 AA

**40,000 Mile
Tread Life
Warranty**

**1st 50%
Free Replacement
Warranty**

HR

Tire Size	Code No.	Rim Width	Max. Load	Max. PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
BLACKWALL									
195/65R15 91H	03946	6.0	1356	44	21.0	11.0	24.97	8.02	\$
205/65R15 94H	03949	6.0	1477	44	22.0	11.0	25.41	8.34	
185/60R14 82H	03961	5.5	1047	44	18.0	11.0	22.73	7.48	
195/60R14 86H	03955	6.0	1168	44	19.0	11.0	23.20	7.97	
195/60R15 88H	03945	6.0	1235	44	20.0	11.0	24.20	8.03	
205/60R15 91H	03952	6.0	1356	44	22.0	11.0	24.65	8.29	
205/60R16 91H	03940	6.0	1389	44	23.0	11.0	25.65	8.49	
225/60R16 98H	03938	6.5	1653	44	25.0	11.0	26.56	9.08	
235/60R16 100H	03943	7.0	1764	44	28.0	11.0	27.10	9.52	
205/55R16 90H	03944	6.5	1356	44	22.0	11.0	24.86	8.95	
215/55R16 93H	03947	7.0	1433	44	23.0	11.0	25.27	8.87	
225/55R16 95H	03942	7.0	1521	44	25.0	11.0	25.77	9.29	
235/55R17 99H	03936	7.5	1709	44	28.0	11.0	27.15	9.94	
205/60R16 87H	03950	6.5	1201	44	21.0	11.0	24.10	8.32	
225/60R18 100H	03948	6.5	1709	44	30.5	11.0	28.62	8.98	

VR

Tire Size	Code No.	Rim Width	Max. Load	Max. PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
BLACKWALL									
205/65R15 94V	03971	6.0	1323	44	22.0	11.0	25.41	8.22	\$
195/55R15 85V	03953	6.0	1135	44	20.0	11.0	23.43	7.92	
205/60R16 92V	03970	6.0	1389	44	23.0	11.0	25.65	8.40	
225/50R16 92V	03958	7.0	1389	44	23.0	11.0	24.89	9.15	
215/55R17 94V	03956	7.0	1477	44	26.0	11.0	26.31	9.46	
215/50R17 91V	03962	7.0	1356	44	25.0	11.0	25.46	9.34	
225/55R17 97V	03959	7.0	1609	44	27.0	11.0	26.76	9.74	
225/50R17 94V	03965	7.0	1477	44	26.0	11.0	25.89	9.66	
235/50R17 96V	03968	7.5	1565	44	28.0	11.0	26.30	9.91	

**30 DAY
"TRUST OUR RIDE"
TEST DRIVE**

Hercules Tire offers you the power of confidence with our free 30 day "Trust Our Ride" test drive on any set of our quality RoadTour™, Tour 4.0 Plus or Ultra Touring passenger tires.

RIDE ON OUR STRENGTH.

HERCULES TIRES
RIDE ON OUR STRENGTH.



**50,000 Mile
Tread Life Warranty**



**UTQG
H-Series 440 A A
T-Series A B
60,000 Mile
Tread Life Warranty**

HR

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
BLACKWALL									
195/65R15 91H	.01110	.6	.1356	.44	.22	.10.5	.24.96	.8.09	\$
205/65R15 94H	.01120	.6	.1477	.44	.23	.10.5	.25.40	.8.42	
195/60R15 88H	.01130	.6	.1235	.44	.21	.10.5	.24.16	.8.10	
205/60R15 91H	.01140	.6	.1356	.44	.22	.10.5	.24.64	.8.40	
225/60R16 98H	.01150	.6.5	.1653	.44	.25	.10.5	.26.55	.9.11	
205/55R16 91H	.01160	.6.5	.1356	.44	.23	.10.5	.24.85	.8.59	
215/55R16 93H	.01170	.7	.1433	.44	.24	.10.5	.25.24	.8.92	
225/55R16 95H	.01114	.7	.1521	.44	.26	.11	.25.76	.8.88	

TR

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
BLACKWALL									
175/65R14 82T	.01125	.5	.1047	.44	.16	.10	.22.95	.6.85	\$
185/65R14 86T	.01135	.5.5	.1168	.44	.17	.10	.23.4	.7.35	
185/65R15 88T	.01145	.5.5	.1235	.44	.18	.10	.24.4	.7.35	
185/70R14 88T	.01105	.5.5	.1235	.44	.17	.10	.24.23	.7.4	
195/65R15 91T	.01155	.6	.1356	.44	.19	.10	.24.9	.7.8	
195/70R14 91T	.01115	.6	.1356	.44	.18	.10	.24.78	.7.8	
205/55R16 91T	.01121	.6.5	.1356	.44	.21	.10	.24.64	.8.3	
205/65R15 94T	.01165	.6	.1477	.44	.20	.10.50	.25.26	.8.16	
205/70R15 96T	.01185	.6	.1565	.44	.20	.10.50	.26.18	.8.11	
215/60R16 95T	.01117	.6.5	.1521	.44	.24	.10.50	.25.93	.8.55	
215/65R15 96T	.01175	.6.5	.1565	.44	.23	.10.50	.25.81	.8.65	
215/65R16 98T	.01113	.6.5	.1653	.44	.24	.10.50	.26.81	.8.65	
215/70R15 98T	.01195	.6.5	.1653	.44	.21	.10.50	.26.68	.8.58	
225/60R16 98T	.01119	.6.5	.1653	.44	.24	.10.50	.26.5	.8.8	
WHITWALL									
205/70R15 96T	.01123	.6	.1565	.44	.20	.10.50	.26.18	.8.11	
215/70R15 98T	.01127	.6.5	.1653	.44	.22	.10.50	.26.68	.8.58	
235/75R15 109S	.01133	.6.5	.2271	.41	.29	.11	.28.85	.9.4	

VR

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
BLACKWALL									
205/60R16 92V	.01122	.6	.1389	.44	.24	.11	.25.65	.8.22	\$
215/50R17 95V	.01124	.7	.1521	.50	.26	.11	.25.46	.8.72	
215/55R17 94V	.01126	.7	.1477	.44	.27	.11	.26.25	.8.75	
215/60R16 95V	.01128	.6.5	.1521	.44	.27	.11	.26.11	.8.82	
225/50R17 94V	.01118	.7	.1477	.44	.27	.11	.25.83	.8.99	



Computer optimized tread design that greatly reduces road noise and vibrations.



Touring - Tread design and siping result in superior all weather performance



IRR Tread Compounding (Increase Rolling Resistance) for the most fuel efficient tire in the Hercules passenger lineup.



Nylon Overwrap added in the green tire aids in the stability and longevity of the Roadtour 655.



Profile design and center rib results in crisp steering response and enhances overall road handling characteristics.

30 DAY
"TRUST OUR RIDE"
TEST DRIVE

TOURING 4.0 PLUS

Passenger Radial



**UTQG 440 AA
H speed**

**UTQG 540 AA
T speed**

45,000 Mile Warranty

- High performance high end touring tire, for luxury cars. Positioned against pretty much every other manufacture out there with tires for high end luxury cars.
- Phase 1-available, 2 and 3 in progress.
- Branded with the M+S symbol, the Hercules Tour 4.0 Plus provides all season capability on wet, dry and light snow.
- The asymmetrical tread design provides a smooth and quiet ride while increasing handling characteristics.
- Cross-block siping provides crisp handling in inclement weather for 4.0 seasons of superior handling.
- Silica enhanced compounds provides superior traction in wet without tread life reduction.
- Nylon overwrap enhances the Hercules Tour 4.0 Plus construction by adding uniformity and increasing ride stability.
- The stylish sidewall and asymmetrical tread design provide a high performance look with all season touring characteristics.

TR									
Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
175/70R13 82T	74897	5.0	1047	44	15	10	7.09	22.6	\$
195/75R14 92T									* COMING SOON
205/75R14 95T									* COMING SOON
185/70R14 88T									* COMING SOON
195/70R14 91T	74903	6.0	1356	44	22	10	8.03	24.72	
205/75R15 97T									* COMING SOON
215/75R15 100T									* COMING SOON
235/75R15 105T	74896	6.5	2040	44	28	11	9.21	28.82	
215/70R16 100T									* COMING SOON
215/65R16 98T	74904	6.5	1653	44	24	10	8.94	26.93	

HR									
Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
185/70R14 88H	71453	5.50	1235	44	18.7	10.0	7.44	24.25	\$
175/65R14 82H	71456	5.00	1047	44	15.9	10.0	6.97	22.99	
185/65R14 86H	71457	5.50	1168	44	18.1	10.0	7.44	23.47	
205/70R15 96H	71454	6.00	1565	44	25.4	10.0	8.23	26.34	
215/70R15 98H	71455	6.50	1653	44	27.8	10.0	8.70	26.89	
185/65R15 88H	71458	5.50	1235	44	19.2	10.0	7.44	24.45	
195/65R15 91H	71459	6.00	1356	44	22.3	10.0	7.91	25.00	
205/65R15 94H	71460	6.00	1477	44	23.1	10.0	8.23	25.47	
215/65R15 96H									* COMING SOON
185/60R15 84H									* COMING SOON
195/60R15 88H									* COMING SOON
205/60R15 91H									* COMING SOON
215/60R15 94H									* COMING SOON
235/65R16 103H									* COMING SOON
215/60R16 95H	71461	6.50	1521	44	24.9	10.0	8.70	26.14	
225/60R16 98H	71462	6.50	1653	44	26.0	10.0	8.98	26.61	
205/55R16 91H									* COMING SOON
225/60R17 99H									* COMING SOON

30 DAY
"TRUST OUR RIDE"
 TEST DRIVE

HERCULES MR IV TOURING

Passenger Radial



UTQG 480 AB

50,000 Mile Tread Life Warranty

State of the art, advanced tread design for quiet, comfortable ride and long mileage. Multiple pitch elements for smooth, quiet ride. Full lateral slots provide resistance to hydroplaning and additional traction.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
WHITEWALL									
P155/80R13 79T	39856	4.5	963	35	13.7	10.0	22.60	6.09	\$
P185/75R14 89T	39860	5.0	1279	35	16.8	11.0	24.85	7.00	
P195/75R14 92T	39861	5.5	1389	35	20.3	11.0	25.33	7.62	
P205/75R14 95T	39862	5.5	1521	35	20.7	11.0	26.02	7.84	
P205/75R15 97T	39864	5.5	1609	35	23.1	11.0	26.96	7.63	
P215/75R15 100T	39865	6.0	1764	35	24.3	11.0	27.51	8.18	
P225/75R15 102T	39866	6.0	1874	35	26.2	11.0	28.16	8.47	
P235/75R15 108T	39868	6.5	2205	41	27.8	11.0	28.81	8.92	
P215/70R14 96T	39873	6.5	1565	35	22.0	11.0	25.84	8.21	
P205/70R15 95T	39874	6.0	1521	35	21.4	11.0	26.19	7.85	
P215/70R15 97T	39875	6.5	1609	35	23.8	11.0	26.80	8.32	
P225/70R15 100T	39876	6.5	1764	35	25.6	11.0	27.31	8.52	
BLACKWALL									
P175/70R13 82T	74589	5.0	1047	35	15.0	10.0	22.50	6.61	
P185/70R14 87T	39870	5.5	1201	35	17.2	10.0	24.13	7.16	
P195/70R14 90T	39871	6.0	1323	35	19.4	10.0	24.72	7.63	
P205/70R15 95T	60275	6	1499	35	22.3	11	26.34	8.23	
P215/70R15 97T	63839	6.5	1620	35	24.5	11	26.89	8.7	
P175/65R14 81T	39877	5.0	1019	35	15.4	10.0	22.90	6.50	
P185/65R15 86T	74611	5.0	1168	35	18.7	10	24.45		NEW
P195/65R15 89T	39881	6.0	1235	35	19.8	10.0	24.88	7.57	
P195/70R15 95T									
P205/65R15 89T	39882	5.5	1279	35	21.4	11.0	25.32	7.85	
P185/60R15 84T	45411	5.5	1102	35	17.2	10	23.74	7.44	
P195/60R15 88T	45413	6	1190	35	20.2	10	24.21	7.91	
P205/60R15 91T	45414	6	1301	35	20.3	11	24.69	8.23	
P215/60R15 94T	45415	6.5	1411	35	22.9	11.0	25.16	8.70	
P215/60R16 94T	39883	6.5	1477	35	24.3	11.0	26.01	8.18	
P225/60R16 97T	39884	6.5	1521	35	24.3	11.0	26.48	8.37	
NEW P205/55R16 89T	45416	6.5	1279	35	20.5	11	24.88	8.43	

HERCULES MRX PLUS IV

Passenger Radial



UTQG 440 AB

**40,000 Mile
Tread Life Warranty**

Two full width steel belts stabilize tread for control and even wear. Slotted shoulders/wide grooves provide all weather traction and hydroplaning resistance. All season tread design for road-biting grip. Variable pitch tread design for a quiet ride. Modern computer designed tread for great looks and long mileage. M&S rated.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
WHITEWALL									
P185/75R14 89S	.01662	5.0	1290	35	18.0	10.0	24.80	7.20	
P195/75R14 92S	.01665	5.5	1400	35	19.0	10.0	25.40	7.60	
P205/75R14 95S	.01668	5.5	1532	35	20.0	11.0	25.90	8.00	
P215/75R14 98S	.01671	6.0	1664	35	22.0	11.0	27.00	8.40	
P205/75R15 97S	.01674	5.5	1598	35	21.0	11.0	27.00	8.00	
P215/75R15 100S	.01677	6.0	1742	35	24.0	11.0	27.60	8.40	
P225/75R15 102S	.01680	6.0	1874	35	25.0	11.0	28.10	8.70	
P235/75R15 105S	.01683	3.5	2128	35	26.0	11.0	28.70	9.10	
P215/70R14 96S	.01605	6.5	1554	35	21.0	10.0	25.80	8.60	
P205/70R15 95S	.01606	6.0	1499	35	22.1	10.0	26.30	8.10	
P215/70R15 97S	.01608	6.5	1620	35	22.0	10.0	26.80	8.60	
P225/70R15 100S	.01607	6.5	1753	35	24.0	10.0	27.30	8.90	
BLACKWALL									
P155/80R13	.01652	4.5	959	35	14.0	10.0	22.80	6.10	
P175/70R13 82S	.01610	5.0	1036	35	14.0	10.0	22.70	6.90	
P175/70R14 84S	.01620	5.0	1102	35	16.0	10.0	23.20	7.00	
P185/70R14 87S	.01614	5.5	1201	35	17.0	10.0	24.20	7.40	
P195/70R14 90S	.01616	6.0	1312	35	17.0	10.0	24.80	7.80	
P205/70R15 95S	.01618	6.0	1499	35	19.0	10.0	26.30	8.10	
P175/65R14 81S	.01622	5.0	1019	35	15.0	10.0	23.00	7.00	
P185/65R14 85S	.01623	5.5	1124	35	17.0	10.0	23.40	7.40	
185/65R15 88T	.02163*	5.5	1235	44	17.0	10.0	24.35	7.35	
P195/65R15 89S	.01611	6.0	1279	35	18.0	10.0	24.90	7.80	
P205/65R15 92S	.01619	6.0	1400	35	19.0	10.0	25.30	8.20	
P215/65R15 95S	.01613	6.5	1510	35	22.0	10.0	25.90	8.70	
215/65R16 98T	.02156*	6.5	1653	44	22.0	10.0	26.80	8.79	
185/60R15 84T	.02161*	5.5	1102	44	16.0	10.0	23.53	7.21	
195/60R15 88T	.02158*	6.0	1235	44	19.0	10.0	24.21	7.91	
205/60R16 92T	.02159*	6.0	1389	44	20.0	10.0	25.47	8.06	
P215/60R16 94S	.01615	6.5	1477	35	22.0	10.0	26.10	8.60	
P225/60R16 97S	.01617	6.5	1609	35	24.0	10.0	26.50	8.80	
P205/55R16 89S	.01625	6.5	1279	35	22.0	10.0	24.80	8.30	

*Coming Soon!

HERCULES RAPTIS

Metric Radial



UTQG 420 AA

**40,000 Mile
Tread Life
Warranty**

- Dual width center rib increases on-road stability at high speed
- Exterior groove contains biting edges for increased traction
- Five ribs provide a smooth, quiet and comfortable ride.
- Four channel grooves provide superior wet traction through drainage.
- All-weather performance touring.

HR 1

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
NEW 175/65R14 82H	.72943	.5J	1047	44	15.5	10	22.99	6.97	..\$
NEW 185/65R14 86H	.72944	.51/2J	1168	44	16.6	10	23.46	7.44	
NEW 185/60R14 82H	.73109	.51/2J	1047	44	15.8	8	22.75	7.44	
205/65R15 94H	.65020	.6J	1477	44	21	10.5	25.8	8.2	
NEW 185/65R15 88H	.73111	.61/2J	1235	44	18	8	24.5	7.4	
NEW 185/60R15 84H	.73110	.61/2J	1102	44	18	8	23.7	7.4	
215/60R16 95H	.65021	6.5J	1521	44	23.8	10.5	26.5	8.7	
225/60R16 98H	.65022	6.5J	1653	44	23.8	10.5	26.9	9.0	

VR 1

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
NEW 195/55R15 85V	.73125		135	44	18.4	10	23.4	7.9	..\$
195/60R15 88V	.65017	.6J	1235	44	18.3	10.5	24.5	7.9	
NEW 205/60R15 91V	.73124		1356	44	20.41	10	24.7	8.2	
195/65R15 91V	.65018	.6J	1356	44	19.5	10.5	25.3	7.9	
205/55R16 91V	.65019	6.5J	1356	44	20.3	10.5	25.2	8.4	
NEW 195/50R16 82V	.73126		1047	44	17.52	10	22.7	7.9	
215/55R17 94V	.65023	.7J	1477	44	24.7	10.5	26.6	8.9	
215/50R17 91V	.65024	.7J	1356	44	25	10.5	25.8	8.9	
225/50R17 94V	.65025	.7J	1477	44	26	10.5	26.2	9.2	

TR 1

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
155/70R13 75T	.73112	4.5	853	44	11.9	.9	21.58	6.18	..\$
165/70R13 79T	.73113	.5	963	44	13.6	9.5	22.13	6.69	
175/70R13 82T	.73114	.5	1047	44	14.5	10	22.68	6.97	
175/70R14 84T	.73115	.5	1102	44	15.4	10	23.7	6.97	
185/70R14 88T	.73116	.5	1235	44	17.2	10	24.25	7.44	
155/80R13 79T	.73117	4.5	963	44	12.9	.9	22.76	6.18	
165/80R13 83T	.73118	4.5	1074	44	14	9.5	23.38	6.49	
185/70R13 86T	.73119	5.5	1168	44	15.8	10	23.23	7.44	
195/70R14 91T	.73120	.6	1356	44	18.3	10	24.80	7.91	
205/70R15 96T	.73121	.6	1565	44	20.9	10	26.34	8.23	
215/70R15 98T	.73122	6.5	165	44	23.6	10	26.89	8.70	
225/70R15 100T	.73123	6.5	1764	44	25	10	27.44	8.97	

HERCULES RAPTIS WR 1

High Performance Radial



UTQG 340 A/A
35,000 Mile
Tread Life Warranty

- Ultra High Performance - W speed rated.
- Exceptional Steering Response in Wet and Dry.
- Asymmetrical Tread Design Results in a Smooth, Quiet Ride.
- 5 Rib Design Creates Stability and Performance, Forcing More Rubber on the Road.
- Built to Navigate Curves, Mother Nature and Your Lead Foot.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
BLACKWALL									
205/50ZR16 87W	59208	6.5	1201	50	20.4	10.0	24.09	8.43	..\$
205/55ZR16 91W	59205	6.5	1356	50	21.8	10.0	24.88	8.43	
215/55ZR16 98W**	59209	7.0	1609	50	22.8	10.0	25.28	8.90	
225/55ZR16 99W	59210	7.0	1709	50	24.7	10.0	25.75	9.18	
205/40ZR17 84W**	59203	7.5	1102	50	18.8	10.0	23.46	8.35	
215/40ZR17 87W**	59202	7.5	1201	50	19.5	10.0	23.78	8.58	
205/45ZR17 88W**	59204	7.0	1235	50	19.5	10.0	24.25	8.11	
215/45ZR17 91W**	59201	7.0	1356	50	20.4	10.0	24.65	8.39	
235/45R17 97W	70509	8	1102	50		10.0			
245/45ZR17 99W	59212	8.0	1709	50	24.3	10.0	25.67	9.57	
205/50ZR17 93W**	59207	6.5	1433	50	20.7	10.0	25.12	8.43	
215/55ZR17 94W	59211	7.0	1653	50	23.4	10.0	26.32	8.78	
225/45ZR17 94W**	59198	7.5	1477	50	20.9	10.0	24.96	8.86	
215/35ZR18 84W**	59206	7.5	1102	50	19.8	10.0	23.90	8.58	
225/40ZR18 92W**	59199	8.0	1389	50	21.9	10.0	25.08	9.06	
245/40ZR18 97W**	59215	8.5	1609	50	24.7	10.0	25.71	9.76	
225/45ZR18 95W**	59200	7.5	1521	50	22.8	10.0	25.95	8.86	
245/45ZR18 100W**	59213	8.0	1764	50	27.4	10.0	26.65	9.57	
255/45ZR18 103W**	59214	8.5	1929	50	28.9	10.0	27.05	10.04	
NEW 235/40R18 95W *	61650	8.5	1521	50	22.9	10.5	25.4	9.5	
NEW 245/35R19 93W *	61651	8.5	1433	50	22.9	10.5	25.4	9.5	
225/35R20XL 93W	67631	8	1323	50	22.8	10.0	26.24	9.06	
NEW 245/35R20 95W *	61652	8.5	1521	50	24.6	10.5	26.77	9.76	
NEW 255/35R20 97W *	61653	9	1609	50	26.7	10.5	27	10.24	

** = EXTRA LOAD

HERCULES H/P 4000

Performance Radial



UTQG 440 AB
(60/65/70)
UTQG 440 AC
(50 Series)
40,000 Mile
Tread Life Warranty

The new generation of H/P 4000. Larger slanted solid letters. Performance enhanced tread design for cutting edge traction in all weather conditions. Ride with the strength of a winner.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
BLACKWALL									
P185/60R14 82T	02808	5.5	1047	44	16.0	11.0	22.80	7.15	..\$
P195/60R15 87T	02812	6.0	1201	44	19.0	11.0	24.30	7.60	
P205/60R15 90T	02814	6.0	1301	44	20.0	11.0	24.73	7.83	
P215/55R16 91T	02805	7.0	1356	44	22.0	11.0	25.25	8.83	
P235/55R16 96T	02806	7.5	1565	44	25.0	11.0	26.15	9.65	
RAISED WHITE LETTER									
P215/70R14 96T	02824	6.5	1565	44	22.0	11.0	25.76	8.66	
P225/70R14 98T	02826	6.5	1653	44	24.0	11.0	26.27	8.92	
P215/70R15 97T	02828	6.5	1609	44	23.0	11.0	26.71	8.71	
P225/70R15 100T	02830	6.5	1764	44	25.0	11.0	27.37	8.71	
P235/70R15 102T	02832	7.0	1874	44	27.9	11.0	27.90	9.46	
P255/70R15 108T	02834	7.5	2205	44	30.0	11.0	28.95	10.40	
P215/65R15 95T	02798	6.5	1521	44	22.0	11.0	26.00	8.38	
P205/60R13 86T	02772	6.0	1168	44	17.0	11.0	22.75	7.86	
P235/60R14 96T	02782	7.0	1565	44	23.0	11.0	25.06	9.11	
P235/60R15 98T	02790	7.0	1653	44	25.0	11.0	26.11	9.15	
P245/60R15 100T	02792	7.0	1764	44	26.0	11.0	26.55	9.47	
P255/60R15 102T	02794	7.5	1874	44	28.0	11.0	27.01	9.73	
P275/60R15 107T	02796	8.0	2149	44	31.0	11.0	28.06	10.70	
P275/60R17 110T	02787	8	2337	44	36.0	11.0	29.98	11.02	
P295/50R15 105S	02770	9.5	2039	35	32.0	11.0	26.80	11.77	

HERCULES TERRA TRAC HT

Light Truck Radial



UTQG 400 A B
35,000 Mile
Tread Life Warranty

- M+S Rated
- Tread design for all season driving conditions.
- Smooth and Quiet ride for highway driving.
- Popular fitment sizes for all Light Truck and SUV applications.

Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
OUTLINED WHITE LETTER											
215/75R15 100S	04176	6.0		1764	35	25.0	11.0	27.48	8.60	..\$	
235/75R15 105S	04170	6.5		2039	35	28.0	11.0	28.70	9.30		
245/75R16 111S	04182	7.0		2403	35	33.0	11.0	30.20	9.60		
265/75R16 116S	04178	7.5		2756	35	37.0	11.0	31.32	10.60		
235/70R16 106S	04174	7.0		2094	35	31.0	11.0	28.73	9.40		
245/70R16 107S	04180	7.0		2149	35	32.0	11.0	29.38	9.85		
255/70R16 111S	04172	7.5		2403	35	34.0	11.0	29.30	10.30		
265/70R16 112S	04184	8.0		2469	44	35.0	11.0	30.20	10.80		
LT235/75R15/6	04194	6.5	1820	50	1985	50	31.0	14.0	28.70	8.90	
NEW LT265/75R16/6	04191	7.5	2270	50	2470	50	40.5	14.0	31.63	10.38	
31X10.50R15/6	04192	8.5		2270	50	38.0	14.0	30.00	10.50		
BLACKWALL											
NEW LT215/85R16/10	04187	6.0	2470	80	2470	80	26.80	8.0	30.2	8.40	
NEW LT225/75R16/10	04196	6.0	2470	80	2680	80	36.0	14.0	29.30	8.50	
LT235/85R16/10	04186	6.5	2778	80	3042	80	40.0	14.0	31.50	9.30	
LT245/75R16/10	04188	7.0	2778	80	3042	80	39.0	14.0	30.40	9.40	

HERCULES MR IV SUV

SUV LT Radial



UTQG 460 A B

40,000 Mile Warranty

- Specially designed for SUV & CUV Fitments.
- Smooth & Quiet "Car-Like" Ride.
- Excellent Wet & Dry Traction.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
OUTLINED WHITE LETTER									
235/75R15 105S	.45409	.6.5	.2039	.43	.29.3	.12.0	.28.86	.9.25	\$
225/75R16 104S	.45407	.6.0	.1984	.43	.33.7	.12.0	.29.29	.8.78	
245/75R16 111S	.45405	.7.0	.2403	.43	.38.5	.12.0	.30.47	.9.76	
265/75R16 116S	.45406	.7.5	.2756	.43	.40.5	.12.0	.31.65	.10.51	
235/70R15 103S	.45408	.7.0	.1929	.43	.31.8	.12.0	.27.99	.9.45	
235/70R16 106S	.45401	.7.0	.2094	.43	.30.0	.12.0	.29.00	.9.40	
245/70R16 107S	.45404	.7.0	.2150	.43	.35.9	.12.0	.29.53	.9.76	
255/70R16 111S	.45385	.7.5	.2403	.43	.34.2	.12.0	.30.10	.10.20	
225/65R17 102T	.70402		.1875	.44	.28.9	.12	.28.5		
235/70R17 107T	.70403		.2150	.44	.32.2	.12	.30		
245/70R17 110S	.45403	.7.0	.2337	.43	.37.3	.12.0	.29.53	.9.76	
265/70R17 115S	.45399	.8.0	.2679	.43	.42.3	.12.0	.31.65	.10.7	
245/65R17 107S	.45400	.7.0	.2150	.43	.37.3	.12.0	.29.53	.9.49	
BLACKWALL									
215/70R16 100S	.45410	.6.5	.1764	.43	.28.0	.12.0	.27.87	.8.70	
LT245/75R16/10 120/116S	.70404		.3042	.80	.41.7	.14	.30.47		
LT265/75R16/10 123/120S	.70405		.3415	.80	.45.9	.14	.31.65		
LT265/70R17/10 121/118S	.70406		.3195	.80	.50.3	.14	.31.65		

HERCULES TERRA TRAC SUV

Light Truck Radial



UTQG 520 AB

60,000 Mile Warranty

Enjoy the ride! The Terra Trac SUV tire delivers exceptional performance and urbane design for the SUV and light truck markets. This tire is designed with a solid center rib for enhanced steering response and siped to perform in wet and dry conditions. Built to go the distance, Terra Trac SUV ensures smooth, quiet driving on the highway or around town.

Tire Size	Code No.	Rim Width	Max Load	Max PSI	Tire Weight	Tread Depth	INFLATED DIMENSIONS		PRICE
							Overall Diameter	Section Width	
OUTLINED WHITE LETTER									
225/75R15 102S	.04328	.6.0	.1874	.44	.27.0	.13.0	.28.20	.8.95	\$
235/75R15 105S	.04332	.6.5	.2039	.44	.29.0	.14.0	.28.85	.9.30	
235/70R15 103S	.04334	.7.0	.1929	.44	.29.0	.12.0	.27.80	.9.65	
225/75R16 103S	.04336	.6.0	.1984	.44	.30.0	.13.0	.29.15	.8.65	
235/75R16 108S	.04344	.6.5	.2205	.44	.33.0	.14.0	.29.70	.9.30	
245/75R16 111S	.04338	.7.0	.2403	.44	.35.0	.14.0	.30.35	.9.60	
265/75R16 116S	.04302	.7.5	.2756	.44	.40.0	.14.0	.31.50	.10.60	
215/70R16 100S**	.04304	.6.5	.1764	.44	.29.0	.13.0	.27.75	.8.80	
235/70R16 106S	.04306	.7.0	.2094	.44	.33.0	.13.0	.28.85	.9.40	
245/70R16 107S	.04308	.7.0	.2149	.44	.33.0	.13.0	.29.40	.9.90	
255/70R16 111S	.04310	.7.5	.2403	.44	.36.0	.14.0	.29.95	.10.30	
265/70R16 112S	.04312	.8.0	.2469	.44	.38.0	.14.0	.30.40	.10.80	
245/70R17 110S	.04314	.7.0	.2337	.44	.36.0	.12.0	.30.43	.9.96	
265/70R17 115S	.04316	.8.0	.2679	.44	.40.0	.12.0	.31.40	.10.65	
255/65R16 109S	.04318	.7.5	.2271	.44	.32.0	.12.0	.29.06	.10.24	
235/65R17 104S	.04322	.7.0	.1984	.44	.31.0	.12.0	.29.06	.9.45	
245/65R17 107S	.04324	.7.0	.2149	.44	.33.0	.12.0	.29.45	.9.62	
275/60R17 110S	.04326	.8.0	.2337	.44	.37.0	.12.0	.29.88	.11.00	
LT215/85R16/10**	.04351	.6.0	.2680	.80	.39.0	.16.0	.30.26	.8.21	
LT235/85R16/10**	.04353	.6.5	.3042	.80	.43.0	.16.0	.31.65	.9.31	
LT245/75R16/10**	.04355	.7.0	.3042	.80	.44.0	.16.0	.30.44	.9.57	
LT265/75R16/10	.04356	.7.5	.3085	.80	.48.0	.16.0	.31.61	.10.40	
LT235/80R17/10	.04350	.6.5	.2835	.80	.44.0	.16.0	.31.65	.9.40	
LT245/70R17/10**	.04352	.7.0	.2755	.80	.46.0	.16.0	.30.60	.9.56	
LT265/70R17/10	.04354	.8.0	.2910	.80	.51.0	.16.0	.31.60	.10.65	
NEW LT275/65R18/10	.04357	.8.0	.3415	.80	.54.0	.18.0	.32.09	.10.90	

** Blackwall

30 DAY
"TRUST OUR RIDE"
 TEST DRIVE

HERCULES TERRA TRAC RADIAL RIB

Light Truck Radial



40,000 Mile Tread Life Warranty

Modern 5-rib design for smooth running performance and exceptionally long mileage. Aggressive center ribs give great all weather performance and outstanding road traction. Wide tread arc provides traction and long even tread wear. M&S rated.

Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
BLACKWALL											
LT215/85R16/10	.03761	.6.0	.2470	.80	.2680	.80	.39.0	.14.0	.30.26	.9.70	\$
LT225/75R16/10	.03764	.6.0	.2470	.80	.2680	.80	.39.0	.14.0	.29.18	.9.50	
LT235/85R16/10	.03763	.6.5	.2778	.80	.3042	.80	.43.0	.14.0	.31.70	.10.10	
LT245/75R16/10	.03766	.7.0	.2778	.80	.3042	.80	.42.0	.14.0	.30.46	.10.30	
7.50R16/8	.03767	.6.0	.2140	.65	.2440	.65	.38.0	.14.0	.31.80	.9.70	
8.00R16.5/8	.03768	.6.0	.1800	.65	.2045	.65	.34.0	.14.0	.28.50	.8.90	
8.75R16.5/8	.03769	.6.8	.2070	.65	.2350	.65	.38.0	.14.0	.29.40	.9.70	

HERCULES TERRA TRAC A/T

Light Truck Radial



**UTQG
(P-Metric)
14" 380 AB
15" 400 AB**

**500 AB
50,000 Mile
Tread Life
Warranty**

Seeking a tire that can handle what Mother Nature throws your way? The newly designed Terra Trac A/T premium all-terrain out performs in the best and worst of driving conditions. Along with strength and durability, the advanced tread pattern is designed for a smooth, quiet ride without compromising traction. Even the aggressively designed sidewall beckons Mother Nature to "bring it on!"

Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
OUTLINED WHITE LETTER											
215/75R15 100S	04082	6.0	1764	44	1764	44	26.0	14.0	27.60	8.40	\$
225/75R15 102S	04084	6.0	1874	44	1874	44	28.0	14.0	28.33	8.70	
235/75R15 105S	04028	6.5	2039	44	2039	44	30.0	14.0	28.90	9.23	
265/75R15 112S	04029	7.5	2469	44	2469	44	37.0	15.0	30.69	10.50	
225/70R15 100S	04032	6.5	1764	44	1764	44	27.0	13.0	27.45	9.00	
235/70R15 103S	04033	7.0	1929	44	1929	44	29.0	13.0	27.99	9.45	
265/70R15 112S	04034	8.0	2469	44	2469	44	36.0	14.0	29.90	10.60	
225/75R16 104S	04086	6.0	1984	44	1984	44	30.0	14.0	29.25	8.71	
235/75R16 108S	04090	6.5	2205	44	2205	44	33.0	14.0	29.84	9.25	
245/75R16 111S	04030	7.0	2403	44	2403	44	34.0	14.0	30.52	9.65	
265/75R16 116S	04031	7.5	2756	44	2756	44	38.0	15.0	31.65	10.51	
215/70R16 100S	04080	6.5	1764	44	1764	44	29.0	14.0	27.87	8.70	
225/70R16 102S	04035	6.5	1874	44	1874	44	30.0	14.0	28.40	8.90	
235/70R16 106S	04037	7.0	2094	44	2094	44	32.0	14.0	28.99	9.46	
245/70R16 107S	04038	7.0	2149	44	2149	44	33.0	14.0	29.59	9.79	
255/70R16 111S	04039	7.5	2403	44	2403	44	35.0	14.0	30.10	10.24	
265/70R16 112S	04040	8.0	2469	44	2469	44	37.0	14.0	30.52	10.73	
245/70R17 110S	04094	7.0	2337	44	2337	44	35.0	14.0	30.10	9.76	
255/70R17 112S	04061	7.5	2469	44	2469	44	41.0	14.0	31.10	10.24	
265/70R17 115S	04041	8.0	2679	44	2679	44	40.0	14.0	31.60	10.70	
235/65R17 104T	04088	7.0	1984	44	1984	44	33.0	14.0	29.10	9.54	
245/65R17 104T	04092	7.0	2149	44	2149	44	34.0	14.0	29.63	9.59	
255/65R17 110S	04096	8.0	2337	44	2337	44	36.0	14.0	30.05	9.88	
265/65R17 112T	04098	7.5	2470	44	2470	44	38.0	14.0	30.55	10.71	
265/70R18 114S	04042	8.0	2756.0	44.0	2756.0	44.0	41.0	14.0	32.6	10.7	
NEW 265/65R18 114T	04104	8.0	2601.0	44.0	2601.0	44.0	40.0	13.5	31.5	10.5	
275/55R20 117S	04101	8.5	2833	50	2833	50	45.0	13.0	31.92	12.69	
LT235/75R15/6	04045	6.5	1820	50	1985	50	35.0	16.0	28.95	9.00	
LT245/75R16/6	04059	7.0	2778	80	3042	80	41.0	17.0	30.52	9.76	
LT245/75R16/10	04048	7.0	2778	80	3042	80	43.0	17.0	30.52	9.62	
LT265/75R16/6	04049	7.5	2270	50	2470	50	45.0	17.0	31.78	10.40	
LT265/75R16/10	04050	7.5	3085	80	3415	80	49.0	17.0	31.81	10.57	
LT285/75R16/8	04051	8.0	3000	65	3305	65	54.0	17.0	32.93	11.47	
LT315/75R16/8	04052	8.5	3195	50	3195	50	62.0	17.0	34.75	12.87	
LT305/70R16/8	04054	9.0	2680	50	2910	50	56.0	17.0	32.80	12.24	
LT235/80R17/10	04060	6.5	2835	80	3085	80	42.0	17.0	31.65	9.30	
LT245/75R17/10	04067	7.0	2910	80	3195	80	46.0	16.0	31.5	9.95	
LT265/70R17/6	04055	8.0	2270	50	2470	50	46.0	17.0	31.60	10.85	
LT265/70R17/10	04062	8.0	2910	80	3195	80	49.0	18.0	31.60	10.65	
LT275/70R17/6	04064	8.0	2335	50	2600	50	49.0	17.0	32.20	11.10	
LT285/70R17/8	04068	8.5	2910	65	3195	65	51.0	17.0	32.76	11.50	
LT315/70R17/8	04069	9.5	2910	50	3195	50	59.0	17.0	34.85	12.90	
LT275/70R18/10	04081	8.0	3305	80	3640	80	55.0	16.0	33.15	11.11	
LT275/65R18/10	04066	8.0	3085	80	3415	80	53.0	16.0	32.09	11.07	
30X9.50R15/6	04056	7.5	01985	50	1985	50	36.0	17.0	29.30	9.30	
31X10.50R15/6	04057	8.5	02270	50	2270	50	40.0	17.0	30.30	10.54	
BLACKWALL											
LT215/85R16/10	04043	6.0	2470	80	2680	80	38.0	17.0	30.30	9.10	
LT225/75R16/10	04046	6.0	2470	80	2680	80	39.0	17.0	29.48	8.82	
LT235/85R16/10	04044	6.5	2778	80	3042	80	42.0	17.0	31.78	9.36	
LT245/75R16/10	04047	7.5	2778	80	3042	80	43.0	17.0	30.52	9.62	
NEW 275/60R20XL 119S	04103	8.0	2998	50	2998	50	46.0	14.0	33.03	11.06	

**30 DAY
"TRUST OUR RIDE"
TEST DRIVE**

HERCULES ALL TRAC A/T

Light Truck Radial



**UTQG 460 A/B
40,000 Mile
Warranty**

- Light truck all-terrain tire with on/off road capability.
- Engineered to promote high mileage and even wear.
- Aggressive tread design performs in all elements.
- Popular original equipment fitments.

Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE	
			Max Load	Max PSI	Max Load	Max PSI						
OUTLINED WHITE LETTER												
235/70R16 106T	59182	7.0	3740	44	3740	44	30.2	12.5	28.97	9.4	\$	
245/70R16 107T	59177	7.0	2150	44	2150	44	32.3	12.5	29.53	9.8		
NEW 245/70R16 XL 111T	73395				2400	49	35	12.5	29.53	9.76		
255/70R16 111T	59181	7.5	2403	44	2403	44	33.9	12.5	30.08	10.2		
265/70R16 112T	59178	8.0	2469	44	2469	44	35.6	12.5	30.63	10.7		
265/75R16 116T	59179	7.5	2756	44	2756	44	37.2	12.5	31.65	10.5		
265/70R17 115T	59180	8.0	2679	44	2679	44	37.2	12.5	31.65	10.7		
275/65R18 116T	59184	8.0	2756	44	2756	44	38.9	12.5	32.09	10.9		
275/70R16 114T XL	64950	6.5	2271	44	2271	44	28.9	13	28.86	9.2		
235/75R15 XL 109T	59183	6.5	2271	44	2271	44	28.9	12.5	28.86	9.2		
31X10.50R15LT/6 109S	59186	8.5	2271	51	2271	51	40.9	16.0	30.51	10.5		
LT215/85R16/10	59189	6.0	2679	51	2679	51	37.6	15.0	30.39	8.5		
LT225/75R16/10	59190	6.0	2679	51	2679	51	36.9	15.0	29.29	8.8		
LT235/85R16/10	59187	6.5	3042	51	3042	51	40.5	15.0	31.73	9.3		
LT245/75R16/10	59188	7.0	3042	51	3042	51	40.1	15.0	30.47	9.8		
LT245/75R17/10	59191	7.0	3197	51	3197	51	42.4	15.0	31.5	9.8		
LT265/70R17/10	59192	8.0	3197	51	3197	51	45.2	16.0	31.65	10.7		
LT265/75R16/10	59185	7.5	3417	51	3417	51	3087	43.8	16.0	31.65	10.5	
30X9.50R15LT 104C	64949											
BLACKWALL												
LT215/85R16/10	59195	6.0	2679	51	2679	51	37.6	15.0	30.39	8.5		
LT225/75R16/10	59196	6.0	2679	51	2679	51	36.9	15.0	29.29	8.9		
LT245/75R16/10	59194	7.0	3042	51	3042	51	40.1	15.0	30.47	9.7		
LT265/75R16/10	59193	7.5	3417	78	3417	78	3087	43.8	16.0	31.65	10.5	
LT265/70R17/10	59197	8.0	3197	51	3197	51	2910	45.2	16.0	31.65	10.7	



Featured in 4Wheel & Off-Road Magazine!

"...Thus by assembling the experience of their clients, they seemed to have taken note of what works and mixed it together into a great product of its own."

- XXL Scooping Tread Lugs
- Stone "Blockers" Increase Puncture Resistance
- Maximum Traction over every obstacle
- Pinned for Studs



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	Stud Size	PRICE
			Max Load	Max PSI	Max Load	Max PSI						
OUTLINED WHITE LETTER												
LT235/75R15/6	.01238	.6.5	.1820	.50	.1985	.50	.33.0	.18.0	.29.09	.9.45	.15	\$
LT265/75R16/10	.01208	.7.5	.3085	.80	.3415	.80	.49.0	.18.5	.32.00	.10.1	.15	
LT285/75R16/8	.01210	.8.0	.3000	.65	.3305	.65	.54.0	.18.5	.33.10	.11.3	.15	
LT315/75R16/8	.01201	.8.5			.3195	.50	.64.0	.20.0	.34.75	.12.47		
LT265/70R17/10	.01230	.8.0	.2910	.80	.3195	.80	.49.0	.18.5	.31.65	.11.03	.15	
LT285/70R17/8 *	.01209	.8.5	.2910	.65	.3195	.65	.58.0	.19.0	.33.00	.11.5		
LT305/70R18/10 *	.01207	.9.0	.3415	.65	.3750	.65	.72.0	.21.0	.35.10	.12.24		
30X9.50R15/6	.01204	.7.5			.1990	.50	.37.0	.19.5	.29.30	.10.1	.17	
33X12.50R15/6	.01206	.10.0			.2225	.35	.52.0	.20.5	.32.50	.12.8	.17	
31X10.50R15/6	.01202	.8.5			.2270	.50	.42.0	.20.0	.30.50	.10.5	.17	
33X12.50R17/8	.01228	.10.0			.2600	.50	.58.0	.20.5	.32.50	.12.8	.17	
35X12.50R17/8	.01226	.10.0			.3000	.50	.63.0	.20.5	.34.85	.12.67	.17	
BLACKWALL												
LT235/85R16/10	.01200	.6.5	.2778	.80	.3042	.80	.44.0	.18.0	.31.80	.9.3	.15	
NEW LT245/75R16/10	.01241		.2778		.3042	.80	.43.0	.17.0				
LT275/70R18/10 *	.01203	.8.0	.3305	.80	.3640	.80	.63.0	.21.0	.33.35	.11		
35X12.50R20LT/10 *	.01205	.10.0			.3195	.65	.71.0	.21.0	.34.66	.12.5		

* Denotes 3 Ply sizes

HERCULES POWER CV

Commercial Van

NEW



• All-season and all position radial, widerfootprint contribute to better wear resistance and wet tractional elements.

Tire Size	Code No.	Svc. Desc.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
				Max Load	Max PSI	Max Load	Max PSI					
185R14C/8	.65901	...102/100Q	...5.5	...1764	...65	...1874	...65	...23.6	...10.5	...25.6	...7.4	...
195R14C/8	.65902	...106/104Q	...5.5	...1984	...65	...2094	...65	...24.3	...11	...26.2	...7.8	...
195/70R15C/8	.65903	...104/102R	...6	...1874	...65	...1984	...65	...24.8	...13	...25.8	...7.9	...
205/70R15C/8	.65904	...106/104R	...6	...1984	...65	...2094	...65	...26.1	...13	...26.4	...8.2	...
225/70R15C/8	.65905	...112/110R	...6.5	...2337	...69	...2469	...69	...31.3	...13	...27.5	...9.0	...
185/75R16C/8	.65906	...104/102R	...5	...1874	...69	...1984	...6910.5	...26.9	...7.2	...
195/65R16C/8	.65908	...104/102R	...6	...1874	...69	...1984	...6912	...26.0	...7.9	...
215/65R16C/8	.65912	...109/107R	...6.5	...2150	...69	...2271	...6912	...27.0	...8.7	...
225/65R16C/8	.65913	...112/110R	...6.5	...2337	...69	...2469	...6912	...27.5	...9.0	...
235/65R16C/8	.65914	...115/113R	...7	...2535	...69	...2679	...6912.5	...28.1	...9.5	...
205/65R15C/6	.70519	...102/100R	...6	...1764	...54	...1874	...5412	...25.5	...8.2	...
195/75R16C/8	.67666	...107/105R	...5.5	...2039	...69	...2150	...6912	...27.5	...7.7	...

HERCULES POWER STR

ST Trailer Radial



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
NEW ST235/85R16	.72985	...6.53960	...9531.739.25	...
ST235/80R16/10	.63964	...6.53520	...80	...40.3	...10.5	...30.799.25	...
ST225/75R15/8	.63963	...62540	...65	...30	...10.5	...28.318.78	...
ST225/75R15/10	.68146	...62830	...80	...30	...10.5	...28.318.78	...
ST205/75R15/8	.63962	...5.52150	...65	...25.1	...10.5	...27.137.99	...
ST205/75R15/6	.63961	...5.51820	...50	...25.1	...10.5	...27.137.99	...
ST205/75R14/6	.63959	...5.51760	...50	...24.9	...10.5	...26.147.99	...
ST215/75R14/6	.63960	...61870	...50	...24.5	...10.5	...26.698.5	...
ST175/80R13/6	.63958	...51360	...50	...17.2	...9.5	...24.026.97	...

HERCULES SUPER EXPRESS

Light Truck Bias



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
7.00-15/6	.58204	...5.5	...1520	...50.00	...1710	...50	...30.2	...13.0	...29.62	...7.95	...
7.00-15/8	.58206	...5.5	...1820	...65.00	...2040	...65	...30.9	...13.0	...29.62	...7.95	...
7.00-15/10	.58208	...5.5	...2040	...80.00	...2335	...80	...31.3	...13.0	...29.62	...7.95	...
7.50-16/8	.58210	...6.0	...2150	...65.00	...2470	...65	...36.4	...14.0	...31.80	...8.65	...
7.50-16/10	.58212	...6.0	...2470	...80.00	...2755	...80	...37.0	...14.0	...31.80	...8.65	...

HERCULES HDT

Light Truck Bias



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
7.00-15/8	.58222	...5.5	...1820	...65	...2040	...65	...30.9	...12.6	...29.62	...7.95	...
7.50-16/10	.58205	...6.0	...2470	...80	...2755	...80	...37.0	...13.9	...31.80	...8.65	...

HERCULES TRAILER LPT

LPT Bias



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	PRICE
			Max Load	Max PSI	Max Load	Max PSI					
7-14.5/12	.58200	...6.0	...2017	...100	...2304	...100	...26.5	...8.0	...26.70	...7.30	...
8-14.5/14	.58202	...6.0	...2712	...110	...3087	...110	...31.9	...8.0	...27.80	...8.00	...



AVALANCHE X-TREME

Passenger



Tire Size	Code No.	Rim Width	Max Load	Max PSI	Weight	Tread Depth	Overall Diameter	Section Width	Stud Size	PRICE
BLACKWALL										
NEW 185/75R14 89S	01090	5.5	1279	44	18	13.5	25.1	7.2		\$
NEW 195/75R14 92S	01091	5.5	1389	44	20	13.5	25.65	7.6		
NEW 205/75R14 95S	01092	5.5	1521	44	21.0	14	26.2	7.95		
185/70R14 88S	01001	5.5	1235	44	18.0	13.0	24.45	7.45	12	
195/70R14 91S	01003	6.0	1356	44	18.0	13.0	25.00	7.75	12	
175/65R14 82T	01005	5.0	1047	44	16.0	13.0	23.10	6.85	12	
185/65R14 86T	01007	5.5	1168	44	17.0	13.0	23.55	7.35	12	
NEW 215/75R15 100S	01096	7.0	1764	44	25.0	14.0	27.80	8.40		
NEW 205/75R15 97S	01093	5.5	1609	44	22.0	14	27.2	7.95		
NEW 225/75R15 102S	01094	6	1874	44	25.0	14	28.3	8.7		
NEW 235/75R15 105S	01097	6.5	2039	44	27.0	14.5	28.90	9.10		
NEW 205/70R15 96S	01099	6.0	1565	44	22.0	13.0	26.40	8.00		
NEW 215/70R15 98S	01101	6.5	1653	44	23.0	13.0	26.90	8.40		
NEW 225/70R15 100S	01095	6.5	1764	44	25.0	13	27.4	8.7		
185/65R15 88T	01009	5.5	1235	44	19.0	13.0	24.51	7.55	12	
195/65R15 91T	01011	6.0	1356	44	20.0	13.0	25.00	7.85	12	
205/65R15 94T	01013	6.0	1477	44	22.0	13.0	25.45	8.02	12	
215/65R15 96T	01017	6.5	1565	44	24.0	13.0	25.98	8.55	12	
185/60R15 84T	01019	5.5	1102	44	19.0	13.0	23.88	7.44	12	
195/60R15 88T	01021	5.5	1235	44	21.0	13.0	24.30	7.80	12	
205/60R15 91T	01023	6.0	1356	44	22.0	13.0	24.75	8.15	12	
215/60R15 94T	01027	6.5	1477	44	23.0	13.0	25.21	8.60	12	
195/55R15 85T	01000	5.5	1135	44	20.0	13.0	23.75	7.91	12	
205/65R16 95T	01004	6.0	1521	44	23.0	13.0	26.45	8.02	12	
215/65R16 98T	01029	6.5	1653	44	26.0	13.0	26.98	8.55	12	
235/65R16 103T	01085	7.0	1929	44	27.0	13.0	27.94	9.56	12	
205/60R16 92T	01031	6.0	1389	44	23.0	13.0	25.77	8.33	12	
215/60R16 95T	01033	6.5	1521	44	24.0	13.0	26.15	8.50	12	
225/60R16 98T	01035	6.5	1653	44	25.0	13.0	26.57	8.75	12	
235/60R16 100T	01006	7.0	1764	44	28.0	13.0	26.96	9.45	12	
205/55R16 91T	01037	6.5	1356	44	23.0	12.0	24.80	8.35	12	
215/55R16 97T	01008	7.0	1609	50	24.0	13.0	25.35	8.90	12	
205/50R16 87T	01010	6.5	1201	44	20.0	13.0	24.27	8.34	12	
225/50R16 92T	01012	7.0	1389	44	25.0	13.0	25.10	9.17	12	
215/65R17 99T	01053	6.5	1709	44	27.3	13.0	28.11	8.93	12	
NEW 225/65R17 102T	01082	6.0	1874	44	26.0	12.0	28.50	8.84	12	
215/60R17 96T	01081	6.5	1565	44	26.0	13.0	27.24	9.03	12	
225/60R17 99T	01075	6.5	1709	44	27	13	27.72	9.14	12	
215/55R17 94T	01073	7.0	1477	44	26.3	13.0	26.36	9.46	12	
225/55R17 97T	01039	7.0	1609	44	28.0	13.0	26.88	9.20	12	
235/55R17 99T	01045	7.5	1709	44	31.0	13.0	27.22	9.79	12	
215/50R17 91T	01014	7.0	1356	44	25.0	13.0	25.69	8.82	12	
NEW 225/50R17 94T	01084	6.0	1477	44		13.0	26.00	89.99	12	
225/45R17 94T	01016	7.5	1477	50	27.0	13.0	25.09	9.03	12	
235/45R17 94T	01047	8.0	1477	44	27.0	13.0	25.53	9.30	12	
NEW 225/60R18 100T	01048	6.5	1764	44	29.0	13.0	28.70	9.01		

AVALANCHE X-TREME (SUV)

Light Truck Radial



Tire Size	Code No.	Rim Width	Max Load	Max PSI	Weight	Tread Depth	Overall Diameter	Section Width	Stud Size	PRICE
BLACKWALL										
265/70R15 112S	01018	8.0	2469	44	35.0	15.0	29.43	10.45	13	\$
225/75R16 104S	01103	6.0	1984	44	31.0	15.0	29.18	8.65		
235/75R16 108S	01025	6.5	2205	44	34.0	15.0	29.85	9.30		
245/75R16 111S	01050	7.0	2403	44	35.0	15.0	30.40	9.60	13	
265/75R16 116S	01052	7.5	2756	44	39.0	15.0	31.60	10.60	13	
215/70R16 100S	01054	6.5	1764	44	30.0	15.0	27.75	8.80	13	
225/70R16 102S	01056	6.5	1874	44	30.0	15.0	28.30	9.00	13	
235/70R16 106S	01058	7.0	2094	44	32.0	15.0	28.85	9.40	13	
245/70R16 107S	01060	7.0	2149	44	34.0	15.0	29.50	9.85	13	
255/70R16 111S	01062	7.5	2403	44	35.0	15.0	29.90	10.30	13	
265/70R16 112S	01064	8.0	2469	44	39.0	15.0	30.40	10.80	13	
245/70R17 110S	01109	7.0	2337	44	35.0	15.0	30.50	9.85		
255/70R17 112S	01071	7.5	2469	44		15.0	31.22	10.28		
265/70R17 115S	01066	8.0	2679	44	41.0	15.0	31.40	10.65	13	
235/65R17 104S	01102	7.0	1984	44	33.0	14.0	29.11	9.45		
255/70R18 113S	01108	7.5	2535	44		15.0	32.22	10.28		
275/65R18 116S	01104	8.0	2756	44		14.0	32.16	11.00		
255/55R18 109S	01068	8.0	2271	50	41.0	14.0	29.12	10.36	13	
275/60R20 119S	01070	8.5	2998	50	50.0	14.0	33.08	12.69	13	
275/55R20 XL 117S	01106	8.5	2833	50		14.0	32.03	11.03		
OUTLINED WHITE LETTER										
255/65R16 109S	01020	7.5	2271	44	36.0	14.0	29.18	10.24	13	
245/65R17 107S	01024	7.0	2149	44	36.0	14.0	29.52	9.82	13	
275/60R17 110S	01026	8.0	2337	44	39.0	14.0	30.10	11.20	13	

AVALANCHE X-TREME (LT)

Light Truck Radial



Tire Size	Code No.	Rim Width	DUAL		SINGLE		Tire Weight	Tread Depth	Overall Diameter	Section Width	Stud Size	PRICE
			Max Load	Max PSI	Max Load	Max PSI						
BLACKWALL												
LT235/75R15/6	.01028	.8.5			2270	.50	40.0	19.0	30.25	10.50	15	\$
LT215/85R16/10	.01040	.6.0	2470	.80	2680	.80	38.0	17.0	30.28	9.10	15	
LT225/75R16/10	.01034	.6.0	2470	.80	2680	.80	39.0	17.0	29.30	8.95	15	
NEW LT285/75R16/8	.01089	.8.0	3000		3305	.65		17.0	32.64	11.26	15	
LT235/85R16/10	.01032	.6.5	2778	.80	3042	.80	42.0	17.0	31.78	9.31	15	
LT245/75R16/6	.01036	.7.0	2006	.50	2205	.50	40.0	17.0	30.44	9.57	15	
LT245/75R16/10	.01038	.7.0	2778	.80	3042	.80	45.0	17.0	30.44	9.57	15	
LT265/75R16/6	.01042	.7.5	2270	.50	2470	.50	44.0	17.0	31.54	10.33	15	
LT265/75R16/10	.01044	.7.5	3085	.80	3415	.80	48.0	17.0	31.54	10.50	15	
LT235/80R17/10	.01076	.6.5	2835	.80	3085	.80	45.0	18.0	31.85	9.40	15	
NEW LT245/75R17/10	.01087	.7.0	2910		3195	.80		17.0	31.83	9.87	15	
LT245/70R17/10	.01046	.7.0	2755	.80	3000	.80	44.0	17.0	30.45	10.70	15	
LT265/70R17/10	.01074	.8.0	2910	.80	3195	.80	50.0	18.0	31.65	11.03	15	
LT275/70R17/6	.01078	.8.0	2335	.50	2600	.50	44.0	18.0	32.20	11.32	15	
LT275/70R18/10	.01080	.8.0	3305	.80	3640	.80	55.0	17.0	33.15	10.95	15	
31X10.50R15/6	.01030	.6.5	1820	.50	1985	.50	34.0	17.0	28.82	9.00	15	

HERCULES S-209

LPT Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
235/75R17.5/16	.86455	.66	6.75	16	5675	125	6005	125	9.17	31.38		\$
215/75R17.5/16	.86454	.57	6.0	15.5	4540	125	4805	125	8.35	30.2		
8R19.5/12	.86456	.61	6.0	12.1	3305	110	3525	110	7.99	33.82		
225/70R19.5/12	.86403	.61	6.75	15.5	3415	.96	3640	.96	8.9	31.93		
245/70R19.5/14	.86407	.74	7.5	16	4300	110	4540	110	9.76	33.03		
265/70R19.5/14	.86307	.81	7.5	19	4675	110	5070	110	10.31	34.13		

HERCULES S-203

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
315/80R22.5/18	.86414	.146	9.0	19.0	7610	120	8270	120	12.28	42.36		\$
315/70R22.5/16	.86289		9.00	18.5	6940	123	7830	123	12.28	39.92		
315/70R22.5/18	.86299		9	18.5	7390	130	8270	130	12.28	39.92		

Drive all steel radial truck tire. Wide and deep transversal grooves provide greater driving force. Deep tread depth for extended mileage. Reinforced bead construction and durable carcass for excellent retreading rate. Service: highway, pickup and delivery, mild on/off road.

HERCULES S-205

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
8R17.5/10	.86330	.57	6.00	15.5	2755	95	2910	95	8.19	30.87		\$
10R17.5/16	.86333	.82	7.50	15.5	4410	110	4675	110	10.0	33.78		
10R22.5/14	.86459	.109	7.50	18	5355	115	5675	115	10.0	40.12		
11R22.5/14	.86449	.118	8.25	18.5	5840	105	6175	105	10.98	41.34		
11R22.5/16	.86448	.119	8.25	18.5	6005	120	6610	120	12.0	41.34		
12R22.5/16	.86498	.136	9.00	19.0	6780	120	7390	120	11.81	42.72		
11R24.5/14	.86452	.125	8.25	18.5	6005	105	6610	105	10.98	43.46		
11R24.5/16	.86453	.126	8.25	18.5	6610	120	7160	120	10.98	43.46		
295/75R22.5/14	.86341	.116	9.00	18.5	5675	110	6175	110	11.73	39.92		
285/75R24.5/14	.86329	.124	8.25	18.5	5675	110	6175	110	11.14	41.34		

Highway all steel radial truck tire. Decoupling groove minimizes uneven shoulder wear and maximizes steering response. Premium tread depth for extended mileage. Reinforced bead construction and durable carcass for excellent retreading rate. Service: highway, pickup and delivery, mild on/off road.

HERCULES S-210

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
7.50R16LT	.86469	.50	6	15	2888	107	3330	105	8.5	31.9		\$

HERCULES S-208

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	86431	118	8.25	18.5	5840	105	6175	105	10.98	41.34	\$	
11R24.5/14	86432	125	8.25	18.5	6005	120	6610	105	10.98	43.46		
11R24.5/16	86419	126	8.25	18.5	6610	120	7160	120	10.98	43.46		
295/75R22.5/14	86433	116	8.25	18.5	5675	110	6175	110	11.7	39.92		
285/75R24.5/14	86434	124	8.25	18.5	5675	110	6175	110	11.1	41.34		

HERCULES S-207

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	86423	127	8.25	26	5840	105	6175	105	10.98	41.69	\$	
11R22.5/16	86420	128	8.25	26	6005	120	6610	120	10.98	41.69		
11R24.5/14	86424	136	8.25	26	6005	105	6610	105	10.98	41.7		
11R24.5/16	86430	137	8.25	26	6610	120	7160	120	10.98	41.7		
295/75R22.5/14	86425	128	8.25	26	5675	110	6175	110	11.73	40.16		
285/75R24.5/14	86426	132	8.25	26	5675	110	6175	110	11.14	41.57		
295/80R22.5/16	86295	138	.9	22	6940	123	7830	123	11.73	41.34		
315/70R22.5/18	86293	141	.9	26	7390	130	8270	130	12.28	40.16		
315/80R22.5/18	86297	157	.9	26	7610	120	8270	120	12.28	42.6		

Drive all steel radial truck tire. Wide and deep transversal grooves provide greater driving force. Deep tread depth for extended mileage. Reinforced bead construction and durable carcass for excellent retreading rate. Service: highway, pickup and delivery, mild on/off road.

HERCULES S-201

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
11R22.5/16	86411	121	8.25	18.5	6005	120	6610	120	10.98	41.34	\$	
11R24.5/16	86309	131	8.25	18.5	6610	120	7165	120	10.98	43.46		

Highway all steel radial truck. Premium tread depth for extended mileage. Reinforced bead construction and durable carcass for excellent retreading rate. Service: Highway, Pickup and Delivery, On/Off Road.

HERCULES S-307

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
11R24.5/14	86402	137	8.25	26	6005	105	6610	105	10.98	41.94	\$	
11R24.5/16	86408	139	8.25	26	6610	120	7160	120	10.98	41.94		
295/75R22.5/14	86412	127	9.00	26	5675	110	6175	110	11.73	40.39		

HERCULES S-309

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
245/70R19.5/14	86458	77	7.50	18.5	4300	110	4540	110	9.76	33.03	\$	

Aggressive, high-traction drive-axle design. Open shoulder for excellent wear and traction. Deep lug tread design for maximum over-the-highway, drive-axle traction performance.

HERCULES S-202

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
8.25R20/14	86317	97	6.5	17	5070	135	5355	135	9.26	38.35	\$	
295/80R22.5/16	86337	130	.9	19	6940	123	7830	123	11.73	41.34		

HERCULES S-204

Medium Truck Radial



Tire Size	Code No.	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
					Max Load	Max PSI	Max Load	Max PSI				
3385/65R22.5/20	.86325	166	11.75	20.5	9920	130	15.31	42.2			\$	
425/65R22.5/20	.86303	193	13.00	20.5	11400	120	16.9	44.25				

H902 HIGHWAY A/P

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	.59220	.144/142M	107.0	8.25	14	5840	105	6175	105	10.94	41.30		\$
11R22.5/16	.64369	.146/143M	107.1	8.55	14.0	6005	120	6610	120.0	10.94	41.30		
255/70R22.5/16	.59219	.140/137L	93.0	7.50	17.0	5070	120	5510	120	9.65	36.61		
225/70R19.5/14	.59217	.128/126	65.0	6.75	16.0	3750	110	3970	110	8.62	32.01		
245/70R19.5/14	.59216	.133/131	73.0	7.50	17.0	4300	110	4540	110	9.57	33.03		
215/75R17.5/16	.59545	.135/133 L	56.0	6.0	16.0	4540	125	4805	125	8.07	30.39		
235/75R17.5/16	.59546	.143/141L	72.0	6.75	17.0	5675	125	6005	125	8.90	31.57		
275/70R22.5/16	.59979	.148/145M	102.0	8.25	19.0	6395	125	6490	125	10.71	37.91		

Long-tread like from 17/32 of application specific compounds. Beefy, solid shoulder design promotes a smooth, even wear in high-scrub use. Heavy-Duty All-Steel casing for excellent retreadability.

H802 PREMIUM STEER

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	.59552	.144/142M	119.9	8.25	19	5842	104	6173	104	10.94	41.38		\$
11R24.5/14	.59554	.146/143M	129.0	8.25	19	6008	104	6614	104	10.94	43.43		
11R22.5/16	.59541	.146/143M	116.0	8.25	19.0	6005	120	6610	120	10.94	41.38		
11R24.5/16	.59542	.149/146M	126.0	8.25	19.0	6610	120	7160	120	10.94	43.43		
285/75R24.5/14	.59555	.144/141M	120.0	8.25	19.0	5677	110	6173	110	10.83	41.42		
295/75R22.5/14	.59553	.144/141M	112.3	8.25	19.0	5677	110	6173	110	8.25	40.04		
285/75R24.5/16	.59543	.147/144M	119.0	8.25	19.0	6175	120	6780	120	10.83	41.42		
295/75R22.5/16	.59544	.146/143M	115.0	8.25	19.0	6005	120	6610	120	10.83	40.40		

Highway Rib Design with Decoupling groove for steer tire positions. Directional tread design provides excellent wear and stability. Horizontal siping for all weather traction and cooler running. Heavy-Duty All-Steel casing for excellent retreadability.

H703 OPEN SHOULDER DRIVE

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	.59537	.144/142L	126.6	8.25	26.0	5842.0	104.0	6173	104	10.94	41.81		\$
11R24.5/14	.59538	.146/143L	135.9	8.25	26.0	6008.0	104.0	6614	104	10.94	43.86		
11R22.5/16	.59970	.146/143L		8.25	26	6005	120	6610	120	10.94	41.81		
11R24.5/16	.59974	.149/146L		8.25	26	6610	120	7160	120	10.94	43.86		
295/75R22.5/14	.59540	.144/141L	120.0	8.25	26.0	5675	110	6175	110	10.83	40.47		
285/75R24.5/14	.59539	.144/141L		8.25		5675	110	6175	110	10.83	41.85		

Deep tread depth for excellent mileage. Staggered tread block design distributes force evenly to withstand irregular wear. Open Shoulder design and tough, siped blocks enhances traction in all weather conditions. Heavy-Duty All-Steel casing for excellent retreadability.

H702 CLOSED SHOULDER DRIVE

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/14	59533	144/142L	124.0									\$	
11R24.5/14	59534	146/143L	123.0										
11R22.5/16	59969	146/143L	124.0	8.25	26.0	6005	120	6610	120	10.94	41.81		
11R24.5/16	59972	149/146L	134.0	8.25	26.0	6610	120	7160	120	10.94	43.86		
295/75R22.5/14	59536	144/141L	121.0	8.25	29.0	5675	110	6175	110	10.83	40.47		
225/70R19.5/12	59977	125/123L	69.0	6.75	20.0	3415	95	3640	95	8.62	32.24		
245/70R19.5/14	59978	133/131L	78.0	7.5	21.0	4300	110	4540	110	9.57	33.35		
285/75R24.5/14	59535	144/141L	126.0	8.25	26.0	5675	110	6175	110	10.83	41.85		

26/32 tread Depth. Solid Shoulder and staggered rows of siped block lugs provides uniform tread wear without sacrificing traction. Features stone ejectors and a self-cleaning tread design. Heavy-Duty All-Steel casing for excellent retreadability.

H302 DEEP LUG

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/16	59532	146/143G	129.90	8.25	32.0	6005	120	6610	120	10.94	42.20	\$	
11R24.5/16	59975	149/146G	139.70	8.25	32.0	6610	120	7160	120	10.94	44.25		

H-903 TRAILER RIB

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
111R22.5/16	59968	146/143M		8.25	14	6005	120	6610	120	10.94	41.3	\$	
11R24.5/16	59971	149/146M		8.25	14	6610	120	7160	120	10.94	43.15		
255/70R22.5/16	59551	140/137L	102.3	7.5	14	5070	120	5510	120	9.65	36.5		
285/75R24.5/14	59549	144/141M	115	8.25	14	5675	110	6175	110	10.83	41.14		
295/75R22.5/14	59550	144/141M	109	8.25	14	5675	110	6175	110	10.83	39.76		
11R22.5/14	59547	144/142	107.6	8.25	14	5840	105	6175	105	10.94	41.3		
11R24.5/14	59548	146/143M	121.3	8.25	14.5	6008	104	6614	104	10.94	43.15		

Trailer and all-position applications. Shallow, non-skid, 5-rib tread design promotes low rolling resistance and enhances fuel economy. Ribs on sidewalls to discourage damage from curbing, cuts, and abrasions. Decoupling groove resist shoulder wear. Heavy-Duty All-Steel casing for excellent retreadability.

H301 HIGHWAY MIXED SERVICE

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
11R22.5/16	72062	146/143K	124.6	8.25	23.5	6008	120	6614	120	10.94	41.65	\$	
11R24.5/16	59973	149/146		8.25	23	6610	120	7160	120	10.94	43.70		
275/70R22.5/16	72078	148/145K	103.7	8.25	22	6395	130	6940	130	10.71	38.11		
315/80R22.5/20	59531	161/157G	144.0	9.00	22.0	9090	130	10200	130	12.09	42.76		

All-position, designed for highway and mixed service applications. Extra-wide footprint, self cleaning sipes and optimal compound enables excellent durability, high speed and resistance to wear. Severe Service compound provides optimum wear in severe conditions. High-strength tread and structure design. Specially formulated on/off highway tread compound to resist chipping and cutting. Heavy-Duty All-Steel casing for excellent retreadability.

H402 MIXED SERVICE

Medium Truck Radial



Tire Size	Code No.	Service Description	Tire Weight	Rim Width	Tread Depth	DUAL		SINGLE		Section Width	Overall Diameter	PRICE	F.E.T.
						Max Load	Max PSI	Max Load	Max PSI				
385/65R22.5/18	59976	158	171.0	11.75	21	9370		9370	120	14.96	42.24	\$	
425/65R22.5/20	59980	165	191	12.25	22	1140		1140	120	16.38	44.29		