



# KUMHO TIRES

Driven Beyond The Expected.™

## KUMHO VICTORACER V700

Competition Racing



**UTQG 50 AA A**

### Special Features

- ARC compounding technology for superior traction and handling.
- Minimum tread grooving for ultimate cornering power.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
185/60R14 82H	1793613	5.0 - 6.5	7.4 on 5.5	22.8	6.0	8.9	18.6	901	44	1047	\$
195/55R14 82V	1793713	5.5 - 7.0	7.9 on 6.0	22.4	6.0	10.2	19.9	901	44	1047	
205/55R14 85V	1793913	5.5 - 7.5	8.4 on 6.5	22.9	6.0	10.4	20.2	895	44	1135	
205/50R15 86Z	1793813	5.5 - 7.5	8.4 on 6.5	23.1	6.0	9.0	20.6	900	44	1168	
225/50R15 91Z	1794213	6.0 - 8.0	9.2 on 7.0	23.9	6.0	9.3	23.7	867	44	1323	
225/50R16 92Z	1794313	6.0 - 8.0	9.2 on 7.0	24.9	6.0	9.7	24.9	839	44	1389	
245/45R16 94Z	1794413	7.5 - 9.0	9.6 on 8.0	24.6	6.0	9.6	25.0	848	44	1477	
265/45R16 92Z	1794813	8.5 - 10.0	10.4 on 9.0	25.3	6.0	11.7	28.0	824	44	1709	
225/45R17 90Z	1794113	7.0 - 8.5	8.9 on 7.5	25.0	6.0	9.7	24.9	839	44	1323	
245/45R17 95Z	1794513	7.5 - 9.0	9.6 on 8.0	25.7	6.0	10.0	26.0	824	44	1521	
255/40R17 94Z	1794613	8.5 - 10.0	10.2 on 9.0	25.0	6.0	9.8	26.8	834	44	1477	
275/40R17 98Z	1794913	9.0 - 11.0	10.9 on 9.5	25.7	6.0	10.0	28.7	824	44	1654	
315/35R17 102Z	1795013	10.5 - 12.5	12.6 on 11.0	25.7	6.0	10.0	31.0	824	44	1874	

## KUMHO ECSTA V710

Competition Racing



**UTQG 30 C A**  
**\*UTQG 50 A A**

### Special Features

- ARC compounding technology for superior traction and handling.
- Minimum tread grooving for ultimate cornering power.
- Asymmetric tread pattern for efficient water evacuation on damp track surfaces.
- Two durable nylon cap plies give high speed stability and resistance to centrifugal forces.
- High ply turn-up and additional nylon reinforcement provides stiff sidewall constructions.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
215/50R13 85W	1798013	6.0 - 7.5	8.6 on 7.0	21.5	4.0	8.4	18.00	970	51	1135	\$
195/55R14 82W	1797613	5.5 - 7.0	7.9 on 6.0	22.4	4.0	10.2	17.60	931	51	1047	
205/55R14 85W	1797813	5.5 - 7.5	8.4 on 6.5	22.9	4.0	10.4	18.75	911	51	1135	
225/50R14 89W	1798113	6.0 - 8.0	9.1 on 7.0	22.9	4.0	10.4	20.48	911	51	1279	
205/50R15 86W	1797713	5.5 - 7.5	9.0 on 8.0	22.9	4.0	9.0	18.2	887	51	1168	
225/50R15 91W	1798213	6.0 - 8.0	9.2 on 7.0	23.9	4.0	9.3	21.50	872	51	1356	
NEW 215/45R16 86W	1903213	7.0-8.0	8.1 on 7.0	23.2	4.0	11.0	20.3	895	51	1167	
215/40R16 82W	1797913	7.0 - 8.5	8.6 on 7.5	22.8	4.0	8.9	18.22	915	51	1047	
225/50R16 92W	1798313	6.0 - 8.0	9.2 on 7.0	24.9	4.0	9.7	23.00	837	51	1389	
NEW 245/45R16 94W	1903513	7.5-9.0	9.6 on 8.0	24.6	4.0	11.4	21.7	844	51	1652	
265/45R16 92W	1798613	8.5 - 10.0	11.2 on 10.0	25.2	4.0	11.6	23.7	827	51	1389	
NEW 215/40R17 83W	1901213	7.0-8.5	9.1 on 8.0	24.1	4.0	11.2	20.4	862	51	1073	
NEW 225/45R17 90W	1909913	7.0-8.5	9.1 on 8.0	25.0	4.0	11.0	22.2	867	51	1322	
245/45R17 95W	1798513	7.5 - 9.0	9.6 on 8.0	25.7	4.0	10.0	23.88	811	51	1521	
NEW 245/40R17 91W	1901313	8.0-9.5	9.8 on 8.5	24.7	4.0	11.5	23.3	841	51	1355	
275/40R17 98W	1798713	9.0 - 11.0	11.4 on 10.5	25.4	4.0	10.0	24.5	821	51	1653	
295/40R17 102W	1798913	10.0 - 11.5	12.2 on 11.5	26.1	4.0	12.1	26.3	799	51	1874	
315/35R17 102W	1799013	10.5 - 12.5	12.9 on 12.0	25.4	4.0	11.8	26.3	821	51	1874	
335/35R17 106W	1799213	11.0 - 13.0	13.8 on 13.0	26.0	4.0	12.0	28.5	802	51	2094	
NEW 225/40R18 88W	1909813	7.5-9.0	9.1 on 8.0	25.1	4.0	11.7	21.9	828	51	1234	
NEW 245/40R18 93W	1910213	8.0-9.5	10.0 on 9.0	25.7	4.0	12.1	24.5	808	51	1432	
245/35R18 88W	1798413	8.0 - 9.5	9.8 on 8.5	24.8	4.0	15.6	21.66	841	51	1235	
285/30R18 93W	1798813	9.5 - 10.5	11.4 on 10.0	24.8	4.0	11.6	23.69	841	51	1433	
315/35R18 101W	1799113	10.5 - 12.5	12.9 on 12.0	26.4	4.0	12.3	27.6	790	51	1819	
NEW 305/30R18 98W	1893113*	10.0-12.0	12.3 on 11.0	25.2	6.0	N/A	27.9	824	51	1653	

## KUMHO ECSTA V700

Competition Racing



**UTQG 50 AA A**

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
245/40R17 91W	1792113	8.0 - 9.5	9.8 on 8.5	24.7	6.0	9.6	22.1	840	44	1356	\$
275/40R17 98W	1792513	9.0 - 11.0	10.9 on 9.5	25.7	6.0	10.0	27.4	818	44	1654	
315/35R17 102W	1793013	10.5 - 12.5	12.6 on 11.0	25.7	6.0	10.0	27.9	821	44	1874	
335/35R17 106W	1793313	11.0 - 13.0	13.5 on 12.0	26.2	6.0	0.0	32.1	802	44	2094	
225/40R18 88W	1790713	7.5 - 9.0	9.1 on 8.0	25.1	6.0	9.8	22.4	831	44	1235	
265/35R18 93W	1792313	9.0 - 10.5	10.7 on 9.5	25.3	6.0	9.9	24.8	825	44	1433	
305/30R18 98W	1792713	10.5 - 11.5	12.4 on 12.0	25.0	6.0	11.7	26.0	827	44	1654	
335/30R18 102W	1793213	11.5 - 12.5	13.5 on 12.0	25.9	6.0	10.1	29.9	809	44	1874	

### Special Features

- Advanced Silica tread compounding for superior wet & dry traction and handling.
- Large lateral and center channels provide maximum water evacuation.
- Advanced directional tread design for superior acceleration, braking and cornering.
- Two durable nylon cap plies give high speed stability and resistance to centrifugal forces.
- Two wide steel belts provide excellent cornering power and stable footprint.
- New polyester casing profile provides comfort and durability.

# KUMHO ECSTA W710

# Ultra High Performance



**UTQG 30 A A**

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
205/50R15 86V		5.5 - 7.5	8.4 on 6.5	22.9	8.0	10.6	15.8	907	51	1168	\$
215/45R16 86V		7.0 - 8.0	8.4 on 7.0	23.7	8.0	10.9	19.6	877	51	1168	
265/45R16 82V		8.0 - 9.5	10.2 on 9.0	25.2	8.0	11.6	24.8	824	51	1389	
275/40R17 98V		9.0 - 11.0	10.9 on 10.0	25.4	8.0	11.7	24.8	818	51	1653	
305/30R18 97V		10.0 - 11.5	11.8 on 11.0	25.5	8.0	11.9	26.5	815	51	1609	
335/30R19 103V		11.5 - 12.5	13.4 on 12.0	27.0	8.0	12.6	31.5	769	51	1929	

### Special Features

- Directional tread design for outstanding wet acceleration, braking and cornering performance.
- Advanced mold shape design optimizes footprint contact area and pressure distribuion for superior road traction.
- Special sidewall construction enhances driver feel and control.
- Extreme tread compound for ultimate wet grip performance.

# KUMHO ECSTA XS KU36

# Ultra High Performance



### Special Features

- Low void asymmetric tread pattern with circumferential grooving for high cornering grip.
- Ultra fine carbon black compounding for maximum traction.
- Ultra wide tread contact with highly rounded shoulders for optimized footprint shape during high lateral loads.
- Developed for quick autocross warm-up while maintaining race track durability.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	UTQG	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>												
205/50R15 86W	2106663	5.5 - 7.5	8.4 on 6.5	22.8	9.0	180 AA/A	10.7	19.2	899	51	1168	\$
225/50R16 92W	2105473	6.0 - 8.0	9.2 on 7.0	25.0	9.0	180 AA/A	11.5	22.6	834	51	1389	
215/45R16 86W	2105703	7.0 - 8.0	8.4 on 7.0	25.0	9.0	180 AA/A	11.0	20.0	919	51	1168	
265/45R16 98W	2107913	8.5 - 10.0	10.5 on 9.0	25.4	8.0	180 AA/A	11.7	28.2	818	51	1653	
215/45R17 87W	2105443	7.0 - 8.0	8.4 on 7.0	24.6	9.0	180 AA/A	11.5	20.7	844	51	1201	
225/45R17 93W	2113963	7.0 - 8.5	8.9 on 7.5	25.0	8.0	180 AA/A	11.6	23.5	831	51	1433	
235/45R17 93W	2105453	7.5 - 9.0	9.3 on 8.0	25.4	11.0	180 AA/A	11.8	23.9	818	51	1433	
245/40R17 91W	2105393	8.0 - 9.5	9.8 on 8.5	24.3	9.0	180 AA/A	11.5	25.0	841	51	1356	
245/45R17 95W	2108103	7.5 - 9.0	9.6 on 8.0	25.7	11.0	180 AA/A	11.9	26.7	808	51	1521	
255/40R17 94W	2105403	8.5 - 10.0	10.2 on 9.0	25.0	8.0	180 AA/A	11.7	25.1	831	51	1477	
275/40R17 98W	2105323	9.0 - 11.0	11.0 on 9.5	25.7	8.0	180 AA/A	11.9	27.9	808	51	1653	
285/40R17 101W	2105503	9.5 - 11.0	11.0 on 9.5	26.0	8.0	180 AA/A	12.0	30.2	799	51	1819	
295/35R17 98W	2105413	10 - 11.5	11.9 on 11.0	25.1	8.0	180 AA/A	11.7	29.8	827	51	1653	
225/40R18 92W	2105343	7.5 - 9.0	9.0 on 8.0	25.0	10.0	180 AA/A	11.8	22.9	828	50	1389	
225/45R18 94W	2106553	7.0 - 8.5	8.9 on 7.5	25.9	10.0	180 AA/A	12.1	22.9	802	50	1477	
235/40R18 95W	2105283	8.0 - 9.5	9.5 on 8.5	25.4	10.0	180 AA/A	11.9	26.6	818	50	1521	
245/35R18 92W	2106703	8.0 - 9.5	9.7 on 8.5	24.8	10.0	180 AA/A	11.7	26.2	838	50	1389	
245/40R18 93W	2107203	8.0 - 9.5	9.7 on 8.5	25.7	9.0	180 AA/A	12.0	26.6	808	51	1433	
265/35R18 97W	2105183	9.0 - 10.5	10.7 on 9.5	25.3	11.0	180 AA/A	12.1	27.2	821	50	1609	
275/35R18 99W	2105493	9.0 - 11.0	10.9 on 9.5	25.6	8.0	180 AA/A	11.9	28.2	811	50	1709	
315/35R17 102W	2105803	10.5 - 12.5	12.6 on 11.0	25.7	8.0	180 AA/A	11.9	32.4	808	51	1874	
335/35R17 106W	2105813	11.0 - 13.0	13.5 on 12.0	26.2	8.0	180 AA/A	12.1	34.4	793	51	2094	
315/30R18 98W	2105823	10.5 - 11.5	12.6 on 11.0	25.5	8.0	180 AA/A	11.9	32.6	815	51	1653	
285/35R19 90W	2107503	9.5 - 11.0	11.4 on 10.0	26.9	8.0	180 AA/A	12.6	31.4	772	51	1323	
345/30R19 98W	2106113	11.5 - 12.5	13.8 on 12.0	27.2	8.0	180 AA/A	12.7	37.4	764	51	1653	

# KUMHO ECSTA MX

# Ultra High Performance



**UTQG 220 AA A**

### Special Features

- Advanced Silica tread compounding for superior wet & dry traction and handling.
- Large lateral and center channels provide maximum water evacuation.
- Advanced directional tread design for superior acceleration, braking and cornering.
- Two durable nylon cap plies give high speed stability and resistance to centrifugal forces.
- Two wide steel belts provide excellent cornering power and stable footprint.
- Rim Protector in the lower sidewall safeguards wheel against scratches and abraisions. (Available in 45 series and below.)

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
245/45R17 95Y **	2102783	7.5 - 9.0	9.6 on 8.0	25.7	9.0		31.7		51	1581	\$
275/40R18 99Y**	2103323	9.0 - 11.0	10.9 on 9.5	26.7	9.0	10.4	34.4	779	52	1709	

\*\* = EXTRA LOAD / RUN FLAT SIZES

# KUMHO LX PLATINUM

Ultra High Performance



**UTQG 600 A A**  
**↑UTQG 601 A A**

### Special Features

Asymmetric tread design optimizes all-season performance.

- Four circumferential channels efficiently evacuate water to maximize wet grip.
- Waffle design sipes remain fully interlocked to deliver high G-force braking.
- Stress relief dimples provide maximum sipe opening for linear snow traction without compromising lateral grip.
- Jointless nylon cap construction provides lower vibration and enhanced ride comfort.
- Sophisticated sidewall design complements today's luxury touring sedans.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
2185/60R14 82H	2105933	5.0 - 6.5	7.3 on 5.5	22.7	11.0	10.4	16.8	915	51	1047	\$
195/60R14 86V	2106743	5.5 - 7.0	7.8 on 6.5	23.1	11.0	10.5	18.7	899	51	1169	
185/65R15 88V	2108593	5.0 - 6.0	7.3 on 5.5	24.4	11.0	11.1	18.5	851	51	1235	
195/55R15 85V	2105973	5.5 - 7.0	7.8 on 6.0	23.6	11.0	10.9	12.0	880	51	1136	
195/60R15 88V	2105113	5.5 - 7.0	7.8 on 6.0	24.1	11.0	11.1	19.7	862	51	1235	
195/65R15 91V	2107023	5.5 - 7.0	7.8 on 6.0	24.9	11.0	11.4	20.3	834	51	1356	
205/60R15 91V	2105123	5.5 - 7.5	8.1 on 6.0	24.6	11.0	11.3	20.9	844	51	1356	
205/65R15 94V	2107523	5.5 - 7.5	8.2 on 6.0	25.5	11.0	11.6	21.7	815	51	1477	
215/60R15 94V	2105983	6.0 - 8.0	8.5 on 6.5	25.1	11.0	11.4	24.0	828	51	1477	
225/60R15 96V	2106453	6.0 - 8.0	8.8 on 6.5	25.6	11.0	11.6	25.0	811	51	1565	
205/55R16 91V	2106463	5.5 - 7.5	8.3 on 6.5	25.0	11.0	11.5	21.9	831	51	1356	
205/60R16 96V*	2107273	5.5 - 7.5	8.1 on 6.0	25.6	11.0	11.7	23.7	811	50	1565	
205/65R16 95V	2106443	5.5 - 7.5	8.1 on 6.0	26.5	11.0	12.1	22.6	784	51	1521	
215/55R16 97W*	2106483	6.0 - 7.5	8.8 on 7.0	25.4	11.0	11.7	25.2	818	50	1609	
215/60R16 95V	2100923	6.0 - 7.5	8.5 on 6.5	26.1	11.0	11.9	25.0	796	51	1521	
225/55R16 95W	2105023	6.0 - 8.0	9.2 on 7.0	25.7	11.0	11.8	24.3	808	51	1521	
225/60R16 98W	2104583	6.0 - 8.0	8.8 on 6.5	26.6	11.0	12.1	28.1	781	51	1653	
235/60R16 100W	2108603	6.5 - 8.5	9.3 on 7.0	27.0	11.0	12.3	29.3	769	51	1764	
205/50R17 93W*	2106783	5.5 - 7.5	8.3 on 6.5	25.0	11.0	11.6	22.5	831	50	1433	
215/50R17 91W	2105893	6.0 - 7.5	8.8 on 7.0	25.4	11.0	11.8	22.9	818	51	1356	
NEW 215/50R17 95W	2127263	6.0 - 7.5	8.8 on 7.0	25.4	11.0	11.8	23.3	818	51	1521	
215/55R17 94W	2104603	6.0 - 7.5	8.8 on 7.0	26.3	11.0	12.1	25.2	790	51	1477	
225/45R17 91W	2104613	7.0 - 8.5	8.9 on 7.5	25.0	11.0	11.6	23.0	831	51	1356	
225/50R17 98W*	2104533	6.0 - 8.0	8.9 on 7.0	25.9	11.0	12.0	26.6	802	50	1653	
225/55R17 101W*	2104293	6.0 - 8.0	9.2 on 7.0	26.8	11.0	12.3	27.5	775	50	1819	
225/60R17 98V**	2105063	6.0 - 8.0	8.9 on 6.5	27.6	11.0	10.8	27.2	753	51	1653	
235/45R17 97W*	2105063	7.5 - 9.0	9.3 on 8.0	25.4	11.0	11.8	26.4	818	50	1609	
235/50R17 96W	2106423	6.5 - 8.5	9.6 on 8.5	26.3	11.0	12.1	28.0	790	51	1565	
235/55R17 103W*	2104523	6.5 - 8.5	9.6 on 8.5	27.2	11.0	12.5	28.6	764	50	1929	
235/55R17 99V**	2106423	6.5 - 8.5	9.6 on 8.5	27.2	11.0	12.5	28.6	764	50	1929	
225/40R18 92W	2104623	7.5 - 9.0	9.0 on 8.0	25.0	11.0	11.7	22.2	831	50	1389	
225/45R18 95W	2104543	7.0 - 8.5	8.9 on 7.5	25.9	11.0	12.1	27.1	802	50	1521	
225/50R18 95W	2106543	6.0 - 8.0	9.3 on 7.0	26.9	11.0	12.5	26.6	772	51	1521	
235/40R18 95W	2105083	8.0 - 9.5	9.5 on 8.5	25.4	11.0	11.9	24.9	818	50	1521	
235/50R18 98W	2106133	6.5 - 8.5	9.6 on 7.5	27.3	11.0	12.6	28.7	761	51	1609	
NEW 245/40R18 97W	2134363	8.0 - 9.5	9.8 on 8.5	25.7	11.0	12.0	26.6	808	51	1609	
245/45R18 100W	2107283	7.5 - 9.0	9.6 on 8.0	26.7	11.0	12.4	29.0	778	50	1764	
255/45R18 99W	2106153	8.0 - 9.5	10.1 on 8.0	27.0	11.0	12.5	30.1	769	51	1708	
245/40R19 98W	2107303	8.0 - 9.5	9.8 on 8.5	26.7	11.0	12.5	29.3	778	50	1653	

\* Reinforced Tire

\*\* XRP- Extended Run Flat Technology

### COMPTON

1714 Anderson Ave.  
Compton, CA 90220  
Local 310-631-8200 • Fax 310-631-2503  
**Toll Free: 1-800-962-5222**

### BAKERSFIELD

7600 District Blvd., Suite B  
Bakersfield, CA 93313  
Local 661-831-5600 • Fax 661-831-5641  
**Toll Free: 1-888-414-8473**

### UNION CITY

33375 Central Ave.  
Union City, CA 94587  
Local 510-489-7600 • Fax 510-489-0494  
**Toll Free: 1-800-447-8473**

### PHOENIX

601 South 65th Avenue, Suite 6  
Phoenix, AZ 85043  
Local 623-474-4660 • Fax 623-474-4661  
**Toll Free: 1-855-825-8473**

### HOUSTON

3635 Willowbend Blvd.  
Houston, TX 77054  
Local 713-660-6600 • Fax 713-660-9633  
**Toll Free: 1-800-711-3919**

### SAN ANTONIO

4530 Tejasco Dr.  
San Antonio, TX 78218  
Local 210-212-8866 • Fax 210-212-8815  
**Toll Free: 1-800-666-8840**

### DALLAS

9500 Royal Lane, Suite 160  
Irving, Texas 75063  
Local 972-484-6900 • Fax 972-484-7742  
**Toll Free: 1-888-455-2234**



### MIAMI

9800 NW 100 Road  
Medley, FL 33178  
Local 305-887-8876 • Fax 305-470-9967  
**Toll Free: 1-888-833-3953**

### TAMPA

9110 King Palm Drive, Suite 106  
Tampa FL 33619  
Local 813-626-0866 • Fax 813-626-0977  
**Toll Free: 1-800-483-2099**

### ORLANDO

2222 Diversified Way  
Orlando, FL 32804  
Local 407-218-4600 • Fax 407-218-4601  
**Toll Free: 1-800-903-0014**

### PORTLAND

7515 N. Leadbetter Dr.  
Portland, Oregon 97203  
Local 503-283-0416 • Fax 503-240-3342  
**Toll Free: 1-866-977-8473**

### CHICAGO

3710 N River Road, Suite 400  
Franklin Park, IL 60131  
Local 708-450-7000 • Fax 708-450-7001  
**Toll Free: 1-866-220-8439**

### OHIO/MICHIGAN

14801 TR 212  
Findlay, OH 45840  
Local 419-425-6508 • Fax 419-425-6514  
**Toll Free: 1-877-309-1972**



**UTQG 420 AA A**

**30,000 Mile Limited Warranty**

**Special Features**

- Asymmetric tread design optimizes all season and dry performance.
- Large outside shoulder blocks for maximized cornering performance.
- High angle slant grooves on inside of tread for optimum water drainage.
- E technology step grooves and sipes increase edge effect for increased wet and snow performance.
- High volume circumferential grooves provide maximum water drainage for hydroplaning resistance.
- High Tech silica tread compound maximizes dry and wet grip without giving up snow traction.
- Multi Zone tread contour provides dynamic casing control for improved comfort and handling.
- Rim protector in the lower sidewall safeguards wheel against scratches and abrasions.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
195/55R15 85V	1741413	5.5 - 7.0	7.9 on 6.0	23.4	10.0	9.1	23.4	887	51	1135	\$
195/60R15 88V	1761813	5.5 - 7.0	7.9 on 6.0	24.2	10.0	9.4	21.2	858	51	1235	
195/65R15 91V	1761913	5.5 - 7.0	7.9 on 6.0	25.0	10.0	9.8	21.2	831	51	1356	
205/50R15 86W	1741613	5.5 - 7.5	8.4 on 6.5	23.1	10.0	9.0	19.3	899	51	1168	
205/55R15 88V	1741913	5.5 - 7.5	8.4 on 6.5	23.9	10.0	9.3	19.8	869	51	1235	
<b>NEW</b> 205/65R15 94V	1761513	5.5-7.5	8.2 on 6.0	25.5	10.0	9.9	21.0	816	51	1477	
205/60R15 91V	1762013	5.5 - 7.5	8.2 on 6.0	24.7	10.0	9.4	22.6	858	51	1356	
225/60R15 96V	1762113	6.0 - 8.0	9.0 on 6.5	25.6	10.0	10.0	25.6	811	51	1565	
195/50R16 84W	1741313	5.5 - 7.0	7.9 on 6.0	23.7	10.0	9.2	18.6	877	51	1102	
205/45R16 87W**	1741513	6.5 - 7.5	8.1 on 7.0	23.2	10.0	9.1	19.3	894	50	1202	
205/50R16 87W	1741713	5.5 - 7.5	8.4 on 6.5	24.1	10.0	9.4	20.1	862	51	1202	
205/55R16 91W	1732513	5.5 - 7.5	8.4 on 6.5	24.9	10.0	9.7	21.6	835	51	1356	
215/50R16 90W	1742013	6.0 - 7.5	8.9 on 7.0	24.5	10.0	9.6	21.1	848	51	1323	
215/55R16 93W	1734113	6.0 - 7.5	8.9 on 7.0	25.3	10.0	9.9	22.8	822	51	1433	
225/50R16 92W	1734313	6.0 - 8.0	9.2 on 7.0	24.9	10.0	9.7	23.4	835	51	1389	
225/55R16 95W	1732013	6.0 - 8.0	9.2 on 7.0	25.7	10.0	10.0	23.8	807	51	1521	
225/60R16 98V	1775613	6.0 - 8.0	9.0 on 6.5	26.6	10.0	10.4	27.5	781	51	1653	
235/60R16 100V	1775713	6.5 - 8.5	9.4 on 7.0	27.1	10.0	10.6	28.6	767	51	1764	
245/50R16 97W	1734613	7.0 - 8.5	10.0 on 7.5	25.7	10.0	10.0	27.2	809	51	1609	
205/40R17 84W**	1733713	7.0 - 8.0	8.3 on 7.5	23.5	10.0	9.2	19.2	885	50	1102	
205/50R17 93W**	1741813	5.5 - 7.5	8.4 on 6.5	25.1	10.0	9.8	22.4	827	50	1433	
215/40R17 87W**	1735713	7.0 - 8.5	8.6 on 7.5	23.8	10.0	9.3	20.7	874	50	1202	
215/45R17 91W**	1734013	7.0 - 8.0	8.4 on 7.0	24.6	10.0	9.6	21.6	843	50	1356	
215/50R17 91W	1742113	6.0 - 7.5	8.9 on 7.0	25.5	10.0	9.9	22.9	814	51	1356	
215/55R17 94V	1762813	6.0 - 7.5	8.9 on 7.0	26.3	10.0	11.7	24.3	822	51	1477	
<b>NEW</b> 215/50R17 95W	2127253	6.0-7.5	8.9 on 7.0	25.5	10.5	9.9	23.0	814	51	1521	
225/45R17 94W**	1735913	7.0 - 8.5	8.9 on 7.5	25.0	10.0	9.7	23.6	832	50	1477	
225/50R17 94W	1758313	6.0 - 8.0	9.2 on 7.0	25.9	10.0	10.1	25.0	802	51	1477	
225/55R17 97W	1758413	6.0 - 8.0	9.2 on 7.0	26.8	10.0	10.4	28.6	776	51	1609	
235/40R17 94W**	1732113	8.0 - 9.5	9.5 on 8.5	24.4	10.0	9.5	23.6	851	50	1477	
235/45R17 94W	1705013	7.5 - 9.0	9.3 on 8.0	25.4	10.0	9.9	24.9	819	51	1477	
235/50R17 96W	1758513	6.5 - 8.5	9.6 on 7.5	26.3	10.0	10.3	28.4	790	51	1565	
235/55R17 99W	1911613	6.5-8.5	9.6 on 7.5	27.2	10.0	N/A	26.7	764	51	1709	
245/40R17 91W	1734513	8.0 - 9.5	9.8 on 8.5	24.7	10.0	9.6	26.3	840	51	1356	
245/45R17 95W	1736113	7.5 - 9.0	9.6 on 8.0	25.7	10.0	10.0	28.2	809	51	1521	
255/40R17 94W	1736213	8.5 - 10.0	10.2 on 9.0	25.0	10.0	9.8	27.8	830	51	1477	
255/45R17 98W	1742413	8.0 - 9.5	10.0 on 8.5	26.1	10.0	10.2	27.9	797	51	1653	
255/50R17 101W	1742613	7.0 - 9.0	10.4 on 8.0	27.1	10.0	10.6	30.1	767	51	1819	
275/40R17 98W	1736313	9.0 - 11.0	10.9 on 9.5	25.7	10.0	10.0	30.1	809	51	1653	
285/40R17 100W	1742913	9.5 - 11.0	11.4 on 10.0	26.0	10.0	10.1	30.7	799	51	1764	
215/35R18 84W**	1735613	7.0 - 8.5	8.6 on 7.5	23.9	10.0	9.3	20.0	869	50	1102	
215/45R18 93W	2102343	7.0-8.0	8.4 on 8.0	25.6	10.0	N/A	N/A	812	50	1433	
225/40R18 92W**	1735813	7.5 - 9.0	9.1 on 8.0	25.1	10.0	9.8	23.0	828	50	1389	
225/45R18 94W	1911413	7.0 - 8.5	8.9 on 7.5	25.9	10.0	N/A	26.0	802	50	1477	
235/45R18 94W	1911513	7.5-9.0	9.3 on 8.0	26.3	10.0	N/A	27.8	790	50	1477	
235/40R18 95W**	1731013	8.0 - 9.5	9.5 on 8.5	25.4	10.0	9.9	24.2	818	50	1521	
235/50R18 97W	1742213	6.5 - 8.5	9.6 on 7.5	27.3	10.0	10.6	27.7	761	51	1609	
245/40R18 93W	1736013	8.0 - 9.5	9.8 on 8.5	25.7	10.0	10.0	26.9	808	51	1433	
245/45R18 100W	1911713	7.5 - 9.0	9.6 on 8.0	26.7	10.0	N/A	29.3	778	50	1764	
<b>NEW</b> 245/40R18 97W	2127283	8.0-9.5	9.8 on 8.5	25.7	10.0	10.0	27.2	808	51	1609	
255/35R18 90W	1742313	8.5 - 10.0	10.2 on 9.0	25.0	10.0	9.8	27.3	831	51	1323	
255/45R18 99W	1742513	8.0 - 9.5	10.0 on 8.5	27.0	10.0	12.5	30.0	768	51	1709	
265/35R18 93W	1742713	9.0 - 10.5	10.7 on 9.5	25.3	10.0	9.9	28.4	821	51	1433	
275/35R18 95W	1742813	9.0 - 11.0	10.9 on 9.5	25.6	10.0	10.0	29.4	813	51	1521	
275/40R18 99W	1736413	9.0 - 11.0	10.9 on 9.5	26.7	10.0	10.4	32.1	779	51	1709	
245/40R20 95W	2102103	8.0 - 9.5	9.7 on 8.5	27.7	10.0	N/A	N/A	742	50	1521	
245/45R20 99W	1892613	7.0 - 9.0	9.6 on 8.0	28.7	10.0	N/A	32.1	724	50	1708	
255/45R20 101W**1899613	8.0 - 9.5	10.0 on 8.5	29.0	10.0	N/A	N/A	33.6	716	50	1819	
245/30R22 92W**	1892513	8.0 - 9.0	9.7 on 8.5	27.8	10.0	N/A	30.4	747	50	1389	
255/30R22 95W**	1888313	8.5 - 9.5	10.2 on 9.0	28.0	10.0	N/A	31.7	742	50	1521	
285/25R22 102W	2102123	10.5	11.6 on 10.5	27.6	10.0	N/A	N/A	753	50	1874	
295/25R22 97W	2102113	10.0 - 11.0	11.9 on 10.5	27.8	10.0	N/A	N/A	747	50	1609	
255/30R24 97W**	1892713	8.5 - 9.5	10.2 on 9.0	30.0	10.0	N/A	35.5	690	50	1565	
275/25R24 96W	2102143	10	11.1 on 10	29.4	10.0	N/A	N/A	707	50	1565	
275/30R24 101W**1889213	9.0 - 10.0	10.9 on 9.5	30.5	10.0	N/A	N/A	38.2	681	50	1819	

\*\* = EXTRA LOAD



**UTQG 320 AA A**

**30,000 Mile Limited Warranty**

**Special Features**

- High dispersion silica expands compound performance envelope for superior wet grip and better treadwear.
- Race proven carcass design with jointless cap plies, wide steel belts, ESCOT carcass profile and high durometer apex delivers razor sharp response and extreme grip without compromising ride quality.
- Three-dimensional lateral grooves optimize water evacuation in footprint.
- Triple tread radius optimizes footprint shape for even pressure distribution.
- Shoulder blocks tilted into direction of travel to improve grip and reduce worn noise.
- Rim protector in the lower sidewall safeguards wheel against scratches and abrasions.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
195/55R16 87V XRP	1852213	5.5 - 7.0	7.9 on 6.0	24.4	10.0	11.3	23.0	851	50	1202	\$
205/55R16 91W	1763713	5.5 - 7.5	8.4 on 6.5	24.9	10.0	9.7	21.5	835	51	1353	
215/55R16 97W**	1765013	6.0 - 7.5	8.9 on 7.0	25.3	10.0	9.9	24.9	822	51	1430	
<b>NEW</b> 225/50R16 92W	1765913	6.0 - 8.0	9.2 on 7.0	24.9	10.0	9.7	23.7	835	51	1389	
225/55R16 99W**	1766113	6.0 - 8.0	9.2 on 7.0	25.7	10.0	10.0	26.1	807	51	1518	
<b>NEW</b> 225/55R16 95W	1905513	6.0 - 8.0	9.2 on 7.0	24.9	11.0	9.7	32.5	835	51	1521	
205/45R17 84V XRP	1805113	6.5 - 7.5	8.1 on 7.0	24.3	10.0	9.5	26.7	857	50	1102	
205/50R17 93W**	1834613	5.5 - 7.5	8.4 on 6.5	25.1	10.0	9.8	23.0	827	50	1430	
215/45R17 91W**	1763913	7.0 - 8.0	8.4 on 7.0	24.6	10.0	9.6	22.3	843	51	1199	
215/50R17 95W**	1822513	6.0 - 7.5	8.9 on 7.0	25.5	10.0	9.9	24.8	814	50	1353	
225/45R17 94W**	1765313	7.0 - 8.5	8.9 on 7.5	25.0	10.0	9.7	23.7	832	50	1353	
225/45R17 91W XRP	1866213	7.0 - 8.5	8.9 on 7.5	25.0	10.0	9.7	28.0	832	50	1356	
225/50R17 98W**	1824313	6.0 - 8.0	9.2 on 7.0	25.9	10.0	10.1	TBD	802	50	1474	
<b>NEW</b> 225/55R17 101W	1822713	6.0 - 8.0	9.2 on 7.0	26.7	10.0	10.4	27.3	776	50	1819	
225/50R17 94W XRP	1866313	6.0 - 8.0	9.2 on 7.0	25.9	10.0	10.1	30.2	802	50	1477	
235/45R17 97W**	1765113	7.5 - 9.0	9.3 on 8.0	25.4	10.0	9.9	25.9	819	50	1474	
235/50R17 96Y	2103673	6.5 - 8.5	9.6 on 7.5	26.3	10.0	12.1	27.1	790	50	1565	
235/55R17 103W	1822813	6.5 - 8.5	9.6 on 7.5	27.0	10.0	12.5	29.2	767	50	1929	
245/40R17 95Y	1769213	8.0 - 9.5	9.8 on 8.5	24.7	10.0	9.6	25.1	840	51	1518	
245/45R17 95W	1768713	7.5 - 9.0	9.6 on 8.0	25.7	10.0	10.0	26.8	809	51	1518	
255/40R17 94Y	1768813	8.5 - 10.0	10.2 on 9.0	25.0	10.0	9.8	25.8	830	51	1474	
255/45R17 98W	1767413	8.0 - 9.5	10.0 on 8.5	26.1	10.0	10.2	29.0	797	51	1650	
255/50R17 101W	1835213	7.0 - 9.0	10.4 on 8.0	27.1	10.0	10.6	29.7	767	51	1815	
275/40R17 98W	1835513	9.0 - 11.0	10.9 on 9.5	25.7	10.0	10.0	29.1	809	51	1650	
285/40R17 100W	1835713	9.5 - 11.0	11.4 on 10.0	26.0	10.0	10.1	31.3	799	51	1760	
215/35R18 94Y**	1767813	7.0 - 8.5	8.6 on 7.5	23.9	10.0	9.3	19.6	869	50	1100	
215/40R18 89Y**	1834813	7.0 - 8.5	8.6 on 7.5	24.8	10.0	9.7	22.2	839	50	1276	
215/45R18 89Y**	1769613	7.0 - 8.0	8.4 on 7.0	25.6	10.0	10.0	21.8	811	50	1276	
225/40R18 92Y**	1765213	7.5 - 9.0	9.1 on 8.0	25.1	10.0	9.8	23.6	828	50	1386	
225/45R18 91Y	1769013	7.0 - 8.5	8.9 on 7.5	25.9	10.0	10.1	24.4	801	51	1353	
235/40R18 95Y**	1766213	8.0 - 9.5	9.5 on 8.5	25.4	10.0	9.9	25.8	818	50	1386	
235/45R18 98W**	1769713	7.5 - 9.0	9.3 on 8.0	26.3	10.0	10.3	27.5	789	50	1650	
235/50R18 101Y**	1769113	6.5 - 8.5	9.6 on 7.5	27.3	10.0	10.6	27.8	761	50	1815	
245/40R18 97Y**	1769313	8.0 - 9.5	9.8 on 8.5	25.7	10.0	10.0	26.6	808	50	1606	
245/40R18 93V XRP	1869513	8.0 - 9.5	9.8 on 8.5	25.7	10.0	10.0	30.3	808	50	1433	
245/45R18 100Y	1890713	7.5 - 9.0	9.7 on 9.0	26.8	10.0	12.4	28.4	775	50	1764	
245/50R18 100W	1768513	7.0 - 8.5	10.0 on 7.5	27.7	10.0	10.8	28.3	751	50	1760	
245/50R18 100W XRP	1852613	7.0 - 8.5	10.0 on 7.5	27.7	10.0	10.8	39.3	751	50	1764	
265/35R18 97Y**	1769513	9.0 - 10.5	10.7 on 9.5	25.3	10.0	9.9	28.2	821	50	1430	
275/35R18 99Y*	1835413	9.0 - 11.0	10.9 on 9.5	25.6	10.0	10.0	29.2	813	50	1705	
275/40R18 99W	1835613	9.0 - 11.0	10.9 on 9.5	26.7	10.0	10.4	31.2	779	51	1705	
295/30R18 94Y	1770013	10.0 - 11.0	11.9 on 10.5	25.0	10.0	11.7	29.8	831	51	1474	
215/35R19 85Y**	1834713	7.0 - 8.5	8.6 on 7.5	24.9	10.0	9.7	22.1	834	50	1133	
225/35R19 88Y**	1834913	7.5 - 9.0	9.1 on 8.0	25.2	10.0	9.8	23.1	823	50	1232	
235/35R19 91Y**	1768613	8.0 - 9.5	9.5 on 8.5	25.5	10.0	9.9	25.1	816	50	1353	
245/35R19 93Y**	1824513	8.0 - 9.5	9.8 on 8.5	25.8	10.0	10.1	26.7	806	50	1430	
<b>NEW</b> 225/40R19 93Y	1894713	7.5 - 9.5	9.4 on 8.0	26.1	10.0	12.3	25.0	796	50	1433	
245/40R19 98Y	1824713	8.0 - 9.5	9.7 on 8.5	26.7	10.0	12.5	28.0	778	50	1477	
245/45R19 100Y	1890813	7.5 - 9.0	9.6 on 8.0	27.6	10.0	12.9	29.5	753	50	1874	
255/35R19 96Y	1893913	8.5 - 10.0	10.2 on 9.0	26.0	10.0	12.2	27.2	799	50	1356	
255/40R 19 100Y	1890913	8.5 - 10.0	10.2 on 9.0	27.0	10.0	12.6	29.9	739	50	1764	
265/30R19 93Y**	1769913	9.0 - 10.0	10.7 on 9.5	25.3	10.0	9.9	27.5	821	50	1430	
275/30R19 97Y**	1825013	9.0 - 10.0	10.9 on 9.5	25.6	10.0	10.0	29.6	813	50	1609	
275/35R19 100Y	1894813			26.6	10.0			50		1764	
275/40R19 105Y	1891013	9.0 - 11.0	10.9 on 9.5	27.6	10.0	12.9	32.7	753	50	2039	
285/35R19 99Y	1899313	9.5 - 11.0	11.4 on 10.0	26.9	10.0	12.9	31.1	772	50	1709	
225/30R20 85Y	1911113	8	9.0 on 8.0	25.3	10.0	12.1	23.5	821	50	1135	
225/35R20 89Y**	1835013	7.5 - 9.0	9.1 on 8.0	26.2	10.0	10.2	24.6	792	50	1276	
235/30R20 88Y	2102463	8.5	9.5 on 8.5	25.5	10.0	12.1	28.1	815	50	1235	
235/35R20 90Y	2103683	8.5	9.3 on 8.0	26.4	10.0	12.3	27.7	787	50	1323	
245/35R20 95Y**	1824613	8.0 - 9.5	9.8 on 8.5	26.8	10.0	10.4	27.8	776	50	1518	
245/40R20 95Y	1824813	8.0 - 9.5	9.7 on 8.5	27.7	10.0	13.0	29.3	750	50	1521	
245/45R20 99Y	2104213	7.5 - 9.0	9.6 on 8.0	28.7	10.0	13.4	32.4	724	50	1708	
255/35R20 97Y**	1769413	8.5 - 10.0	10.2 on 9.0	27.0	10.0	10.5	28.5	769	50	1606	
275/30R20 97Y**	1835313	9.0 - 10.0	10.9 on 9.5	26.5	10.0	10.3	30.8	783	50	1606	
275/35R20	1894913	9.0 - 11.0	10.9 on 9.5	27.5	10.0	13.0	32.6	755	50	1653	
285/30R20 99Y		9.5 - 10.5	11.4 on 10.0	26.7	10.0			50		1708	
235/30R22 90Y	2102453	8.5	9.5 on 8.5	27.6	10.0	13.1	31.5	753	50	1323	
265/30R22 93Y	1899113	9.0 - 10.0	10.6 on 9.5	28.3	10.0	13.5	31.5	734	50	1433	
285/35R22 102Y	2103693	9.5 - 11.0	11.4 on 10.0	29.8	10.0	14.1	34.1	697	50	1874	
295/25R22 97Y	1899413	10.0 - 11.0	11.8 on 10.5	27.8	10.0	13.3	33.2	747	50	1609	
<b>YELLOW</b>											
255/40R17 94W	1867013	8.5 - 10.0	10.2 on 9.0	25.0	10.0	9.8	25.8	830	51	1474	
<b>COLORED SMOKE TIRES</b>											
245/40R17 95W	2105383	8.0 - 9.0	9.8 on 8.5	24.7	10.0	11.5	24.9	841	51	1521	
255/35R18 94W	2105193	8.5 - 10.0	10.2 on 9.0	25.0	10.0	11.7	26.9	831	51	1477	
265/30R19 93W	2111453	9.0 - 10.0	10.7 on 9.5	25.3	10.0	9.9	27.7	821	50	1433	

\*\* = EXTRA LOAD  
XPR = XTREME RUNFLAT PROTECTION

# KUMHO ECSTA AST

# High Performance Tuner Radial



## UTQG 420 A A

### Special Features

- Advanced belt package design is constructed using high tensile steel belt & jointless nylon capply to reinforce the tread area assuring high speed stability.
- An ultra hard filler material is used to maximize lateral grip and high speed stability.
- Outstanding all-Season compound is designed to improve wear resistance and ride comfort.
- A specially designed, high strength bead wire increases the tire's load capacity and minimizes the vibration caused by road surfaces.
- Rim protector in the lower sidewall safeguards wheel against scratches and abrasions.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
195/50R15 82H	1825113	5.5 - 7.0	7.9 on 6.0	22.7	10.0	8.9	17.9	914	51	1047	\$
205/50R15 86H	1844713	5.5 - 7.5	8.4 on 6.5	23.1	10.0	9.0	19.2	899	51	1168	
225/50R15 91H	1845313	6.0 - 8.0	9.2 on 7.0	23.9	10.0	9.3	21.1	869	44	1356	
205/40R16 83H**	1844313	7.0 - 8.0	8.3 on 7.5	22.4	10.0	8.8	18.6	926	50	1074	
205/45R16 87H**	1844513	6.5 - 7.5	8.1 on 7.0	23.2	10.0	9.1	19.9	894	51	1202	
205/50R16 87H	1844813	5.5 - 7.5	8.4 on 6.5	24.1	10.0	9.4	20.0	862	51	1202	
225/50R16 92H	1845413	6.0 - 8.0	9.2 on 7.0	24.9	10.0	9.7	22.7	835	51	1389	
245/50R16 97H	1845613	7.0 - 8.5	10.0 on 7.5	25.7	10.0	10.0	26.1	809	51	1609	
205/45R17 88H**	1844613	6.5 - 7.5	8.1 on 7.0	24.3	10.0	9.5	20.8	857	50	1235	
215/45R17 91H**	1845113	7.0 - 8.0	8.4 on 7.0	24.6	10.0	9.6	22.3	843	51	1356	
225/45R17 94H**	1840713	7.0 - 8.5	8.9 on 7.5	25.0	10.0	9.7	23.5	832	51	1477	
235/45R17 94H	1781913	7.5 - 9.0	9.3 on 8.0	25.4	10.0	9.9	23.5	819	51	1477	
245/45R17 95H	1845513	7.5 - 9.0	9.6 on 8.0	25.7	10.0	10.0	25.9	809	51	1521	
205/40R17 84H**	1844413	7.0 - 8.0	8.3 on 7.5	23.5	10.0	9.2	19.3	885	50	1102	
215/40R17 87H**	1845013	7.0 - 8.5	8.6 on 7.5	23.8	10.0	9.3	20.5	874	51	1202	
225/40R18 92H**	1845213	7.5 - 9.0	9.1 on 8.0	25.1	10.0	9.8	22.9	828	51	1389	
215/35R18 84H**	1844913	7.0 - 8.5	8.6 on 7.5	23.9	10.0	9.3	19.8	869	50	1102	

\*\* = EXTRA LOAD

# KUMHO SOLUS KH-16

# Performance Radial



### Special Features

- KUMHO's patented design technology optimizes casing shape, tread contact and sidewall stiffness to maintain outstanding ability to absorb bumps even while increasing the response.
- Computer aided design and high technology tread compound creates a perfect blend of tread block stiffness that increases mileage delivered by the KH16.
- Multi siped tread design and optimum groove placement increases bad weather grip for driving in rain, snow or shine.
- KUMHO's exclusive Cornering Lag Technology (CLT) greatly reduces the time lag from when the steering wheel is turned until the vehicle reacts. "CLT" increases steering response without giving up ride comfort.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	UTQG	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>												
<b>NEW</b> P175/70R14 84T	2126053	4.5 - 5.5	7.0 on 5.0	23.7	10	440 AA/A	10.9	15.7	879	44	1102	\$
<b>NEW</b> P185/65R14 85H	1918413	5.0 - 6.5	7.3 on 6.0	23.4	10.0	440 AA/A	10.7	16.5	888	44	1124	
P185/60R14 82H	1770213	5.0 - 6.5	7.4 on 5.5	22.8	10.0	440 AA/A	8.9	16.7	913	44	1047	
P195/60R14 85H	1775413	5.5 - 7.0	7.9 on 6.0	23.2	10.0	440 AA/A	9.1	18.0	894	44	1135	
P185/65R15 86H	1799413	5.0 - 6.5	7.4 on 5.5	24.5	10.0	440 AA/A	9.5	18.4	850	44	1168	
P195/55R15 84V	1757913	5.5 - 7.0	7.9 on 6.0	23.4	10.0	440 AA/A	10.7	18.2	888	44	1102	
<b>NEW</b> P195/60R15 87H	2123043	5.5 - 7.0	7.9 on 6.0	24.2	10.0	440 AA/A	9.4	18.2	858	44	1190	
P195/65R15 89H	1755913	5.5 - 7.0	7.9 on 6.0	25.0	10.0	440 AA/A	9.8	19.8	830	44	1279	
P205/60R15 90H	1774713	5.5 - 7.5	8.2 on 6.0	24.7	10.0	440 AA/A	9.6	20.2	842	44	1323	
<b>NEW</b> P205/65R15 92H	1775513	5.5 - 7.5	8.2 on 6.0	25.5	10.0	400 AA/A	9.9	21.0	818	44	1477	
P215/60R15 93H	1774813	6.0 - 7.5	8.7 on 6.5	25.2	10.0	440 AA/A	9.8	23.3	826	44	1411	
P215/65R15 95H	1770413	6.0 - 7.5	8.7 on 6.5	26.0	10.0	440 AA/A	10.1	24.2	798	44	1510	
<b>NEW</b> P195/55R16 86V	2102073	5.0 - 7.0	7.9 on 6.0	24.4	10.0	440 AA/A	11.3	19.7	851	44	1168	
P205/55R16 89H	1756213	5.5 - 7.5	8.4 on 6.5	24.9	10.0	440 AA/A	9.7	21.3	835	44	1279	
P205/60R16 91H	1745613	6.0 - 51.0	8.2 on 6.0	25.7	10.0	440 AA/A	10.0	20.7	812	44	1356	
P205/65R16 94H	1725913	5.5 - 7.5	8.2 on 6.0	26.5	10.0	440 AA/A	10.3	23.4	785	44	1477	
P215/55R16 91H	1782113	6.0 - 7.5	8.9 on 7.0	25.3	10.0	440 AA/A	9.9	23.1	822	44	1356	
P215/60R16 94H	1767913	6.0 - 7.5	8.7 on 6.5	26.1	10.0	440 AA/A	10.2	23.9	795	44	1477	
P215/65R16 96H	1799613	6.0 - 7.5	8.7 on 6.5	27.0	10.0	440 AA/A	10.5	25.3	769	44	1565	
P225/55R16 94H	1768013	6.0 - 8.0	9.2 on 7.0	25.8	10.0	440 AA/A	10.0	25.9	807	44	1477	
<b>NEW</b> P225/60R16 97H	2100403	6.0 - 8.0	8.8 on 6.5	26.6	10.0	440 AA/A	12.1	24.4	781	44	1609	
P235/55R16 98H	1770513	6.5 - 8.5	9.6 on 7.5	26.1	10.0	440 AA/A	10.2	27.8	795	44	1565	
P235/60R16 99H	1774913	6.5 - 8.5	9.4 on 7.0	27.1	10.0	440 AA/A	10.6	27.3	767	44	1709	
P205/50R17 91H	2102093	5.5 - 7.5	8.4 on 6.5	25.1	10.0	440 A/A	9.8	21.4	827	44	1356	
P215/50R17 93H	1756413	6.0 - 7.5	8.9 on 7.0	25.5	10.0	440 A/A	9.9	23.2	814	44	1433	
<b>NEW</b> P215/55R17 93V	1923413	6.0 - 7.5	8.9 on 7.0	26.3	10.0	440 A/A	10.3	23.1	790	44	1433	
P215/60R17 95H BW	2103293	6.0 - 7.50	8.7 on 6.5	27.2	10.0	440 A/A	12.9	25.9	764	44	1521	
P215/65R17 98H BW	2103283	6.0 - 7.5	8.7 on 6.5	28.0	10.0	440 A/A	12.8	27.5	742	44	1653	
P225/50R17 93V	1775013	6.0 - 8.0	9.2 on 7.0	25.9	10.0	440 A/A	10.1	24.1	802	44	1433	
<b>NEW</b> P225/55R17 95H	1915313	6.0 - 8.0	9.2 on 7.0	26.8	10.0	440 A/A	10.4	10.0	776	44	1521	
P225/60R17 98H	1823113	6.0 - 8.0	9.0 on 6.5	27.6	10.0	440 A/A	10.8	27.6	752	44	1653	
P235/50R17 95H	2102083	6.5 - 8.5	9.6 on 7.5	26.3	10.0	440 A/A	12.1	27.8	790	44	1521	
P235/60R17 102T	1730713	6.5 - 8.5	9.5 on 7.0	27.1	11.0	440 A/A	12.8	27.9	767	44	1874	
<b>NEW</b> P225/65R17 100H	2103333			28.5	10.0			27.8		44	1764	
P235/65R17 103H	1823213	6.5 - 8.5	9.4 on 7.0	29.1	10.0	440 A/A	10.0	29.6	715	44	1929	
P255/60R17 106H	2103243	7.0 - 9.0	10.2 on 7.5	29.1	10	440 A/A	13.2	32.9	714	44	2094	
P225/50R18 94H	2103253	6.0 - 8.0	9.2 on 7.0	26.9	10	440 A/A	12.5	28	772	44	1477	
P225/60R18 99H	2103303	6.0 - 8.0	9.0 on 6.5	28.6	10	440 A/A	13.1	28.8	726	44	1709	
<b>NEW</b> P235/50R18 97V	1847013	6.5 - 8.5	9.5 on 7.5	27.1	10	440 A/A	12.6	37.2	767	44	1609	
P225/55R18 97H	2103263	6.0 - 8.0	9.2 on 7.0	27.8	10	440 A/A	12.8	28.9	747	44	1609	
P235/55R18 99H	2103273	6.5 - 8.5	9.7 on 7.5	28.2	10	440 A/A	12.9	30.7	737	44	1709	
P245/45R18 96H	2103313	7.5 - 9.0	9.6 on 8.0	26.7	10	440 A/A	12.5	29.5	778	44	1565	
P255/55R18 109V	2103233	7.0 - 9.0	10.4 on 8.0	29	10	440 A/A	13.3	34.3	716	44	1984	



**100,000 Mile  
Limited Warranty**

**Special Features**

- Specially designed tread pattern utilizes unique groove and block shapes to improve stability for longer mileage.
- Four wide, circumferential grooves give outstanding hydroplaning resistance without sacrificing wear, handling or dry performance.
- High angle lateral grooves and multi-depth sipes increase biting edges for increased wet and snow traction. Groove and sipe placement are carefully crafted to retain tread block rigidity for longer wear.
- Kumho's ETOPS and ESCOT technologies ensure precise calculation of the optimum casing shape and profile to deliver a perfect combination of ride comfort and handling.
- Kumho's proprietary noise simulation know-how delivers exceptionally low-noise operation.
- Formulated with rubber compounds that are free of High Aromatic Oils, the eco Solus HM greatly reduces harmful effects on the environment. Less rolling resistance also delivers improved fuel economy, thus less strain on non-renewable resources.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	Max Air (PSI)	Max Load (LBS)	PRICE		
P175/70R13 82T	2125683	4.5 - 6.0	7.1 on 5.0	22.6	11	740 A/B	10.3	16	919	44	1036	\$
P175/65R14 81T	2125493	5.0 - 6.0	7.2 on 5.0	22.9	11	800 A/B	10.5	16.4	907	44	1019	
P185/65R14 85T	2125533	5.0 - 6.5	7.7 on 5.5	23.3	11	800 A/B	10.6	17.5	892	44	1124	
185/70R14 88T	2126703	4.5 - 6.0	7.6 on 5.5	24.2	11	740 A/B	11	18.2	858	44	1235	
P195/70R14 90T	2125983	5.0 - 6.5	8.0 on 6.0	24.8	11	740 A/B	11.2	19.5	838	44	1312	
P185/60R15 84T	2125543	5.0 - 6.5	7.7 on 5.5	23.6	11	800 A/A	11	17.9	880	44	1102	
P195/60R15 87T	2125513	5.5 - 7.0	8.1 on 6.0	24.1	11	800 A/A	11	18.9	862	44	1190	
P205/60R15 90T	2125693	5.5 - 7.5	8.5 on 6.0	24.6	11	800 A/A	11.2	21	844	44	1301	
P215/60R15 93T	2125703	6.0 - 7.5	8.9 on 6.5	25	11	800 A/A	11.4	23.1	831	44	1411	
P185/65R15 86T	2125573	5.0 - 6.5	7.7 on 5.5	24.3	11	800 A/B	11.1	18.5	855	44	1168	
P195/65R15 89T	2125503	5.5 - 7.0	8.1 on 6.0	24.9	11	800 A/B	11.3	20.2	834	44	1279	
P205/65R15 92T	2125523	5.5 - 7.5	8.5 on 6.0	25.4	11	800 A/B	11.5	21.6	818	44	1400	
P205/70R15 95T	2125993	5.0 - 7.0	8.3 on 6.0	26.3	11	800 A/B	11.9	22.4	790	44	1499	
P205/55R16 89T	2125713	5.5 - 7.5	8.7 on 6.5	24.8	11	800 A/A	11.4	21.5	838	44	1279	
P205/60R16 91T	2125743	5.5 - 7.5	8.5 on 6.0	25.6	11	800 A/A	11.7	22.3	811	44	1356	
P215/60R16 94T	2125553	6.0 - 7.5	8.9 on 6.5	26	11	800 A/A	11.9	24.6	799	44	1477	
P225/60R16 97T	2125563	6.0 - 8.0	9.2 on 6.5	26.5	11	800 A/A	12.1	26.2	784	44	1609	
P235/60R16 99T	2126003	6.5 - 8.5	9.7 on 7.0	27	11	800 A/A	12.2	27	769	44	1709	
P205/65R16 94T	2126033	5.5 - 7.5	8.5 on 6.0	26.3	11	800 A/B	12	23	790	44	1477	
P225/55R17 89T	2125723	6.0 - 8.0	9.6 on 7.0	26.7	11	800 A/A	12.2	27	778	44	1521	
P215/60R17 95T	2126023	6.0 - 7.5	8.9 on 6.5	27	11	800 A/A	12.4	25.8	769	44	1521	
P225/60R17 98T	2125733	6.5 - 8.5	9.2 on 6.5	27.5	11	800 A/A	12.6	27.3	755	44	1653	
P215/65R17 98T	2126013	6.0 - 7.5	8.9 on 6.5	27.9	11	800 A/B	12.8	27	745	44	1653	

**WE ARE YOUR SUPPLIER**

**NOT YOUR COMPETITOR**

# KUMHO SOLUS KR21

## Passenger Radial



**UTQG 640AB**

**85,000 Mile Limited Warranty**

The Solus KR21 is a high mileage premium passenger tire designed to deliver long mileage, outstanding ride comfort and all season traction.

Created for drivers of domestic and imported sedans, minivans and wagons, the Solus KR21 provides high levels of handling and grip while maintaining low noise levels throughout the life of the tire. Utilizing Kumho's newest compounding technology, improved wet, dry and snow traction make the SOLUS KR21 the perfect choice for a wide variety of vehicles and drivers.

### Special Features

- Tread design and advanced carbon tread compound delivers outstanding wet, dry and snow traction – and exceptional mileage. Outstanding 85,000 mile warranty, road hazard coverage for first 25% of wear, and 24-hour roadside assistance.
- Cross groove shoulder design provides "biting edges" for enhanced traction in snow, making the Solus KR21 an outstanding all season performer.
- 3 rib design increases rubber contact area for improved handling and wear resistance. Wide circumferential grooves effectively channel water from under the tread to deliver outstanding resistance to hydroplaning and improved stability in wet weather.
- ESCOT, KUMHO's proprietary profile technology, enhances ride comfort without sacrificing handling capability.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	UTQG	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>WHITEWALL</b>												
P155/80R13 79T	1905813	4.0 - 5.0	6.2 on 4.5	22.8	10.0	640AB	8.8	13.4	.922	44	957	\$
P185/75R14 89T	1906513	4.5 - 6.0	7.2 on 5.0	25.0	10.0	640AB	9.7	14.8	.832	44	1287	
P195/75R14 92T	1906813	5.0 - 6.5	7.7 on 5.5	25.5	10.0	640AB	9.9	18.8	.814	44	1518	
P205/75R14 95T	1907313	5.0 - 7.0	8.0 on 5.5	26.1	10.0	640AB	10.2	20.2	.795	44	1529	
P205/70R15 95T	1907213	5.0 - 7.0	8.2 on 6.0	26.3	10.0	680 A/B	10.3	20.8	.789	44	1496	
P205/75R15 97T	1907413	5.0 - 7.0	8.0 on 5.5	27.1	10.0	680 A/B	10.6	22.0	.766	44	1595	
P215/70R15 97T	1907813	6.0 - 7.5	8.7 on 6.5	26.0	10.0	680 A/B	10.5	27.0	.773	44	1617	
P215/75R15 100T	1908013	5.5 - 7.0	8.7 on 6.5	26.9	10.0	680 A/B	10.8	24.6	.751	44	1738	
P225/75R15 102T	1908513	6.0 - 7.5	8.8 on 6.0	28.3	10.0	680 A/B	11.0	26.5	.734	44	1870	
P235/75R15 105T	1909113	6.0 - 8.0	9.2 on 6.5	28.9	10.0	640AB	11.1	27.6	.720	44	2024	
P235/75R15 108T	1909213	6.0 - 8.0	9.2 on 6.5	28.9	10.0	640AB	11.1	27.6	.720	44	2179	
<b>BLACKWALL</b>												
P175/70R13 82T	1899813	4.5 - 6.0	7.0 on 5.0	22.7	10.0	640AB	8.8	14.6	.916	44	1034	
P185/70R13 85T	1906313	4.5 - 6.0	7.4 on 5.5	23.2	10.0	640AB	9.1	15.6	.894	44	1133	
P175/65R14 81T	1906013	5.0 - 6.0	7.0 on 5.0	23.0	10.0	640AB	9.0	15.4	.904	44	1016	
P185/60R14 82T	1899913	5.0 - 6.5	7.4 on 5.5	22.8	10.0	640AB	8.9	16.2	.913	44	1045	
P185/65R14 85T	1900013	5.0 - 6.5	7.4 on 5.5	23.5	10.0	640AB	9.2	16.6	.885	44	1122	
P185/70R14 87T	1906413	4.5 - 6.0	7.4 on 5.5	24.2	10.0	640AB	9.5	16.4	.857	44	1199	
P185/75R14 89T	2104303	4.5 - 6.0	7.2 on 5.0	25.0	10.0	640 A/B	9.7	17.4	.832	44	1287	
P195/60R14 85T	1901013	5.5 - 7.0	7.9 on 6.0	23.2	10.0	640AB	9.1	16.9	.894	44	1133	
P195/65R14 88T	1906613	5.5 - 7.0	7.9 on 6.0	24.0	10.0	640AB	9.4	17.5	.865	44	1232	
P195/70R14 90T	1906713	5.0 - 6.5	7.9 on 6.0	24.8	10.0	640AB	9.7	17.4	.838	44	1309	
P195/75R14 92T	2104323	5.0 - 6.5	7.7 on 5.5	25.5	10.0	640 A/B	9.9	18.7	.814	44	1518	
P205/70R14 95T	1900713	5.0 - 7.0	8.2 on 6.0	25.4	10.0	640AB	9.9	18.8	.819	44	1521	
P205/75R14 95T	2104343	5.0 - 7.0	8.0 on 5.5	26.1	10.0	640 A/B	10.2	20.5	.795	44	1529	
P215/70R14 96T	1900813	5.5 - 7.0	8.7 on 6.5	25.9	10.0	640AB	10.1	21.0	.802	44	1551	
P185/60R15 84T	1906213	5.0 - 6.5	7.3 on 5.5	23.7	10.0	680 A/B	10.8	17.4	.877	44	1102	
P185/65R15 86T	1900113	5.0 - 6.5	7.4 on 5.5	24.5	10.0	680A/B	9.5	17.6	.850	44	1168	
P195/60R15 87T	1900213	5.5 - 7.0	7.9 on 6.0	24.2	10.0	680A/B	9.4	17.9	.858	44	1188	
P195/65R15 89T	1900313	5.5 - 7.0	7.9 on 6.0	25.0	10.0	680A/B	9.8	18.5	.830	44	1276	
P205/60R15 90T	1900413	5.5 - 7.5	8.2 on 6.0	24.7	10.0	680A/B	9.6	19.6	.842	44	1298	
P205/65R15 92T	1900613	5.5 - 7.5	8.2 on 6.0	25.5	10.0	680A/B	9.9	20.2	.818	44	1397	
P205/70R15 95T	2104363	5.0 - 7.0	8.2 on 6.0	26.3	10.0	680 A/B	10.3	20.4	.789	44	1496	
P205/75R15 97T	2104383	5.0 - 7.0	8.0 on 5.5	27.1	10.0	680 A/B	10.6	21.6	.766	44	1595	
P215/60R15 95T	1907513	6.0 - 7.5	8.7 on 6.5	25.2	10.0	680 A/B	9.8	22.2	.826	44	1521	
P215/65R15 95T	1907613	6.0 - 7.5	8.7 on 6.5	26.0	10.0	680 A/B	10.1	23.3	.798	44	1507	
P215/70R15 97T	2104483	6.0 - 7.5	8.7 on 6.5	26.8	10.0	680 A/B	10.5	23.3	.773	44	1617	
P215/75R15 100T	2104403	5.5 - 7.0	8.7 on 6.5	27.7	10.0	680 A/B	10.8	23.8	.751	44	1738	
P225/60R15 95T	1908113	6.0 - 8.0	9.0 on 6.5	25.6	10.0	680 A/B	10.0	23.0	.811	44	1518	
P225/70R15 100T	1908313	6.0 - 7.5	9.0 on 6.5	27.4	10.0	680 A/B	10.7	24.9	.757	44	1749	
P225/75R15 102T	2104423	6.0 - 7.5	8.8 on 6.0	28.3	10.0	680 A/B	11.0	25.7	.734	44	1870	
P235/70R15 102T	1908913	6.0 - 8.0	9.4 on 7.0	28.0	10.0	681 A/B	10.9	26.9	.742	44	1892	
P235/75R15 105T	2104443	6.0 - 8.0	9.2 on 6.5	28.9	10.0	680 A/B	11.1	27.6	.720	44	2028	
P235/75R15 108T	2104463	6.0 - 8.0	9.2 on 6.5	28.9	10.0	680 A/B	11.1	29.9	.720	44	2183	
P205/55R16 89T	1906913	5.5 - 7.5	8.4 on 6.5	24.9	10.0	680 A/B	9.7	21.0	.835	44	1276	
P205/60R16 91T	1900513	5.5 - 7.5	8.2 on 6.0	25.7	10.0	680 A/B	10.0	20.8	.812	44	1353	
P205/65R16 94T	1907113	5.5 - 7.5	8.2 on 6.0	26.5	10.0	680 A/B	10.3	21.9	.785	44	1474	
P215/60R16 94T	1909313	6.0 - 7.5	8.7 on 6.5	26.1	10.0	680 A/B	10.2	23.5	.795	44	1474	
P215/65R16 96T	1907713	6.0 - 7.5	8.7 on 6.5	27.0	10.0	680 A/B	10.5	24.8	.769	44	1518	
P215/70R16 99T	1907913	5.5 - 7.0	8.7 on 6.5	27.8	10.0	680 A/B	10.8	24.3	.747	44	1705	
P225/60R16 97T	1900913	6.0 - 8.0	9.0 on 6.5	26.6	10.0	680 A/B	10.4	24.6	.781	44	1606	
P225/70R16 101T	1908413	6.0 - 7.5	9.0 on 6.5	28.7	10.0	680 A/B	10.9	28.1	.724	44	1815	
P235/60R16 99T	1908613	6.5 - 8.5	9.4 on 7.0	27.1	10.0	680 A/B	10.6	26.7	.767	44	1705	
P235/65R16 103T	2100573	6.5 - 8.5	9.5 on 7.0	29.0	10.0	680 A/B	13.0	28.8	.716	44	1929	
P235/70R16 104T	1909013	6.0 - 8.0	9.5 on 7.0	29.2	10.0	680 A/B	13.3	28.4	.711	44	1984	
P225/60R17 98T	1908213	6.0 - 8.0	9.0 on 6.5	27.6	10.0	680 A/B	12.6	26.6	.753	44	1649	
P235/60R17 100T	2100473	6.5 - 9.0	7.5 on 7.0	28.1	10.0	680 A/B	12.8	27.6	.739	44	1764	
P235/65R17 103T	1908713	6.5 - 8.5	9.5 on 7.0	29.0	10.0	680 A/B	13.2	29.6	.716	44	1929	
P235/65R18 104T	1908813	6.5 - 8.5	9.5 on 7.0	30.0	10.0	680 A/B	13.2	31.0	.693	44	1984	

# KUMHO ORIGINAL EQUIPMENT

Tire Size	Code No.	Tread Design	Make/Model	Year	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	UTQG	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>Chevy</b>															
P185/60R14 82H	.34119	.722	.Aveo	.05	5.0 - 6.0	7.4 on 5.5	22.8	10.5	380/A/A	10.5	15.9	913	44	1047	\$
<b>Dodge</b>															
LT215/85R16 112/115Q	.58524	.KL78	.Sprinter	.07	5.0 - 7.0	8.5 on 6.0	30.4	15	N/A	13.6	40.8	688	80	3042	
<b>Hyundai</b>															
P195/55R15 84H	.45854	.716	.Accent GLS	.07	5.5 - 6.5	7.7 on 5.5	23.5	10	440/A/A/A	10.9	17.6	891	44	1102	
P195/65R15 89T	.59151	.KH16	.Elantra	.07	5.5 - 7.0	7.9 on 6.0	25	10	440/A/A/A	9.8	19.9	830	44	1279	
P195/70R14 90H	.34120	.722	.Sonata	.00	5.5 - 6.5	7.9 on 6.0	24.8	11	380/A/A	9.7	19.1	838	35	1323	
<b>NEW</b> P205/65R16 94H	.73925	.KH25	.Sonata	10-11	5.5-7.5	8.2 on 6.0	26.5	10	480 A/A	10.3	22.9	785	44	1477	
P205/55R16 89V	.55996	.716	.Tiburon FX	.05	5.5 - 7.0	8.4 on 6.5	24.9	11	360/A/A	11.5	21.3	835	44	1279	
P215/65R16 96T	.36533	.716	.Tuscon	.05	6.0 - 7.0	8.7 on 6.5	27	11	360/A/B	12.6	25.1	769	44	1565	
P235/60R16 99T	.57441	.716	.Tuscon	.05	6.5 - 8.5	9.4 on 7.0	27.1	10	360/A/A	10.6	27.2	767	35	1709	
<b>Kia</b>															
P225/60R16 97H	.59589		.Amanti	.07	6.0 - 8.0	8.8 on 6.5	26.6	10	440/AA/A	12.1	24.2	781	44	1609	
P205/60R15 90H	.34121	.722	.Optima	02-04	5.5 - 7.5	8.1 on 6.0	24.6	10	380/A/A	11.4	19.2	858	35	1323	
P205/60R15 91H	.39011	.KH16	.Optima	.06	5.5 - 7.5	8.4 on 6.0	25.6	10	440/A/A	11.7	21.6	811	44	1356	
P175/65R14 81T	.34126	.KH14	.Rio	02-04	5.0 - 6.0	7.1 on 5.5	23.1	10	360A/B	10.6	14.7	904	44	1019	
P205/65R15 92H	.39008	.KH16	.Rondo	.07	5.5 - 7.5	8.2 on 6.0	25.5	10	440AA/A	9.9	20.9	818	44	1477	
215/70R50 98H	.34123	.798	.Sedona	02-04	5.5 - 7.0	8.4 on 6.5	26.7	11	400A/B	11.9	24	773	44	1654	
225/70R16 102T	.44809	.KH16	.Sedona	.06	6.0 - 7.5	9.1 on 6.5	28.4	11	440AA/A	13.1	27.8	731	44	1874	
P245/70R16 106H	.34125	.798	.Sorento	03-04	6.5 - 8.0	10.0 on 7.0	29.4	12	440A/A	13	30.2	703	44	2094	
P225/75R16 104S	.34124	.798	.Sorento	05-06	6.0 - 7.5	9.6 on 6.5	29.3	9	440A/A	13.2	30	709	44	1904	
P215/65R16 96T	.36533	.716	.Sportage	.06	6.0 - 7.5	8.7 on 6.5	27	11	360A/B	12.6	25.1	769	44	1565	
P205/75R15 97S	.34122	.798	.Sportage	95-02	5.0 - 7.0	8.1 on 5.5	27.1	11	400A/B	12.2	24.1	766	35	1609	
P235/61R16 99T	.57441	.716	.Sportage	.05	6.5 - 8.5	9.4 on 7.0	27.1	10	360A/A	10.6	27.2	767	35	1709	
<b>Suzuki</b>															
P195/55R15 84H	.45854	.716	.Forenza & Reno	.07	5.5 - 7	7.7 on 6.0	23.4	11	360/A/A	10.7	17.4	887	44	1102	
<b>Dodge</b>															
<b>NEW</b> 225/65R17 100T	.2004483	.KH16	.Journey	.09	6.0 - 8.0	8.9 on 6.5	28.5	10.0	440 A/A	17.5	28.0	729	44	1764	
<b>NEW</b> 225/55R19 99T	.1888411	.KH16	.Journey	.09	6.0 - 8.0	9.1 on 7.0	28.9	10.0	440 A/A	13.5	30.4	719	44	1709	
<b>NEW</b> 225/55R19 99H	.1855811	.KH16	.Journey	.09	6.0 - 8.0	9.1 on 7.0	28.9	10.0	440 A/A	13.5	30.4	719	44	1709	
<b>Ford</b>															
<b>NEW</b> P215/45R17 87H2103863	.KH16	.KH16	.Focus	.09	7.0 - 8.0	8.4 on 7.0	24.7	10.0	440 A/A	14.5	20.6	841	44	1202	
<b>NEW</b> P205/50R16 86H	.2100663	.KH16	.Focus	.09	5.5 - 7.5	8.4 on 6.5	24.1	10.0	440 A/A	14.0	20.1	862	44	1168	
<b>Hyundai</b>															
<b>NEW</b> P185/65R14 85H	.2005343	.KH16	.Accent	.08	5.0 - 6.5	7.4 on 5.5	23.5	10.0	440 AA/A	10.8	17.4	890	44	1135	
<b>NEW</b> P195/55R15 84V	.2005353	.KH16	.Accent	.08	5.5 - 6.5	7.7 on 5.5	23.5	10.0	440 AA/A	10.9	19.1	891	44	1102	
<b>NEW</b> P205/45R16 83V	.2104503	.KH16	.Accent	.08	6.5 - 7.5	8.1 on 7.0	23.2	10.0	440 A/A	9.1	18.9	894	44	1074	
<b>Hyundai</b>															
<b>NEW</b> P225/60R16 97V	.1854513	.KH16	.Azera	06-08	6.0 - 8.0	8.8 on 6.5	26.6	10.0	440 AA/A	12.1	25.4	781	44	1609	
<b>NEW</b> P235/55R17 98V	.1861913	.KH16	.Azera	06-08	6.5 - 8.5	9.6 on 7.5	27.2	10.0	440 AA/A	12.5	27.7	764	44	1653	
<b>NEW</b> P185/65R15 86T	.1763213	.KH16	.Elantra	07-09	5.0 - 6.5	7.4 on 5.5	24.5	10.0	440 AA/A	17.6	9.5	850	44	1168	
<b>NEW</b> P195/65R15 89T	.2125593	.KH16	.Elantra	07-11	5.5 - 7.0	7.9 on 6.0	25.0	10.0	440 AA/A	19.3	9.8	830	44	1279	
<b>NEW</b> P205/55R16 89H	.1837513	.KH16	.Elantra	07-09	5.5 - 7.5	8.4 on 6.5	24.9	10.0	440 AA/A	20.9	9.7	835	44	1279	
<b>NEW</b> P215/60R16 94H	.2111463	.KH16	.Sonata	06-08	6.0 - 7.5	8.7 on 6.5	26.1	11.0	400 A/A	12.0	23.1	795	44	1477	
<b>NEW</b> P215/55R17 93V	.1923411	.KH16	.Sonata	06-08	6.0 - 7.5	8.9 on 7.0	26.3	10.0	440 A/A	10.3	24.1	790	44	1433	
<b>NEW</b> 215/45R17 91V	.1799513	.KH16	.Tiburon	07-08	7.0 - 8.0	8.4 on 7.0	24.6	10.0	440 A/A	9.6	22.8	843	44	1356	
<b>Kia</b>															
<b>NEW</b> P235/55R17 98V	.1861913	.KH16	.Amanti	04-07	6.5 - 8.5	9.6 on 7.5	27.2	10.0	440/AA/A	12.5	27.7	764	44	1653	
<b>NEW</b> 225/70R16 102T	.1739413	.KH16	.Sedona	.06	6.0 - 7.5	9.1 on 6.5	28.4	11.0	440/AA/A	13.1	27.9	731	44	1874	
<b>Suzuki</b>															
<b>NEW</b> P205/65R15 92H	.1915013	.KH16	.Verona	.08	5.5 - 7.0	8.1 on 6.0	25.5	10.0	360/A/A	11.7	20.6	818	44	1389	



ECSTA HP4 716



STEEL RADIAL 722



STEEL RADIAL 798



KH14



KH16

# KUMHO ROAD VENTURE MT (KL71)

## Suv/Light Truck Radial



### Special Features

- Durable cut & chip tread prevents cut & chip even under the roughest driving condition.
- Undertread for ride comfort-A newly developed compound has been used between the tread and steel belt. This blocks out impact and noise from the road surface and enhances ride comfort.
- High tensile steel belt & jointless cap ply enhance durability and reduce noise levels.
- Dual body plies protect the KL71 from the stress of on and off road use.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	Max Air RPM (PSI)	Max Load (LBS)	PRICE	F.E.T
<b>BLACKWALL</b>											
31X10.50R15/6	1764313	7.0 - 9.0	10.6 on 8.5	30.8	19.0	13.6	44.8	680	50	2270	\$
32X11.50R15/6	1871513	8.0 - 10.0	11.4 on 9.0	31.5	20.0	14.0	52.1	658	50	2535	
33X12.50R15/6	1803713	8.5 - 11.0	12.5 on 10.0	32.8	19.0	14.2	55.5	638	35	2205	
35X12.50R15/6	1861313	8.5 - 11.0	12.5 on 10.0	34.8	21.0	17	65.1	599	35	2535	
35X12.50R17/10	1912113	8.5 - 11.0	12.6 on 10.0	34.4	17	13.4	74.8	608	35	2535	
35X12.50R18/8	1825213	7.5 - 11.0	11.4 on 10.0	34.8	22.0	16.2	73.3	597	50	2910	
33X12.50R18/10	2108023	8.5 - 11.0	12.7 on 10.0	33	21	20.7	74	630	65	2910	
38X15.50R18/8	1831613	11.0 - 13.0	14.3 on 12.0	37.8	22.0	17.5	93.4	550	50	3970	
<b>NEW</b> 33X12.50R20 114Q	2107263	8.5 - 11.0	12.5 on 10.0	32.8	21.0	15.0	67.3	989	65	2600	
<b>NEW</b> 35X12.50R20 121Q/10	2119053	8.5 - 11.0	12.5 on 10.0	34.8	21.0	15.7	75.2	597	65	3195	
37X13.50R20/10	1829613	8.5 - 11.0	12.5 on 11.0	36.8	22.0	17.1	84.4	565	65	3860	
38X15.50R20/10	1830613	11.0 - 13.0	14.3 on 12.0	37.8	22.0	17.5	92.7	550	65	3635	
37X13.50R22/8	1825413	8.5 - 11.0	12.5 on 11.0	36.8	22.0	17.1	79.7	565	50	3415	
38X14.00R24/10	1831513	9.0 - 12.5	14.1 on 11.0	37.8	22.0	17.5	83.9	550	65	2910	
37X14.00R24/8	1767513	9.0 - 12.0	13.6 on 11.0	36.8	19.0	16.8	78.9	574	50	2680	
205/80R16 104Q	1853913	5.5 - 7.0	8.0 on 5.5	28.9	18	13.1	36.4	719	50	1985	
LT235/75R15/6	1854113	6.0 - 7.0	9.2 on 6.5	28.9	18.0	11.3	40.9	719	50	1985	
LT225/75R16 /8	1854013	6.0 - 7.0	8.8 on 6.0	29.3	18.0	13.3	43.4	708	65	2335	
LT235/85R16 /10	1875313	6.0 - 7.5	9.2 on 6.5	31.7	19.0	14.2	51.0	654	80	3042	
LT245/75R16/10	1854213	6.5 - 8.0	9.8 on 7.0	30.5	19.0	13.7	50.2	681	80	3042	
<b>NEW</b> LT265/75R16/8	1854313	7.0-8.0	10.5 on 7.5	31.6	19	14.2	53.5	656	80	3417	
LT265/75R16/10	1911913	7.0 - 8.0	10.5 on 7.5	31.9	19.0	12.4	55.9	656	80	3415	
LT285/75R16/10	1917713	7.5 - 9.0	11.26 on 8.0	32.8	19.0	14.5	58.8	633	80	3415	
<b>NEW</b> LT305/70R16/10 121/124Q	1912013	8.0-9.5	12.2 on 9.0	33.1	18.5	14.6	58.8	628	65	3195	
<b>NEW</b> LT315/75R16/10 127/124Q	2107223	8.0-10.0	12.3 on 8.5	34.5	18.5	22.4	78.2	602	65	3860	
LT265/70R17/10	1911813	7.0 - 8.5	10.7 on 8.0	31.9	19	14.3	54.2	651	80	3195	
<b>NEW</b> LT285/70R17/8 121/118Q	2119043	7.5-9.0	11.5 on 8.5	32.7	18.5	14.7	55.6	635	65	3195	
LT315/70R17/8	1871313	8.5-10.0	12.7 on 9.5	34.6	19	15.4	71.8	600	50	3195	

# KUMHO ECSTA STX (KL12)

## Performance Radial



### Special Features

- Integral wet traction tread design: Significantly reduces the risk of hydroplaning.
- Large stable tread blocks: Provide sure footing and crisp handling for even the most discriminate vehicles.
- Nylon cap plies and bead reinforcement: Ensures durability and promote customer peace of mind.
- All season performance.
- New vehicle ride prioritized mold shape: Filters out road irregularities and does not transmit them to the passenger compartment.
- Rim protector in the lower sidewall: Safeguards wheel against scratches and abrasions.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	Max Air RPM (PSI)	Max Load (LBS)	PRICE		
<b>BLACKWALL</b>												
255/65R16 109 V	1637613	7.0 - 9.0	10.2 on 7.5	29.1	11.0	420 A/A	13.1	35.0	717	51	2271	\$
265/60R18 110 V	1638413	7.5 - 9.5	10.7 on 8.0	30.5	11.0	420 A/A	13.9	40.4	683	51	2337	
285/60R18 116V	1635713	8.0 - 10.0	11.5 on 8.5	31.5	11.0	420 A/A	14.2	46.3	662	51	2756	
235/60R18 107V	2101323	6.5 - 8.5	9.5 on 7.0	29.1	11.0	420 A/A	17.7	44.7	714	51	2149	
P275/55R18 114V	2101383	7.5 - 9.5	11.18 on 8.5	29.8	11.0	420 A/A	18.2	38.2	697	51	2601	
255/55R18 109V	1638313	7.0 - 9.0	10.4 on 8.0	29.0	11.0	420 A/A	13.3	37.6	716	50	2271	
<b>NEW</b> 255/50R19 103W	1867213	7.0-9.0	10.4 on 8.0	29.1	11.0	420 A/A	13.4	33.1	714	51	1929	
<b>NEW</b> 285/45R19 107W	1861513	9.0-10.5	11.2 on 9.5	29.1	11.0	420 A/A	13.4	35.7	714	51	2149	
<b>NEW</b> 275/40R20 106W	2103413	9.0-11.0	10.9 on 9.5	28.7	11.5	420 A/A	13.2	34.2	724	51	2094	
<b>NEW</b> 275/45R20 106W	1851913	8.5-10.5	10.7 on 9.0	29.8	11.5	420 A/A	14.4	36.1	683	80	2094	
275/55R20 117V	1832813	7.5 - 9.5	11.2 on 8.5	31.9	11.0	420 A/A	14.8	43.7	652	51	2833	
285/50R20 112V	1832913	8.0 - 10.0	11.7 on 9.0	31.3	11.0	420 A/A	14.5	42.4	666	51	2469	
305/50R20 120V	1648913	8.5 - 11.0	12.4 on 9.5	32.0	11.0	420 A/A	14.6	48.5	651	50	3086	
265/35R22 102W	1851713	9.0 - 10.5	10.7 on 9.5	29.3	11.0	420 A/A	13.8	35.2	621	51	1874	
265/40R22 106V	2101303	9.0 - 10.5	10.7 On 9.5	30.5	11.0	420 A/A	17.6	34.5	681	51	2094	
P275/45R22 112V	2101403	8.5 - 10.0	10.8 on 9.0	31.7	11.0	420 A/A	18.6	41.6	655	51	2469	
285/45R22 114V	2101423	8.5 - 10.5	11.2 on 9.5	32.1	11.0	420 A/A	18.9	43.4	647	51	2601	
285/25R22 96V	2101343	10.5	11.6 On 10.5	27.6	10.0	420 A/A	15.4	33.5	753	51	1521	
285/30R22 101W	1713413	9.5 - 10.5	11.4 on 10.0	28.8	11.0	420 A A	13.6	36.5	724	50	1819	
305/45R22 118V	1649113	9.5 - 11.5	11.9 on 10.0	32.8	11.0	420 A/A	15.2	48.8	636	50	2910	
305/40R22 114V	1682113	10.0 - 12.0	12.3 on 11.0	31.6	11.0	420 A A	14.4	46.3	657	50	2601	
285/35R23 107V	2101363	9.5 - 11.0	11.3 on 10.0	30.9	11.0	420 A/A	19.1	40.3	672	50	2149	
305/40R23 115V	1636513	10.0 - 12.0	12.3 on 11.0	32.6	11.0	420 A/A	15.3	48.7	636	50	2679	
285/40R24 112V	2101463	9.5 - 11.0	11.3 On 10.0	32.9	11.0	420 A/A	18.9	44.6	631	51	2469	
295/35R24 110V	2101443	10.0 - 11.5	11.9 On 10.5	32.1	11.0	420 A/A	18.3	43.5	647	51	2337	
305/35R24 114V	1673913	10.0 - 12.0	12.3 on 11.0	32.4	11.0	420 A A	15.3	48.7	640	50	2602	
305/30R26 110V	1681913	10.5 - 11.5	12.3 on 11.0	33.2	11.0	420 A A	16.1	49.3	626	50	2337	
325/35R28 120V	1757613	10.0-12.0	13.3 on 11.0	37.0	11.0	420 A/A	17.4	62.8	563	50	3086	

# Eco SOLUS (KL21)

# Suv/Light Truck Radial



**UTQG 550 A/A**

### Special Features

- Low Rolling Resistance (LRR) technology utilizes high dispersion silica (HDS) that strengthens the molecular structure of the rubber to improve fuel economy up to 5% and provide lower operating cost per mile.
- Eco-friendly design reduces rubber dust particle emission by 10% without sacrificing performance attributes like ride comfort, noise levels, steering stability or all-season traction in wet conditions.
- Anti-abrasion carbon black technology with HDS improves wear resistance and maintains high traction capability in both wet and dry conditions for better gas mileage, performance and comfort – all while reducing its carbon footprint.
- Kumho's proprietary noise simulation know-how delivers exceptionally low noise operation.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
235/65R16 103T	2119253	6.5 - 8.5	9.4 on 7.0	28	11	12.8	28.6	742	51	1929	\$
215/70R16 100H	2119243	5.5 - 7.0	8.7 on 6.5	27.9	10	12.6	25.1	745	51	1764	
P235/70R16 104T	2121813	6.0 - 8.0	9.4 on 7.0	29	11.5	13.1	28.9	716	44	1984	
235/60R17 102T	2119263	6.5 - 8.5	10.2 on 7.0	28.1	11	12.8	28.3	739	51	1874	
255/60R17 106V	2119273	7.0 - 9.0	10.2 on 7.5	29.1	10	13.2	32.3	714	51	2094	
P235/65R17 103T	2114823	6.5 - 8.5	9.4 on 7.0	27.6	11.5	13.2	28.8	753	44	1929	
245/65R17 107H	2113353	7.0 - 8.5	9.8 on 7.0	29.5	11	13.4	30.6	704	44	2149	
225/55R18 98H	2115353	6.0 - 8.0	9.2 on 7.0	27.8	10	12.8	27.6	747	44	1653	
235/55R18 104V XL	2119333	6.5 - 8.5	9.6 on 7.5	28.1	10	13	31.3	739	50	1984	
255/55R18 109V XL	2119343	7.0 - 9.0	10.4 on 8.0	29	10	13.3	34	716	50	2271	
P235/60R18 102H	2109723	6.5 - 8.5	9.4 on 7.0	29.1	11.5	13.3	28.9	714	44	1874	
245/60R18 105H	2113313	7.0 - 8.5	9.8 on 7.0	29.6	11	13.5	31.1	702	44	2039	
265/60R18 110V	2119303	7.5 - 9.5	10.7 on 8.0	30.5	10	13.9	35	681	44	2337	
275/60R18 113V	2119313	8	11.0 on 8.0	30.9	11.1	14.1	36.8	681	44	2535	
235/65R18 106T	2119293	6.5 - 8.5	9.4 on 7.0	30	11	13.7	31.5	692	51	2094	
P275/65R18 114T	2119323	7.5 - 9.5	11.0 on 8.0	32.1	11	14.5	39.7	647	51	2601	
P265/70R18 114T	2119283	7.0 - 9.0	10.7 on 8.0	32.6	11	14.7	39.4	637	51	2601	
285/45R19 107V	2119393	9.0 - 10.5	11.2 on 9.5	29.1	10	13.4	33.3	714	51	2149	
255/50R19 107V XL	2119353	7.0 - 9.0	10.4 on 8.0	29.1	10	13.4	33.5	714	50	2149	
255/55R19 111V XL	2119363	7.0 - 9.0	10.4 on 8.0	30	10	13.8	35	692	50	2403	
265/50R20 107V	2119373	7.5 - 9.0	10.7 on 8.5	30.5	10	14.1	36.8	681	44	2149	

- Durable belt construction including two full-width steel belt layers, high-tensile bead wire construction and lower rolling resistance mold profile provides strength, durability, ride comfort and better fuel economy.

# KUMHO ROAD VENTURE APT (KL51)

# Light Truck Radial



**UTQG 600 A A**

### Special Features

- Improved Wear, Noise, Breaking, Durability and Handling.
- M/S Rated
- Four Large Circumferential Grooves provide exceptional water evacuation.
- Solid Center Rib Provide Steering response and straight line stability.
- Interlocking Shoulder blocks improve wear and provide cornering stability.
- Interlocking Sipes assist with Heal and toe wear also provide larger footprint during cornering.
- Full width Steel belts and jointless construction provide quality and a comfortable ride.
- Road Harmonics (road noise) is to a minimum due to shoulder blocks staggered in size thus creating a variable pitch.
- Q, S, T, H and V Performance Ratings.
- P-Metric and LT Sizes available.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>BLACKWALL</b>											
265/70R15 112T	1861213	7.0-9.0	10.7 on 8.0	29.6	12.0	13.2	35.4	702	51	2337	\$
P215/70R16 99T	2103123	5.5-7.0	8.7 on 6.5	27.9	12.0	17.3	27.7	745	51	1709	
P215/75R16 101T	2102893	5.5-7.0	8.5 on 6.0	28.9	12.0	18.1	29.3	719	51	1819	
P245/75R13 109T	1919213	6.5 - 8.0	9.8 - on 7.0	30.1	12	13.6	34.8	691	51	2271	
P255/60R16 104H	1885113	7.5-9.0	10.2 on 8.5	28.0	11.0	12.7	32.1	742	51	1984	
P255/65R16 109H	1821913	7.0 - 9.0	10.2 on 8.0	29.1	12.0	13.1	34.2	714	51	2271	
P275/7016 114H	1876413	6.0 - 8.0	11.0 on 8.0	31.2	12	13.9	41.4	666	51	2601	
225/55R17 97H	1885313	6.0 - 7.5	9.2 on 7.5	25.7	12	11.9	30	808	51	1609	
225/65R17 101H	2102913	6.0 - 8.0	8.9 on 6.5	28.5	12.0	17.5	30.4	729	51	1874	
P235/65R17 104H	1860713	7.0 - 8.5	9.4 on 7.0	29.1	12.0	13.2	31.2	714	51	1984	
P245/65R17 105T	1876013	7.5 - 8.5	9.7 on 7.0	29.5	12.0	13.4	32.9	704	51	2039	
P265/65R17 112H	1855213	7.5 - 9.5	10.7 on 8.0	30.6	12.0	13.8	38.4	679	51	2469	
275/55R17 109H	1885613	7.5 - 9.5	11.2 on 8.0	28.9	12	13.1	38.1	719	51	2271	
P275/60R17 110H	1878913	7.5 - 9.5	10.9 on 8.0	30	12	13.6	39.3	693	51	2337	
P275/65R17 113H	1876313	7.5 - 9.5	10.9 on 8.0	31.1	12.0	14.0	41.6	668	51	2535	
235/55R18 100V	1858413	6.5 - 8.5	9.6 on 7.5	28.1	11.0	13.0	32.4	739	51	1764	
235/60R18 103V	1855413	7.0 - 9.0	9.4 on 7.0	29.1	11.0	13.3	32.7	714	50	1929	
NEW 255/55R18 XL 109V	2140683	7.0 - 9.0	10.2 on 8.0	29.0	12.0	13.3	32.0	716	51	2271	
255/60R18 112V	1855613	7.0 - 9.0	10.2 on 8.0	30.0	11.0	13.7	36.1	693	51	2469	
P275/55R20 117T	2103183	7.5 - 9.5	11.1 on 8.5	29.1	11	19.3	42.3	714	51	2833	
P275/60R20 114T	2103163	7.5 - 9.5	10.9 on 8.0	32.9	11	20.1	44.1	631	51	2601	
LT215/85R16/10	2103043	5.5 - 7.0	8.5 on 6.0	30.4	15.0	14.1	38.6	688	51	1215	
LT225/75R16/10	2102813	6.0 - 7.0	8.8 on 6.0	29.3	15.0	13.7	36.5	709	51	2680	
LT235/85R16/10	2103063	6.0 - 7.5	9.2 on 6.5	31.7	15.5	14.7	43.6	655	51	3042	
LT245/75R16/10	2103083	6.5 - 8.0	9.8 on 7.0	30.5	15.5	14.1	41.9	681	51	3042	
LT265/70R16/8	1879013	7.0 - 8.5	10.7 on 8.0	30.6	15.0	13.7	45.6	679	51	2835	
LT275/70R18/10	2103103	7.0 - 8.5	10.9 on 8.0	33.2	15.0	20.9	53.1	626	51	1650	

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE
<b>OUTLINE WHITE LETTER</b>											
P225/70R15 110T	1918713	6.0 - 7.5	9.0 on 6.5	27.4	12.0	12.4	27.8	758	51	1753	\$
P225/75R15 102T	1875913	6.0 - 7.5	8.7 on 6.0	28.3	12.0	12.7	29.7	734	51	1874	
P235/70R15 102T	1918913	6.0 - 8.0	9.5 on 7.0	28.9	12.0	12.6	29.9	719	51	1896	
P235/75R15 105T	1855113	6.5 - 8.5	9.3 on 7.0	29.1	12.0	12.9	32.1	714	51	2028	
255/70R15 108H	1859813	6.5 - 8.5	10.2 on 8.0	29.1	12.0	13.0	34.1	417	51	2205	
P225/70R16 102T	1918813	6.0 - 7.5	9.0 on 7.5	29.3	12.0	12.8	29.2	709	51	1874	
P225/75R16 104T	1878313	6.0 - 7.5	8.8 on 9.0	27.1	12.0	13.2	31.1	767	51	1984	
235/60R16 104H	1861013	6.0 - 8.0	9.4 on 7.0	29	12.0	12.3	30.2	717	51	1984	
235/70R16 106T	1855513	6.0 - 8.0	9.4 on 8.0	29	12.0	13.1	33	716	51	2094	
P235/75R16 106T	1919013	6.0 - 8.0	9.3 on 7.0	29.5	12.0	13.4	32.9	704	51	2094	
P245/70R16 107H	1919113	6.5 - 8.0	9.8 on 9.5	30.5	12.0	13.3	33.5	682	51	2149	
P255/70R16 109T	1876113	6.5 - 8.5	10.2 on 7.5	30.6	12.0	13.5	36.2	678	51	2271	
P265/70R16 111T	1919313	7.0 - 9.0	10.7 on 8.0	31.7	12.0	13.7	38.7	656	51	2403	
P265/75R16 114T	1878813	7.0 - 9.0	10.5 on 7.5	28.1	12.0	14.1	39.4	739	51	2601	
235/60R17 102V	1861113	7.0 - 9.0	9.4 on 7.0	30.1	12.0	12.8	29.9	691	51	1874	
P245/70R17 108T	2103143	6.5 - 8.0	9.7 on 7.0	30.6	12.0	19.1	35.4	679	51	2205	
P255/65R17 108T	1885213	7.0 - 9.0	10.2 on 7.5	29.1	12.0	13.6	36.4	714	51	2205	
P265/70R17 113H	1919413	7.0 - 9.0	10.7 on 8.0	31.7	12.0	14.2	40	655	51	2535	
LT225/75R16/8	2102793	6.0 - 7.0	8.8 on 6.0	29.3	15.0	13.7	35				
LT235/75R15/6	2103023	6.0 - 7.0	9.2 on 6.5	28.9	15.0	13.4	34.1	719	51	1820	
LT265/75R16/10	2102853	7.0 - 8.0	10.5 on 7.5	31.6	15.0	14.6	46.2	657	51	2778	
LT245/70R17/10	2102873	6.5 - 8.0	9.7 on 7.0	30.1	15.0	14.6	46.2	690	51	1360	

## ROAD VENTURE SAT (KL61)

## Suv/Light Truck Radial



**60,000 Mile Limited Warranty**

### Special Features

- Kumho Tire ESCOT casing technology for ride comfort and steering response.
- Tread compound offers a wide operating temperature range and all around performance with outstanding winter traction.
- Tread design consists of a semi center rib for steering stability and reduced noise.
- The tie bars, visible between the shoulder blocks, provide tread block stiffness that increases steering stability and promote even wear.
- Rotation Wear indicators (RWI) strategically placed across the tread surface area.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE	
<b>BLACKWALL</b>												
P245/75R16 109S	2113623	6.5-8.0	9.7 on 7.0	30.5	14.0	640 A/B	13.7	34.5	628	51	2271	\$
P265/70R16 111S	2113683	7.0-9.0	10.6 on 8.0	30.6	14.0	640 A/B	13.7	39.1	627	51	2403	
P235/65R17 103S	2113743	6.5-8.5	9.4 on 7.0	29.0	12.5	640 A/B	13.2	32.3	661	51	1929	
P245/65R17 105S	2126483	7.0-8.5	9.7 on 7.0	29.5	12.0	640 A/B	13.4	33.0	704	51	2039	
P245/70R17 108S	2113723	6.5-8.5	9.7 on 7.0	30.5	13.0	640 A/B	13.8	33.9	628	51	2205	
P265/65R17 110S	2114693	7.5-9.5	10.5 on 8.0	30.6	13.0	640 A/B	13.8	38.9	628	51	2337	
P265/70R17 113S	2114633	7.0-9.0	10.6 on 8.0	31.6	13.0	640 A/B	14.2	40.9	606	51	2535	
P285/70R17 117S	2114653	7.5-9.5	11.4 on 8.5	32.7	13.0	640 A/B	14.6	45.2	587	51	2833	
<b>OUTLINE WHITE LETTER</b>												
P225/75R15 102S	2113583	6.0-7.5	8.7 on 6.0	28.2	14.0	640 A/B	12.7	30.6	679	51	1874	
P235/70R15 102S	2126423	6.0-8.0	9.4 on 7.0	28.0	14.0	640 A/B	12.6	30.1	742	51	1896	
P235/75R15 105S	2113603	6.0-8.0	9.2 on 6.5	28.8	14.0	640 A/B	12.9	32.7	666	51	2028	
P265/75R15 112S	2126463	7.0-8.0	10.5 on 7.5	30.6	14.0	640 A/B	13.6	36.0	679	51	2469	
P235/70R16 104S	2113643	6.0-8.0	9.4 on 7.0	29.0	14.0	640 A/B	13.1	31.8	661	51	1984	
P245/70R16 106S	2113663	6.5-8.0	9.7 on 7.0	29.5	14.0	640 A/B	13.3	32.9	649	51	2094	
P255/70R16 109S	2113703	6.5-8.5	10.2 on 7.5	30.1	14.0	640 A/B	13.5	36.9	637	51	2271	
P255/65R17 108S	2113553	7.0-9.0	10.2 on 7.5	30.0	14.0	640 A/B	13.6	38.0	639	51	2205	
P255/70R17 110S	2126443	6.5-8.5	10.2 on 7.5	31.0	13.0	640 A/B	14.0	35.7	670	51	2337	
P265/70R18 114S	2114673	7.0-9.0	10.6 on 8.0	32.6	13.0	640 A/B	14.7	40.4	588	51	2601	
P275/65R18 114S	2114713	7.5-9.5	10.9 on 8.0	32.0	13.0	640 A/B	14.5	43.6	599	51	2601	
30X9.50R15LT 104S	2114553	6.5-8.5	9.4 on 7.5	29.3	16.0		13.1	38.3	654	50	1985	
31X10.50R15LT 109S	2114573	7.0-9.0	10.6 on 8.5	30.5	16.0		13.6	43.1	628	50	2270	
LT235/75R15 104/101S	2114533	6.0-8.0	9.2 on 6.5	28.6	15.0		12.8	35.7	670	50	1985	
LT215/85R16 115/112Q	2114593	5.5-7.0	8.5 on 6.0	30.2	16.0		13.5	41.8	635	80	2680	
LT235/85R16 120/116Q	2114613	6.0-7.5	9.2 on 6.5	31.5	16.0		14.0	46.6	609	80	3042	
LT225/75R16 115/112Q	2112313	6.0-7.0	8.7 on 6.0	29.1	15.5		13.1	39.2	660	80	2680	
LT245/75R16 120/116Q	2112333	6.5-8.0	9.7 on 7.0	30.2	16.0		13.6	45.1	634	80	3042	
LT265/75R16 112/109Q	2112353	7.0-8.0	10.4 on 7.5	31.4	15.5		14.0	44.9	610	50	2470	
LT265/75R16 123/120Q	2112373	7.0-8.0	10.4 on 7.5	31.4	15.5		14.0	49.7	610	80	3415	
LT285/75R16 122/119Q	2112393	7.5-9.0	11.2 on 8.0	32.7	17.5		14.5	53.7	587	65	3305	
LT245/75R17 121/118R	2126383	6.5-7.5	9.7 on 7.0	31.4	16.0		14.1	42.7	662	80	3195	
LT285/70R17 121/118R	2126403	7.5-9.0	11.4 on 8.5	32.7	16.0		14.6	50.0	635	65	3195	
LT275/70R18 125/122S	2126953	7.0-8.5	11.0 on 8.0	33.1	16.0		14.9	52.7	628	80	3640	

# KUMHO ROAD VENTURE A/T (KL78)

## Suv/Light Truck Radial



500 A B

### Special Features

- Circumferential zig-zag grooves, along with multiple lateral grooves and sipes, provides excellent driving traction on and off the highway.
- Full depth circumferential tread grooves evacuate water from the footprint area, reducing the risk of hydroplaning and improving wet handling and braking.
- Optimized tread groove tapers promote self cleaning of mud and snow for better all-terrain traction.
- High tensile steel belts and endless cap ply application promote a uniform tire shape for excellent durability and higher speed capability, for the life of the tire.
- Tread compound specifically designed to combat cutting and chipping.
- Computer generated sequential pitch design for optimum traction and a quiet ride.

Tire Size	Code No.	Rim Width	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth	Static Load Radius	Tire Weight	RPM	Max Air (PSI)	Max Load (LBS)	PRICE	F.E.T.
<b>BLACKWALL</b>												
P235/65R17 103S	1904213	6.5 - 8.5	9.5 on 7.0	29.1	14.0	13.2	31.1	714	51	1929	\$	
P245/65R17 105S	1904313	7.0 - 8.5	9.6 on 7.0	29.5	12.0	13.4	33.6	704	51	2039		
P245/70R17 108S	1904413	6.5 - 8.5	9.7 on 7.0	30.6	12.0	13.8	35.5	679	51	2205		
P265/65R17 110S	1872413	7.5 - 9.5	10.7 on 8.0	30.6	14.0	13.8	39.7	679	51	2337		
P265/70R18 114S	1803213	7.0 - 9.0	10.7 on 8.0	32.6	14.0	14.7	35.3	637	44	2601		
P275/55R20 116S	2102313	7.5 - 9.5	11.2 on 8.5	31.9	14.0	14.6	47.5	651	35	2756		
P305/50R20 120S	1904613	8.5 - 11.0	12.0 on 9.5	32.0	12.0	14.7	51.3	649	50	3085		
305/55R20 121/118Q	1905113	8.5 - 11.0	12.4 on 9.5	33.2	16.0	15.1	61.6	626	65	3195		
LT215/85R16/10 115/112	1916113	5.5-7.0	8.5 ON 6.0	30.4	15.0	13.6	40	688	80	2680		
LT315/75R16 121Q	1818213	8.0 - 10.0	12.3 on 8.5	34.6	16.0	15.2	66.1	601	50	3195		
LT305/70R16 124Q	1818113	8.0 - 9.5	12.2 on 9.0	32.8	16.0	14.5	61.5	635	65	3525		
LT265/70R17 121/118S	1838613	7.0 - 8.5	10.7 on 8.0	31.7	16.0	14.2	52	655	80	3195		
LT315/70R17 121Q/118Q	1905213	8.5 - 10.0	12.7 on 9.5	34.4	16.0	15.3	64	604	50	3195		
LT275/70R18/10 125/122Q	2102253	7.0 - 8.5	10.9 on 8.0	33.1	16.0	14.9	54.2	628	80	3640		
LT325/65R18 121S	1817813	9.0 - 12.0	13.3 on 9.5	34.9	17.0	15.5	66.4	595	50	3195		
LT355/65R18 125S	1821013	10.0 - 12.0	14.1 on 10.6	36.5	18.0	16.2	77.4	569	50	3640		
LT325/60R18 119S	1817713	9.0 - 12.0	13.0 on 9.5	33.4	17.0	15.1	63.7	618	50	3000		
LT235/60R20 121S	1774513	9.0 - 12.0	13.0 on 9.5	35.3	17.0	15.9	68.7	590	50	3197		
LT355/60R20 122S	1823713	10.0 - 12.0	14.2 on 10.5	36.8	18.0	16.5	69.1	565	65	3305		
LT355/50R20 122S	1823613	10.0 - 12.0	14.2 on 10.5	34.0	18.0	15.4	79	612	65	3305		
LT325/50R22 121S	1768313	9.0 - 11.0	13.2 on 9.5	34.8	17.0	16	74.1	597	65	3197		
<b>OUTLINED WHITE LETTER</b>												
P225/75R15 100S	2100073	6.0-7.5	8.8 on 6.0	28.3	14.0	17.9	28.7	734	35	1742		
P235/75R15 105S	1809913	6.0 - 8.0	9.3 on 6.5	28.9	14.0	12.9	31.0	720	44	2028		
P235/75R15 108S	1810033	6.0 - 8.0	9.3 on 6.5	28.9	14.0	12.9	32.5	720	41	2183		
32X11.50R15/6 113S	2102173	8.0 - 10.0	11.4 on 9.0	31.4	16.0	13.9	47.0	662	35	2535		
33X12.50R15/6 108S	2102153	8.5 - 11.0	12.50 on 10.0	32.5	18.0	14.2	50.6	639	35	2205		
P225/75R16 104S	2100063	6.0 - 7.5	8.8 on 6.0	29.3	14.0	13.2	30.5	709	51	1984		
P235/70R16 104S	1802513	6.0 - 8.0	9.4 on 7.0	29.0	14.0	13.1	32.7	717	44	1984		
P245/70R16 106S	2004543	6.5 - 8.0	9.8 on 7.0	29.5	14.0	13.3	34.8	703	44	2094		
P245/75R16 109S	2004493	6.5 - 8.0	9.8 on 7.0	30.5	14.0	13.7	36.7	682	44	2271		
P255/70R16 109S	1802913	6.5 - 8.5	10.2 on 7.5	30.1	14.0	13.5	36.3	691	44	2271		
P265/70R16 111S	2004503	7.0 - 9.0	10.7 on 8.0	30.6	14.0	13.7	38.5	678	44	2403		
P265/75R16 114S	1803313	7.0 - 9.0	10.5 on 7.5	31.6	14.0	14.1	39.5	656	44	2600		
P255/65R17 108S	1802813	7.0 - 9.0	10.2 on 7.5	30.1	14.0	13.6	37.0	691	44	2205		
P265/70R17 113S	2004513	7.0 - 9.0	10.7 on 8.0	31.7	14.0	14.2	39.2	656	44	2535		
P285/70R17 117S	2004523	7.5 - 9.0	11.5 on 8.5	32.8	14.0	14.6	45.2	634	44	2833		
P265/70R18 114S	2004533	7.0 - 9.0	10.7 on 8.0	32.6	14.0	14.7	41.4	637	44	2601		
P275/65R18 114H	2102293	7.5 - 9.5	11.0 on 8.0	32.0	14.0	14.4	44.5	649	35	2601		
P275/60R20 114S	1904513	7.5 - 9.0	10.9 on 8.0	33.0	12.0	15.1	44.1	630	51	2601		
30X9.50R15/6 104S	1785213	6.5 - 8.5	9.4 on 7.5	29.5	16.0	13.1	38.2	708	50	1985		
31X10.50R15/6 109S	1785313	7.0 - 9.0	10.5 on 8.5	30.5	16.0	14.1	42.9	685	50	2271		
33X12.50R17/6 105S	2102273	8.5 - 11.0	12.50 on 10.0	31.4	16	14.1	59.4	662	35	2040		
35X12.50R17/6 111S	2102193	8.5 - 11.0	12.50 on 10.0	34.6	16	14.1	60.3	600	35	2405		
LT215/75R15/6 100/97S	1784123	5.5 - 7.0	8.5 on 6.0	27.7	15.0	12.4	31.3	756	50	1765		
LT235/75R15/6 104/101S	1784523	6.0 - 7.0	9.2 on 6.5	28.9	15.0	12.9	34.1	725	50	1985		
LT215/85R16/8 110/107Q	1819513	5.5 - 7.0	8.5 on 6.0	30.4	15.0	13.6	37.2	688	65	2335		
LT215/85R16/10 115/112	1784213	5.5 - 7.0	8.5 on 6.0	30.4	15.0	13.6	40.8	688	80	2680		
LT235/85R16/10 120/116Q	1784613	6.0 - 7.5	9.3 on 6.5	31.7	16.0	14.1	44.8	659	80	3042		
LT225/75R16/8 110/107Q	1784313	6.0 - 7.0	8.8 on 6.0	29.3	15.0	13.2	36.5	714	65	2335		
LT225/75R16/10 115/112Q	1784413	6.0 - 7.0	8.8 on 6.0	29.3	15.0	13.2	39.1	714	80	2680		
LT245/75R16/10 120/116Q	1784713	6.5 - 8.0	9.8 on 7.0	30.5	16.0	13.6	46.1	686	80	3042		
LT265/75R16/6 112/109S	1784813	7.0 - 8.0	10.5 on 7.5	31.6	16.0	14.1	43.3	661	50	2470		
LT265/75R16/8 119/116S	1784913	7.0 - 8.0	10.5 on 7.5	31.6	16.0	14.1	45.8	661	65	3000		
LT265/75R16/10 123/120Q	1785013	7.0 - 8.0	10.5 on 7.5	31.6	16.0	14.1	48.9	661	80	3415		
LT285/75R16/8 122/119Q	1785113	7.5 - 9.0	11.3 on 8.0	32.8	17.0	14.5	51.4	636	65	3305		
LT235/80R17 /10 120/117Q	1904713	6.0 - 7.5	9.2 on 6.5	32.1	16.0	14.2	46.3	648	80	3085		
LT245/75R17 /10 121/118Q	1904813	6.5 - 7.5	9.7 on 7.0	31.7	16.0	14.1	46.2	655	80	3195		
LT265/70R17/6 109/112Q	2102213	7.0 - 8.5	10.7 on 8.0	31.7	16.0	14.2	52	655	50	2470		
LT285/70R17/8 121/118Q	1905013	7.5 - 9.5	11.5 on 8.5	32.7	16.0	14.6	50.6	635	65	3195		
LT275/65R18/10 123/120Q	1904913	7.5 - 9.0	10.9 on 8.0	32.1	16.0	14.5	52.1	647	80	3415		
LT285/65R18/8 108/112Q	2102233	8.0 - 10.0	11.5 on 8.5	32.6	16.0	14.6	52.7	637	65	3195		

# KUMHO 853

## LPT Radial



Tire Size	Code No.	Rim Standard	Approved	Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load Single	Dual	RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
8.25R15/18	6001263	21309	6.50	33.2	9.1	15.4	5840@125	5675@125	626	14	64.8	\$	

### Power Fleet - Trailer

# KUMHO 954

LPT Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
7.50R16/14	.6001613	.600	.550	.31.8	.8.1	.15.1	.3305@105	.3195@105	.653	.14	.55.3	.....\$	

Power Fleet - All-Position

# KUMHO KRT02

LPT Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
215/75R17.5/16	.1614813	.600	.675	.30.5	.8.5	.14.0	.4805@125	.4540@125	.682	.16	.61.8	.....\$	
235/75R17.5/18	.1660213	.675	.600	.31.5	.9.4	.14.6	.6005@125	.5675@125	.660	.17	.69.5	.....\$	

Regional Trailer

# KUMHO KRS03

LPT Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
8R17.5/10	.1693913	.600	.525	.30.8	.8.1	.14.2	.2830@90	.2760@90	.675	.15	.49.4	.....\$	
225/70R19.5/12	.1702613	.675	.600	.32.0	.8.7	.14.8	.3640@95	.3415@95	.650	.16	.62.2	.....\$	
245/70R19.5/14	.1693213	.750	.675	.33.3	.9.6	.15.4	.4540@110	.4300@110	.625	.16	.75.3	.....\$	
265/70R19.5/14	.1707913	.750	.825	.34.2	.10.1	.15.9	.5070@110	.4675@110	.608	.17	.82.9	.....\$	
NEW 305/70R22.5/16	.1667113	.900	.825	.39.3	.11.8	.18.2	.7390@120	.6940@120	.529	.15	.117.0	.....\$	
315/80R22.5/18	.1671013	.900	.975	.42.4	.12.1	.19.7	.8270@120	.7165@120	.490	.20	.148.3	.....\$	
315/80R22.5/20	.1645913	.900	.975	.42.4	.12.1	.19.7	.9000@130	.8270@130	.490	.20	.148.3	.....\$	
225/70R19.5/12	.2129753	.675	.600	.32.0	.8.7	.14.8	.3640@95	.3415@95	.650	.16	.62.5	.....\$	

Premium Regional Rib - All Position Use

# KUMHO 937

LPT Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
225/70R19.5/12	.1652413	.675	.600	.32.3	.8.8	.15.0	.3640@95	.3415@95	.642	.20	.66.7	.....\$	

High Traction Drive

# KUMHO 857

LPT Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
185R14/8	.1575013	.50	.60	.25.6	.7.4	.11.9	.1874@65	.1764@65	.817	.10	.22.2	.....\$	
195R14/8	.1575213	.50	.60	.26.2	.7.8	.12.2	.2094@65	.1984@65	.797	.9	.24.7	.....\$	
205R14/8	.1577813	.55	.650	.27.0	.8.2	.12.5	.2271@65	.2150@65	.774	.10	.27.0	.....\$	

All Position Rib Tire

# KUMHO KRD02

Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
245/70R19.5/14	.1664213	.750	.675	.33.5	.9.5	.15.7	.4540@110	.4375@110	.620	.19	.84.3	.....\$	
NEW 305/70R22.5/16	.1627813	.900	.825	.39.6	.11.7	.18.3	.7390@120	.6940@120	.525	.24	.133.0	.....\$	

High Mileage Drive

# KUMHO KLS01

Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/14	.1682913	.825	.750	.41.3	.10.8	.19.4	.6175@105	.5840@105	.503	.19	.124.6	.....\$	
11R24.5/14	.1683413	.825	.750	.43.3	.10.8	.20.4	.6610@105	.6005@105	.480	.19	.133.1	.....\$	
295/75R22.5/14	.1682513	.900	.825	.40.3	.11.2	.18.9	.6175@110	.5675@110	.515	.19	.119.6	.....\$	
285/75R24.5/14	.1682413	.825		.41.4	.10.7	.19.5	.6175@110	.5675@110	.502	.19	.122.7	.....\$	

Premium Highway Rib - Linehaul Steer

# KUMHO KRS02

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
9.00R20/14	6002423	7.00	7.50	40.2	10.0	18.9	5675@115	5355@115	517	19	100.2	\$	
10.00R20/16	6002383	7.50	8.00	41.4	10.8	19.4	6610@120	6005@120	502	20	118.9		
10R22.5/14	1649613	7.50	6.75	40.2	10.0	18.9	5675@115	5355@115	517	19	100.7		
11R22.5/16	1634713	8.25	7.50	41.4	10.8	19.4	6610@120	6005@120	502	20	121.4		
12R22.5/16	1647313	9.00	8.25	42.8	11.6	20.2	7390@120	6780@120	485	20	134.3		
11R24.5/16	1634813	8.25	7.50	43.4	10.8	20.4	7160@120	6610@120	479	20	129.5		
295/75R22.5/14	1647913	9.00	8.25	40.4	11.0	19.0	6175@110	5675@110	515	20	116.1		
285/75R24.5/14	1662513	8.25	9.00	41.5	10.7	19.6	6175@110	5675@110	501	20	117.1		
295/75R22.5/16	1674613	9.00	8.25	40.4	11.2	19.0	6610@120	6005@120	515	20	116.1		
255/70R22.5/16	1832413	7.50	8.25	36.5	9.7	17.0	5510@120	5070@120	569	18	92.3		

Premium Highway Rib - All Position Use

# KUMHO KLS02

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/14 G	2106883	8.25		41.4	11.0	19.9		105		19	119.0	\$	
11R24.5/14 G	2105643	8.25		43.4	11	20.3		105		19	129		
285/75R24.5/14 G	2105563	8.25		41.5	11.2	19.5		110		20	118		
295/75R22.5/14 G	1715713	9		40.3	295	18.8		110		18	117		

Premium Highway Rib - All Position Use

# KUMHO KLT02

## Medium Truck Radial



Tire Size	Code #	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/14	1782613	8.25	7.50	41.5	11.0	19.3	6175@105	5840@105	505	13	104.5	\$	
11R24.5/14	1782713	8.25	7.50	43.5	11.0	20.3	6610@105	6005@105	482	13	114.4		
295/75R22.5/14	1646613	9.00	8.25	40.0	11.2	18.8	6175@110	5675@100	519	13	101.8		
285/75R24.5/14	1782813	8.25		41.3	11.1	19.4	6172@110	5675@110	504	13	105.4		

Shallow Tread Rib - All Position Use

# KUMHO 955

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/16	1235123	8.25	7.50	41.3	10.9	19.3	6610@120	6005@120	503	18	113.0	\$	
11R24.5/16	1193823	8.25	7.50	43.3	10.9	20.3	7160@120	6610@120	480	18	123.6		

# KUMHO 943/943W

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
<b>943</b>													
10.00R20/16	6001063	7.50	8.00	41.5	10.9	19.5	6610@120	6005@120	500	22	122.4	\$	
10R22.5/14	1413513	7.50	6.75	40.3	10.0	18.9	5675@115	5355@115	515	21	102.7		
11R22.5/16	1250913	8.25	7.50	41.5	10.9	19.4	6610@120	6005@120	500	22	116.1		
12R22.5/16	1251713	9.00	8.25	42.9	11.5	20.1	7390@120	6780@120	484	22	131.4		
11R24.5/16	1251613	8.25	7.50	43.5	10.9	20.4	7160@120	6610@120	477	22	125.1		
295/75R22.5/14	1417513	9.00	8.25	40.5	11.5	19.0	6175@110	5675@110	513	22	119.8		
285/75R24.5/14	1405913	8.25		41.5	10.6	19.5	6175@110	5675@110	500	22	117.2		
<b>943W</b>													
385/65R22.5/18	1547813	11.75	12.25	42.3	15.0	19.6	9370@120		495	20	170.5	\$	
445/65R22.5/20	1540713	14.00	13.00	46.1	17.1	21.1	12300@120		454	26	215.1		

# KUMHO KRD03

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/16	1683213	8.25	7.50	41.8	10.8	19.6	6610@120	6005@120	497	26	129.1	\$	
11R24.5/16	1698813	8.25	7.50	43.8	10.8	20.6	7160@120	6610@120	497	26	137.8		

Deep, Non-Skid Mileage Drive

# KUMHO KRD01

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/16	1628113	8.25	7.50	41.9	10.8	19.7	6610@120	6005@120	496	28	130.3	\$	
11R24.5/16	1648113	8.25	7.50	43.9	10.8	20.7	7160@120	6610@120	474	28	138.7		
295/75R22.5/14	1658013	9.00	8.25	40.9	11.2	19.2	6175@110	5675@110	509	28	122.0		
285/75R24.5/14	1657913	8.25		42.0	10.7	19.8	6175@110	5675@110	495	28	126.8		

Extra-Deep, Non-Skid Mileage Drive

# KUMHO KLD01

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/14	1682813	8.25	7.50	41.7	10.8	19.6	6175@105	5840@105	501	26	128.4	\$	
11R24.5/14	1683313	8.25	7.50	43.7	10.8	20.6	6610@105	6005@105	478	26	137.0		
295/75R22.5/14	1681813	9.00	8.25	40.6	11.2	19.0	6175@110	5675@110	515	26	125.9		
285/75R24.5/14	1682313	8.25		41.8	10.7	19.7	6175@110	5675@110	499	26	126.5		

Solid Shoulder Highway Drive

# KUMHO 934

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
11R22.5/16	1390013	8.25	7.50	42.3	10.7	19.9	6610@120	6005@120	491	31	134.9	\$	

On/Off Road, Extra Deep High Traction Drive

# KUMHO 973

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
12R22.5/16	1507213	9.00	8.25	42.8	11.5	20.0	7390@120	6780@120	485	23	139.0	\$	
11R22.5/16	1553013	8.25	7.50	41.6	10.8	19.6	6610@120	6005@120	500	22	123.0		
11R24.5/16	1551113	8.25	7.50	43.6	10.8	20.6	7160@120	6610@120	477	22	131.1		
315/80R22.5/20	1504513	9.00	9.75	42.6	12.1	20.0	9000@130	8255@130	488	23	143.8		
NEW 12.00R24/20	6011243	8.00		47.2	11.9	22.2	9370@120	8540@120		20	167.7		

On/Off Road Rib Tire - All Position Use

# KUMHO 939

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
12.00R24/18	6002153	8.50	9.00	49.5	12.2	23.3	9370@120	8540@120	420	40	205.6	\$	

Power Fleet - All-Position

# KUMHO 983

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
385/65R22.5/18	1442813	11.75	12.25	42.3	15.0	19.6	9370@120		495	20	166.5	\$	
425/65R22.5/20	1466313	12.25	11.75	44.3	16.2	20.5	11000@120		472	20	192.0		

On/Off Road Mixed Services

# KUMHO KMA02

## Medium Truck Radial



Tire Size	Code No.	Rim		Overall Diam. (Inches)	Section Wid. (Inches)	Static Load Radius	Max Tire Load		RPM	Tread Depth (32nds)	Tire Wt.	PRICE	F.E.T.
		Standard	Approved				Single	Dual					
385/65R22.5/18	1687113	11.75		42.3	15.0	19.6	9370			24	171	\$	
425/65R22.5 20/L	2109393	12.25		44.5	16.5	20.5	11000			20	196		
445/65R22.5 20/L	2109463	14		45.9	17.7	21.1	12300			20	217		

On/Off Road Mixed Services

