



COMPOUND & CONSTRUCTION

M/T Tires are compounded by size and application. The following points are general application suggestions. Mickey Thompson is not responsible for misapplications. The catalog number suffix indicates a construction, size or compound enhancement for particular applications.

To identify the Compound of your current M/T Drag Tires look at the Serial Number on the Sidewall of the Tire.

Example: C Y 1 J M **5 F J** 2 6 0 1

Compound Code

CONSTRUCTION:

- ST = Suggested for manual transmissions (medium Compound)**
- W = Extra tread width (please note actual tread and section width on spec sheet)**
- S = Stiff sidewall construction, aids in quicker reaction time due to less tire distortion**
- SS = Super Stiff Sidewall Construction**
- L = Light Weight**
- C = Sport Compact**
- D = Dragster Application**
- R = Radial Construction**

COMPOUNDS:

- B1 For Motorcycles**
- B2 For Motorcycles**
- L4 For Dragsters, Lightweight Vehicles & Vehicles without Rear Suspension**
- L7 For Motorcycles**
- L8 Good Compound for General Use**
- M2 For Jr. Dragsters**
- M5 Good Compound for General Use**
- M7 Good Compound for General Use**
- M9 Aggressive Compound for Heavy Cars, 3000 lbs. and up**
- R1 Special Compound for ET Drag Radial**
- R2 Special Compound for ET Street Radial**



- A proven drag strip winner.
- Compounded for maximum traction.
- Requires little or no burnout.
- Engineered for consistent performance.

SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Compound	Suggested Tube	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Circumference	PRICE
22.0/8.0-13	.3010	.14	L8	.9534	.7	.9.2	.7.9	.22.4	.70	\$
24.5/8.0-13	.3014	.16	L8	.9553	.7	.10.5	.7.7	.24.5	.77	
24.5/9.0-13	.3016	.16	L8	.9553	.7	.10.9	.8.8	.24.5	.77	
26.0/8.5-14	.3020	.18	L8	.9553	.8	.10.2	.8.2	.26.0	.82	
22.0/8.0-15	.3019	.14	L8	.9553	.7	.8.6	.7.9	.22.4	.70	
24.5/8.0-15	.3015	.17	L8	.9553	.8	.9.6	.7.7	.24.5	.77	
26.0/8.5-15	.3052	.19	L8	.9553	.8	.9.9	.8.1	.25.9	.82	
26.0/10.0-15	.3053	.22	L8	.9553	.10	.11.6	.9.6	.26.0	.82	
26.0/10.0-15S	.3053S	.24	M5	.9553	.10	.11.5	.9.8	.26.5	.83	
28.0/9.0-15	.3054	.22	L8	.9553	.8	.10.8	.8.6	.27.3	.86	
28.0/10.5-15	.3055	.23	M5	.9553	.10	.11.7	.10.0	.28.1	.88	
28.0/10.5-15C	.3055C	.23	L4	.9553	.10	.12.0	.10.0	.28.1	.88	
28.0/10.5-15S	.3055S	.24	M5	.9553	.10	.11.7	.10.0	.28.1	.88	
28.0/10.5-15W	.3055W	.26	M5	.9555	.10	.13.1	.10.9	.28.1	.88	
28.0/11.5-15	.3057	.26	M5	.9555	.10	.12.9	.11.0	.28.0	.88	
28.0/11.5-15C	.3057C	.22	L4	.9555	.10	.12.9	.11.0	.28.1	.88	
29.5/9.0R15 RADIAL	.3056R	.23	R1	Tubeless	.10	.11.5	.8.5	.29.5	.92	
29.5/9.0-15ST	.3056ST	.22	M5	.9553	.8	.11.4	.8.9	.29.3	.92	
29.5/9.0-15	.3056	.22	L8	.9553	.8	.11.4	.8.9	.29.3	.92	
29.5/10.5-15	.3062	.25	M5	.9555	.10	.13.1	.10.2	.29.9	.94	
29.5/10.5-15S	.3062S	.27	M5	.9555	.10	.13.2	.10.2	.29.9	.94	
29.5/10.5-15W	.3062W	.30	M5	.9555	.10	.13.6	.11.2	.29.6	.93	
29.5/11.5-15	.3064	.27	M5	.9555	.10	.13.6	.11.1	.29.9	.94	
29.5/13.5-15	.3065	.29	M5	.9555	.12	.16.0	.13.1	.30.2	.95	
30.0/9.0-15	.3066	.22	L8	.9555	.10	.12.5	.8.8	.30.0	.94	
30.0/9.0R15 RADIAL	.3066R	.23	R1	Tubeless	.10	.12.5	.9.0	.29.7	.93	
30.0/9.0R15 RADIAL	.3067R	.23	R1	Tubeless	.10	.11.8	.8.5	.30.0	.93.75	
31.0/10.5-15W	.3068W	.33	M5	.9555	.10	.14.5	.10.8	.31.3	.99	
31.0/13.0-15	.3072	.32	M5	.9558	.12	.15.7	.13.0	.31.0	.98	
31.25/12.2-15W	.3073W	.29	L8	.9558	.12	.15.8	.13.2	.31.5	.98	
31.25/12.2R15W	.3073R	.30	R1	Tubeless	.14	.16.3	.13.5	.31.9	.100	
32.0/14.0-15	.3074	.33	L8	.9558	.14	.17.2	.14.2	.31.8	.100	
32.0/14.0R15 RADIAL	.3074R	.32	R1	Tubeless	.14	.17.4	.14.0	.32.3	.101.75	
32.0/14.0-15S	.3074S	.35	L8	.9558	.14	.17.1	.14.2	.32.2	.100	
32.0/14.5-15	.30751	.38	L8	.9558	.14	.18.0	.14.8	.32.5	.103	
33.0/10.5-15W	.3069W	.33	M5	.9558	.10	.14.5	.11.2	.32.9	.103	
33.0/14.5R15	.3078R	.35	R1	Tubeless	.14	.17.6	.14.5	.33.0	.103	
33.0/15.0-15	.30791	.37	L4	.9558	.14	.18.1	.14.8	.33.6	.105	
33.0/16.5-15S	.3084S	.41	L8	.9558	.15	.20.0	.16.7	.33.5	.105	
33.0/10.5-16W	.3169W	.34	M5	.9558	.15	.16.8	.11.3	.33.0	.104	
33.5/16.5-16	.3185 #	.42	M5	.9558	.16	.20.8	.16.5	.33.7	.106	
34.5/17.0-16	.3186 #	.45	M5	N/A	.16	.21.0	.17.0	.35.0	.110	
34.5/17.0-16	.3187 #	.45	M7	N/A	.16	.21.0	.17.0	.35.0	.110	

A Proven Drag Strip Winner

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.



- A proven drag strip winner.
- Compounded for maximum traction.
- Requires little or no burnout.
- Engineered for consistent performance.
- Specialty sizes for sport compact applications.

SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Compound	Suggested Tube	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Circumference	PRICE
22.0/8.0-13	.3010	.14	L8	.9534	.7	.9.2	.7.9	.22.4	.70	\$
24.5/8.0-13	.3014	.16	L8	.9553	.7	.10.5	.7.7	.24.5	.77	
24.5/9.0-13	.3016	.16	L8	.9553	.7	.10.9	.8.8	.24.5	.77	
26.0/8.5-14	.3020	.18	L8	.9553	.8	.10.2	.8.2	.26.0	.82	
22.0/8.0-15	.3019	.14	L8	.9553	.7	.8.6	.7.9	.22.4	.70	
24.5/8.0-15	.3015	.17	L8	.9553	.8	.9.6	.7.7	.24.5	.77	
28.0/10.5-15C	.3055C	.23	L4	.9553	.10	.12.0	.10.0	.28.1	.88	
29.5/9.0-15	.3056	.22	L8	.9553	.8	.11.4	.8.9	.29.3	.92	

The Number One Sport Compact Drag Tire!

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.
IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.



SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Compound	Suggested Tube	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Circumference	PRICE
26X10.50-15LT	.3752	.20	.M5	.9553	.80	10.5	.83	26.1	.82\$
26X11.50-15LT	.3753	.22	.M5	.9553	10.0	12.0	.98	26.3	.82
27X10.50-15LT	.3758	.22	.M5	.9553	.80	10.6	.89	27.0	.85
28X11.50-15LT	.3754	.22	.M5	.9553	.80	11.1	.86	27.6	.87
28X12.50-15LT	.3755	.24	.M5	.9553	10.0	12.6	10.0	28.1	.88
28X13.50-15LT	.3757	.28	.M5	.9555	10.0	13.2	11.0	28.0	.88
30X12.50-15LT	.3762	.26	.M5	.9555	10.0	13.3	10.2	30.0	.94
30X13.50-15LT	.3763	.31	.M5	.9555	10.0	13.7	11.1	30.0	.94
31X14.50-15LT	.3768	.33	.M5	.9555	10.0	14.5	10.8	31.3	.99
31X16.50-15LT	.3772	.34	.M5	.9558	12.0	15.5	12.4	31.5	.99
32X17.50-15LT	.3774	.37	.M5	.9558	14.0	17.7	14.2	32.2	1.01
33X18.50-15LT	.3780	.43	.M5	.9558	14.0	18.8	15.8	33.3	1.04
26X10.50-16LT	.3792	.22	.M5	.9553	.90	10.3	.84	25.9	.82
26X11.50-16LT	.3793	.24	.M5	.9553	10.0	10.8	.97	26.2	.82
28X11.50-16LT	.3796	.24	.M5	.9553	.80	10.7	.87	28.0	.88
26X11.50-17LT	.3743	.23	.M5	.9553	11.0	11.1	.95	26.5	.83

- D.O.T. approved.
- Compounded for maximum traction.
- Requires little or no burnout.
- Engineered for consistent performance.

Worlds Fastest D.O.T. Class Race Tire.

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.

IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.

CAUTION: It is NOT RECOMMENDED that RADIAL and NON-RADIAL Tires be mixed on the same Vehicle.



SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Approximate Rim	Measuring Rim Width	Sidewall Width	Tread Width	Overall Diameter	Circumference	PRICE
18/8-8	.3621	.6	.M2	.8	10.5	.73	18	.55\$
18/8.5-8	.3623	.6	.M2	.8	10.8	.81	18.1	.56
19/8-10	.3644	.9	.M2	.8	9.5	.72	19.5	.61

Acceptable practice for rim width is tread width plus or minus 1 inch. All dimensions @ 10 psi cold on measuring rim.

IMPORTANT: ALL DRAG DRIVE TIRES MUST BE MATCHED TO BE WITHIN 1/2" ROLL OUT.

- A proven Jr. drag winner.
- Compounded for maximum traction.
- Requires little or no burnout.
- Engineered for consistent performance.





WORLD'S FASTEST STREET RADIAL

- D.O.T. approved.
- Soft compound for superior traction on drag strip.
- Special sidewall construction for quick launches.
- Radial construction for excellent ride control on the street.
- Low void, directional tread for maximum dry traction.
- Polyester ply, steel belted for strength and durability.



OPTIMIZED FOR MODERN SPORTS CARS & SPORT COMPACTS

- NEW to the ET STREET Radial line, this tire specifically designed for modern performance cars including sport compacts, Mustangs, Corvettes, Vipers and others that require bigger wheel diameters for brake clearance.
- Soft Compound For Superior Traction On Drag Strip.
- Radial construction for excellent ride control on the street.
- Polyester Ply, Steel Belted For Strength And Durability.

SPECIAL ORDER ONLY

Tire Size	Code No.	Equivalent Size	Weight	Compound	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Circumference	PRICE
STREET RADIAL											
P235/60R15	3752R	26 X 9.50R15	27	R2	6.5-8.5	7	9.5	8.4	26.1	82	\$
P275/50R15	3753R	26 X 11.50R15	31	R2	7.5-9.5	8.5	11.3	10.5	26.1	82	
P255/60R15	3756R	27 X 10.50R15	30	R2	7.0 - 9.0	7.5	10.1	9.0	27.1	85	
P275/60R15	3754R	28 X 11.50R15	33	R2	7.5-9.5	8	11	9.5	28	87	
NEW P295/55R15	3755R	28X12.50R15	TBD	R2	8-10.5	9.5	12	10.9	27.8	87	
P325/50R15	3757R	28 X 13.50R15	37	R2	9.0-12.0	10	13.1	11.6	28	87	
P295/65R15	3762R	30 X 12.50R15	38	R2	8.0-10.0	8.5	11.9	10.9	30	94	
P315/60R15	3763R	30 X 13.50R15	39	R2	8.5-11.0	9.5	12.9	11.9	30	94	
P255/50R16	3793R	26 X 10.50R16	29	R2	7.0-9.0	8	10.5	9.6	26.1	82	
P275/40R17	3743R	26 X 11.50R17	28	R2	9.0 - 10.0	9	11	10.0	26	82	
SPORTS CARS & SPORT COMPACTS											
NEW P205/50R14	3730R	22X8.5R14	19	R2	5.5-7.5	6.5	8.3	7.25	22.3	70	
NEW P215/60R14	3732R	24X8.50R14	20	R2	6.0-7.5	6.5	8.6	7	24.2	76	
P205/50R15	3750R	23X8.0R15	22	R2	5.5 - 7.5	6.5	8.40	7.6	23.13	73.0	
P225/50R15	3751R	24X9.0R15	23	R2	6.0 - 8.0	7.0	9.10	8.2	23.98	75.3	
P315/45R16	3795R	27X12.50R16	34	R2	10.0 - 12.0	11.0	12.61	11.2	27.19	85.5	
P295/50R16	3794R	28X11.50R16	33	R2	8.0 - 10.0	9.5	12.09	10.8	27.69	86.9	
NEW P205/40R17	3740R	24X8.50R17	19	R2	7.0-8.0	7.5	8.30	7.3	23.5	74.0	
P315/35R17	3744R	28X11.50R17	33	R2	9.5 - 11.0	11.0	12.70	11.7	27.19	85.4	
P295/45R17	3745R	26X12.50R17	31	R2	11.0 - 12.0	10.0	11.60	10.6	25.78	81.0	
NEW P245/40R18	3780R	26X9.50R18	25	R2	8.0-9.5	8.5	9.60	8.5	25.8	81.0	
NEW P315/30R18	3784R	26X12.50R18	30	R2	11.0-12.0	11.0	12.40	11	25.5	80.0	
NEW P265/40R18	3782R	27X10.50R18	28	R2	9.0-10.0	9.5	10.60	9.6	26.5	83.0	
P305/35R18	3785R	27X12.50R18	31	R2	10.0 - 12.0	11.0	12.50	11.5	26.39	82.9	
P345/35R18	3788R	28X13.50R18	35	R2	11.0 - 13.0	12.0	13.89	12.8	27.49	86.3	
NEW P305/45R18	3786R	29X11.50R18	32	R2	9.5-11.0	10.0	11.80	10.3	28.8	91.0	



SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Suggested Tube	Approved Rim	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	PRICE
26X7.50-15	1572	16	TUBELESS	3.5 - 6.5	4	6.3	4.8	26	\$
26X7.50-15 8 PLY	1573*	19	TUBELESS	3.5 - 6.5	4	6.3	4.8	26	
28X7.50-15	1574	20	TUBELESS	3.5 - 6.5	4	6.9	5.5	28	
26X8.50-15	1575	22	TUBELESS	4.5 - 7.0	6	8.3	6.7	27	

Narrow Front Tire That Compliments Our Sportsman™ And Sportsman Pro® Tire Lines.

CAUTION: It is NOT RECOMMENDED that RADIAL and NON-RADIAL tires be mixed on the same vehicle.

*** FRONT TIRE FOR CARS AND TRUCKS OVER 3,000 LBS**

- Widest Hi-Performance street legal tire.
- D.O.T. approved.
- Wrinkle wall sidewall.
- Street compound and drag compound (pro).
- Matching front tires.

MICKEY THOMPSON E.T. FRONT TIRES

Drag Series

SPECIAL ORDER ONLY



Tire Size	Code #	Weight	Picture	Approved Rim	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Circumference	PRICE
22.0/2.5-17	3004	4	C	2.5	2.5	2.7	1.5	22.0	67	\$
22.5/4.5-15	3005	7	A	3.5 - 5.0	4.0	5.1	4.1	22.5	71	
24.0/4.5-15	3006	11	A	3.5 - 5.0	4.0	6.4	4.8	23.8	75	
NEW 25.0/4.5-15	3001	11	A	3.5 - 4.0	4.0	6.5	4.5	25.0	78	
26.0/4.5-15	3007	12	A	3.5 - 5.0	4.0	6.8	4.9	25.9	81	
27.5/4.5-15	3009	13	A	3.5 - 5.0	4.0	7.0	5.0	27.3	86	
28.0/4.5-15	3002	13	A	3.5 - 4.5	4.0	7.2	5.1	28.0	88	
29.0/4.5-15	3008**	12	B	3.5 - 5.0	4.0	7.3	4.5	28.7	90	

** Not Acceptable for Land Speed Record use.

- Ultra-lightweight design reduces rolling resistance.
- Acceptable for high speed use.
- Tubless.

MICKEY THOMPSON SPORTSMAN ST



Tire Size	Code No.	Service Desc.	Sidewall	Meas. Rim	Approx. Widths	Overall Diameter	Section Width	Tread Width	Weight Lbs	UTQG	PRICE	F.E.T.
P215/70R15	.6023	.97T	.RWL	.6.5	.5.5-7.0	.26.7	.8.7	.7	.26	.440-A-B	\$	
P225/60R15	.6024	.95T	.BLK	.6.5	.6.0-8.0	.25.7	.8.6	.7.2	.23	.440-A-B		
P225/70R15	.6025	.100T	.RWL	.6.5	.6.0-7.5	.27.4	.9.1	.7.2	.27	.440-A-B		
P235/60R15	.6026	.98T	.RWL	.7	.6.5-8.5	.26.1	.9.2	.7.6	.26	.440-A-B		
P245/60R15	.6027	.100T	.RWL	.7	.7.0-8.5	.26.6	.9.5	.8	.26	.440-A-B		
P255/60R15	.6028	.102T	.RWL	.7.5	.7.0-9.0	.27	.10.24	.8.2	.27	.440-A-B		
P275/60R15	.6030	.107T	.RWL	.8	.7.5-9.5	.28.1	.10.7	.8.9	.31	.440-A-B		
P295/50R15	.6031	.105S	.RWL	.9.5	.8.0-10.0	.26.8	.12.22	.10.1	.32	.440-A-C		



SPECIAL ORDER ONLY



- Radial construction for high mileage and smooth ride.
- Unique "Flamed" tread pattern.
- Custom sizes for street rods and muscle cars.
- Available for 15", 18", and 20" wheel diameters.
- Matching front "Skinny's" for staggered fitments.

Tire Size	Code #	Weight	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	PRICE
24X5.00R15LT	.6651	15.0	3.5 - 4.5	4	5.8	4.5	24.0	\$
26X6.00R15LT	.6652	20.0	3.5-5.0	4	6.5	5.7	26.0	
26X8.00R15LT	.6650	21.0	5.0 - 7.0	6	8.5	7.0	26.1	
26X10.00R15LT	.6653	23.0	7.0 - 9.0	8	10.3	8.8	26.1	
26X12.00R15LT	.6654	26.0	8.0 - 10.0	10	12.0	10.6	26.1	
28X10.00R15LT	.6640	27.0	7.0 - 8.5	8	10.3	8.7	28.0	
28X12.00R15LT	.6641	31.0	8.5 - 10.0	10	12.1	10.4	28.0	
29X15.00R15LT	.6642	42.0	10.0 - 13.0	12	15.0	13.0	29.0	
29X18.00R15LT	.6655	49.0	14.0 - 16.0	14	17.6	15.8	29.0	
30X12.00R15LT	.6643	36.0	8.5 - 10.0	10	12.6	10.2	30.0	
31X16.00R15LT	.6644	47.0	12.0 - 14.0	12	16.0	13.9	31.0	
31X18.00R15LT	.6656	50.0	14.0 - 16.0	14	17.9	15.7	31.0	
33X22.00R15LT	.6657	59.0	15.0 - 18.0	15	20.0	17.8	32.0	
26X6.00R18LT	.6682	18.0	4.5 - 5.5	5	6.3	5.7	26.0	
26X8.00R18LT	.6680	21.0	5.5 - 7.0	6	7.7	7.2	26.2	
26X10.00R18LT	.6683	24.0	8.0 - 9.0	9	9.5	8.8	26.2	
26X12.00R18LT	.6684	27.0	8.0 - 10.0	10	11.0	10.6	26.4	
28X10.00R18LT	.6670	28.0	7.5 - 9.0	8	9.8	8.7	27.9	
28X12.00R18LT	.6671	33.0	9.0 - 10.0	10	11.6	10.6	28.0	
30X12.00R18LT	.6672	36.0	9.0 - 11.0	10	12.3	10.2	29.9	
33X22.00R18LT	.6687	59.0	15.0 - 18.0	16	19.3	17.8	32.0	
29X15.00R20LT	.6620	41.0	13.0 - 14.0	14	14.7	13.0	29.0	
29X18.00R20LT	.6625	46.0	15.0 - 16.0	16	17.2	15.5	29.0	
31X18.00R20LT	.6626	50.0	15.0 - 16.0	16	17.3	15.7	31.1	
33X22.00R20LT	.6627	58.0	16.0 - 18.0	17	18.9	17.8	32.0	

A Must For Any Street Rod or Street Machine Builder

SPECIAL ORDER ONLY



- Widest Hi-Performance street legal tire.
- D.O.T. approved.
- Wrinkle wall sidewall.
- Street compound and drag compound (pro).
- Matching front tires.

Tire Size	Code #	Weight	Suggested Tube	Approved Rim	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	PRICE
26X10.50-15LT	.6542	23	.9553	7.0 - 10.0	8	10.4	8.0	26	\$
28X10.50-15LT	.6546	23	.9553	7.0 - 9.0	8	11.2	8.3	28	
28X12.50-15LT	.6548	26	.9553	8.0 - 11.0	10	13.1	10.4	28	
29X12.50-15LT	.6557	27	.9555	8.0 - 11.0	10	13.0	10.0	29	
29X15.50-15LT	.6558	32	.9558	10.0 - 13.0	12	15.3	12.7	29	
29X18.50-15LT	.6559	37	.9558	14.0 - 16.0	14	17.6	15.5	29	
31X16.50-15LT	.6560	34	.9558	12.0 - 14.0	12	15.7	12.2	31	
31X18.50-15LT	.6562	37	.9558	14.0 - 16.0	14	17.5	14.3	31	
33X19.50-15LT	.6564	39	.9558	14.0 - 16.0	14	18.0	14.5	32	
33X21.50-15LT	.6565	44	.9558	15.0 - 18.0	15	19.6	16.6	32	

Widest High Performance Street Legal Tire.

CAUTION: It is NOT RECOMMENDED that RADIAL and NON-RADIAL Tires be mixed on the same Vehicle.



- Advance radial construction for high mileage and smooth ride.
- High load ratings for great towing capabilities.
- Solid rib for enhanced ride and handling.
- Spiral nylon over wraps for better handling & performance
- Siped tread lugs for better grip on smooth surfaces & ice.

Tire Size	Code No.	Equivalent Size	Weight	Max Load Single	Max PSI	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Tread Depth	PRICE	F.E.T.
30X9.50R15/6	5150		36	1985	50 psi	6.5 - 8.5	7.50	9.30	7.30	29.3	16.5	\$	
31X10.50R15/6	5151		40	2270	50 psi	7.0 - 9.0	8.50	10.50	8.20	30.3	16.5		
32X11.50R15/6	5152		44	2535	50 psi	8.0 - 10.0	9.00	11.40	9.00	31.5	17.0		
33X12.50R15/6	5153		50	2205	35 psi	8.5 - 11.0	10.00	12.50	9.60	32.5	17.0		
LT225/75R16/10	5160	28X9.50R16	38	2680	80 psi	6.0 - 7.0	6.00	8.90	6.90	29.4	16.5		
LT245/75R16/10	5161	31X9.50R16	43	3042	80 psi	6.5 - 7.5	7.00	9.60	7.40	30.5	16.5		
LT235/85R16/10	5164	32X9.50R16	43	3042	80 psi	6.0 - 7.0	6.50	9.40	6.70	31.8	16.5		
LT265/75R16/10	5162	32X10.50R16	48	3415	80 psi	7.0 - 8.0	7.50	10.60	7.80	31.8	16.5		
LT285/75R16/8	5163	33X11.50R16	51	3305	65 psi	7.5 - 9.0	8.00	11.50	8.80	32.9	17.0		
LT305/70R16/8	5165	33X12.50R16	55	2910	50 psi	8.0 - 9.5	9.00	12.20	9.70	33.0	17.0		
LT315/75R16/8	5166	35X12.50R16	62	3195	50 psi	8.0 - 10.0	8.50	12.90	9.80	34.8	17.0		
LT245/70R17/10	5170	31X9.50R17	43	3000	80 psi	6.5 - 8.0	7.00	9.80	7.30	30.6	16.5		
LT265/70R17/10	5171	32X10.50R17	50	3195	80 psi	7.0 - 8.5	8.00	10.70	8.50	31.6	16.5		
33X12.50R17/8	5173		55	2600	50 psi	8.5 - 11.0	10.00	12.50	9.60	32.5	17.0		
LT285/70R17/8	5174	33X11.50R17	52	3195	65 psi	7.5 - 9.0	8.50	11.50	9.00	32.8	17.0		
LT315/70R17/8	5175	35X12.50R17	61	3195	50 psi	8.5 - 10.0	9.50	12.90	9.90	34.9	17.0		
LT275/65R18/10	5180	32X11.50R18	52	3415	80 psi	7.5 - 9.5	8.00	11.00	8.80	32.1	16.0		

Popular Sizes Available For Today's Modern Vehicles!

MICKEY THOMPSON BAJA ATZ RADIAL

Baja Series



- Advance radial construction for high mileage and smooth ride.
- High load ratings for large towing capabilities.
- Self cleaning tread with "Stone Kicker" rock ejectors.
- Extra wide footprint for better traction and even wear.
- Enhanced sidebiters for added traction & sidewall protection.
- Siped tread lugs for better grip on smooth surfaces & ice.

Tire Size	Code No.	Equivalent Size	Weight	Max Load Single	Max PSI	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Tread Depth	PRICE	F.E.T.
TRADITIONAL SIZES													
33X12.50R15/6	5353		.52	2205	35	8.5 - 11.0	10.00	12.40	9.80	32.6	20		\$
LT265/75R16/10	5362	32X10.50R16	.48	3415	80	7.0 - 8.0	7.50	10.50	8.10	31.8	18		
LT285/75R16/8	5363	33X11.50R16	.57	3305	65	7.5 - 9.0	8.00	11.30	9.20	32.8	20		
LT305/70R16/8	5365	33X12.50R16	.57	2910	50	8.0 - 9.5	9.00	12.30	10.00	32.8	18		
LT315/75R16/8	5366	35X12.50R16	.65	3195	50	8.0 - 10.0	8.50	12.90	10.00	34.6	20		
LT265/70R17/10	5371	32X10.50R17	.51	3195	80	7.0 - 9.0	8.00	10.70	8.40	31.7	18		
LT285/70R17/8	5374	33X11.50R17	.55	3195	65	7.5 - 9.0	8.50	11.40	9.10	32.8	18		
LT305/65R17/10	5373	33X12.50R17	.59	3195	65	8.5 - 11.0	9.00	12.20	9.80	32.6	20		
35X12.50R17/8	5375		.67	3000	50	8.5 - 11.0	10.00	12.90	10.20	34.9	20		
LT275/70R18/10	5388	33X11.50R18	.56	3640	80	7.0 - 9.0	8.00	11.00	8.80	33.3	18		
LT305/60R18/10	5387	33X12.50R18	.65	3195	65	8.5 - 11.0	9.00	12.10	9.80	32.6	20		
LT305/70R18/10	5389	35X12.50R18	.71	3750	65	8.0 - 10.0	9.00	12.20	9.80	35.0	20		
LT305/55R20/10	5328	33X12.50R20	.66	3195	65	8.5 - 11.0	9.50	12.50	10.10	33.4	20		
35X12.50R20/10	5329		.71	3195	65	8.5 - 11.0	10.00	12.50	9.80	34.5	20		
SPECIALTY SIZES													
LT325/60R18/10	5181	33X13.50R18LT	.76	3,525	65 psi	9.0 - 12.0	9.5	13.3	10.8	33.2	19.0		
LT325/65R18/10	5183	35X13.50R18LT	.79	3,860	65 psi	9.0 - 12.0	9.5	13.5	10.8	34.8	19.0		
LT325/50R20/10	5120	33X13.50R20LT	.73	3,085	65 psi	9.0 - 12.0	10.0	13.2	10.8	33.0	19.0		
35X13.50R20/10	5121		.81	3,305	65 psi	8.5 - 11.0	11.0	13.6	10.7	34.8	19.0		

SPECIALTY LIGHT TRUCK SIZES FEATURES 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE

Popular Sizes Available For Today's Modern Vehicles!

MICKEY THOMPSON BAJA MTZ RADIAL

Baja Series



- Advance radial construction for high mileage and smooth ride.
- Self cleaning high-void tread lugs for traction in mud or snow.
- Deep shoulder lugs provides aggressive traction and bold looks.
- Enhanced sidebiters for added traction and sidewall protection.
- Siped tread lugs for better grip on smooth surfaces and ice.

Tire Size	Code No.	Equivalent Size	Weight	Max Load Single	Max PSI	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Tread Depth	PRICE	F.E.T.
TRADITIONAL SIZES													
31X10.50R15/6	5251		.47	2270	.50 psi	7.0 - 9.0	8.5	10.9	8.3	30.8	19.0		\$
33X12.50R15/6	5253		.56	2205	.35 psi	8.5 - 11.0	10.0	12.1	9.7	32.8	20.5		
35X12.50R15/6	5254		.66	2535	.35 psi	8.5 - 11.0	10.0	12.2	10.0	34.8	19.5		
LT265/75R16/10	5262	32X10.50R16	.53	3415	.80 psi	7.0 - 8.0	7.5	10.1	8.3	32.0	18.5		
LT285/75R16/8	5263	33X11.50R16	.56	3305	.65 psi	7.5 - 9.0	8.0	11.3	8.9	33.1	18.5		
LT305/70R16/8	5265	33X12.50R16	.61	2910	.50 psi	8.0 - 9.5	9.0	12.0	9.8	33.1	19.0		
LT315/75R16/8	5266	35X12.50R16	.67	3195	.50 psi	8.0 - 10.0	8.5	11.9	9.8	34.5	19.0		
LT265/70R17/10	5271	32X10.50R17	.53	3195	.80 psi	7.0 - 9.0	8.0	10.8	8.3	31.9	18.5		
LT285/70R17/8	5272	33X11.50R17	.58	3195	.65 psi	7.5 - 9.0	8.5	11.5	8.9	33.0	18.0		
33X12.50R17/8	5273		.63	2600	.50 psi	8.5 - 11.0	10.0	12.5	9.8	32.8	20.5		
LT315/70R17/8	5275	35X12.50R17	.68	3195	.50 psi	8.0 - 11.0	9.5	11.9	9.8	34.6	19.0		
LT275/70R18/10	5288	33X11.50R18	.62	3640	.80	7.0-9.0	8.0	11.0	8.8	33.4	20.5		
LT305/60R18/10	5289	33X12.50R18	.64	3195	.65	8.5-11.0	9.0	12.1	9.8	32.6	20.5		
LT305/70R18/10	5290	35X12.50R18	.71	3750	.65	8.0-10.0	9.0	12.2	9.8	35.1	20.5		
LT305/55R20/10	5227	33X12.50R20	.69	3195	.65	8.5-11.0	9.5	12.5	10.1	33.5	20.5		
35X12.50R20LT	5226		.70	3195	.65	8.5-11.0	10.0	12.5	9.8	34.7	20.5		
SPECIALTY SIZES													
36X15.50R15/6	5256		.88	3,000	.35 psi	11.0 - 13.0	12.0	15.7	12.2	35.9	23.0		
LT375/55R16/10	5267	33X15.50R16LT	.80	3,750	.65 psi	10.0 - 13.0	12.0	15.4	11.8	32.4	23.0		
LT375/65R16/8	5268	36X15.50R16LT	.89	3,750	.50 psi	10.0 - 13.0	11.0	15.0	12.2	35.4	23.0		
LT395/70R16/6	5269	38X15.50R16LT	.93	3,415	.35 psi	12.0 - 13.0	12.0	16.0	12.2	37.9	23.0		
37X12.50R17LT	5277		.83	3,525	.50 psi	8.5-11.0	10.0	13.1	10.0	36.9	23		
LT325/60R18/10	5281	33X13.50R18LT	.75	3,525	.65 psi	9.0 - 12.0	9.5	13.3	10.5	33.2	20.5		
LT375/50R18/10	5282	33X15.50R18LT	.81	3,525	.65 psi	10.0 - 13.0	12.0	15.4	12.0	33.0	23.0		
LT325/65R18/10	5283	35X13.50R18LT	.78	3,860	.65 psi	9.0 - 12.0	9.5	13.5	10.6	34.8	20.5		
LT375/60R18/8	5284	36X15.50R18LT	.90	3,640	.50 psi	10.0 - 13.0	11.0	15.0	12.0	35.9	23.0		
LT395/65R18/6	5286	38X15.50R18LT	.97	3,415	.35 psi	11.0 - 14.0	12.0	15.7	12.2	37.9	23.0		
36X15.50R20/10	5222		.92	3,525	.65 psi	11.0 - 13.0	12.0	15.3	11.9	36.4	21.0		
38X15.50R20/8	5223		.99	3,525	.50 psi	11.0 - 13.0	12.0	15.7	12.2	37.9	23.0		

SPECIALTY LIGHT TRUCK SIZES FEATURES 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE

Popular Sizes Available For Today's Demanding Off-Road Vehicles!

MICKEY THOMPSON BAJA CLAW RADIAL

Baja Series



- Advance radial construction for high mileage and smooth ride.
- Self cleaning high-void tread lugs for traction in mud or snow.
- Circumferential grooves for hydroplane resistance.
- Aggressive sidebiters for added traction & sidewall protection.
- Directional 23 degree tread pattern and extra wide footprint for the extreme traction off-roader's demand.

Tire Size	Code No.	Equivalent Size	Weight	Max Load Single	Max PSI	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Tread Depth	PRICE	F.E.T.
TRADITIONAL SIZES													
31X10.50R15/6	.5751		.42	.2270	.50 psi	.7.0 - 9.0	.8.5	.10.5	.8.3	.30.5	.20.0		\$
33X12.50R15/6	.5754		.52	.2205	.35 psi	.8.5 - 11.0	.10.0	.12.8	.9.9	.32.5	.20.5		
35X12.50R15/6	.5756		.63	2,535	.35 psi	.8.5 - 10.0	.10.0	.12.9	.10.0	.34.9	.20.5		
LT285/75R16/8	.5763	.33x11.50R16	.54	.3305	.65 psi	.7.5-9.0	.8.0	.11.3	.8.9	.33.1	.16.5		
LT305/70R16/8	.5766	.33X12.50R16LT	.57	2,910	.50 psi	.8.0 -9.5	.9.0	.11.9	.9.8	.32.9	.18.5		
LT315/75R16/8	.5768	.35X12.50R16LT	.62	3,195	.50 psi	.8.0 - 10.0	.8.5	.12.5	.9.8	.34.8	.20.0		
33X12.50R17/8	.5774		.57	2,600	.50 psi	.8.5 - 11.0	.10.0	.12.5	.10.0	.32.5	.20.5		
35X12.50R17/8	.5776		.63	3,000	.50 psi	.8.5 - 11.0	.10.0	.12.7	.9.8	.34.9	.20.5		
SPECIALTY SIZES													
LT325/80R16/8	.5769	.37X13.50R16LT	.84	3,525	.50 psi	.8.5 - 11.0	.9.0	.13.1	.10.8	.36.9	.22.5		
35X13.50R20/10	.5722		.76	3,305	.65 psi	.8.5-11.0	.11.0	.13.7	.10.5	.34.7	.21.0		

**SPECIALTY LIGHT TRUCK SIZES FEATURES 3 PLY SIDEWALL AND 6 PLY TREAD FOR ADDED STRENGTH AND PUNCTURE RESISTANCE

The Original Extreme Terrain Tire!

MICKEY THOMPSON BAJA CLAW BIAS

Baja Series



- Up to 20" of contact patch from sidebiter to sidebiter.
- Full 6 ply lower sidewall with cut resistant compound.
- Directional, self-cleaning tread design.
- Circumferential grooves allow flexing for better rock crawling.
- New tread pattern with 23 degree lugs & extra large sidebiters for extra traction and protection.

SPECIAL ORDER ONLY

Tire Size	Code #	Weight	Max Load Single	Max PSI	Approved Rims	Measuring Rim Width	Section Width	Tread Width	Overall Diameter	Tread Depth	PRICE
NEW 16/38.5-16/6	.2676	.102	3,415	.30	.10.0 - 12.0	.12.0	.16.5	.12.5	.39.0	.21.0	\$
19.5/46-16/6	.2678	.137	3,500	.30 psi	.12.0 - 16.0	.14.0	.20.5	.14.6	.46.0	.28.0	
19.5/46-20/6	.2698	.149	3,500	.30	.12.0 - 16.0	.14.0	.18.8	.14.6	.46.0	.28.0	

Polyester/Fiberglass Belted, Black Letters



MICKEY THOMPSON OFF-ROAD RACING TIRES Off Road Race Tires

SPECIAL ORDER ONLY



BAJA PRO



DESERT KING



MINI MAG

Tire Size	Code #	Product Model	Estimated Weight	Approved Rim	Measuring Rim	Sidewall Width	Tread Width	Tire Diameter	PRICE
30/7.0-15	2548	Baja Pro	28	3.0 - 6.0	4.0	6.9	4.9	30	\$
33/9.0-15	2554	Baja Pro	37	4.0 - 8.0	7.0	9.6	7.8	33	
33x10.50-15	2553	Desert King	40	7.0 - 9.0	8.0	11.3	8.7	32	
E78-15	2551	Mini Mag	21	4.0 - 6.0	4.0	6.5	5.2	27	

MICKEY THOMPSON CLASSIC II WHEELS

SPECIAL ORDER ONLY



- Steel inserts in the lug holes provide a stonger seat area.
- Highly polished surface.
- Hand hole are polished inside for a more distinctive and attractive look.
- High load rating.
- Chrome center cap included.
- Lifetime limited guarantee for structural defects.

Wheel Size	Code #	Weight	Bolt Pattern	Back Space	Offset	Max Load Single	Cap#	PRICE
15X8	358421	17	5-4 1/2"	3 5/16"	-30.0MM	2,000	401216	\$
15X8	358441	17	5-4 3/4"	3 5/16"	-30.0MM	2,000	401216	
15X8	358401	17	5-5 1/2"	3 5/16"	-30.0MM	2,000	401214	
15X8	358431	17	5-5"	3 5/16"	-30.0MM	2,000	401216	
15X8	358411	17	6-5 1/2"	3 5/16"	-30.0MM	2,000	401214	
15X10	350421	20	5-4 1/2"	3 5/8"	-58.0MM	2,500	401216	
15X10	350401	20	5-5 1/2"	3 5/8"	-58.0MM	2,500	401214	
15X10	350411	20	6-5 1/2"	3 5/8"	-58.0MM	2,500	401214	
15X12	352401	23	5-5 1/2"	3 5/8"	-73.0MM	3,000	401214	
15X12	352411	23	6-5 1/2"	3 5/8"	-73.0MM	3,000	401214	
16X8	368452	21	5-135mm	3 3/4"	-19.0MM	3,100	401414	
16X8	368421	21	5-4.5	4 7/16"	0.0MM	3,100	401216	
16X8	368431	24	5-5"	4	-13.0MM	3,100	401216	
16X8	368401	21	5-5 1/2"	4 7/16"	0.0MM	3,100	401214	
16X8	368411	21	6-5 1/2"	4 7/16"	0.0MM	3,100	401214	
16X8	368412	21	6-5 1/2"	3 5/8"	-22.2MM	3,100	301514	
16X8	368170	21	8-6.5	4"	-13.0MM	3,100	301218	
16x8	368482	21	8-6 1/2"	4"	-13.0MM	3,100	301218	
16X10	360412	24	6-5 1/2"	4 7/16"	-27.0MM	3,100	301514	
16X10	360170	24	8-170mm	4 7/16"	-27.0MM	3,100	301218	
16X10	360481	24	8-6 1/2"	4 7/16"	-27.0MM	3,100	301218	
16X12	361412	24	6-5 1/2"	4 1/2"	-51.0MM	3,600	401514	
16X12	361170	24	8-170mm	4 1/2"	-51.0MM	3,600	401218	
16X12	361481	24	8-6 1/2"	4 1/2"	-51.0MM	3,600	401218	
117X9	379452	23	5-135mm	4 1/2"	-12.0MM	3,000	401414	
17X9	379403	23	5-150mm	5 1/2"	+13.0MM	3,000	401515	
17X9	379421	26	5-4 1/2"	4 1/2"	-12.0MM	3,000	401516	
17X9	379431	26	5-5"	4 1/2"	0.0MM	3,000	401216	
17X9	379402	23	5-5 1/2"	4 1/2"	-12.0MM	3,000	401214	
17X9	379462	23	6-135mm	5 1/2"	12.0MM	3,000	401414	
17X9	379411	23	6-5 1/2"	5"	0.0MM	3,000	401214	
17X9	379412	26	6-5 1/2"	4 1/2"	-12.0MM	3,000	401514	
17X9	379413*	24	6-5 1/2"	5"	0.0MM	3,000	401514	
17X9	379170	24	8-170mm	5"	0.0MM	3,000	401218	
17X9	379481	24	8-6 1/2"	5"	0.0MM	3,000	401218	

* Hub Centering Ring included for late Model Chevy/GMC Applications

MICKEY THOMPSON NATURAL RUBBER TIRES

Code #	Size	Weight	Application	PRICE
9553	9.50-15/16	4.1	24.5" To 28" Diameter with 8.0 To 10.5" tread	\$
9555	11.50-15	5.6	28" To 31" Diameter with 10.5" To 11.5" tread	
9558	15.00-15/16	8.1	31" To 33.5" Diameter with 12.0 To 17.0" tread	

- 100% Natural rubber tubes with an air craft style removable valve stem that clamps to the wheel.
- Extremely light weight and durable these tubes are a must for racing applications.
- Natural rubber is a far superior to other materials because of its ability to conform to sidewall distortion and its resistance to deterioration due to many heat cycles.

MICKEY THOMPSON CLASSIC LOCK WHEEL



- Large bolt on simulated bead lock ring.
- Street legal with a real competition "look."
- M/T logo embossed into simulated lock ring.
- Highly polished surface.
- Hand hole are polished inside for a more disintictive and attractive look.
- High load rating.
- Valve stem, center cap, & polished ring included.
- Lifetime limited guarantee for structural defects.

SPECIAL ORDER ONLY

Wheel Size	Code #	Weight	Bolt Pattern	Back Space	Offset	Max Load Single	Cap#	PRICE
15X10	450421A	32	5 X 4 1/2"	3 5/8"	-58.0MM	2,500	401216	\$
15X10	450401A	32	5 X 5 1/2"	3 5/8"	-58.0MM	2,500	401214	
15X10	450411A	32	6 X 5 1/2"	3 5/8"	-58.0MM	2,500	401214	
16X8	468452	22	5-135mm	4"	-12.0MM	3,100	401414	
16X8	468421	24	5-4 1/2"	4"	-12.0MM	3,100	401516	
16X8	468401	24	5-5 1/2"	4"	-12.0MM	3,100	401214	
16X8	468412*	24	6-5 1/2"	4"	-12.0MM	3,100	401514	
16X8	468170	24	8-170mm	4 1/4"	-6.0MM	3,100	401218	
16X8	468482	22	8-6 1/2"	4 1/4"	-6.0MM	3,100	401218	
16X10	460421	24	5-4 1/2"	4 1/2"	-25.4MM	3,100	401216	
16X10	460401	24	5-5 1/2"	4 1/2"	-25.4MM	3,100	401214	
16X10	460412*	24	6-5 1/2"	4 1/2"	-25.4MM	3,100	401514	
16X10	460170	23	8-170mm	4 1/4"	-32.0MM	3,100	401218	
16X10	460481	23	8-6 1/2"	4 1/4"	-32.0MM	3,100	401218	
16X12	461412	26	6-5 1/2"	4 1/2"	-51.0MM	3,100	401514	
16X12	461170	26	8-170mm	4 1/2"	-51.0MM	3,100	401218	
16X12	461481	24	8-6 1/2"	4 1/2"	-51.0MM	3,100	401218	
17X9	479452	26	5-135mm	4 1/2"	-12.0MM	2,500	401414	
17X9	479421	26	5-4 1/2"	4 1/2"	-12.0MM	2,500	401216	
17X9	479402	26	5-5 1/2"	4 1/2"	-12.0MM	2,500	401214	
17X9	479431	23	5-5"	5"	0.0MM	2,500	401216	
17X9	479462	26	6-135mm	5 1/2"	12.0MM	2,500	401414	
17X9	479412*	26	6-5 1/2"	4 1/2"	-12.0MM	2,500	401514	
17X9	479170	26	8-170mm	5"	0.0MM	3,100	401218	
17X9	479481	26	8-6 1/2"	5"	0.0MM	3,100	401218	
20X10	420481	32	8-6 1/2"	4 1/2"	-25.4MM	3,100	401218	

* Hub Centering Ring included for late Model Chevy/GMC Applications

visit us at:



OPEN 24 HRS / 7 DAYS A WEEK

MICKEY THOMPSON SIDEBITER



Tire Size	Code No.	Tire Weight	Bolt Circle	Back Spacing	Offset (mm)	Load Capacity	Replacement Cap	PRICE	F.E.T.
15X8.0	158421	.20	.5x4.5	.3.31	.30mm	.2000	.401518		\$
15X8.0	158401	.20	.5x5.5	.3.31	.30mm	.2000	.401519		
15X8.0	158411	.20	.6x5.5	.3.31	.30mm	.2000	.401517		
15X10	150421	.30	.5x4.5	.3.63	.46mm	.2500	.401518		
15X10	150401	.30	.5x5.5	.3.63	.46mm	.2500	.401519		
15X10	150411	.30	.6x5.5	.3.63	.46mm	.2500	.401517		
16X8 6x5.5 4-1/2	168412	.24	.6x5.5	.4.5	.0mm	.2500	.401517		
16X8 8x170 4-1/2	168170	.28	.8x170	.4.5	.0mm	.3100	.401520		
16X8 8x6.5 4-1/2	168482	.24	.8x6.5	.4.5	.0mm	.3200	.401520		
17X9 5x5 4-1/2	179431	.26	.5x5.0	.4.5	.12mm	.3100	.401518		
17X9 5x5.5 5	179402	.26	.5x5.5	.5	.0mm	.3100	.401519		
17X9 6X135 5-1/2	179462	.26	.6x135	.5.5	.12mm	.3100	.401517		
17X9 6X5.5 5	179412	.26	.6x5.5	.5	.0mm	.3100	.401517		
17X9 8X6.5 5	179481	.26	.8x170	.5	.0mm	.3400	.401520		
17X9 8X170 5	179170	.26	.8x6.5	.5	.0mm	.3400	.401520		

- Styled after one of the best known innovations in off-road history, Mickey Thompson's revolutionary "tread-on-the-side-wall" tire design called SideBiters®, this new wheel is built to be a heavy duty performer with an easy to clean high gloss finish and exceptional styling designed to make your Jeep, Truck, or 4x4 look great!
- Tough High Gloss Black Finish
- High Strength Low Pressure Casting
- Embossed Center Cap With M/T Logo
- Lifetime Limited Guarantee Against Structural Defects

MICKEY THOMPSON WHEEL CAPS & RING KITS

Code #	Description	PRICE
ALUMINUM CAPS		
101214CLOSED CAP\$
101215OPEN CAP
101216CLOSED CAP (FOR 5-4 1/2 B.C. & 5-5 B.C.)
101217OPEN CAP (FOR 5-4 1/2 B.C.)
101218CLOSED CAP (FOR 8-6 1/2 B.C.)
101219OPEN CAP (FOR 8-6 1/2 B.C. EXC. DANA 60)
101220LONG CLOSED CAP (FOR 8-6 1/2 B.C.)
101221SHORT CLOSED CAP (FOR 8-6 1/2 B.C.)
101222OPEN CAP (DANA 60) OLD #8167
CHROME STEEL CAPS		
301214M/T CLASSIC II CLOSED CAP (For 6-5 1/2 B.C.)
301216M/T CLASSIC II CLOSED CAP (For 5 Lug)
301218M/T CLASSIC II CLOSED CAP (For 8-6 1/2 B.C.)
301514M/T CLASSIC II CLOSED CAP (Chevy, Toyota, External Mount)
CLASSIC LOCK CAPS		
401214CLOSED CAP FOR 5 & 6 ON 5.5" B.C.
401216CLOSED CAP FOR 5 ON 4.5", 4.75" & 5" B.C.
401218CLOSED, SHORT CAP FOR 8 ON 6.5 & 17MM B.C.
401414CLOSED CAP 6-135MM
401514CLOSED EXTERNAL MOUNT CAP FOR 5 & 6 ON 5.5" B.C.
401516CLOSED EXTERNAL MOUNT CAP FOR 5 ON 4.5" B.C.

Code #	Description	PRICE
CLASSIC LOCK SINGLE RING KIT		
51150115" BLACK\$
51150215" BLUE
51150315" GOLD
51150415" RED
51150515" POLISHED
51160116" BLACK
51160216" BLUE
51160316" GOLD
51160416" RED
51160516" POLISHED
51170117" BLACK
51170217" BLUE
51170317" GOLD
51170417" RED
51170517" POLISHED
51180118" BLACK
51180218" BLUE
51180318" GOLD
51180418" RED
51180518" POLISHED
51120120" BLACK
51120220" BLUE
51120320" GOLD
51120420" RED
51120520" POLISHED

