



ROAD FORCE

RF 516 Premium Steer Highway



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R22.5/14 144/142M	.63971	.18.5	.117.2	.41.5	.8.25	.5840	.105	.6175	.105	.10.98	\$
11R22.5/16 146/143M	.63974	.18.5	.118.3	.41.5	.8.25	.6005	.120	.6610	.120	.10.98	

RF 517 Trailer



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R22.5/14 146/143M	.63978	.14	.119.1	.43.46	.8.25	.6005	.105	.6610	.105	.10.98	\$
295/75R22.5/14 144/141M	.63982	.14	.107.4	.39.92	.9	.5675	.110	.6175	.110	.11.73	
285/75R24.5/14 144/141M	.63985	.14	.114.2	.41.34	.8.25	.5675	.110	.6175	.110	.11.14	

All Position Non-Decoupling Groove.

RF 519 Closed Shoulder



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R22.5/14 144/142K	.63972	.26	.124	.41.93	.8.25	.5840	.105	.6175	.105	.10.98	\$
11R22.5/16 146/143M	.63975	.26	.125	.41.93	.8.25	.6005	.120	.6610	.120	.10.98	
11R24.5/14 146/143K	.63977	.26	.133.1	.43.78	.8.25	.6005	.105	.6610	.105	.10.98	
11R24.5/16 149/146K	.63980	.26	.134.1	.43.78	.8.25	.6610	.120	.7160	.120	.10.98	
12R22.5/18 152/149L	.63913	.19.5	.67	.42.72	.9	.7160	.135	.7820	.135	.11.81	
295/75R22.5/14 144/141K	.63981	.26	.120.3	.40.16	.9	.5675	.110	.6175	.110	.11.73	
285/75R24.5/14 144/141K	.63984	.26	.128.7	.41.57	.8.25	.5675	.110	.6175	.110	.11.14	

RF 526 Premium Steer



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
315/80R22.5 /18 154/151M	.63989	.21	.142	.42.36	.9	.7610	.120	.8270	.120	.12.28	\$
315/80R22.5/20156/150L	.63993	.21	.145.5	.42.36	.9	.7760	.120	.8818	.120	.12.28	

RF 529 Mixed Service



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
315/80R22.5 /18 154/151L	.63990	.21	.156.2	.42.6	.9	.7610	.120	.8270	.120	.12.28	\$
315/80R22.5/20 156/150L	.63994	.22.5	.156.5	.42.6	.9	.7760	.120	.8818	.120	.12.28	

RF 569

Mixed Service



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
385/65R22.5/18 158K	.63991	.21	.170	.42.44	.11.75	.9370	.120	.15.31		\$	
385/65R22.5/20 160K	.63992	.21	.172	.42.44	.11.75	.9920	.130	.15.31			

RF 616

Trailer



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R22.5/14 144/142M	.63973	.14	.104.3	.41.5	.8.25	.5840	.105	.6175	.105	.10.98	\$

RF 766

Premium Steer



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R24.5/14 146/143M	.63976	.19	.150	.43.46	.8.25	.6005	.105	.6610	.105	.10.98	\$
11R24.5/16 149/146M	.63979	.19	.121.2	.43.46	.8.25	.6610	.120	.7160	.120	.10.98	
11R22.5/16 146/143M	.63917	.18.5	.118.3	.41.5	.8.25	.6005	.120	.6610	.120	.10.98	
11R22.5/14 144/142M	.63916	.18.5	.117.2	.41.5	.8.25	.5840	.105	.6175	.105	.10.98	
12R22.5/18 152/149M	.63912	.19.5	.63.5	.42.72	.9	.7160	.135	.7820	.135	.11.81	
295/75R22.5/14 144/141M	.63995	.18.5	.53.4	.39.92	.9	.5675	.110	.6175	.110	.11.73	
295/80R22.5/16 150/147	.63908	.19.5	.136.4	.41.1	.9	.6780	.120	.7390	.120	.11.73	
295/80R22.5/18 152/149	.63910	.19.5	.139	.41.1	.9	.7160	.130	.7830	.130	.11.73	

RF 118

Chip and Cut On/Off Highway



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
10.00R20/18 149/146K	.63902	.21	.61.7	.41.5	.7.5	.6610	.135	.7160	.135	.10.94	\$
11.00R20/18 152/149K	.63903	.21.5	.70.7	.42.72	.8	.7160	.135	.8270	.135	.11.54	
12.00R20/18 154/151K	.63905	.22.0	.80.4	.44.29	.8.5	.7610	.120	.8270	.120	.12.4	
8.25R20/16 137/137K	.63920	.18.5	.98.3	.38.34	.6.5	.5070	.135	.5355	.135	.9.29	
9.00R20/16 144/142K	.63901	.19.5	.54.8	.40.12	.7	.5840	.130	.6170	.130	.10.2	
295/80R22.5/16 150/147K	.63921	.21	.136.4	.38.34	.9	.6780	.120	.7390	.120	.11.7	
295/80R22.5/18 152/149K	.63922	.21	.139	.41.1	.9	.7160	.130	.7830	.130	.11.7	
11R22.5/14 144/142L	.63918	.21	.118	.41.5	.8.3	.5840	.105	.6175	.105	.10.98	
11R22.5/16 146/143L	.63919	.21	.119	.41.5	.8.3	.6005	.120	.6610	.120	.10.98	
11R24.5/16 149/146M	.63924	.19	.121.2								

RF 539

MT-Open Shoulder DR



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
295/80R22.5/16 150/147L	.63909	.28.5	.66.4	.41.57	.9	.6780	.120	.7390	.120	.11.73	\$
295/80R22.5/18 152/149L	.63911	.28.5	.66.5	.41.57	.9	.7160	.130	.7830	.130	.11.73	

RF 909

Open Shoulder DR



Tire Size	Code No.	Tread Depth	Tire Weight	Overall Diam.	Rim Width	DUAL		SINGLE		Section Width	PRICE
						Max Load	Max PSI	Max Load	Max PSI		
11R22.5/16 146/143M	.63926	.26	.125	.41.93		.6005	.120	.6610	.120	.10.98	\$
11R24.5/14 146/143K	.63927	.26	.134.1	.43.78	.8.25	.6005	.105	.6610	.105	.10.98	
11R24.5/16 149/146K	.63928	.26	.134.1	.43.78	.8.25	.6610	.120	.7160	.120	.10.98	