



## RM185 Regional Steer



Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Space w/o Chains	Dual Loaded Radius	Rev. Per Mile	Tread Depth (32nds mm)	Buff Rad.	Buff Width	PRICE
<b>185 TUBELESS</b>															
295/75R22.5 G 144/141L	+92053	(9.0) 8.25-9.0	110	5675	6175	39.90	11.65	12.58	13.3	18.7	521	18.5	24	9.375	117
11R22.5G 144/142L	92034	(8.25) 7.5-8.25	105	5840	6175	41.42	10.79	11.65	12.5	19.4	502	18.5	24	8.500	119
11R22.5H 146/143L	92036	(8.25) 7.5-8.25	120	6005	6610	41.42	10.79	11.65	12.5	19.4	502	18.5	24	8.500	119
285/75R24.5 G 144/141L	92045	(8.25) 8.25	110	5675	6175	41.50	10.75	11.66	12.5	19.3	501	18.5	26	8.375	120
11R24.5 G 146/143L	92054	(8.25) 7.5-8.25	105	6005	6610	43.46	10.94	11.82	12.5	20.3	478	18.5	22	8.750	130
11R24.5 H 149/146L	92056	(8.25) 7.5-8.25	120	6610	7160	43.46	10.94	11.82	12.5	20.3	478	18.5	22	8.750	130
<b>185A TUBELESS</b>															
295/75R22.5 G 144/141L	97853	(9.0) 8.25-9.0	110	5675	6175	40.10	11.25	12.3	13.3	18.5	518	18.5	26	8.750	111

- Special Features**
- 18.5/32" tread depth combined with solid shoulder ribs make this tire ideally suited to regional haul and pick-up & delivery service.
  - The rib edge siping is designed to promote even wear in longer hauls.



## RM180 Long Haul Steer



Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Space w/o Chains	Dual Loaded Radius	Rev. Per Mile	Tread Depth (32nds mm)	Buff Rad.	Buff Width	PRICE
<b>TUBELESS</b>															
295/75R22.5 G 144/141L	93853	(9.0) 8.25-9.0	110	5675	6175	40.10	11.38	12.4	13.2	18.7	517	18	26	8.75	110
11R22.5 G 144/142L	93834	(8.25) 7.5-8.25	105	5840	6175	41.36	10.99	11.9	12.5	19.3	502	18	26	8.75	114
285/75R24.5 G 144/141L	93845	(8.25) 8.25	110	5675	6175	41.40	10.96	11.9	12.5	19.4	501	18	26	8.75	115
11R24.5 G 146/143L	93854	(8.25) 7.5-8.25	105	6005	6610	43.40	10.92	11.8	12.5	20.2	478	18	26	9.00	122



- Special Features**
- Decoupling grooves resist uneven shoulder wear in line haul applications.
  - Micro sipes on groove edges provide enhanced traction in wet road conditions.

## RM235 Regional Drive



Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Space w/o Chains	Dual Loaded Radius	Rev. Per Mile	Tread Depth (32nds mm)	Buff Rad.	Buff Width	PRICE
<b>TUBELESS 235</b>															
295/75R22.5 G 144/141L	+92053	(9.0) 8.25-9.0	110	5675	6175	39.90	11.65	12.58	13.3	18.7	521	18.5	24	9.375	122
11R22.5 G 144/142L	92034	(8.25) 7.5-8.25	105	5840	6175	41.42	10.79	11.65	12.5	19.4	502	18.5	24	8.500	124
11R22.5 H 146/143L	92036	(8.25) 7.5-8.25	120	6005	6610	41.42	10.79	11.65	12.5	19.4	502	18.5	24	8.500	124
285/75R24.5 G 144/141L	92045	(8.25) 8.25	110	5675	6175	41.50	10.75	11.66	12.5	19.3	501	18.5	26	8.375	126
11R24.5 G 146/143L	92054	(8.25) 7.5-8.25	105	6005	6610	43.46	10.94	11.82	12.5	20.3	478	18.5	22	8.750	131
11R24.5 H 149/146L	92056	(8.25) 7.5-8.25	120	6610	7160	43.46	10.94	11.82	12.5	20.3	478	18.5	22	8.750	131
<b>TUBELESS 235A</b>															
295/75R22.5 G 144/141L	97853	(9.0) 8.25-9.0	110	5675	6175	40.10	11.25	12.3	13.3	18.5	518	18.5	26	8.750	110

- M+S Rated**
- Special Features**
- Open shoulder lugs provide the traction needed in regional and pick-up and delivery applications.
  - High density center elements resist uneven wear.



# RM275

# Long Haul Drive



**M+S Rated**

**Special Features**

- With deep 27.5/32" tread depth and solid shoulder ribs, the RM275 is designed to deliver long tread life in highway service while the center tread lugs provide traction in wet and snow.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Rev. Loaded Radius	Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
<b>TUBELESS 275</b>																
295/75R22.5 G 144/141L	+92153	(9.0) 8.25-9.0	110	5675	6175	40.22	11.39	12.35	13.2	18.9	517	27.5	22	9.375	125	\$
11R22.5 G 144/142L	92134	(8.25) 7.5-8.25	105	5840	6175	42.06	10.84	11.71	12.5	19.7	494	27.5	22	8.875	129	
11R22.5 H 146/143L	92136	(8.25) 7.5-8.25	120	6005	6610	42.06	10.84	11.71	12.5	19.7	494	27.5	22	8.875	130	
285/75R24.5 G 144/141L	92145	(8.25) 8.25	110	5675	6175	41.85	10.71	11.61	12.5	19.7	497	27.5	22	8.875	132	
11R24.5 G 146/143L	92154	(8.25) 7.5-8.25	105	6005	6610	44.06	10.71	11.57	12.5	20.6	472	27.5	24	8.625	140	
11R24.5 H 149/146L	92156	(8.25) 7.5-8.25	120	6610	7160	44.06	10.71	11.57	12.5	20.6	472	27.5	24	8.625	141	
<b>TUBELESS 275A</b>																
295/75R22.5 G 144/141L	97953	(9.0) 8.25-9.0	110	5675	6175	40.60	11.60	12.1	13.2	19.2	512	27.5	26	8.750	120	

+ To Be Discontinued - Limited Availability



# RM160

# All Position



Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Rev. Loaded Radius	Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
<b>TUBELESS</b>																
215/75R17.5 F 135/133L	92804	(6.0) 6.0-6.75	125	4540	4805	30.20	8.31	9.01	9.3	14.2	689	16	22	7.0	62	\$
235/75R17.5 J 143/141J	92805	(6.75) 6.75-7.5	125	5675	6005	31.40	9.00	10.17	10.3	14.4	662	16	24	7.5	71	
225/70R19.5 F 125/123L	+92802	(6.75) 6.0-6.75	95	3415	3640	31.93	8.72	9.40	10.0	15.0	651	16	28	7.0	68	
245/70R19.5 G 133/131L	+92801	(7.5) 6.75-7.5	110	4300	4540	33.03	9.76	10.50	11.0	15.5	629	16	26	8.0	77	

+ To Be Discontinued - Limited Availability



**Special Features**

- This 5-rib tire is designed to perform in all positions on smaller vehicles in pick-up & delivery applications.
- The 17.5" size tires are engineered for the demanding low platform trailer fitment.

# RM190

# Directional Drive



**M+S Rated**

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Rev. Loaded Radius	Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
<b>TUBELESS</b>																
225/70R19.5 F 125/123L	92902	(6.75) 6.0-6.75	95	3415	3640	32.00	8.60	9.25	10.0	15.3	649	19	18	7.3	69	\$
245/70R19.5 G 133/131L	92901	(7.5) 6.75-7.5	110	4300	4540	33.15	9.50	10.80	11.0	15.5	627	19	22	8.0	80	



**Special Features**

- The complement to the RM160 for vehicles in pick-up & delivery applications.
- The directional tread design promotes even wear and extra traction.

# RM120

# Long Haul Trailer



**Special Features**

- Wide shoulder ribs resist scrubbing and rib edge sipes promote even wear.
- Stone ejectors enhance casing durability by helping to prevent stone drilling.

Tire Size	Code No.	Meas. Rim Width/ Approved Rim Width	PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Rev. Loaded Radius	Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
<b>TUBELESS 120</b>																
295/75R22.5 G 144/141L	+92353	(9.0) 8.25-9.0	110	5675	6175	39.35	11.54	12.52	13.2	18.5	528	12	28	9.125	109	\$
255/70R22.5 H 140/137L	92322	(7.5) 7.5-8.25	120	5070	5510	36.68	10.16	11.02	11.3	17.2	566	16	28	8.000	91	
11R22.5 G 144/142L	92334	(8.25) 7.5-8.25	105	5840	6175	41.11	10.88	11.75	12.5	19.2	505	12	24	8.500	109	
11R22.5 H 146/143L	92336	(8.25) 7.5-8.25	120	6005	6610	41.11	10.88	11.75	12.5	19.2	505	12	24	8.500	109	
285/75R24.5 G 144/141L	92345	(8.25) 8.25	110	5675	6175	40.92	10.81	11.72	12.5	19.2	508	12	24	8.625	112	
11R24.5 G 146/143L	92354	(8.25) 7.5-8.25	105	6005	6610	43.13	10.89	11.76	12.5	20.2	482	12	24	8.500	116	
11R24.5 H 149/146L	92356	(8.25) 7.5-8.25	120	6610	7160	43.13	10.89	11.76	12.5	20.2	482	12	24	8.500	116	
<b>TUBELESS 120A</b>																
295/75R22.5 G 144/141L	98153	(9.0) 8.25-9.0	110	5675	6175	39.66	11.28	12.1	13.2	18.8	524	12	26	8.750	102	

+ To Be Discontinued - Limited Availability



# RM185HH

## Regional All Position



Tire Size	Code No.	Meas. Rim Width/ Approved		PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
		Rim Width															
<b>TUBELESS</b>																	
315/80R22.5 L 157/154K	+91822	(9.0)	9.75	130	8270	9090	42.28	12.25	13.52	13.8	19.5	491	18.5	26	9.50	133	\$
315/80R22.5 J 154/151L	91838	(9.0)	9.75	120	7610	8270	42.28	12.25	13.52	13.8	19.5	491	18.5	26	9.50	133	\$

+ To Be Discontinued - Limited Availability



### Special Features

- Lateral siping enhances traction and braking ability in adverse weather conditions.
- Four-belt construction enhances performance and durability.

# RM230HH

## On/Off Road All Position



Tire Size	Code No.	Meas. Rim Width/ Approved		PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
		Rim Width															
<b>TUBELESS</b>																	
11R22.5 H 146/143K	93336	(8.25)	7.5-8.25	120	6005	6610	41.30	10.55	12.20	12.5	19.5	503	23			127	\$
315/80R22.5 L 160/154J	*93373	(9.00)	9.75	130	8270	10000	42.80	12.50	13.87	13.8	19.6	500	23			149	\$
11R24.5 H 149/146K	93356	(8.25)	7.5-8.25	120	6610	7160	43.66	11.06	12.10	12.5	20.3	476	23			134	\$

\* Availability To Be Announced



### Special Features

- Deep 23/32" tread provides extended tread life in On/Off road applications.
- The cut and chip resistant compounding is specifically designed to address mixed service requirements.

# RM300HH

## On/Off Road Drive



Tire Size	Code No.	Meas. Rim Width/ Approved		PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
		Rim Width															
<b>TUBELESS</b>																	
11R22.5 H 146/143K	93734	(8.25)	7.5-8.25	120	6005	6610	42.08	11.15	12.20	12.5	19.5	494	30			129	\$
11R24.5 H 149/146K	93756	(8.25)	7.5-8.25	120	6610	7160	44.10	11.11	12.23	12.5	20.5	472	30			139	\$



### Special Features

- Rugged 30/32" of tread provides excellent traction and durability.
- The cut and chip resistant tread compound is designed to tackle mixed service requirements.

# RM170

## All Position Pick-Up & Delivery



Tire Size	Code No.	Meas. Rim Width/ Approved		PSI	Dual Max. Load	Single Max. Load	Overall Diameter	Section Width	Loaded Width	Min. Dual Space w/o Chains	Loaded Radius	Rev. Per Mile	Tread Depth (32nds)	Buff Rad.	Buff Width	Buff Wt.	PRICE
		Rim Width															
<b>TUBELESS</b>																	
225/70R19.5 F 125/123L	95802	(6.75)	6.0-6.75	95	3415	3640	32.01	8.80	9.54	10.0	15.0	649	15	28	7.6	65	\$
225/70R19.5 G 128/126L	95803	(6.75)	6.0-6.75	110	3750	3970	32.01	8.80	9.54	10.0	15.0	649	15	28	7.6	65	\$
245/70R19.5 G 133/131L	95801	(7.5)	6.75-7.5	110	4300	4540	33.10	9.85	10.70	11.0	15.4	626	16	26	8.4	74	\$



### Special Features

- The RM170's wide tread profile and optimized footprint design delivers long, even treadwear.
- The V-shaped design of the tread grooves fight to prevent stone retention.