



# SOLIDEAL®

"THE NATURAL CHOICE"

## SOLIDEAL HAULER XD44 Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10-16.5	10	57536	8.25	75	4718	.5	31	44	86.0	\$
12-16.5	12	57537	9.75	80	6349	.5	33	44	107.0	

## SOLIDEAL LIFEMASTER SKZ Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10-16.5	10	20696	8.25	75	4718	.5	31	37	73.0	\$
12-16.5	10	20697	9.75	64	5611	.5	33	37	89.0	
31X15.5-15	8	57538							78.0	
33X15.5-16.5	14	57540	12.00	70	6944	.5		38		
14-17.5	14	57542	10.5	80	8543	.5	37	48	144.0	

**Compactor Pneumatic**

## SOLIDEAL HAULER LOADER SKS Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
23X8.5-12	6	4881	7.00	50	1819	.5	23	16	25.0	\$
27X8.5-15	6	4882	7JA	44	2480	.5	27	12	32.0	
27X10.5-15	8	57546	8.50	59	3064	.5	28	20	46.0	
31X15.5-15	8	17954	13.00	44	3726	.5	31	28	82.0	
10-16.5(30)	8		8.25	60	4134	.5	30	17	52.0	
10-16.5(30)	10		8.25	75	0	.5	30	17	0.0	
10-16.5	8	4883	8.25	55	3924	.5	31	17	54.0	
10-16.5	10	45623	8.25	75	4718	.5	31	17	54.0	
31.5X13-16.5	10	57551	9.75	70	5368	.5	31	17	67.0	
12-16.5	10		9.75	60	5357	.5	32	20	78.0	
12-16.5	10	4884	9.75	64	5611	.5	32	20	78.3	
33X15.5-16.5	14	34708	12.00	70	6944	.5	33	22	108.0	
14-17.5	10		10.5	55	6845	.5	0	48	0.0	
14-17.5	14	4885	10.5	80	8543	.5	37	30	115.0	
380/65-19.5(14.5-19.5) 12°			11.75	60	9193	.5	39	31	0.0	
15-19.5	8		11.75	40	7176	.5	0	31	0.0	
15-19.5	14	4886	11.75	80	11177	.5	40	31	146.0	
385/65-22.5(15-22.5)	12		11.75	72	12676	.5	43	31	170.0	
385/65-22.5(15-22.5)	16	57560	11.75	100	15520	.5	437	31	181.0	

**Hauler Skid Steer Loader SKS**

Still the best skid steer tire made today. All natural rubber compounding along with heavy duty construction makes. Hauler sks the best performing skid tire available. Wide wall - rim guard - extra deep tread - less void to lug ratio - 3 step tread - tubeless.

# SOLIDEAL SKS XTRA WALL

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
23X8.5-12	.6	.57561	.7.001	.32	.1411	.5	.0	.18	.0.0	.....\$
26X12-12	.10	.7454	.10.50	.64	.3593	.5	.26	.30	.43	.....
<b>NEW</b> 27X8.5-15	.6	.57563	.7.00	.44	.2480	.5	.27	.17	.30	.....
10-16.5	.8	.20188	.8.25	.60	.4134	.5	.30	.20	.64	.....
10-16.5	.10	.57565	.8.25	.75	.4718	.5	.31	.20	.50.71	.....
12-16.5	.8	.20186	.9.75	.50	.4806	.5	.33	.20	.64	.....
12-16.5	.10	.20185	.9.75	.64	.5611	.5	.32	.20	.64	.....
14-17.5	.12	.57569	.10.50	.69	.7826	.5	.36	.35	.116.84	.....

# SOLIDEAL GRIPPER

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
12-16.5	.10	.58856	.12.5	.65	.5599	.5MPH	.32.5	.23/32	.55.1	.....\$

Innovative compounding and tread design technology in our ultra competitive skid steer line. Designed and manufactured according to the highest OEM standards with full North American ply ratings. Premium natural rubber compounds for enhanced cut resistance. A proven, durable tread design for long life and extra traction.

# SOLIDEAL MPT / TRACTIONMATER R1 / DUMPER PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
<b>I3</b>										
10.5-18	.8		.9 x 18	.43	.3704	.31	.0	.31	.0.0	.....\$
10.5-18	.10	.57578	.9 x 18	.54	.4200	.31	.35	.31	.77.0	.....
12.5-18	.12	.57580	.11x18	.50	.4817	.31	.39	.28	.105.0	.....
10.5 - 20	.10	.53413	.9 x 20	.54	.4442	.31	.37	.28	.72.0	.....
12.5 - 20	.12	.41114	.11 x 20	.50	.4938	.31	.41	.30	.127.0	.....
14.5 - 20	.14	.57584	.11 x 20	.50	.5831	.31	.44	.34	.143.0	.....
405/70-20	.14	.57586	.13 x 20	.50	.8267	.25	.43	.34	.132.0	.....
405/70-24	.14	.57587	.13 x 24	.50	.8818	.25	.47	.37	.154.0	.....
<b>R1</b>										
29x12.5-15	.8	.57598	.10LB	.44	.0	.0	.0	.0	.0.0	.....
31x15.5-15	.8	.57599	.13.00	.44	.3726	.5	.32	.26	.61.0	.....
10.0/75-15.3	.8		.9 x 15.3	.44	.0	.0	.0	.28	.0.0	.....
11.5/80-15.3	.8		.9 x 15.3	.39	.3748	.25	.34	.29	.56.0	.....
33X15.5-16.5	.10	.57601	.12.00	.49	.6008	.5	.0	.29	.0.0	.....
15.5/80-24	.14	.57593	.13 x 24	.50	.9921	.25	.51	.45	.157.0	.....
<b>R4</b>										
10.0/75-15.3	.8	.20703	.9 x 15.3	.44	.0	.0	.0	.28	.51.0	.....
11.5/80-15.3	.10	.20705	.9 x 15.3	.49	.0	.0	.0	.31	.68.0	.....



# SOLIDEAL HAULER PNEUMATIC FORKLIFT

Industrial



## Hauler LT

Hauler Lt, with its natural rubber compounds, is acknowledged as the finest quality, highest performance industrial tire on the market. Hauler Lt's massive tread and wide wall rim guard give all-around protection. Hauler Lt "the original". The one every-body tries to copy is de-signed to give the longest service possible with less void to lug ratio and extra deep tread.



## Portmaster



## Halftrac

Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load Steer	Max Load Drive	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
<b>LT</b>											
5.00-8	10	4860	3.00D	143	2403	3120	6	19	11	19.0	..\$
18X7-8	18	4863	4.33R	150	4079	5302	6	19	13	26.0	
6.00-9	10	4864	4.00E	122	2910	3781	6	21	14	28.0	
6.50-10	10	4865	5.00F	111	3307	4299	6	23	14	26.0	
7.00-12	14	4867	5.00S	129	4674	6074	6	27	14	40.0	
27X10-12	24	4868	8.00G	143	9370	12180	6	27	14	71.0	
7.00-15	14	4870	5.50	129	5677	7385	6	29	16	45.0	
7.50-15	14	4871	6.00	132	6173	8025	6	0	16	45.0	
8.25-15	14	4873	6.50	114	7165	9314	6	33	9	78.0	
28X9-15(8.15-15)	14	4872	7.00	129	6393	8311	6	28	16	55.0	
2.50-15	20	4875	7.50	150	8818	11464	6	29	16	77.0	
3.00-15	20	4877	8.00	136	10747	13977	6	33	20	106.0	
28X12.5-15	24	4874	9.75	143	10196	13261	6	27	16	96.0	
32X12.1-15	24	4878	9.75	143	13228	17196	6	32	20	130.0	
10.00-20	16	4879	7.50	129	11023	13228	6	43	23	177.0	
12.00-20	20	4880	8.50	143	15102	18122	6	46	23	203.0	
<b>PORTMASTER</b>											
12.00-20	20	37915	8.50	143	15102	18122	6	45	72	222	
12.00-20	28	57609	8.50	143	15102	18122	6	45	72	224.87	
<b>SMOOTH</b>											
10.00-20	16	57611	7.50	129	11023	13228	6	43		186.0	
12.00-20	20	57612	8.50	143	15102	18122	6	45		213.0	
<b>HALFTRAC</b>											
10.00-20	16	57614	7.50	129	11023	13228	6	43	23	183.0	
12.00-20	20	57615	8.50	143	15102	18122	6	45	23	229.0	

# SOLIDEAL EXTRA DEEP PNEUMATIC FORKLIFT

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load Steer	Max Load Drive	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
5.00-8	8	4842	3.00D	118	2094	2723	6	18	9	13.0	..\$
18X7-8	16	57648	4.33R	143	3638	4729	6	18	9	18.0	
6.00-9	10	4843	4.00E	122	2910	3781	6	21	10	21.0	
21X8-9	14	4852	6.00E	129	4299	5589	6	21	14	29.0	
6.50-10	10	4844	5.00F	111	3307	4299	6	23	12	26.0	
23X9-10	16	57652	6.50F	114	5071	6592	6	23	10	42.0	
7.00-12	12	4845	5.00S	122	4541	5908	6	27	11	37.0	
23X10-12	14	17948	8.00G	118	5512	7165	6	23	10	42.0	
27X10-12	16	57654	8.00G	114	6614	8598	6	0	14	60.0	
7.00-15	14	4846	5.50	129	5677	7385	6	30	11	49.0	
7.50-15	14	4847	6.00	132	6173	8025	6	31	25	0.0	
8.25-15	14	4849	6.50	114	7165	9314	6	33	25	72.0	
28X9-15(8.15-15)	14	4848	7.00	129	6393	8311	6	28	24	57.0	
2.50-15	16	4853	7.50	118	7385	9601	6	29	28	74.0	
3.00-15	18	4854	8.00	114	10196	13261	6	32	30	105.0	
7.50-16	12	20682	6.00	114	6393	8311	6	32	27	57.0	
9.00-20	14	38949	7.00	129	9810	11773	6	41	25	103.0	
10.00-20	16	4850	7.50	129	11023	13228	6	42	25	117.0	

# SOLIDEAL GRADER G2/L2 PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
NEW 13.00-24 TL	.12	.65451								..\$
13.00-24 TG	.12	.9554	8.00TGx24	.43	.6008	.25	.50	.33	.161.0	.....
14.00-24 TG	.12	.9555	8.00TGx24	.36	.6779	.25	.52	.33	.183.0	.....
14.00-24 TG	.16	.57662	8.00TGx24	.79			.52	.33	.183.0	.....

Industrial grade compounding - extra tear resistant - outstanding casing protection from thick undertreads. Full dimension sizing - excellent bruise resistance - long wearing properties.

# SOLIDEAL BACKHOE PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
<b>F3</b>										
11L-15SL	.10	.17957	.8LBx15	.51	.2337	.31	.30	.16	.47.0	.....\$
11L-16SL	.10	.4887	.8LBx16	.51	.2469	.31	.32	.16	.50.0	.....
11L-16SL	.12	.57666	.8LBx16	.51	.3428	.31	.32	.16	.52.0	.....
14.5/75-16.1SL	.10	.17958	.W11Cx16.1	.40	.4795	.9	.37	.21	.94.0	.....
<b>R4</b>										
10.5/80-18	.10	.7455	.W9x18	.53	.2998	.19	.34	.26	.61.0	.....
12.5/80-18	.12	.7456	.W9x18	.53	.5842	.19	.38	.38	.89.0	.....
14.9-24	.12	.21548	.W13x24	.41	.6393	.25	.49	.38	.151.0	.....
16.9-24	.12	.21549	.W15Lx24	.37	.7165	.25	.51	.33	.189.0	.....
16.9-28	.12	.21551	.W15Lx28	.37	.7826	.25	.56	.42	.220.0	.....



# SOLIDEAL SLA R4

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
16.9-24	.12	.61223	.W14Lx24			A8	.50.4	.17.7		.....\$
17.5L-24	.12	.61236	.W14Lx24			A8	.48.9	.17.5		.....
19.5L-24	.12	.61238	.W16Lx24			A8	.52.3	.19.6		.....
21L-24	.12	.61240	.W18Lx24			A8	.54.4	.21		.....

Extremely low tread related vibrations. More Flexible carcass. Triple angle lugs. Rim Guard and sidewall protection. Unique Solideal three-stepped tread which breaks and removes mud.

# SOLIDEAL COMPACTOR PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
7.50-15 NHS	.14	.4859	.6.00-15	.122	.6250	.6	.31		.56.0	.....\$
8.50/90-15K	.6	.20701	.6.00G-15	.50			.30		.41.0	.....

# SOLIDEAL WHEEL LOADER PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
<b>L2</b>										
15.5-25	.12	.54122	12.00/1.3	.57	12346	.6	.50	.31	160.0	.....\$
			12.00/1.3	.32	5842	.25	.0	.31	0.0	.....
			12.00/1.3	.36	7165	.31	.0	.31	0.0	.....
17.5-25	.12	.54123	14.00/1.5	.50	13558	.6	.53	.33	192.0	.....
			14.00/1.5	.29	6393	.25	.0	.33	0.0	.....
			14.00/1.5	.32	8047	.31	.0	.33	0.0	.....
17.5-25	.16	.37329	14.00/1.5	.68	16094	.6	.0	.33	223.0	.....
			14.00/1.5	.39	7385	.25	.0	.33	0.0	.....
			14.00/1.5	.43	9370	.31	.0	.33	0.0	.....
20.5-25	.16	.37333	17.00/2.0	.50	18188	.6	.59	.38	293.0	.....
			17.00/2.0	.32	8818	.25	.0	.38	0.0	.....
			17.00/2.0	.39	12015	.31	.0	.38	0.0	.....
<b>L3</b>										
15.5-25	.12	.54125	12.00/1.3	.57	12346	.6	.0	.33	163.0	.....
			12.00/1.3	.32	5842	.25	.0	.33	0.0	.....
			12.00/1.3	.36	7165	.31	.0	.33	0.0	.....
15.5-25	.16	.54126	12.00/1.3	.79	15212	.6	.0	.33	172.0	.....
			12.00/1.3	.39	6614	.25	.0	.33	0.0	.....
			12.00/1.3	.43	8818	.31	.0	.33	0.0	.....
17.5-25	.12	.37330	14.00/1.5	.50	13561	.6	.0	.35	262.0	.....
			14.00/1.5	.29	6393	.25	.0	.35	0.0	.....
			14.00/1.5	.32	8047	.31	.0	.35	0.0	.....
17.5-25	.16	.37331	14.00/1.5	.68	16094	.6	.0	.35	0.0	.....
			14.00/1.5	.39	7385	.25	.0	.35	0.0	.....
			14.00/1.5	.43	9370	.31	.0	.35	0.0	.....
20.5-25	.16	.37334	17.00/2.0	.50	18188	.6	.59	.40	348.0	.....
			17.00/2.0	.32	8818	.25	.0	.40	0.0	.....
			17.00/2.0	.39	12015	.31	.0	.40	0.0	.....
20.5-25	.20	.54128	17.00/2.0	.64	20944	.6	.60	.40	351.0	.....
			17.00/2.0	.46	13228	.31	.0	.40	0.0	.....
23.5-25	.20	.54130	19.5/2.5	.54	24030	.6	.62	.47	483.0	.....
			19.5/2.5	.43	16094	.31	.0	.47	0.0	.....
26.5-25	.20	.54132	22.00/3.0	.50	29101	.6	.69	.50	617.0	.....
			22.00/3.0	.36	18188	.31	.0	.50	0.0	.....
26.5-25	.28		22.00/3.0	.68	34171	.6	.70	.50	0.0	.....
26.5-25	.28		22.00/3.0	.50	22046	.31	.0	.50	0.0	.....

# SOLIDEAL EXCAVATOR PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10.00-20	.16	.20700	7.50-20	.122	9348	.6	.42	.33	103.0	.....\$
11.00-20	.16	.30256	8.00-20	.122			.43	.33	132.0	.....

visit us at:



**TDWONLINE.NET**

**OPEN 24 HRS / 7 DAYS A WEEK**