

TOYO TIRES

TOYO PROXES 1

Ultra-High Performance Radial



UTQG 240 AA

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Re Mile	PRICE
235/40R18 91Y	100500	8.0-8.5-9.5	24.9	10	25.4	9.7	11.9	1356	51	817	\$
245/40R18 93Y	100580	8.0-8.5-9.5	25.6	10	25.7	9.8	12	1433	51	808	
265/40R18 XL 101Y	100510	9.0-9.5-10.5	28.7	10	26.3	10.8	12.3	1819	50	789	
295/35R18 99Y	100520	10.0-10.5-11.5	31.8	9	26.2	11.9	12.2	1709	51	793	
235/35R19 87Y	100540	8.0-8.5-9.5	24.9	10	25.6	9.7	12.1	1201	51	813	
255/35R19 XL 96Y	100590	9.5-9.0-10.0	26.7	10	26.1	10.2	12.3	1565	50	796	
255/40R19 96Y	100530	8.5-9.0-10.0	28.9	10	27.1	10.2	12.7	1565	51	767	
285/35R19 99Y	100550	9.5-10.0-11.0	31.8	9	26.9	11.5	12.6	1709	51	773	
295/30R19 XL 100Y	100560	10.0-10.5-11.0	31.3	9	26.1	12	12.3	1764	50	796	
305/30R19 XL 102Y	100570	10.5-11.0-11.5	33.1	9	26.3	12.3	12.3	1874	50	790	

TruForm Technology

- Reduces tread deformation for better uniformity. • Improves handling performance.

Multi-Compound Tread: Outside

- Engineered for cornering performance.

Multi-Compound Tread: Inside

- Engineered for braking performance.

Unique Tread Compound and Design: Rear Sizes (285 and wider)

- Improved cornering power. • Improved vehicle balance.

Interlocking Tread Blocks

- Improved directional stability in straight-away driving. • Provide stability during cornering with slanted groove closure.

Multi-Function Taper

- Obtains uniform contact pressure during cornering. • Provides a wide water channel for better hydroplaning resistance.

Silent Wall Technology

- Reduces pipe resonance, resulting in a quieter ride.

TOYO PROXES R888

Ultra-High Performance Radial



UTQG 100 AA A

Introducing Toyo's next generation D.O.T. approved competition radial, the Toyo Proxes R888. In competition, the R888's improvements in casing design and the new V-shaped tread pattern improves dry performance.

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Tread Width	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
185/60R13 80V	168280	5.0-5.5-6.5	17	6.3	7.0	21.6	7.4	9.9	992	51	961	\$
205/60R13 86V	168270	5.5-6.0-7.5	19	6.3	7.8	22.6	8.2	10.2	1168	51	921	
225/45R13 84V	169360	7.0-7.5-8.5	18	6.4	8.7	20.8	8.8	9.6	1102	51	997	
205/55R14 85V	168060	5.5-6.5-7.5	20	6.3	8.0	22.8	8.4	10.4	1135	51	911	
225/50R14 89V	168070	6.0-7.0-8.0	21	6.3	8.9	22.8	9.3	10.4	1279	51	910	
195/55R15 85V	155120	5.5-6.0-7.0	20	6.3	7.5	23.3	8.0	10.7	1135	51	891	
195/50R15 82V	160560	5.5-6.0-7.0	19	6.3	7.5	22.6	7.8	10.5	1047	51	918	
205/50ZR15 86W	168200	5.5-6.5-7.5	20	6.3	8.0	23.0	8.5	10.6	1168	51	903	
225/50ZR15 91W	160680	6.0-7.0-8.0	22	6.3	8.7	23.7	9.1	10.9	1356	51	875	
235/50ZR15 94W	162860	6.5-7.5-8.5	24	6.4	9.2	24.2	9.6	11.1	1477	51	859	
225/45ZR15 87W	168020	7.0-7.5-8.5	20	6.4	8.7	22.8	8.9	10.5	1201	51	911	
205/55ZR16 90W	168220	5.5-6.5-7.5	22	6.3	7.9	24.7	8.4	11.4	1323	51	840	
195/50ZR16 84W	168290	5.5-6.0-7.0	20	6.4	7.5	23.5	7.9	10.9	1102	51	883	
225/50ZR16 92W	168150	6.0-7.0-8.0	24	6.3	8.7	24.7	9.3	11.4	1389	51	840	
255/50ZR16 99W	168050	7.0-8.0-9.0	27	6.4	10.0	25.9	10.6	11.8	1709	51	803	
225/45ZR16 89W	168260	7.0-7.5-8.5	21	6.3	8.7	23.8	9.0	11.0	1279	51	872	
245/45R16 94W	168030	7.5-8.0-9.0	24	6.3	9.4	24.4	9.8	11.3	1477	51	850	
215/45ZR17 91W RD	168160	7.0-8.0	22	6.3	8.2	24.6	8.5	11.5	1356	50	846	
225/45ZR17 94W RD	168170	7.0-7.5-8.5	24	6.3	8.7	25.0	9.1	11.6	1477	50	832	
235/45ZR17 93W	168190	7.5-8.0-9.0	24	6.3	9.1	25.3	9.5	11.7	1433	51	821	
205/40ZR17 84W RD	168180	7.0-7.5-8.0	19	6.3	8.0	23.5	8.3	11.1	1102	50	882	
235/40ZR17 90W	156650	8.0-8.5-9.5	24	6.3	9.4	24.6	9.6	11.5	1323	51	846	
245/40ZR17 91W	168130	8.0-8.5-9.5	25	6.4	9.4	24.7	9.8	11.5	1356	51	842	
255/40ZR17 94W	168140	8.5-9.0-10.0	26	6.3	10.2	25.1	10.4	11.7	1477	51	827	
275/40ZR17 98W	168010	9.0-9.5-11.0	29	6.4	10.9	25.7	11.0	11.9	1653	51	809	
315/35ZR17 102W	168540	10.5-11.0-12.5	30	6.4	11.8	25.6	12.6	11.9	1874	51	812	
225/40ZR18 92Y RD	168210	7.5-8.0-9.0	23	6.3	8.7	25.1	8.8	11.8	1389	50	827	
235/40ZR18 91Y	168230	8.0-8.5-9.5	25	6.3	9.4	25.5	9.6	11.9	1356	51	814	
245/40ZR18 93Y	159490	8.0-8.5-9.5	26	6.3	9.8	25.7	9.8	12.0	1433	51	808	
275/40ZR18 99W	168110	9.0-9.5-11.0	29	6.4	10.9	26.7	11.0	12.4	1709	51	779	
255/35ZR18 94Y RD	160980	8.5-9.0-10.0	26	6.3	10.1	25.1	10.2	11.8	1477	50	828	
265/35ZR18 97Y RD	168240	9.0-9.5-10.5	27	6.3	10.6	25.4	10.8	11.9	1609	50	817	
275/35ZR18 99Y RD	162800	9.0-9.5-11.0	28	6.4	10.9	25.7	11.0	12.0	1709	50	809	
305/35ZR18	162810	10.0-11.0-12.0	33	6.4	12.1	26.3	12.4	12.2	1819	51	790	
285/30ZR18 97Y RD	168250	9.5-10.0-10.5	28	6.3	11.4	24.8	11.3	11.7	1609	50	836	
295/30ZR18 98Y RD	160960	10.0-10.5-11.0	29	6.3	11.8	25.1	11.8	11.8	1653	50	828	
315/30ZR18 98Y	162820	10.5-11.0-11.5	30	6.4	12.5	25.5	12.5	11.9	1653	51	814	
335/30ZR18 102Y	162830	11.5-12.0-12.5	32	6.4	13.4	26.0	13.3	12.1	1874	51	799	
235/35ZR19 87Y	162850	8.0-8.5-9.5	25	6.4	9.3	25.7	9.5	12.1	1201	51	809	
265/30R19 93Y RD	168300											
295/30ZR19 100Y RD	162840	10.0-10.5-11.0	29	6.4	11.8	26.0	11.7	12.2	1764	50	798	
305/30ZR19 102Y RD	168000	10.5-11.0-11.5	31	6.4	12.3	26.5	12.0	12.4	1874	50	784	
NEW 285/35R20 100Y	162980	9.5-10.0-11.0		6.0		27.7	11.5					
NEW 315/30R20 101Y	162990	10.5-11.0-11.5		6.0		27.6	12.5					

TOYO PROXES T1-R

Ultra-High Performance Radial



UTQG 280 AA A

The Proxes T1-R is Toyo's latest generation of ultra-high performance tire designed exclusively for high-end sport sedans and coupes. The Proxes T1-R features a refined tread design and construction that offers exceptional dry and wet handling and performance. A wide range of sizes are available in V, W and Y speed ratings.



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
195/45R14 77V	245800	6.0-6.5-7.5	15	10	20.9	7.7	9.7	908	44	992	\$
185/55R15 82V	245630	5.0-6.0-6.5	16	11	23.0	7.6	10.6	1047	44	903	
205/55R15 88V	245660	5.5-6.5-7.5	19	11	23.8	8.4	10.9	1235	44	872	
205/50R15 89V *RD	245710	5.5-6.5-7.5	18	11	23.1	8.3	10.7	1279	50	899	
195/45R15 78V	245810	6.0-6.5-7.5	16	10	22.0	7.7	10.2	937	44	946	
NEW 195/55R16 91V BW	246700	6	18	11	24.3			1356	50		
225/55ZR16 99W *RD	245690	6.0-7.0-8.0	25	11	25.6	9.1	11.8	1709	50	811	
195/50R16 84V	245740	5.5-6.0-7.0	18	11	23.6	7.8	11.0	1102	44	879	
225/50ZR16 92W	245760	6.0-7.0-8.0	21	11	24.7	9.2	11.4	1389	44	840	
205/45ZR16 87W *RD	245850	6.5-7.0-7.5	19	10	23.2	8.2	10.8	1201	50	894	
245/45ZR16 94W	245870	7.5-8.0-9.0	22	10	24.6	9.6	11.4	1477	44	844	
225/55ZR17 97Y	246130	6.0-7.0-8.0	26	11	26.6	9.0	12.2	1609	44	781	
205/50ZR17 93Y *RD	245770	5.5-6.5-7.5	21	11	25.0	8.3	11.6	1433	50	831	
215/50ZR17 91Y	245780	6.0-7.0-7.5	22	11	25.4	8.9	11.8	1356	44	819	
225/50ZR17 94Y	246500	6.0-7.0-8.0	25	10	25.9	9.0	12.0	1477	44	802	
235/50ZR17 96Y	246510	6.5-7.5-8.5	27	10	26.2	9.4	12.1	1565	44	793	
225/45ZR17 94Y *RD	245600	7.0-7.5-8.5	23	10	24.9	8.7	11.6	1477	50	834	
235/45ZR17 97Y *RD	245890	7.5-8.0-9.0	25	10	25.4	9.4	11.8	1609	50	819	
245/45ZR17 99Y *RD	245900	7.5-8.0-9.0	26	10	25.6	9.6	11.9	1709	50	811	
205/40ZR17 84W *RD	245610	7.0-7.5-8.0	19	10	23.6	8.6	11.1	1102	50	879	
215/40ZR17 87W *RD	245960	7.0-8.0-8.5	21	10	23.8	8.7	11.1	1201	50	874	
235/40ZR17 94Y *RD	245970	8.0-9.0-9.5	24	10	24.4	9.5	11.4	1477	50	852	
245/40ZR17 95Y *RD	245980	8.0-9.0-9.5	23	10	24.7	9.7	11.5	1521	50	842	
255/40ZR17 98Y *RD	245990	8.5-9.0-10.0	24	10	25.0	10.2	11.6	1653	50	831	
265/40ZR17 96Y	246000	9.0-10.0-10.5	27	11	25.3	10.6	11.7	1565	44	821	
235/50ZR18 101Y *RD	245790	6.5-7.5-8.5	27	11	27.1	9.6	12.6	1819	50	766	
215/45ZR18 93Y *RD	246520	7.0-8.0	22	10	25.7	8.1	12.0	1433	50	807	
225/45ZR18 95Y *RD	246440	7.0-8.0-8.5	23	10	25.9	8.7	12.1	1521	50	802	
NEW 235/45ZR18 98Y RD	246660	7.5-8.0-9.0	27	10.3	26.3	9.2	12.3	1653	50	789	
245/45ZR18 96Y	245910	7.5-8.0-9.0	27	11	26.6	9.5	12.4	1565	44	781	
255/45ZR18 99Y	245920	8.0-9.0-9.5	29	10	27.0	9.8	12.5	1709	44	769	
215/40ZR18 89Y *RD	246530	7.0-7.5-8.5	22	10	24.9	8.6	11.7	1279	50	835	
225/40ZR18 92Y *RD	246010	7.5-8.0-9.0	23	10	25.1	9.1	11.8	1389	50	828	
235/40ZR18 95Y *RD	246020	8.0-9.0-9.5	24	10	25.3	9.5	11.9	1521	50	821	
245/40ZR18 97Y *RD	246030	8.0-9.0-9.5	26	10	25.6	9.6	12.0	1609	50	811	
255/40ZR18 99Y *RD	246180	8.5-9.0-10.0	26	10	25.9	10.2	12.1	1709	50	801	
275/40ZR18 99Y	246190	9.0-9.5-11.0	30	10	26.5	10.8	12.3	1709	44	784	
205/35ZR18 81Y *RD	246250	7.0-7.5-8.0	18	10	23.7	8.3	11.2	1019	50	878	
215/35ZR18 84W *RD	246050	7.0-8.0-8.5	19	10	23.9	8.6	11.3	1102	50	868	
225/35ZR18 87Y *RD	246060	7.5-8.0-9.0	20	10	24.3	9.0	11.4	1201	50	857	
245/35ZR18 88Y	246070	8.0-9.0-9.5	23	11	24.8	9.6	11.6	1235	44	839	
255/35ZR18 94Y *RD	246080	8.5-9.0-10.0	25	10	25.0	10.1	11.7	1477	50	830	
265/35ZR18 97Y *RD	246090	9.0-10.0-10.5	26	10	25.4	10.5	11.9	1609	50	819	
275/35ZR18 99Y *RD	246100	9.0-10.0-11.0	27	10	25.6	10.7	11.9	1709	50	813	
285/35ZR18 101Y *RD	246260	9.5-10.0-11.0	29	10	25.7	11.2	12.0	1819	50	807	
295/35ZR18 103Y *RD	246270	10.0-10.5-11.5	31	10	26.0	11.7	12.1	1929	50	798	
225/40ZR19 93Y *RD	246210	7.5-8.0-9.0	25	10	26.1	9.0	12.3	1433	50	796	
245/40ZR19 98Y *RD	246220	8.0-9.0-9.5	26	10	26.7	9.7	12.5	1653	50	778	
NEW 255/40R19 96Y *RD	246650	8.5-9.0-10.0	29	10	27.0	10.2	12.6	1764	50	770	
275/40R19 101Y	246150	9.0-9.5-10.5	30	10	27.6	10.8	12.9	1819	44	753	
NEW 245/45R19 102Y	246710	7.5-8.0-9.0	30	10	27.8	9.4	12.9	1874	50	748	
235/35ZR19 91Y *RD	246110	8.0-8.5-9.5	22	10	25.5	9.5	12.0	1356	50	814	
245/35ZR19 93Y *RD	246290	8.0-8.5-9.5	24	10	25.8	9.6	12.2	1433	50	804	
255/35ZR19 96Y *RD	246300	8.5-9.0-10.0	25	10	26.0	10.1	12.2	1565	50	798	
275/35ZR19 100Y *RD	246310	9.0-9.5-11.0	28	10	26.6	10.6	12.5	1764	50	782	
285/35ZR19 99Y	246320	9.5-10.0-11.0	31	10	26.9	11.2	12.6	1709	44	774	
255/30ZR19 91Y *RD	246460	8.5-9.0-9.5	24	10	25.1	10.0	11.9	1356	50	828	
265/30ZR19 93Y *RD	246400	9.0-9.5-10.0	24	10	25.4	10.5	12.0	1433	50	818	
275/30ZR19 96Y *RD	246410	9.0-9.5-10.0	26	10	25.6	10.6	12.1	1565	50	812	
285/30ZR19 98Y *RD	246420	9.5-10.0-10.5	27	10	25.8	11.2	12.1	1653	50	806	
315/25ZR19 98Y *RD	246570	11.0-11.5-12.0	30	10	25.2	12.8	11.9	1653	50	824	
245/40R20 99Y *RD	246630	8.0-8.5-9.5	28	9	27.7	9.8	13.0	1709	50	749	
245/35ZR20 95Y *RD	246330	8.0-8.5-9.5	25	10	26.8	9.6	12.6	1521	50	776	
255/35ZR20 97Y *RD	246340	8.5-9.0-10.0	27	10	27.0	10.2	12.7	1609	50	769	
275/35R20 102Y *RD	246640	9.0-9.5-11.0	29	9	27.6	10.6	12.9	1874	50	754	
235/30ZR20 88Y *RD	246470	8.5	22	10	25.6	9.3	12.2	1235	50	812	
245/30ZR20 90Y *RD	246540	8.0-8.5-9.0	24	10	25.9	9.5	12.3	1323	50	801	
255/30R20 94Y *RD	246350	8.5-9.5-9.5	25	10	26.1	10.0	12.4	1389	50	796	
265/30R20 94Y *RD	246370	9.0-9.5-10.0	27	10	26.3	10.5	12.5	1477	50	789	
275/30ZR20 97Y *RD	246430	9.0-9.5-10.0	26	10	26.6	10.6	12.6	1609	50	782	
285/30ZR20 99Y *RD	246550	9.5-10.0-10.5	29	10	26.8	11.4	12.6	1709	50	776	
285/25ZR20 93Y *RD	246580	10.5	27	10	25.6	11.5	12.2	1433	50	813	

*RD = REINFORCED

TOYO PROXES T1-R

Continued

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
305/25ZR20 97Y *RD	.246380	.10.5-11.0-11.5	.29	.10	.26.0	.12.2	.12.3	.1609	.50	.799	..\$
315/25ZR20 99Y *RD	.246590	.11.0-11.5-12.0	.33	.10	.26.3	.12.6	.12.5	.1709	.50	.789
255/30ZR21 93Y *RD	.246480	.8.5-9.0-9.5	.26	.10	.27.1	.10.2	.12.9	.1433	.50	.767
285/30ZR21 100Y *RD	.246680	.9.5-10.0-10.5	.30	.10	.27.8	.11.2	.13.2	.1764	.50	.747
295/25ZR21 96Y *RD	.246490	.10.0-10.5-11.0	.30	.10	.27.0	.11.7	.12.8	.1565	.50	.770
NEW 345/25R20 104Y	.246390	.12.0-12.5-13.0	.36	.10	.26.8	.13.6	.12.6	.1984	.50	.776
255/30ZR22 95Y *RD	.246610	.8.5-9.0-9.5	.30	.10	.28.1	.10.2	.13.4	.1521	.50	.740
265/30ZR22 97Y *RD	.246670	.9.0-9.5-10.0	.30	.10	.28.4	.10.5	.13.5	.1609	.50	.732
285/25R22 95Y	.246720			.10	.27.6	.11.4				
NEW 295/25ZR22 97Y *RD	.246620	.10.0-10.5-11.0	.32	.10	.27.9	.11.5	.13.3	.1609	.50	.745

*RD = REINFORCED

TOYO PROXES R1R

Ultra-High Performance Radial



UTQG 140 AA A

Developed from year of grueling on track experience and engineered to elevated performance standards. Toyo's new Proxes R1R allows capabilities beyond normal driving limitations. An aggressive, arrowhead tread design, extra wide footprint, high-grip compound, and advanced autocross inspired casing design provide every advantage while driving hard through the corners and quickly accelerating in the straight-aways. It's extreme performance for serious street driving.

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Tread Width	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
195/55R15 85V	.170270	.5.5-6.0-7.0	.20	.8.4	.7.4	.23.5	.8.1	.10.8	.1135	.51	.883	..\$
195/50R15 82V	.170100	.5.5-6.0-7.0	.20	.8.2	.7.2	.22.8	.7.8	.10.6	.1047	.51	.910
205/50R15 86V	.170030	.5.5-6.5-7.5	.20	.8.2	.7.9	.23.0	.8.5	.10.6	.1168	.51	.903
225/45ZR15 87W	.170140	.7.0-7.5-8.5	.22	.8.1	.8.3	.23.0	.8.9	.10.6	.1201	.21	.905
205/55R16 91V	.170200	.5.5-6.5-7.5	.22	.8.6	.7.6	.24.8	.8.1	.11.4	.1356	.51	.838
205/50R16 87V	.170260	.5.5-6.5-7.5	.22	.8.6	.7.7	.24.3	.8.4	.11.2	.1201	.51	.856
225/50R16 92V	.170250	.6.0-7.0-8.0	.23	.8.8	.8.3	.24.8	.9.0	.11.4	.1389	.51	.838
205/45R16 83W	.170040	.6.5-7.0-7.5	.19	.8.2	.7.9	.23.2	.8.1	.10.8	.1074	.51	.894
225/45ZR16 89W	.170290	.7.0-7.5-8.5	.22	.8.1	.8.3	.23.9	.9.0	.11.1	.1279	.51	.871
215/45ZR17 87W	.170190	.7.0-8.0	.22	.7.9	.8.8	.24.5	.8.3	.11.4	.1201	.51	.847
NEW 225/45R17 91W	.170130	.7.0-7.5-8.5		.8.0		.25.0	.8.9				
235/45ZR17 94W	.170170	.7.5-8.0-9.0	.24	.8.2	.8.8	.25.3	.9.4	.11.8	.1477	.51	.820
245/45ZR17 95W	.170180	.7.5-8.0-9.0	.28	.8.2	.9.3	.26.0	.9.7	.12.0	.1521	.51	.799
235/40ZR17 90W	.170090	.8.0-8.5-9.5	.24	.8.2	.8.8	.24.4	.9.4	.11.4	.1323	.51	.850
245/40ZR17 91W	.170160	.8.0-8.5-9.5	.24	.8.2	.9.9	.24.7	.9.8	.11.5	.1356	.51	.840
255/40ZR17 94W	.170150	.8.5-9.0-10.0	.26	.8.2	.9.6	.25.2	.10.3	.11.7	.1477	.51	.825
275/40ZR17 98W	.170020	.9.0-9.5-11.0	.27	.8.2	.9.9	.25.6	.10.8	.11.9	.1653	.51	.811
245/35ZR17 91W XL	.170010	.8.0-8.5-9.5	.24	.8.2	.9.4	.23.8	.9.7	.11.2	.1356	.50	.872
225/40ZR18 88W	.170050	.7.5-8.0-9.0	.23	.8.2	.8.5	.25.0	.9.0	.11.7	.1235	.51	.830
245/40ZR18 93W	.170110	.8.0-8.5-9.5	.25	.8.2	.8.9	.26.0	.9.6	.12.1	.1433	.51	.800
255/35ZR18 90W	.170060	.8.5-9.0-10.0	.24	.8.2	.9.3	.25.1	.10.1	.11.8	.1323	.51	.828
265/35ZR18 93W	.170070	.9.0-9.5-10.5	.26	.8.2	.9.9	.25.4	.10.6	.11.9	.1433	.51	.817

TOYO EXTENSA H/P

Performance Radial



UTQG 360 AA

Interlocking Tread Blocks

- Slanted adjacent grooves close in cornering, creating stiffer linked blocks for directional stability and improved cornering performance.

Three Variable Pitch Design

- Block pitch pattern is distributed non-sequentially to reduce irregular shoulder wear and pattern noise.

Silent "Wall" Technology

- Thousands of vertical serrations along main groove wall disrupt the sound waves, reducing audible noise.

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
195/50R15 86V XL	.195300	.5.5-6.0-7.0	.17	.9	.22.6	.7.7	.10.5	.1168	.50	.918	..\$
P195/55R15 84V	.195310	.5.5-6.0-7.0	.17	.9	.23.3	.7.7	.10.8	.1102	.51	.890
205/45R16 87V XL	.195320	.6.5-7.0-7.5	.18	.9	.23.2	.8	.10.8	.1201	.50	.896
205/50R16 91V XL	.195330	.5.5-6.5-7.5	.18	.9	.24.1	.8.2	.11.1	.1356	.50	.864
P225/50R16 91V	.195340	.6.0-7.0-8.0	.22	.10	.24.8	.9.1	.11.4	.1367	.51	.839
P225/55R16 94V	.195350	.6.0-7.0-8.0	.22	.10	.25.6	.9	.11.7	.1477	.51	.812
205/40R17 84V XL	.195420	.7.0-7.5-8.0	.19	.9	.23.5	.8.4	.11.1	.1102	.50	.882
205/50R17 93V XL	.195370	.5.5-6.5-7.5	.21	.9	.25.1	.8.2	.11.7	.1433	.50	.828
215/45R17 91V XL	.195380	.7.0-8.0	.21	.10	.24.6	.8.2	.11.5	.1356	.50	.843
P215/55R17 93V	.195430	.6.0-7.0-7.5	.23	.10	.26.3	.8.7	.12.1	.1433	.51	.789
225/45R17 94V XL	.195390	.7.0-7.5-8.5	.22	.10	.24.9	.8.7	.11.6	.1477	.50	.835
P225/50R17 93V	.195440	.6.0-7.0-8.0	.24	.10	.25.9	.8.9	.12	.1433	.51	.802
P225/55R17 95V	.195360	.6.0-7.0-8.0	.25	.10	.26.7	.9	.12.3	.1521	.51	.778
235/45R17 97V XL	.195400	.7.5-8.0-9.0	.22	.10	.25.2	.9.1	.11.7	.1609	.50	.823
P245/45R17 95W	.195410	.7.5-8.0-9.0	.24	.10	.25.6	.9.4	.11.8	.1521	.51	.813
215/35R18 84V XL	.195470	.7.0-7.5-8.5	.19	.10	.24	.8.5	.11.3	.1102	.50	.866
225/40R18 92V XL	.195450	.7.5-8.0-9.0	.22	.10	.25.1	.8.9	.11.9	.1389	.50	.827
235/40R18 95V XL	.195460	.8.0-8.5-9.5	.23	.10	.25.4	.9.4	.11.9	.1521	.50	.817
225/35R20 90V XL	.195490	.7.5-8.0-9.0	.21	.10	.26.3	.8.9	.12.4	.1323	.50	.791
245/35R20 95V XL	.195480	.8.0-8.5-9.5	.24	.10	.26.8	.9.5	.12.6	.1521	.50	.776

TOYO PROXES 4

Ultra-High Performance Radial



UTQG 300 A A

The Proxes 4 is Toyo's new all-season ultra-high performance tire. It is designed primarily for plus-fitment applications on sport compact cars, sports sedans, and coupes. A wide range of tire sizes are available in V and W speed ratings.



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
205/55R15 92V *RD	..197320	..5.5-6.5-7.5	..20	..10	..23.9	..8.3	..11.0	..1389	..50	..868	..\$
195/50R15 86V *RD	..197290	..5.5-6.0-7.0	..17	..10	..22.8	..7.7	..10.5	..1168	..50	..911	
205/50R15 89V *RD	..197300	..5.5-6.5-7.5	..20	..10	..23.1	..8.3	..10.6	..1279	..50	..900	
225/50R15 95V *RD	..197310	..6.0-7.0-8.0	..21	..10	..23.9	..9.1	..11.0	..1521	..50	..869	
205/55R16 94V *RD	..197260	..5.5-6.5-7.5	..21	..10	..25.0	..8.4	..11.5	..1477	..50	..832	
215/55R16 97V *RD	..197270	..6.0-7.0-7.5	..22	..10	..25.4	..8.8	..11.7	..1609	..50	..818	
225/55R16 99V *RD	..197280	..6.0-7.0-8.0	..25	..10	..25.7	..9.2	..11.8	..1709	..50	..808	
195/50R16 88V *RD	..197220	..5.5-6.0-7.0	..19	..10	..23.8	..7.8	..11.0	..1235	..50	..872	
205/50R16 91V *RD	..197230	..5.5-6.5-7.5	..21	..10	..24.1	..8.3	..11.2	..1356	..50	..862	
225/50R16 96V *RD	..197240	..6.0-7.0-8.0	..23	..10	..24.9	..9.1	..11.5	..1565	..50	..835	
245/50R16 97V	..197250	..7.0-7.5-8.5	..24	..10	..25.6	..9.8	..11.7	..1609	..44	..812	
205/45ZR16 87W *RD	..197210	..6.5-7.0-7.5	..19	..10	..23.3	..8.3	..10.9	..1201	..50	..890	
205/40ZR16 83W *RD	..197200	..7.0-7.5-8.0	..18	..10	..22.5	..8.6	..10.5	..1074	..50	..924	
235/55ZR17 103W *RD	..197370	..6.5-7.5-8.5	..28	..10	..27.2	..9.6	..12.5	..1929	..50	..764	
215/50ZR17 95W *RD	..197380	..6.0-7.0-7.5	..24	..10	..25.5	..8.7	..11.8	..1521	..50	..814	
225/50ZR17 98W *RD	..197390	..6.0-7.0-8.0	..25	..10	..25.9	..9.0	..12.0	..1653	..50	..802	
235/50ZR17 100W *RD	..197400	..6.0-7.5-8.5	..27	..10	..26.3	..9.5	..12.1	..1764	..50	..791	
205/45ZR17 88W *RD	..197140	..6.5-7.0-7.5	..21	..10	..24.4	..8.3	..11.4	..1235	..50	..852	
215/45ZR17 91W *RD	..197150	..7.0-7.0-8.0	..22	..10	..24.8	..8.4	..11.5	..1356	..50	..839	
225/45ZR17 94W *RD	..197160	..7.0-7.5-8.5	..23	..10	..25.1	..8.9	..11.7	..1477	..50	..828	
235/45ZR17 97W *RD	..197170	..7.5-8.0-9.0	..24	..10	..25.4	..9.4	..11.8	..1609	..50	..819	
245/45ZR17 99W *RD	..197180	..7.5-8.0-9.0	..25	..10	..25.7	..9.8	..11.9	..1709	..50	..808	
205/40ZR17 84W *RD	..197110	..7.0-7.5-8.0	..19	..10	..23.5	..8.6	..11.1	..1102	..50	..882	
215/40ZR17 87W *RD	..197120	..7.0-7.5-8.5	..20	..10	..23.9	..8.9	..11.2	..1201	..50	..869	
245/40ZR17 95W *RD	..197410	..8.0-8.5-9.5	..23	..10	..24.7	..9.6	..11.5	..1521	..50	..840	
255/40ZR17 98W *RD	..197130	..8.5-9.0-10.0	..25	..10	..25.0	..10.3	..11.6	..1653	..50	..830	
275/40ZR17 98W	..197420	..9.0-9.5-11.0	..28	..11	..25.6	..10.9	..11.9	..1653	..44	..812	
225/50ZR18 95W	..197630	..6.0-7.0-8.0	..27	..10.0	..26.9	..9.0	..12.5	..1521	..44	..773	
235/50ZR18 101W *RD	..197430	..6.5-7.5-8.5	..28	..10	..27.2	..9.4	..12.6	..1819	..50	..762	
NEW 215/45R18 93W *RD	..197650	..7.0-8.0	..22	..10	..25.4	..8.3	..11.9	..1433	..50	..818	
225/45ZR18 95W *RD	..197360	..7.0-7.5-8.5	..23	..10	..25.9	..8.7	..12.1	..1521	..50	..802	
235/45ZR18 98W *RD	..198000	..7.5-8.0-9.0	..26	..10	..26.4	..9.3	..12.3	..1653	..50	..786	
245/45ZR18 100W *RD	..197440	..7.5-8.0-9.0	..27	..10	..26.8	..9.7	..12.4	..1764	..50	..776	
255/45ZR18 103W *RD	..197450	..8.0-8.5-9.5	..29	..10	..27.1	..10.1	..12.5	..1929	..50	..767	
215/40ZR18 89W *RD	..197070	..7.0-7.5-8.5	..21	..10	..24.8	..8.7	..11.6	..1279	..50	..839	
225/40ZR18 92W *RD	..197080	..7.5-8.0-9.0	..22	..10	..25.1	..9.1	..11.8	..1389	..50	..827	
235/40ZR18 95W *RD	..197090	..8.0-8.5-9.5	..23	..10	..25.4	..9.6	..11.9	..1521	..50	..819	
245/40ZR18 97W *RD	..197100	..8.0-8.5-9.5	..24	..10	..25.7	..9.8	..12.0	..1609	..50	..808	
255/40R18 99W *RD	..197990	..8.5-9.0-10.0	..25	..10	..26.1	..10.3	..12.1	..1709	..50	..797	
215/35ZR18 84W *RD	..197050	..7.0-7.5-8.5	..20	..10	..24.0	..8.6	..11.3	..1102	..50	..865	
275/35ZR18 99W *RD	..197460	..9.0-9.5-11.0	..27	..11	..25.4	..10.7	..11.9	..1709	..50	..817	
225/35ZR19 88W *RD	..197020	..7.5-8.0-9.0	..21	..10	..25.2	..8.9	..11.9	..1235	..50	..824	
235/35ZR19 91W *RD	..197030	..8.0-8.5-9.5	..22	..10	..25.6	..9.4	..12.1	..1356	..50	..813	
245/35ZR19 93W *RD	..197040	..8.0-8.5-9.5	..24	..10	..25.7	..9.8	..12.1	..1433	..50	..807	
NEW 255/35R19 96W *RD	..197580	..8.5-9.0-10.0	..25	..10	..26.0	..10.0	..12.2	..1565	..50	..798	
265/30ZR19 93W *RD	..197470	..9.0-9.5-10.0	..26	..10	..25.3	..10.6	..11.9	..1433	..50	..822	
295/30ZR19 100W *RD	..197480	..10.0-10.5-11.0	..30	..11	..25.9	..11.7	..12.2	..1764	..50	..801	
245/45ZR20 103W *RD	..197490	..7.5-8.0-9.0	..31	..10	..28.7	..9.6	..13.4	..1929	..50	..724	
255/45ZR20 105W *RD	..197500	..8.0-8.5-9.5	..32	..10	..29.1	..10.1	..13.5	..2039	..50	..715	
245/40ZR20 99W *RD	..197570	..8.0-8.5-9.5	..27	..10	..27.6	..9.6	..13.0	..1709	..50	..752	
275/40ZR20 106W *RD	..197510	..9.0-9.5-11.0	..33	..11	..28.7	..9.9	..13.4	..2094	..50	..725	
225/35ZR20 90W *RD	..197350	..7.5-8.0-9.0	..21	..10	..26.4	..9.0	..12.5	..1323	..50	..786	
245/35ZR20 95W *RD	..197330	..8.0-8.5-9.5	..26	..10	..26.8	..9.6	..12.6	..1521	..50	..776	
255/35ZR20 97W *RD	..197340	..8.5-9.0-10.0	..27	..10	..27.0	..10.2	..12.7	..1609	..50	..768	
275/35ZR20 102W *RD	..197590	..9.0-9.5-11.0	..30	..11	..27.5	..10.7	..12.9	..1874	..50	..756	
235/30R20 88W RD	..198020	..8.5	..25	..10	..25.7	..9.4					
NEW 215/30ZR20 82W *RD	..197520	..7.5	..20	..10	..25.1	..8.5	..12.0	..1047	..50	..827	
255/30ZR20 92W *RD	..197530	..8.5-9.0-9.5	..26	..10	..26.1	..10.0	..12.4	..1389	..50	..797	
295/30ZR20 101W *RD	..197540	..10.0-10.5-11.0	..31	..11	..26.9	..11.7	..12.7	..1819	..50	..771	
295/25ZR20 95W *RD	..197550	..10.0-10.5-11.0	..29	..11	..26.0	..11.6	..12.3	..1521	..50	..799	
255/35ZR22 99W *RD	..197810	..8.5-9.0-10.0	..30	..10	..29.1	..10.0	..13.8	..1709	..50	..715	
235/30ZR22 90W *RD	..197820	..8.5	..25	..10	..27.8	..9.5	..13.3	..1323	..50	..747	
NEW 245/30ZR22 92W *RD	..197610	..8.0-8.5-9.0	..28	..10	..28.0	..9.4	..13.3	..1389	..50	..743	
255/30R22 95W *RD	..198010	..8.5-9.0-9.5	..29	..10	..28.1	..9.8	..13.4	..1521	..50	..738	
265/30ZR22 97W *RD	..197830	..9.0-9.5-10.0	..30	..10	..28.3	..10.4	..13.5	..1609	..50	..734	
285/30ZR22 101W *RD	..197840	..9.5-10.0-10.5	..32	..11	..28.8	..11.2	..13.7	..1819	..50	..721	
305/25ZR22 99W *RD	..197850	..10.5-11.0-11.5	..33	..11	..28.0	..12.0	..13.4	..1709	..50	..741	
255/30ZR24 97W *RD	..197910	..8.5-9.0-9.5	..32	..10	..30.0	..10.0	..14.4	..1609	..50	..692	
NEW 265/25ZR24 93W	..198030	..9.5	..31	..11	..29.3	..10.3	..14.1	..1433	..50		
275/25ZR24 96W *RD	..197940	..10.0	..32	..11	..29.5	..10.6	..14.1	..1565	..50	..704	
275/25R26 98V *RD	..197950	..10.0	..33	..10	..31.4	..10.7	..15.1	..1653	..50	..661	
275/25ZR28 99W *RD	..197960	..10.0	..37	..10	..33.3	..10.7	..16.1	..1709	..50	..624	
NEW 265/25R30 99W	..197970										

*RD = REINFORCED

TOYO PROXES TQ

Performance Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
P225/50R16	172020	7.0-8.0-9.0	28	6	26.1	10.4	11.9	1687	44	796	\$
P275/45R16 LL	172070	8.5-9.0-10.5	27	6	25.8	10.8	11.8	1477	44	806	
P275/40R17 LL	172010	9.0-9.5-11.0	28	6	25.8	11	11.9	1433	44	805	
P315/35R17 LL	172030	10.5-11.0-12.5	31	6	25.6	12.6	11.8	1433	44	813	
P345/40R17 LL	172050	10.5-11.0-12.5	31	6	25.6	12.6	11.8	1433	44	813	
P315/35R18 LL	172060	10.5-11.0-12.5	31	6	26.6	12.5	12.4	1521	44	780	

The brand new Toyo Proxes TQ D.O.T. Approved Drag Radial keeps the power to the ground on high horsepower muscle cars and street machines.

A New drag radial compound, strengthened radial construction, and optimized tread design work together to provide superior grip, straight-line performance, and high-speed stability as your power down the trak, yet provides low noise as your drive home.

TOYO PROXES ST II

Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
NEW 265/70R16 112V	244010										\$
NEW 275/60R16 109V	244020										
235/65R17 104V	244030	6.5-7.0-8.5	30	11.0	29.0	9.3	13.2	1984	51	717	
255/60R17 110V XL	244060	7.0-7.5-9.0	34	11.0	29.0	10.1	13.2	2337	50	717	
275/60R17 110V	244040	8.5-8.0-9.5	37	11.0	29.9	10.8	13.5	2337	51	694	
285/60R17 114V	244050	8.0-8.5-10.0	39	11.0	30.4	11.4	13.7	2601	51	684	
225/55R17 97V	244070	6.0-7.0-8.0	28	11.0	26.7	9.1	12.3	1609	51	777	
275/55R17 109V	244080	7.5-8.5-9.5	35	11.0	28.9	10.9	13.1	2271	51	720	
255/60R18 112V XL	244090	7.0-7.5-9.0	36	11.0	30.0	9.9	13.7	2469	50	693	
285/60R18 116V	244100	8.0-8.5-10.0	40	11.3	31.3	11.3	14.2	2756	51	663	
255/55R18 109V XL	244110	7.0-8.0-9.0	34	11.0	29.0	10.2	13.3	2271	50	717	
255/50R18 106V XL	244130	7.0-8.0-9.0	33	11.0	25.6	10.2	11.9	2094	50	813	
255/45R18 99V	244150	8.0-8.5-9.5	29	10.0	27.0	9.8	12.5	1709	51	769	
295/45R18 108V	244160	9.5-10.0-11.0	34	11.0	28.3	11.4	13.0	2205	51	733	
255/55R19 111V XL	244170	7.0-8.0-9.0	36	11.0	30.0	10.3	13.8	2403	50	693	
255/50R19 103V	244180	7.0-8.0-9.0	34	11.0	29.1	10.2	13.4	1929	51	715	
275/45R19 108Y XL	244190	8.0-8.5-10.5	32	10.0	28.7	10.7	13.3	2205	50	724	
275/55R20 117V XL	244210	7.5-8.5-9.5	43	11.0	31.8	10.9	14.6	2833	50	653	
245/50R20 102V	244220	7.0-7.5-8.5	36	11.0	29.7	10.0	13.8	1874	51	698	
255/50R20 109V XL	244230	7.0-8.0-9.0	38	11.0	30.0	10.2	13.9	2271	50	692	
265/50R20 111V XL	244240	8.0-8.5-9.5	39	11.0	30.4	10.8	14.1	2403	50	683	
285/50R20 116V XL	244250	8.0-9.0-10.0	43	11.0	31.2	11.4	14.4	2756	50	665	
305/50R20 120V XL	244260	8.5-9.5-11.0	47	12.0	32.0	12.1	14.7	3086	50	649	
255/45R20 105V XL	244270	8.0-8.5-9.5	33	10.0	29.0	9.9	13.5	2039	50	716	
265/45R20 108V XL	244280	8.5-9.0-10.0	35	11.0	29.4	10.2	13.7	2205	50	707	
275/45R20 110V XL	244290	8.5-9.0-10.5	39	11.0	29.7	10.6	13.8	2337	50	700	
295/45R20 114V XL	244300	9.5-10.0-11.0	40	11.0	30.4	11.6	14.1	2601	50	683	
255/40R20 101V XL	244310	8.5-9.0-10.0	33	10.0	28.0	10.0	13.1	1819	50	741	
275/40R20 106W XL	244320	9.0-9.5-11.0	34	11.0	28.6	10.7	13.4	2094	50	725	
295/40R20 106V	244330	10.0-10.5-11.5	39	11.0	29.3	11.7	13.6	2094	51	710	
NEW 315/35R20 110W	244540	10.5-11.0-12.5	37	11.0	28.6	12.2	13.4	2337	50	726	
NEW LT285/50R22/10 121H	244530	8.0-9.0-10.0	57	13	33.1	11.2	15.3	3195			
265/45R22 109V XL	244360	8.5-9.0-10.0	36	11.0	31.4	10.3	14.7	2271	50	661	
285/45R22 114V XL	244370	9.0-9.5-10.5	42	11.0	32.0	11.1	14.9	2601	50	648	
305/45R22 118V XL	244380	9.5-10.0-11.5	44	11.0	32.8	11.8	15.2	2910	50	634	
265/40R22 106V XL	244390	9.0-9.5-10.5	37	11.0	30.3	10.5	14.2	2094	50	686	
285/40R22 110V XL	244500	9.5-10.0-11.0	41	11.0	31.0	11.1	14.5	2337	50	669	
305/40R22 114V XL	244510	10.0-11.0-12.0	44	11.0	31.6	12.1	14.7	2601	50	657	
265/35R22 102W XL	244410	9.0-9.5-10.5	33	11.0	29.3	10.5	13.8	1874	50	709	
285/35R22 106W XL	244420	9.5-10.0-11.0	37	11.0	29.8	11.2	14.0	2094	50	698	
305/40R23 115V XL	244440	10.0-11.0-12.0	44	11.0	32.5	12.1	15.2	2679	50	639	
285/40R24 112V XL	244470	9.5-10.0-11.0	43	11.0	32.9	11.7	15.5	2469	50	631	
305/35R24 112V XL	244480	10.0-11.0-12.0	44	11.0	32.4	12.1	15.3	2469	50	640	
295/30R24 105V XL	244490	10.0-10.5-11.0	39	11.0	31.0	11.1	14.7	2039	50	670	
305/30R26 109V XL	244520	10.5-11.0-11.5	46	11.0	33.2	12.1	15.8	2271	50	625	

The Proxes ST II is Toyo's newest high performance tire created to meet the demands of plus-sized applications, by providing a smooth stable ride and height, luxurious image.

Wet And Dry Performance

- Computer optimized, unidirectional, all-season tread design.
- Continuous center contact area with optimized water evacuation channels.
- Cap/base tread compound.

All-Season Performance

- Computer-optimized, unidirectional, all-season tread design.
- Cap/base compound.
- M&S Rated

Steering Response

- Specially engineered polyester casing.
- High-ply turn-up construction.
- High bead filler.
- Two wide, high-tensile steel belts.

Quiet, Stable Ride

- Toyo's "Silent Wall" technology reduces pipe resonance for a quiet ride.
- Five variable-pitch shoulder design reduces pattern noise.
- Jointless bead wire.
- Jointless cap ply (construction may vary by size).

Durability and Tread Life

- Linear grooving on the tapered edge of the center blocks lowers pressure on the block edge for better wear and handling.
- Multi-wave sipes in the shoulder block help minimize heel and toe wear.
- Rim protector.

Appearance:

- Stylish, unidirectional, all-season tread with sporty design accents.
- Computer optimized low profile design.

TOYO PROXES RA-1

D.O.T. Approved Competition Radial



The Toyo® Proxes RA-1, a DOT-approved competition tire designed specifically for improved touring racing and autocross, features all the high-tech components to provide you with an uncommon competitive advantage. It's a proven winner.

From its aggressive directional tread design to its steel wire-reinforced sidewalls, the purpose is clear—to maintain your winning edge.

At its full tread depth (8/32 inch) the RA-1 provides wet traction, but shave it to 4/32 inch and hang on as your dry lap times drop!

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
205/60R13 86V	236700	5.5-6.0-7.5	20	8	22.7	8.2	10.4	1158	44	.970	..\$
205/55R14 85V	236870	5.5-6.5-7.5	21	8	22.9	8.4	10.0	1135	44	.918	..
225/50R14 89V	236900	6.0-7.0-8.0	23	8	22.9	8.9	10.5	1279	44	.918	..
205/50ZR15	236840	5.5-6.5-7.5	20	8	23.1	8.4	10.6	1135	44	.917	..
225/50ZR15	236830	6.0-7.0-8.0	23	8	23.9	9.2	10.9	1323	44	.886	..
225/45ZR15	236970	7.0-7.5-8.5	23	8	22.9	9.0	10.6	1201	44	.908	..
225/50ZR16	236890	6.0-7.0-8.0	23	8	24.9	9.2	11.2	1390	44	.853	..
P255/50ZR16	236880	7.0-8.0-9.0	27	8	26.1	10.4	11.7	1687	44	.815	..
245/45ZR16	236800	7.5-8.0-9.0	25	8	24.7	9.6	11.2	1477	44	.861	..
255/40ZR17	236770	8.5-9.0-10.0	26	8	25.0	10.4	11.7	1477	44	.828	..
275/40ZR17	236780	9.0-9.5-11	29	8	25.7	10.9	11.9	1653	44	.812	..

*RD = REINFORCED



VERSADO LXII

Premium Luxury Passenger Radial



UTQG
H/V RATED - 400 AA
W/Y RATED - 360 AA

Mile Treadwear Limited Warranty

H-Rated 60,000 Miles

V-Rated 50,000 Miles

V and Y Rated 40,000 Miles

Asymmetric, Non-Directional Tread Design

- Enables cross rotation to reduce irregular wear.

Larger Contact Patch On Outside Tread

- More Tread to the ground increases lateral stiffness and traction.

Higher Sipe Density On Inside Tread

- More Biting edges for increased traction in the snow.

Silent Wall Technology

- Reduces pipe resonance, resulting in a quieter ride

Multi-Wave Sipes

- Minimize irregular wear for a smooth, quiet ride.
- Increase all-season traction.

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	UTQG	PRICE
195/60R15 88H	112280	5.5-6.0-7.0	19.6	10	24.2	7.8	11.1	1235	51	.858	400 AA	..\$
195/60R15 88V	112290	5.5-6.0-7.0	19.6	10	24.2	7.8	11.1	1235	51	.858	400 AA	..
195/65R15 91H	112160	5.5-6.0-7.0	20.9	10	24.2	7.7	11.4	1356	51	.832	400 AA	..
205/65R15 94H	112250	5.5-6.0-7.5	22.9	10	25.5	8	11.6	1477	51	.816	400 AA	..
205/55R16 91H	112510	5.5-6.5-7.5	21.4	10	24.8	8.3	11.4	1356	51	.836	400 AA	..
205/55R16 91V	112090	5.5-6.5-7.5	21.4	10	24.9	8.3	11.5	1356	51	.835	400 AA	..
205/60R16 92H	112120	5.5-6.0-7.5	21.8	10	25.6	8.2	11.8	1389	51	.811	400 AA	..
205/60R16 92V	112130	5.5-6.0-7.5	21.8	10	25.6	8.2	11.8	1389	51	.811	400 AA	..
205/65R16 95H	112420	5.5-6.0-7.5	22.7	10	26.3	8.1	12	1521	51	.789	400 AA	..
215/50R16 90V	112430	6.0-7.0-7.5	21.7	10	24.3	8.7	11.2	1323	51	.855	400 AA	..
215/55R16 93H	112100	6.0-7.0-7.5	22.7	10	25.2	8.8	11.6	1433	51	.823	400 AA	..
215/60R16 95V	112110	6.0-6.5-7.5	24	10	26	8.6	11.9	1521	51	.798	400 AA	..
225/50R16 92V	112390	6.0-7.0-8.0	22.3	10	24.8	9	11.4	1389	51	.839	400 AA	..
225/55R16 95V	112220	6.0-7.0-8.0	25.1	10	25.7	9.1	11.8	1521	51	.809	400 AA	..
225/60R16 98H	112490	6.0-6.5-8.0	27	11	26.5	9	12.1	1653	51	.783	400 AA	..
225/65R16 100H	112170	6.0-6.5-8.0	29.2	10	27.5	9	12.5	1764	51	.756	400 AA	..
235/60R16 100H	112310	6.5-7.0-8.5	28.2	11	27	9.5	12.3	1764	51	.769	400 AA	..
205/50R17 93V XL	112470	5.5-6.5-7.5	21.4	10	25.1	8.2	11.7	1433	50	.827	400 AA	..
215/50R17 95V XL	112460	6.0-7.0-7.5	24.5	10	25.5	8.6	11.8	1521	50	.814	400 AA	..
215/55R17 94V	112180	6.0-7.0-7.5	26	10	26.3	8.8	12.1	1477	51	.791	400 AA	..
215/60R17 96H	112270	6.0-6.5-7.5	26.2	10	27.1	8.5	12.4	1565	51	.766	400 AA	..
225/45R17 94V XL	112350	7.0-7.5-8.5	23.8	10	25	8.8	11.6	1477	50	.832	400 AA	..
235/45R17 94W	112140	7.5-(8.0)-9.0	24	10	25.4	9.3	11.8	1477	51	.819	400 AA	..
225/50R17 94V	112330	6.0-7.0-8.0	25.1	10	26	8.9	12	1477	51	.800	400 AA	..
225/50R17 94W	112480	6.0-7.0-8.0	25.6	10	25.9	8.9	12	1477	51	.802	360 AA	..
225/55R17 97H	112060	6.0-7.0-8.0	27.3	10	26.7	9	12.3	1609	51	.777	400 AA	..
225/55R17 97V	112070	6.0-7.0-8.0	27.3	10	26.7	9	12.3	1609	51	.777	400 AA	..
225/60R17 99H	112240	6.0-6.5-8.0	28.1	11	27.5	8.9	12.6	1709	51	.754	400 AA	..
235/50R17 96V	112230	6.5-7.5-8.5	27.1	10	26.3	9.3	12.1	1565	51	.790	400 AA	..
235/55R17 99H	112200	6.5-7.5-8.5	27.8	10	27.1	9.6	12.4	1709	51	.766	400 AA	..
245/45R17 99V XL	112410	7.5-8.0-9.0	26.5	10	25.6	9.4	11.9	1709	50	.811	400 AA	..
245/50R17 99V	112260	7.0-7.5-8.5	30.1	10	26.6	9.7	12.3	1709	51	.780	400 AA	..
255/45R17 98V	112360	8.0-8.5-9.5	29.5	11	26	10	12	1653	51	.798	400 AA	..
235/40R18 95Y XL	112370	8.0-8.5-9.5	23.8	10	25.3	9.5	11.9	1521	50	.820	360 AA	..
235/45R18 94V	112450	7.5-8.0-9.0	26.5	10	26.4	9.3	12.3	1477	51	.788	400 AA	..
245/45R18 96V	112150	7.5-(8.0)-9.0	28	10	26.6	9.4	12.4	1565	51	.781	400 AA	..
235/50R18 97V	112300	6.5-7.5-8.5	28.2	10	27.2	9.5	12.6	1609	51	.764	400 AA	..
235/55R18 100V	112210	6.5-7.5-8.5	29.3	10	28.1	9.6	12.9	1764	51	.739	400 AA	..
245/40R18 93V	112340	8.0-8.5-9.5	25.6	10	25.7	9.5	12	1433	51	.808	400 AA	..
245/50R18 100V	112500	7.0-7.5-8.5	31.8	10	27.6	9.8	12.7	1764	51	.753	400 AA	..
255/45R18 103V XL	112380	8.0-8.5-9.5	28.9	11	27	10	12.5	1929	50	.770	400 AA	..
275/35R18 95V	112440	9.0-9.5-11.0	27.3	11	25.6	10.7	12	1521	51	.800	400 AA	..



**S/T SPEED-RATED
UTQG 440 A B**

**H/V SPEED-RATED
UTQG 440 A A**

**50,000 Mile Treadwear
Limited Warranty**

- All season Luxury Performance**
- Designed Specifically for Crossovers
- Exceptionally Quite, Smooth, and Comfortable Ride**
- All-New, Low Rolling-Resistance**
- Fuel-Efficient Compound
 - Improved Tread Pressure
 - Distribution to enhance Handling and Stability
- S, T, H and V Speed-rated sizes available**

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	PRICE
P215/65R17 98T	120000	6.0(6.5)-7.5	26	10	28	8.6	12.8	1653	44	742	\$
225/65R17 102H	120010	6.0(6.5)-8.0	28	10	28.5	8.8	13	1874	51	729	
NEW 235/65R17 104H	120260	6.5(7.0)-8.5	30	11	29.1	9.3	13.2	1984	51	715	
235/55R17 99H	120060	6.5(7.5)-8.5	27	10	27.1	9.6	12.4	1709	51	767	
235/60R17 102T	120030	6.5(7.0)-8.5	28	10	28.1	9.3	12.8	1874	44	740	
235/65R17 108V XL	120020	6.5(7.0)-8.5	31	11	29	9.4	13.2	2205	50	716	
255/60R17 106V	120040	7.0(7.5)-9.0	33	11	29.1	10.3	13.2	2094	51	715	
215/55R18 95T	120120	6.0(7.0)-7.5	25	10	27.3	8.8	12.6	1521	44	760	
225/55R18 98V	120130	6.0(7.0)-8.0	26	10	27.8	9	12.8	1653	51	747	
235/50R18 97V	120160	6.5(7.5)-8.5	26	10	27.3	9.3	12.6	1609	51	760	
235/55R18 100V	120140	6.5(7.5)-8.5	27	10	28.2	9.4	13	1764	51	735	
235/60R18 107V XL	120090	6.5(7.0)-8.5	31	10	29.1	9.4	13.3	2149	50	715	
235/65R18 106T	120070	6.5(7.0)-8.5	31	11	30	9.3	13.7	2094	44	692	
245/60R18 105H	120100	7.0(8.5)	33	11	29.7	9.5	13.6	2039	51	700	
255/55R18 109V XL	120150	7.0(8.0)-9.0	34	11	28.9	10.2	13.3	2271	50	718	
P255/65R18 109S	120080	7.0(7.5)-9.0	36	11	31.1	10	14.1	2271	44	669	
265/60R18 110V	120110	7.5(8.0)-9.5	37	11	30.5	10.6	13.9	2337	51	681	
235/55R19 105V XL	120180	6.5(7.5)-8.5	31	10	29.2	9.5	13.5	2039	50	711	
P245/55R19 103T	120190	7.0(7.5)-8.5	33	10	29.6	9.7	13.6	1929	44	701	
NEW 235/50R19 99H	120270	6.5(7.5)-8.5	28	10	28.5	9.4	13.2	1709	51	729	
255/50R19 107V XL	120250	7.0(8.0)-9.0	34	11	29.1	10.3	13.4	2149	50	714	
P255/60R19 108H	120170	7.0(7.5)-9.0	37	11	31	10.2	14.2	2205	51	669	
265/50R19 110V XL	120210	7.5(8.5)-9.5	36	11	29.4	10.8	13.6	2337	50	706	
275/55R19 111V	120200	7.5(8.5)-9.5	39	11	30.9	11	14.1	2403	51	673	
P235/55R20 102T	120220	6.5(7.5)-8.5	32	10	30.2	9.6	14	1874	44	688	
P245/50R20 102V	120230	7.0(7.5)-8.5	35	10	29.7	9.8	13.8	1874	51	700	
NEW 265/50R20 107V	120240	7.5(8.5)-9.5	37	11	30.5	10.8	14.1	2149	51	681	

COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222



BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-283-0416 • Fax 503-240-3342
Toll Free: 1-866-977-8473

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78218
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

PHOENIX

601 South 65th Avenue, Suite 6
Phoenix, AZ 85043
Local 623-474-4660 • Fax 623-474-4661
Toll Free: 1-855-825-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO/MICHIGAN

14801 TR 212
Findlay, OH 45840
Local 419-425-6508 • Fax 419-425-6514
Toll Free: 1-877-309-1972

TOYO EXTENSA A/S

Passenger Radial



Symmetric, Non-Directional Tread Design

- Enables cross rotation to reduce irregular wear.
- Improves all-season traction and tire life.

Optimized Center Block Arrangement

- Variable-pitch angles on center blocks provide good road contact for increased ride comfort.

Four Wide Circumferential Grooves and Variable Pitch Channels

- Evacuate water to improve wet traction.

Shoulder Rib

- Connects shoulder blocks to minimize irregular wear.
- Increases stability.

Multi-Wave Sipes

- Minimize irregular wear for longer life and smooth, quiet ride.
- Increase all-season traction.

Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	UTQG	PRICE
WHITEWALL												
P185/75R14 89S	147300	4.5-5.0-6.0	.19	11.5	25.0	7.1	11.3	1290	44	832	.620 A B	\$
P195/75R14 92S	147310	5.0-5.5-6.5	.19	11.6	25.5	7.6	11.5	1400	44	814	.620 A B	
P205/75R15 97S	147420	5.0-5.5-7.0	.24	11.7	27.1	7.8	12.2	1598	44	766	.620 A B	
P215/75R15 100S	147430	5.5-6.0-7.0	.25	11.8	27.6	8.4	12.4	1742	44	751	.620 A B	
P235/75R15 105S	147450	6.0-6.5-8.0	.28	12.1	28.9	9.1	12.9	2028	44	720	.620 A B	
P205/70R15 95S	147460	5.0-6.0-7.0	.23	11.7	26.3	8.2	11.9	1499	44	791	.620 A B	
215/70R15 98T	147470	5.5-6.5-7.0	.24	11.8	26.8	8.7	12.1	1653	44	776	.620 A B	
P225/70R15 100T	147480	6.0-6.5-7.5	.26	12.0	27.3	9.0	12.3	1753	44	760	.620 A B	
BLACKWALL												
P155/80R13 79S	147270	4.0-4.5-5.0	.13	10.1	22.8	6.1	10.3	959	44	911	.620 A B	
P175/70R13 82T	147280	4.5-5.0-6.0	.16	11.3	22.6	6.8	10.2	1036	44	920	.620 A B	
P185/70R13 85S	147290	4.5-5.5-6.0	.17	11.5	23.2	7.4	10.5	1135	44	896	.620 A B	
P205/75R14 95S	147320	5.0-5.5-7.0	.22	11.7	26.1	7.8	11.7	1532	44	796	.620 A B	
P215/75R14 98S	147330	5.5-6.0-7.0	.24	12.0	26.7	8.3	12.0	1664	44	778	.620 A B	
P185/70R14 87T	147340	4.5-5.5-6.0	.17	11.5	24.2	7.5	11.0	1201	44	859	.620 A B	
P195/70R14 90T	147350	5.0-6.0-6.5	.19	11.6	24.8	7.9	11.2	1312	44	839	.620 A B	
P205/70R14 93T	147360	5.0-6.0-7.0	.22	11.7	25.2	8.3	11.4	1433	44	823	.620 A B	
P215/70R14 96T	147370	5.5-6.5-7.0	.23	12.0	25.8	8.8						
P175/65R14 81T	147380	5.0-6.0	.16	11.3	22.9	6.9	10.5	1019	44	908	.620 A B	
185/65R14 86H	147390	5.0-5.5-6.5	.16	10.1	23.5	7.2	10.7	1168	51	885	.360 A A	
185/65R14 85T	147710	5.0-5.5-6.5	.18	11.0	23.4	7.3	10.7	1124	44	887	.620 A B	
P185/60R14 82H	147400	5.0-5.5-6.5	.17	10.0	22.8	7.3	10.4	1047	51	913		
195/60R14 86H	147410	4.5-5.5-6.0	.17	10.2	23.2	7.7	10.6	1168	51	896	.360 A A	
P225/75R15 102S	147440	6.0-6.0-7.5	.26	12.0	28.3	8.6	12.7	1874	44	734	.620 A B	
P185/65R15 86T	147490	5.0-5.5-6.5	.19	11.5	24.4	7.3	11.2	1168	44	851	.620 A B	
185/65R15 88H	147500	5.0-5.5-6.5	.18	10.1	24.4	7.3	11.2	1235	51	851	.360 A A	
P195/65R15 89T	147510	5.5-6.0-7.0	.19	11.6	24.9	7.8	11.4	1279	44	833	.620 A B	
P205/65R15 92T	147520	5.5-6.0-7.5	.21	11.7	25.4	7.9	11.6	1400	44	817	.620 A B	
P215/65R15 95T	147530	6.0-6.5-7.5	.23	11.8	25.9	8.7	11.8	1510	44	802	.620 A B	
P185/60R15 84T	147540	5.0-5.5-6.5	.18	11.2	23.7	7.4	10.9	1102	44	878	.620 A B	
P195/60R15 87T	147550	5.5-6.0-7.0	.19	11.3	24.2	7.7	11.1	1190	44	859	.620 A B	
P205/60R15 90T	147560	5.5-6.0-7.5	.20	11.5	24.6	8.1	11.3	1301	44	843	.620 A B	
P215/60R15 93H	147570	6.0-6.5-7.5	.22	10.5	25.1	8.6	11.4	1411	51	828	.360 A A	
205/50R15 86H	147590	5.5-6.5-7.5	.21	10.0	23.0	8.3	10.6	1168	51	903		
225/60R15 96H	147580	6.0-6.5-8.0	.24	10.6	25.6	8.9	11.6	1565	51	813	.360 A A	
P205/65R16 94T	147600	5.5-6.0-7.5	.24	11.7	26.3	7.9	12.0	1477	44	789	.620 A B	
215/65R16 98T	147610	6.0-6.5-7.5	.24	11.8	26.9	8.7	12.3	1653	44	772	.620 A B	
235/65R16 103T	147620	6.5-7.0-8.5	.28	11.8	27.9	9.4	12.6	1929	44	744	.620 A B	
P205/60R16 91T	147630	5.5-6.0-7.5	.21	11.5	25.7	8.1	11.8	1356	44	809	.620 A B	
P215/60R16 94T	147250	6.0-6.5-7.5	.24	11.6	26.0	8.6	11.9	1477	44	798	.620 A B	
P225/60R16 97T	147260	6.0-6.5-8.0	.24	11.7	26.6	9.1	12.1	1609	44	782	.620 A B	
P235/60R16 99T	147640	6.5-7.0-8.5	.28	12.0	27.0	9.3	12.3	1709	44	769		
205/55R16 91H	147650	5.5-6.5-7.5	.22	10.0	24.8	8.3	11.4	1356	51	838	.360 A A	
P225/55R16 94T	147660	6.0-7.0-8.0	.26	11.2	25.7	9.1	11.8	1477	44	809	.620 A B	
P215/60R17 95T	147670	6.0-6.5-7.5	.27	11.6	27.1	8.6	12.4	1521	44	766		
P225/60R17 98T	147680	6.0-6.5-8.0	.28	12.0	27.6	8.9	12.6	1653	44	754		
P225/55R17 95T	147690	6.0-7.0-8.0	.27	11.2	26.7	9.1	12.3	1521	44	778		
P215/50R17 90T	147700	6.0-7.0-7.5	.25	11.1	25.4	8.6	11.8	1323	44	817	.620 A B	

TOYO ORIGINAL EQUIPMENT

Passenger Radial

Tire Size	Brand	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	Max Load	Max PSI	Rev Mile	OE Model	PRICE
P205/55R16 89H	PROXES A05B	154620	5.5-6.5-7.5	.21	10.1	24.9	8.1	11.5	1279	44	835	04-08 Mazda 3 02-03 Camry	\$
P215/55R17 93V	PROXES J33B	238130	6.0-7.0-7.5	.25	9	26.4	8.8	12.2	1433	44	788	04-08 Camry 04-08 Camry Solara 04-06 Lexus ES330 07-08 Lexus ES350	
205/40R17 80W	PROXES R28	238810	7.0-7.5-8.0	.19	9	23.46	8.23	11.02	992	44	885		
P195/65R15 89H	PROXES A18	154610	5.5-6.0-7.0	.19	9.7	24.88	7.80	11.4	1279	44	835	04-08 Mazda 3	
NEW 205/50R17 88V	PROXES 18A	238860	.7	8.0	25.00	8.50						Mazda 3	
NEW 205/50R17 89V	PROXES A19	238820	5.5-6.5-7.5	.22	10.3	25.1	8.2	11.6	1279	44	834	06-08 Mazda 5	
215/70R16 99S	A14	120920	5.5-6.5-7.0	.23	9	27.7	8.7	12.6	1709	44	749	RAV 4	
235/60R16 100H	A14	144430	.7	25.2	8	27.0	9.3	12.5	1764	44	774	02-03 RAV 4	
NEW P225/70R16 101S	A11B	141000	6.0-6.5-7.5	.25	c7.6 / s9.7	28.31	9.69	12.80	1819	44			
NEW P275/65R18 114T	OPEN COUNTRY A/T	301640	7.5-8.0-9.5	.47	13	32.20	10.90	14.5	2601	35	646		
NEW 215/45R17 87V B/TL	OPEN COUNTRY A20	238880	.7	10	24.7	8.6						New Toyota Prius	
225/65R17 101H TL BW	OPEN COUNTRY A20	300780	.7	10	28.6	9.1						2009 RAV 4	
235/55R18 99H TL BW	OPEN COUNTRY A20	300790	.7	10	28.2	9.4						2010 RAV 4	
NEW 195/60R15 87H	TYA20	140510	.6	9	24.2	8						New Nissan Cube	
NEW 195/55R16 86V	TYA20	140520	.6	9	24.5	7.7						New Nissan Cube	
NEW 205/55R16 89H	TYA20	140500	.65	9	24.7	8.4						Mazda 3	
NEW 245/55R19 103S TL BW	Open Country A20A	300930	.75	33.29	10				1929	44			
NEW P245/65R17 105S BW	Open Country A20A	300920	.75	29.6	10				2039	44			
NEW P215/45R17 87V BW	Open Country A20A	238880	.7	24.7	10								

TOYO OPEN COUNTRY A/T

SUV/Light Truck Radial



UTQG: 500 AB

Warranty

**P-Metric Sizes:
50,000-Mile
Treadwear Limited
Warranty.**

**LT & Non P-Metric Sizes,
Up to 17": 40,000**

**18" and Higher Wheel
Diameter:
Workmanship and
Materials Only.**

The durable Open Country A/TTM offers aggressive wet and snow traction with exceptional mileage for pickups, vans and sport utility vehicles.

This versatile all-terrain radial delivers rugged good looks without compromising handling, ride comfort or on-and-off-road stability.

Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Revs/Mile	PRICE	F.E.T.
										Single	Dual	Single	Dual			
P-METRIC																
P225/70R14	300190	.98S	..OWL	6.0-6.5-7.5	24	13	26.60	8.90	11.9	1675	35	781
P205/75R15	300080	.97S	..OWL	5.0-5.5-7.0	23	12	27.10	8.00	12.3	1598	35	764
P215/75R15	300070	100S	..OWL	5.5-6.0-7.0	25	12	27.70	8.50	12.4	1742	35	751
P225/75R15	300060	102S	..OWL	6.0-7.5	27	13	28.30	8.80	12.7	1874	35	732
P235/75R15	300050	105S	..OWL	6.0-6.5-8.0	29	13	28.90	9.30	12.9	2028	35	719
P235/75R15 XL	300220	108S	..OWL	6.0-6.5-8.0	31	13	28.90	9.30	12.9	2183	41	719
P265/75R15	300040	112S	..OWL	7.0-7.5-9.0	36	13	30.70	10.50	13.6	2469	35	677
P225/70R15	300310	100T	..OWL	6.0-6.5-7.5	26	13	27.40	9.00	12.4	1753	35	754
P235/70R15	300170	102S	..OWL	6.0-7.0-8.0	27	13	28.00	9.50	12.6	1896	35	743
P265/70R15	300160	110S	..BLK	7.0-8.0-9.0	35	13	29.70	10.70	13.2	2337	35	701
P225/75R16	300030	104S	..BLK	6.0-7.5	27	13	29.30	8.80	13.2	1984	35	706
P235/75R16	300250	106T	..OWL	6.0-6.5-8.0	32	13	29.90	9.30	13.4	2094	35	695
P245/75R16	300020	109S	..OWL	6.5-7.0-8.0	35	13	30.50	9.80	13.7	2271	35	681
P265/75R16	300010	114S	..OWL	7.0-7.5-9.0	39	13	31.70	10.50	14.1	2601	35	656
P215/70R16	300150	.99S	..BLK	5.5-6.5-7.0	24	12	27.90	8.70	12.7	1709	35	742
P225/70R16	300140	101S	..OWL	6.0-6.5-7.5	28	13	28.40	9.00	12.9	1819	35	727
P245/70R16	300120	106S	..OWL	6.5-7.0-8.0	33	13	29.50	9.80	13.2	2094	35	708
P255/70R16	300110	109S	..OWL	6.5-7.5-8.5	35	13	30.10	10.20	13.5	2271	35	691
P265/70R16	300330	111T	..OWL	7.0-8.0-9.0	39	13	30.60	10.70	13.8	2403	35	676
P275/70R16	300090	114H	..BLK	7.0-8.0-9.0	41	13	31.20	11.00	13.9	2601	35	708
255/65R16	300200	109H	..BLK	7.0-7.5-9.0	33	13	29.10	11.20	13.2	2271	44	673
P235/75R17	300560	108S	..OWL	6.0-6.5-8.0	34	13	30.90	9.30	13.9	2205	35	660
P245/75R17	300570	110S	..OWL	6.5-7.0-8.0	37	13	31.50	9.80	14.1	2373	35	647
P255/75R17	300470	113S	..OWL	6.5-7.0-8.5	39	13	32.10	10.00	14.4	2535	35	694
P235/70R17 XL	300550	108S	..OWL	6.0-7.0-8.0	32	13	29.90	9.60	13.5	2205	41	694
NEW P245/70R17	301720	108S	..BLK	6.5-7.0-8.0	41	13	30.40	9.50	13.7	2205	35	683
P245/70R17	300230	108S	..BLK	6.5-7.0-8.0	35	13	30.60	9.80	13.8	2205	35	680
P255/70R17	300660	108S	..OWL	6.5-7.5-8.5	39	13	31.10	10.20	14.0	2337	35	668
NEW P265/70R17	301570	113S	..BLK	7.0-8.0-9.0	46	13	31.50	10.90	14.2	2535	35	659
P265/70R17	300210	113S	..OWL	7.0-8.0-9.0	39	13	31.70	10.70	14.2	2535	35	658
P285/70R17	300580	113S	..OWL	7.0-8.5-9.5	44	13	32.70	11.40	14.6	2833	35	636
NEW P285/70R17	301710	117T	..BLK	7.5-8.5-9.5	49	14	32.60	11.70	14.6	2833	35	638
P235/65R17	300260	103H	..OWL	6.5-7.0-8.5	31	12	29.00	9.40	13.2	1929	35	717
NEW P235/65R17	301730	103H	..BLK	6.5-7.0-8.5	36	13	29.10	9.40	13.2	1929	35	713
NEW P245/65R17	301700	105T	..BLK	7.0-7.0-8.5	39	13	29.50	9.80	13.4	2039	35	704
P245/65R17	300270	105T	..OWL	7.0-8.5	31	13	29.50	9.60	13.4	2039	35	704
P255/65R17	300380	108S	..BLK	7.0-7.5-9.0	37	13	30.10	10.00	13.6	2205	35	690
NEW P265/65R17	301690	110S	..BLK	7.5-8.0-9.5	42	13	30.50	10.70	13.8	2337	35	681
P265/65R17	301490	110S	..OWL	7.5-8.0-9.5	38	13	30.50	10.60	13.8	2337	35	681
P75/65R17	301530	115T	..BLK	7.5-8.0-9.5	41	13	31.00	11.00	14.0	2679	44	670
235/60R17	300370	102H	..OWL	6.5-7.0-8.5	31	13	28.10	9.40	12.8	1874	44	739
P275/60R17	300280	110T	..OWL	7.5-8.0-9.5	35	13	29.90	11.10	13.5	2337	35	694
P265/70R18	301520	114S	..OWL	7.0-8.0-9.0	44	13	32.60	10.70	14.7	2601	35	636
NEW P265/70R18	301650	114S	..BLK	8	35	16	32.60	10.70	14.7	2601	35	636
P265/65R18	300860	112S	..OWL	7.5-8.0-9.5	41	12	31.60	10.60	14.3	2469	35	657
NEW P265/65R18	301680	112S	..BLK	7.5-8.0-9.5	44	13	31.70	10.70	14.3	2469	35	656
P275/65R18	300640	114T	..BLK	7.0-8.0-9.5	42	13	32.10	11.00	14.5	2601	35	647
P265/60R18	300460	109S	..BLK	7.5-8.0-9.5	38	13	30.60	10.70	13.9	2271	35	679
285/60R18 RD	301300	120S	..BLK	8.0-8.5-10.0	49	14	31.30	11.50	14.2	3086	50	664
NEW P255/70R18	301740	112T	..BLK	6.5-7.5-8.5	44	13	32.20	10.40	14.5	2469	35	645
255/65R18	301510	109H	..BLK	7.0-8.0-9.0	34	12	29.00	10.30	13.3	2271	50	716
P275/60R20	300290	114T	..OWL	7.5-8.0-9.5	42	13	32.87	10.98	15.0	2601	35	632
P275/55R20	300840	111S	..OWL	7.5-8.0-9.5	43	12	31.90	11.20	14.6	2403	35	652
285/50R20	300590	116T	..BLK	8.0-9.0-10.0	44	12	31.30	11.50	14.4	2756	50	664
305/50R20	300300	120T	..OWL	8.5-9.5-11.0	46	14	31.89	12.20	14.6	3086	50	651
305/40R22	301460	114S	..BLK	10.0-11.0-12.0	45	14	31.60	12.20	14.7	2601	50	658
NEW 305/45R22	300830	118S	..BLK	9.5-10.0-11.5	45	13	32.60	11.90	14.7	2601	50	658
LIGHT TRUCK																
30X9.50R15/6	300520	104S	..OWL	6.5-7.5-8.5	36	16	29.50	9.50	13.1	1985	50
31X10.50R15/6	300510	109 S	..OWL	7.0-8.5-9.0	39	16	30.50	10.50	13.5	2270	50
LT235/75R15/6	301100	104S	..OWL	6.0-6.5-7.0	33	14	28.90	9.30	12.9	1985	1820	50	50	50
LT215/85R16/8	301020	110Q	..BLK	5.5-6.0-7.0	38	15	30.40	8.50	13.6	2335	2150	65	65	65
LT215/85R16/10	301030	115Q	..BLK	5.5-6.0-7.0	38	15	30.40	8.50	13.6	2680	2470	80	80	80
LT235/85R16/10	301010	120Q	..BLK	6.0-6.5-7.0	43	15	31.70	9.30	14.2	3042	2778	80	80	80
LT225/75R16/10	301090	115Q	..BLK	6.0-7.0	36	14	29.30	8.80	13.2	2680	2470	80	80	80
LT245/75R16/6	301060	108S	..OWL	6.5-7.0-7.5	40	15	30.50	9.80	13.6	2205	2006	50	50	50
LT245/75R16/10	301070	120Q	..OWL	6.5-7.0-7.5	41	15	30.50	9.80	13.6	3042	2778	80	80	80
LT265/75R16/6	301040	112S	..OWL	7.0-7.5-8.0	43	16										

TOYO OPEN COUNTRY A/T (continued)

SUV/Light Truck Radial

Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Tire/Mile	PRICE	F.E.T.
										Single	Dual	Single	Dual			
LT285/70R17/8 (33X11.50R17)	301400	121S	..OWL	7.5-8.5-9.0	.53	..17	..32.70	..11.30	..14.6	..3195	..65
LT285/70R17/10 (33X11.50R17)	301480	126S	..OWL	7.5-8.5-9.0	.53	..17	..32.70	..11.50	..14.6	..3750	..80
LT325/70R17/8 (35X13.0R17)	301350	122R	..BLK	8.5-9.5-10.0	.77	..17	..34.90	..13.00	..15.5	..3305	..50
LT355/70R17/8 (37X14.0R17)	301360	127R	..BLK	9.5-10.5-11.0	.85	..17	..36.50	..14.20	..16.1	..3860	..50
P255/70R18	300850	112T	..OWL	6.5-7.5-8.5	.41	..13	..32.10	..10.30	..14.5	..2469	..35
LT285/75R18 (35X11.5R18)	300420	129S	..BLK	7.5-8.0-9.0	.66	..17	..34.80	..11.30	..15.6	..4080	..80
LT275/70R18/10 (33X11.0R18)	300620	125S	..OWL	7.0-8.0-8.5	.55	..16	..33.10	..11.00	..14.9	..3640	..80
LT275/65R18/6 (32X11.0R18)	300600	113T	..OWL	7.5-8.0-9.0	.51	..16	..31.90	..10.90	..14.4	..2535	..50
LT275/65R18/10	300680	123S	..OWL	7.5-8.0-9.0	.52	..16	..32.00	..11.00	..14.5	..3415	..80
LT285/65R18/10	300630	125S	..OWL	8.0-8.5-10.0	.57	..17	..32.50	..11.40	..14.6	..3640	..80
LT325/60R18/8 (33X13.0R18)	301310	119S	..BLK	9.5-10.5	.60	..16	..33.00	..12.60	..14.9	..2998	..50
LT325/65R18/8 (35X13.0R18)	301430	121R	..BLK	9.0-9.5-10.0	.75	..17	..34.90	..13.30	..15.6	..3195	..50
LT355/65R18/ (37X14.0R18)	301440	125R	..BLK	10.0-10.5-11.0	.86	..17	..36.60	..14.10	..16.3	..3640	..50
LT275/65R20/10	301140	126S	..OWL	7.5-8.0-9.5	.57	..15	..34.00	..11.00	..15.5	..3750	..80
LT305/60R20/10	300610	123S	..BLK	8.5-9.0-11.0	.65	..16	..34.30	..12.60	..15.6	..3415	..65
LT325/60R20/8 (35X13.0R20)	301410	121R	..BLK	9.5-10.5	.74	..16	..36.20	..12.90	..15.9	..3195	..50
LT355/60R20/8 (37X14.0R20)	301370	125R	..BLK	10.0-10.5-11.5	.88	..17	..36.80	..14.20	..16.5	..3640	..50
LT285/55R20/10	301150	122S	..OWL	8.0-9.0-10.0	.52	..15	..32.30	..11.70	..14.8	..3305	..80
LT305/55R20/10 (33X12.0R20)	301340	121S	..BLK	9.0-9.5-10.0	.57	..16	..33.20	..12.40	..15.2	..3195	..65
305/35R22	300830	118S	..BLK	9.5-10.0-11.5	.45	..13	..32.60	..11.90	..15.1	..2910	..50
LT325/50R22/10 (35X13.0R22)	301380	122R	..BLK	9.5-10.0-12.0	.72	..17	..34.80	..13.00	..16.0	..3305	..65

TOYO OPEN COUNTRY M/T

Light Truck Radial



The Open Country M/T is designed for full-size pickups and SUV's driven by enthusiasts who require extra ground clearance, load-carrying capacity and off-road capability with great on-road performance.

Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Tire/Mile	PRICE	F.E.T.
										Single	Dual	Single	Dual			
LT235/85R16/10	360440BLK	6.0-6.5-7.5	.52	..18	..32	..9.4	..14.90	..3042	..80
LT255/85R16	360460BLK	6.5-7.0-8.0	.60	..19.0	..33.5	..10.2	..15.6	..3415	..80
123/120P E/10	360450BLK	6.5-7.0-8.0	.52	..18	..30.7	..9.9	..14.30	..3042	..80
LT245/75R16/10	360320	123Q	..BLK	7.0-7.5-8.0	.58	..19	..31.8	..10.8	..14.80	..3415	..80
LT265/70R17/10	360130BLK	7.0-8.0-8.5	.63	..19	..32	..10.8	..14.90	..3195	..80
LT275/70R18/10	360120	125S	..BLK	7.0-8.0-8.5	.66	..19	..33.60	..11.00	..15.6	..3640	..80
LT275/65R20/10	360410BLK	7.5-8.0-9.5	.71	..19	..34.5	..11.0	..16.0	..3750	..80
31X10.50R15/6	360490	109Q	..B/TL	7.0-8.5-9.0	.55	..19	..31.1	..10.7	..14.4	..2270	..50
33X10.50R15LT	360470B/TL	7.0-8.5-9.0	.57	..19.0	..32.8	..10.9	..15.2	..2600	..50
114P C/6	360100BLK	8.0-10-11	.73	..21	..33.0	..12.8	..15.4	..2205	..35
33x13.50R15/6	360290	109Q	..BLK	8.5-11.0	.75	..21	..33.1	..13.9	..15.4	..2270	..35
LT285/75R16/10 (33 x 11.50R16)	360280	126P	..BLK	7.5-8.0-9.0	.68	..19	..33.0	..11.6	..15.4	..3740	..80
LT305/70R16/10 (33.0X12.0R16)	360110	124P	..BLK	8.0-9.0-9.5	.72	..20	..33.0	..12.2	..15.4	..3525	..65
NEW LT285/70R16/6	360170	114P	..B/TL	7.5-8.5-9.5	.61	..19	..32.0	..11.1	..14.9	..2600	..50
LT285/75R17/10	360430BLK	7.5-8.0-9.5	.71	..19	..34.1	..11.6	..15.8	..3195	..80
LT295/70R17/10 (33X11.50R17)	360360	128P	..BLK	8.0-8.5-9.5	.73	..19	..33.5	..11.9	..15.6	..3970	..80
NEW 32X11.50R16LT/6 Non DOT	360080	112P	..BLK	9.00	.53	..19	..32.0	..9.0	..14.70	..2470	..50
33X12.50R18/10	360340	118Q	..BLK	8.5-10.0-11.0	.75	..21	..33.0	..12.7	..15.3	..2910	..65
33X12.50R20/10	360330	114Q	..BLK	8.5-10.0-11.0	.72	..21	..33.0	..12.6	..15.3	..2600	..65
NEW 33X12.50R22/10	360520	109Q	..B/TL	8.5-10.0-11.0	.79	..21	..33.0	..12.4	..15.6	..3415	..65
NEW 35X12.50R22/10	360540	117Q	..B/TL	8.0-10.0-11.0	.81	..21	..35.0	..12.8	..16.0	..3750	..80
35X13.50R15/6	361000	114Q	..BLK	8.5-11.0	.84	..21	..34.8	..14.4	..15.2	..2600	..35
LT315/75R16/10 (35 x 12.50R16)	360230	127Q	..BLK	8.0-8.5-10.0	.76	..21	..34.9	..12.9	..16.2	..3860	..65
35x12.50R17/10	360310	125Q	..BLK	8.5-10.0-11.0	.83	..21	..34.8	..13.2	..16.2	..3640	..65
LT285/75R18/10	360420BLK	7.5-8.0-9.5	.71	..19	..35.1	..11.6	..16.3	..4080	..80
35X12.50R18/10	360090	123Q	..BLK	8.5-10.0-11.0	.81	..21	..35.0	..13.2	..15.6	..3415	..65
NEW LT315/60R20/10 (35X12.50R20)	360510	125/122Q	..B/TL	8.5-9.5-11.0	.81	..21	..35.0	..12.6	..15.6	..3415	..65
NEW LT315/70R18/10 (36X13.00R18)	360560	127/124Q	..B/TL	8.0-9.5-11.0	.81	..21	..35.7	..13.0	..16.0	..3750	..80
37x14.50R15/6	360260	120Q	..BLK	10.0-12.0	.94	..21	..36.7	..15.6	..17.0	..3080	..35
37x13.50R17/10	360270	131Q	..BLK	8.5-11.0	.93	..21	..37.0	..14.6	..17.2	..4300	..65
37x13.50R18/8	360300	124Q	..BLK	8.5-11.0	.93	..21	..37.0	..14.2	..17.2	..3525	..50
37X13.50R20/10	360220	127Q	..BLK	8.5-11.0	.94	..21	..37.0	..14.0	..17.2	..3860	..65
37X13.50R22/10	360210	123Q	..BLK	8.5-11.0	.90	..21	..37.0	..14.0	..17.2	..3420	..65
37X13.50R24/10	360350	120Q	..BLK	8.5-11.0	.89	..21	..37.0	..13.6	..17.2	..3085	..65
NEW LT385/70R16/8 130Q	360480	130Q	..BLK	10.0-11.0-12.0	.97	..21	..37.7	..15.6	..17.2	..3860	..65
38X15.50R18/8	360180	128Q	..BLK	11.0-12.0-13.0	1.06	..21	..37.7	..15.9	..17.5	..3970	..50
38X13.50R20/8	360390	124Q	..BLK	8.5-11.0	1.00	..21	..37.7	..14.3	..17.5	..3525	..50
38X15.50R20/8	360190	125Q	..BLK	11.0-12.0-13.0	1.01	..21	..37.7	..15.9	..17.5	..3640	..50
NEW 40X13.50R17/LT	360040	121L	..BLK	11.0-12.0-13.0	1.01	..21	..39.8	..15.9	..17.5	..3195	..35
40X15.50R20/8	360370	130Q	..BLK	11.0-12.0-13.0	1.12	..21	..39.7	..15.9	..18.4	..4190	..50
40X15.50R22/8	360200	127Q	..BLK	11.0-12.0-13.0	1.10	..21	..39.7	..15.9	..18.5	..3860	..50



BAJA 1000 WINNER

TOYO M-55

Light Truck Radial



Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		PRICE	F.E.T.
										Single	Dual	Single	Dual		
LT215/75R15/6	309160	100/97M	BLK	5.5-6.0-7.0	31	17	27.68	8.50	13.1	1765	1610	50	50		\$
LT235/75R15/6	309200	104/101M	BLK	6.0-6.5-7.0	35	18	28.86	9.25	13.6	1985	1820	50	50		
LT215/85R16/10	309440	115/112N	BLK	5.5-6.0-7.0	43	16	30.7	8.6	14.3	2680	2470	80	80		
LT235/85R16	309460	120/116N	BLK	6.0-6.5-7.5	49	17	32.0	9.3	14.9	3042	2778	80	80		
LT255/85R16	309470	123/120M	BLK	6.5-7.0-8.0	56	18	33.3	10.4	14.7	3415	3085	80	80		
LT225/75R16	309410	115/112N	BLK	6.0-7.0	39	16	29.4	8.5	13.7	2680	2470	80	80		
LT245/75R16	309420	120/116N	BLK	6.5-7.0-8.0	46	17	30.7	9.8	14.3	3042	2778	80	80		
LT265/75R16	309430	123/120M	BLK	7.0-7.5-8.0	54	18	31.9	10.8	14.2	3415	3085	80	80		
LT285/75R16/10	309180	126/123M	BLK	7.5-8.0-9.0	60	18.9	33.19	11.30	15.4	3740	3415	80	80		
LT265/70R17	309480	121N	BLK	7.0-8.0-8.5	53	18	31.9	10.6	14.8	3195		80			
LT235/80R17	309490	120N	BLK	6.0-6.5-7.5	49	17	31.9	9.3	14.8	3085		80			
LT245/75R17	309500	121N	BLK	6.5-7.0-7.5	49	17	31.9	9.7	14.8	3195		80			
LT275/70R18	309510	125N	BLK	7.0-8.0-8.5	57	18	33.6	11.0	15.6	3640		80			

M55 All size studable

TOYO OPEN COUNTRY HT

SUV/Light Truck Radial



Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		PRICE	F.E.T.
										Single	Dual	Single	Dual		
P225/75R15 102S	362140	102S	OWL	6.0-7.5	28	13	28.3	8.9	12.7	1874		35			\$
P235/75R15 105S	362150	105S	OWL	6.0-6.5-8.0	31	13	28.9	9.3	12.9	2028		35			
205/70R15 96H	362380	96H	BLK	5.0-6.0-7.0	24	12	26.3	8.2	11.9	1565		44			
P225/70R15 100T	362030	100T	OWL	6.0-6.5-7.5	26	13	27.4	8.9	12.4	1753		35			
P235/70R15 102S	362040	102S	OWL	6.0-7.0-8.0	28	13	28.0	9.4	12.6	1896		35			
P265/70R15 110S	362050	110S	BLK	7.0-8.0-9.0	37	13	29.6	10.4	13.2	2337		35			
P225/75R16 104S	362160	104S	OWL	6.0-7.5	31	13	29.3	8.9	13.2	1984		35			
P235/75R16 106S	362660	106S	OWL	6.0-6.5-8.0	34	13	29.8	9.4	13.4	2094		35			
P245/75R16 109S	362170	109S	OWL	6.5-7.0-8.0	40	13	30.4	9.8	13.6	2271		35			
P265/75R16 114T	362180	114T	OWL	7.0-7.5-9.0	41	13	31.5	10.4	14.1	2601		35			
P215/70R16 99H	362060	99H	BLK	5.5-6.5-7.0	28	12	27.9	8.7	12.6	1709		35			
P225/70R16 101T	362070	101T	OWL	6.0-6.5-7.5	29	13	28.4	9.0	12.8	1819		35			
P235/70R16 104T	362080	104T	OWL	6.0-7.0-8.0	30	13	28.9	9.3	13.0	1984		35			
P245/70R16 106S	362090	106S	OWL	6.5-7.0-8.0	35	13	29.4	9.6	13.2	2094		35			
P255/70R16 109S	362100	109S	OWL	6.5-7.5-8.5	37	13	30.0	10.1	13.5	2271		35			
P265/70R16 111S	362110	111S	OWL	7.0-8.0-9.0	40	13	30.6	10.4	13.7	2403		35			
P275/70R16 114H	362120	114H	BLK	7.0-8.0-9.0	41	13	31.1	10.8	13.9	2601		35			
215/65R16 98H	362340	98H	BLK	6.0-6.5-7.5	26	12	27.0	8.8	12.3	1653		44			
235/65R16 101S	362360	101S	BLK	6.5-7.0-8.5	31	12	28.0	9.6	12.7	1819		35			
255/65R16 109H	362350	109H	BLK	7.0-7.5-9.0	34	13	29.1	10.2	13.1	2271		44			
235/60R16 100H	362330	100H	BLK	6.5-7.0-8.5	28	12	27.1	9.4	12.3	1764		44			
P235/75R17 108S	362670	108S	OWL	6.0-6.5-8.0	36	13	30.9	9.5	13.9	2205		35			
P245/75R17 110S	362680	110S	OWL	6.5-7.0-8.0	37	13	31.5	9.8	14.2	2337		35			
P235/70R17 108S	362650	108S	OWL	6.0-7.0-8.0	32	13	29.9	9.4	13.5	2205		41			
NEW P235/70R17 108S	363070	108S	BLK		33	13				2205		41			
P245/70R17 108S	362300	108S	OWL	6.5-7.0-8.0	38	13	30.60	9.80	13.8	2205		35			
NEW P245/70R17 108S	363020	108S	BLK		38	13						35			
NEW P255/70R17 110S	363050	110	BLK	6.5-7.5-8.5	42	13	31.10	10.30	14.0	2337		35			
P255/70R17 110S	362310	110S	OWL	6.5-7.5-8.5	41	13	31.10	10.30	14.0	2337		35			
NEW P265/70R17 113S	362980	113S	BLK	7.0-8.0-9.0	45	13	31.50	10.80	14.1	2535		35			
P265/70R17 113T	362130	113T	OWL	7.0-8.0-9.0	42	13	31.5	10.7	14.2	2535		35			
P285/70R17 117T	362540	117T	BLK	7.5-8.5-9.5	45	13	32.7	11.4	14.6	2833		35			
225/65R17 102H	362510	102H	BLK	6.0-6.5-8.0	30	12	28.5	8.9	13.0	1874		44			
NEW P235/65R17 104H	363000	104H	BLK	6.5-7.0-8.5	36	12	29.1	9.4	13.2	1984		44			
235/65R17 104H	362370	104H	OWL	6.5-7.0-8.5	33	12	29.0	9.4	13.2	1984		44			
NEW P245/65R17 105H	362990	105H	BLK	7.0-8.5	38	13	29.5	9.7	13.4	2039		35			
P245/65R17 105H	362010	105H	OWL	7.0-8.5	34	13	29.5	9.7	13.4	2039		35			
P255/65R17 108S	362430	108S	BLK	7.0-7.5-9.0	38	13	30.10	10.30	13.6	2205		35			
NEW P265/65R17 110S	363010	110S	BLK	7.5-(8.0)-9.5	42	13	30.60	10.80	13.8	2337		35			
P265/65R17 110S	362020	110S	OWL	7.5-8.0-9.5	40	13	30.5	10.6	13.8	2337		35			
P235/60R17 100S	362630	100S	OWL	6.5-7.0-8.5	32	11	29.20	9.40	12.9	1764		35			
NEW P235/60R17 100S	363060	100S	BLK		32	11				1764		35			
255/60R17 106H	362590	106H	BLK	7.0-7.5-9.0	35	13	29.10	10.30	13.2	2094		44			
235/55R17 99H	362520	99H	BLK	6.5-7.5-8.5	28	13	27.20	9.40	12.5	1709		44			
NEW P255/65R17 108S	363030	108S	BLK	7.0-7.5-9.0	40	13	30.10	10.40	13.6	2205		35			
255/70R18 113S	362610	113S	BLK	6.5-7.5-8.5	39	12	32.20	10.40	14.5	2535		44			
NEW P265/70R18 114S	362830	114S	BLK	8	44		32.60	10.80	14.7	2601		35			
P265/70R18 114S	362320	114S	OWL	7.0-8.0-9.0	44	13	32.60	10.70	14.7	2601		35			
P235/65R18 104T	362640	104T	BLK	6.5-7.0-8.5	32	12	30.20	9.60	13.7	1984		35			
NEW P275/65R18 114T	362840	114T	BLK	8	45		32.20	11.00	14.5	2601		35			
P265/65R18 112S	362910	112S	BLK	7.5-8.0-9.5		13	31.50	10.70							
P275/65R18 114T	362470	114T	OWL	7.5-8.0-9.5	45	13	32.20	11.00	14.5	2601		35			
235/60R18 107V	362560	107V		6.5-7.0-8.5	33	11	29.10	9.40	13.3	2150		50			
P245/60R18 104H	362760	104H	BLK	7.0-8.5	35	13	29.60	9.60	13.5	1984		35			
255/60R18 112H	362600	112H	BLK	7.0-7.5-9.0	37	13	30.00	10.10	13.7	2469		50			
NEW P265/60R18 109T	363080	109T	BLK		45	13				2271		35			
P265/60R18 109T	362460	109T	BLK	7.0-8.0-9.5	45	13	30.50	10.60	13.9	2271		35			
P275/60R18 111H	362710	111H	BLK	7.0-8.0-9.5	39	13	30.80	10.90	14.0	2403		35			
235/55R18 100V	362400	100V	BLK	6.5-7.5-8.5	27	10	28.10	9.60	13.0	1764		44			
255/55R18 109V	362570	109V		7.0-8.0-9.0	36	12	29.10	10.40	13.3	2271		50			
255/55R19 111V	362580	111V		7.0-8.0-9.0	37	12	30.00	10.40	13.8	2403		50			
P245/55R19 103S	362850	103S	BLK	7.0-7.5-8.5	34	12	29.70	9.60	13.7	1929		44			
P275/60R20 114S	362890	114S	OWL	7.5-8.0-9.5	47	13	33.10	10.90	15.1	2601		35			
P235/55R20 102T	362860	102T	BLK	6.5-7.5-8.5	34	12	30.20	9.40	14.0	1874		44			
265/50R20 112V	362690	112V		7.5-8.5-9.5	40	11	30.40	10.90	14.1	2403		50			
275/55R20 117S	362700	117S	OWL	7.5-8.5-9.5	42	13	31.90	11.40	14.6	2833		50			
285/45R22 114H	362720	114H		9.0-9.5-10.5	43	12	32.00	11.20	14.9	2601		50			
LIGHT TRUCK															
LT235/75R15/6	362210	104S	OWL	6.0-6.5-7.0	34	14	28.8	9.5	12.9	1985	1820	50	50		
31x10.50R15/6	362000	109S	OWL	7.0 - 8.5-9.0	43	16	30.3	10.9	13.5	2270		50			
LT215/85R16/10	362290	115S	BLK	5.5-6.0-7.0	41	15	30.4	8.9	13.6	2680	2470	80	80		
LT235/85R16/10	362280	120S	OWL												

TOYO OPEN COUNTRY HT (continued)

SUV/Light Truck Radial

Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		PRICE	F.E.T
										Single	Dual	Single	Dual		
LT265/75R16/6	362240	112S	OWL	7.0-7.5-8.0	.45	.16	31.6	10.8	14.1	2470	2270	.50	.50	\$	
LT265/75R16/8	362250	119S	OWL	7.0-7.5-8.0	.49	.16	31.6	10.8	14.1	3000	2755	.65	.65		
LT265/75R16/10	362260	123S	OWL	7.0-7.5-8.0	.50	.16	31.6	10.8	14.1	3415	3085	.80	.80		
LT285/75R16/10	362920	126S	OWL	7.5-8.0-9.0		.17	32.8	11.4							
LT235/80R17/10	362270	120S	BLK	6.0-6.5-7.5	.43	.15	31.7	9.2	14.2	3085	2835	.80	.80		
NEW LT245/75R17/10	362780	121S	BLK	7	.47	.10	31.5	9.9	14.2	3195		.80			
LT245/70R17/10	362620	121S	OWL	6.5-7.0-7.5	.47	.15	31.5	9.9	14.2	3195		.80			
NEW LT245/70R17/10	363040	119S	BLK	6.5-7.0-8.0	.46	.15	30.6	9.9	13.8	3000	2755	.80	.80		
LT245/70R17/10	362190	119S	OWL	6.5-7.0-8.0	.44	.15	30.5	9.8	13.8	3000	2755	.80	.80		
NEW LT265/70R17/10	362770	121S	BLK	8	.47		31.6	10.6	14.2	3195	2910	.80	.80		
LT265/70R17/10	362200	121S	OWL	7.0-8.0-8.5	.50	.16	31.6	10.7	14.2	3195	2910	.80	.80		
LT285/70R17/10	362940	121S	OWL	7.5-8.5-9.0		.16	32.7	11.7							
NEW LT275/70R18/10	363090	125S	BLK	7.0-8.0-8.5	.55	.16	33.1	11.2	14.9	3640		.80			
LT275/70R18/10	362450	125S	BLK	7.0-8.0-8.5	.52	.16	33.10	11.00	14.9	3640		.80			
NEW LT275/65R18/10	362790	123S	BLK	8	.37	.16	32.00	10.90	14.4	3415		.80			
LT275/65R18/10	362480	123S	BLK	7.5-8.0-9.0	.52	.16	32.00	10.90	14.4	3415		.80			

TOYO OPEN COUNTRY HT-3

SUV/Light Truck Radial



Tire Size	Code #	Load Index	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Revs/Miles	PRICE	F.E.T
									Single	Dual	Single	Dual			
LT235/85R16/10	364010	120/116Q	6.0-6.5-7.5	.44	.16	31.6	9.2	14.10	3042	2778	.80	.80	657	\$	
LT245/75R16/10	364020	120/116R	6.5-7.0-8.0	.45	.16	30.6	9.9	13.7	3042	2778	.80	.80	680		
LT265/75R16/10	364030	123/120Q	7.0-7.5-8.0	.50	.16	31.6	10.6	14.1	3415	3085	.80	.80	658		
LT285/75R16/10	364040	126/123Q	7.5-8.0-9.0	.55	.17	32.8	11.3	14.6	3750	3415	.80	.80	632		
NEW LT225/75R17/10	364060	116/113Q	6.0-7.5	.41	.14	30.3	8.7	13.7	2755	2535	.80	.80	685		
LT265/70R17/10	364050	121/118R	7.0-8.0-8.5	.49	.16	31.5	10.8	14.2	3195	2910	.80	.80	660		

Deep Tread Depth Tread Depth up to 17/32nds

- Increases tread life for longer wear.

Tuff Duty 3-Belt Construction

- Reinforces and stabilizes internal tire construction for increased tread life.

Less Tread Void

- More rubber equals larger, more evenly distributed contact with the road for longer tread life.

Tuff Duty logo on sidewall

- Unique mark distinguished Open Country H/T with Tuff duty technology from standard Open Country H/T tires.

TOYO M-54

Light Truck Radial



Tire Size	Code #	Load Index	Sidewall	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		PRICE
										Single	Dual	Single	Dual	
LT215/85R16/8	308040	110/107M	BLK	5.5-6.0-7.0	.38	.14	30.39	8.50	14.2	2335	2150	.65	.65	\$
LT235/85R16/10	308120	120/116M	BLK	6.0-6.5-7.0	.48	.14	31.73	9.25	14.8	3042	2778	.80	.80	

TOYO M-147

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
295/75R22.5/14	547300	8.25-9.0	.118	.19	40.2	11.1	18.7	.6175	.5675	.110	.110	.517	\$	
285/75R24.5/14	547310	8.25	.115	.19	41.3	11.1	19.2	.6175	.5675	.110	.110	.502		
11R22.5/14	547320	7.5-8.25	.117	.19	41.3	11.1	19.3	.6175	.5840	.105	.105	.501		
11R22.5/16	547330	7.5-8.25	.117	.19	41.3	11.1	19.3	.6610	.6005	.120	.120	.501		
11R24.5/14	547340	7.5-8.25	.125	.19	43.4	11.1	20.2	.6610	.6005	.105	.105	.478		
11R24.5/16	547350	7.5-8.25	.125	.19	43.4	11.1	20.2	.7160	.6610	.120	.120	.478		

DISCO II Technology incorporates a unique Side Differential Groove to assure long original mileage with improved resistance to irregular wear without compromising tracting, casing endurance or retreadability.

TOYO M-127

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
295/75R22.5/14	541300	8.25	.104	.13	39.8	11.1	15.5	.6175	.5675	.110	.110	.522	\$	
285/75R24.5/14	541310	8.25	.109	.13	41.0	11.1	16.0	.6175	.5675	.110	.110	.507		
11R22.5/14	541320	8.25	.108	.13	41.0	11.1	16.0	.6175	.5840	.105	.105	.506		
11R24.5/14	541330	8.25	.116	.13	43.0	11.1	16.8	.6610	.6005	.105	.105	.483		

Premium free rolling wheel position radial design. Provides long, even wear in any over-the-highway application with rugged construction for extended tire life. Features DSOC II technology.

TOYO M-143

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
215/75R17.5/14	.306100	6.0-6.75	.58	.16	30.6	8.3	14.2	.3750	.3530	.105	.105	.679	\$	
NEW 225/70R19.5	.562150													
NEW 225/70R19.5	.562140													
245/70R19.5/16	.562100	6.75-7.5	.75	.16	33.2	10.0	15.4	.4805	.4540	.120	.120	.625		
265/70R19.5/14	.562110	6.75-7.5-8.25	.87	.16	34.3	10.0	15.9	.5070	.4675	.110	.110	.605		
285/70R19.5/16	.562120	7.5-8.25-9.0	.95	.17	35.2	10.8	16.3	.6395	.6005	.125	.125	.590		

TOYO M-1430

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
215/75R17.5/16	.520500	6.0-6.75	.60	.15	30.5	8.3	14.2	.4805	.4540	.125	.125	.681	\$	
235/75R17.5/16	.520510	6.75-7.50	.65	.15	31.6	9.2	14.3	.6000	.5680	.125	.125	.657		

TOYO M-122

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
295/75R22.5/14	.548000	8.25-9.0	.106	.17	40.0	11.1	18.6	.6175	.5675	.110	.110	.519	\$	
NEW 285/75R24.5	.548030			.109	41.1	10.8	11.7	.6175	.5675	.110	.110	.505		
11R22.5/14	.548020	7.5-8.25	.112	.17	41.3	11.1	19.2	.6175	.5840	.105	.105	.503		
11R24.5/14	.548010	7.5-8.25	.121	.17	43.3	11.1	20.1	.6610	.6005	.105	.105	.480		

TOYO M-120Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
255/70R22.5/16	.547640	7.50	.92	.17	36.5	9.9	17.0	.5510	.5070	.120	.120	.568	\$	
8R19.5/12	.547500	6.00	.62	.15	33.7	8.0	15.7	.3525	.3305	.110	.110	.616		
9R22.5/12	.547700	6.75	.85	.15	38.1	8.9	17.7	.4540	.4300	.105	.105	.544		
10R22.5/14	.547720	7.50	.99	.17	39.9	10.0	18.5	.5675	.5355	.115	.115	.520		
11R22.5/16	.547800	8.25	.113	.17	41.3	11.1	19.2	.6610	.6005	.120	.120	.502		
11R24.5/16	.547880	8.25	.115	.17	43.3	11.1	20.2	.7160	.6610	.120	.120	.479		

Exceptional durability, superior traction. Well suited for all positions including trailers.

TOYO M-140

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBE TYPE														
8.25R20/14	.548551	6.0-6.5-7.0	.90	.16	38.2	9.2	17.8	.4940	.4675	.120	.120	.543	\$	
9.00R20/14	.548541	6.5-7.0-7.5	.104	.16	39.8	10.0	18.5	.5675	.5355	.115	.115	.521		
10.00R20/14	.548511	7.0-7.5-8.0	.114	.18	41.4	10.9	19.3	.6175	.5840	.105	.105	.501		
10.00R20/16	.548521	7.0-7.5-8.0	.115	.18	41.4	10.9	19.3	.6610	.6005	.120	.120	.501		
11.00R20/16	.548531	7.5-8.0-8.5	.136	.18	42.6	11.5	19.8	.7390	.6780	.120	.120	.487		

Designed specifically for motor coach, specialty trailer, and regional fleet applications where quality and long life are desired. DSOC II technology provides resistance to irregular wear and provides for retreadability.

TOYO M-627Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
295/75R22.5/14	.558100	8.25	117	.28	40.70	11.4	18.9	.6175	.5675	.110	.110	.509	\$	
285/75R24.5/14	.558110	8.25	122	.28	42.00	11.1	19.5	.6175	.5675	.110	.110	.494		
11R22.5/14	.558120	8.25	125	.28	41.97	11.1	19.5	.6175	.5840	.105	.105	.494		
11R22.5/16	.558130	8.25	125	.28	41.97	11.1	19.5	.6610	.6005	.120	.120	.494		
11R24.5/14	.558140	8.25	132	.28	44.00	11.1	20.4	.6610	.6005	.105	.105	.472		
11R24.5/16	.558150	8.25	134	.28	44.00	11.1	20.4	.7160	.6610	.120	.120	.472		

TOYO M-137

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
295/75R22.5	.547010	8.25-9.0	108	.15	40	11.1	18.6	.6175	.5675	.110	.110	.519	\$	
285/75R24.5	.547020	8.25	111	.15	41.1	11.1	19.1	.6175	.5675	.110	.110	.505		



e-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing. e-balance design provides even contact pressure distribution across the tread surface resulting in smooth wear and long life.

TOYO M-111Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
12R22.5/16	.546520	9.00	140	.19	42.6	11.6	19.8	.7390	.6780	.120	.120	.488	\$	
315/80R22.5/20	.546160	9.00	142	.18	42.5	12.3	19.8	.9090	.8270	.130	.130	.489		

***Speed restriction of 55mph for urban use only, not be used on Highway application

Features a five-rib, zig-zag tread with wide grooves for excellent traction. Ideal for steel axle position in local and regional applications.

TOYO M-610ZL

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
295/75R22.5/14	.556510	8.25	123	.28	40.7	11.4	18.9	.6175	.5675	.110	.110	.510	\$	
285/75R24.5/14	.556500	8.25	130	.28	42.0	11.1	19.5	.6175	.5675	.110	.110	.494		
11R22.5/14	.556520	8.25	129	.28	42.0	11.1	19.5	.6175	.5840	.105	.105	.494		
11R22.5/16	.556530	8.25	129	.28	42.0	11.1	19.5	.6610	.6005	.120	.120	.494		
11R24.5/14	.556460	8.25	138	.28	44.0	11.1	20.4	.6610	.6005	.105	.105	.471		
11R24.5/16	.556470	8.25	138	.28	44.0	11.1	20.4	.7160	.6610	.120	.120	.471		

Designed for long haul, over-the-highway service. Ideal tire for fleets that require resistance to irregular wear that occurs with deep lug tractors. Features DSOC II Technology.

TOYO M-605Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
12R22.5/16	555280	9.00	142	29	43.2	11.6	20.1	7390	6780	120	120	483		\$

TOYO M-608Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
225/70R19.5/12	556070	6.0-6.75	.72	20	32.3	8.3	15.0	3640	3415	95	95	642		\$
245/70R19.5/14	556040	7.50	.79	19	33.2	9.4	15.4	4540	4300	110	110	624		
9R22.5/14	556000	6.75	.85	19	38.3	8.9	17.8	4940	4675	120	120	542		
NEW 225/70R19.5	556100	6.00-6.75	.72	20	32.3	8.3	15	3970	3750	110	110	642		
NEW 285/70R19.5/16	556120													

TOYO M-1090Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBE TYPE														
8.25R15/14	520301	6.5	.71	15	33.1	9.1	15.4	4080	3580	120	120	627		\$
8.25R15/18	520401	6.5	.71	15	33.1	9.1	15.4	6010	5675	125	125	627		
10.00R15/14	520701	7.5	.91	16	35.8	10.8	16.7	5070	4805	105	105	579		
10.00R15/18	520711	7.5	.92	16	35.8	10.8	16.7	6945	6395	125	125	579		

Rugged, low-platform trailer for maximum wear. Specifically constructed for high load capacity in high-cube trailer applications. Features DSOC II Technology.

TOYO M-320Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
11R22.5/16	549010	7.5-8.25	.131	23	41.8	11.1	19.4	6610	6005	120	120	497		\$
11R24.5/16	549020	7.5-8.25	.138	23	43.8	11.1	20.4	7160	6610	120	120	474		
315/80R22.5/20	549050	9.00-9.75	.158	23	43.0	12.3	20.0	10000	8255	130	130	483		
12R22.5/16	549060	8.25-9.00	.144	23	42.8	11.6	19.9	7390	6780	120	120	485		
NEW 385/65R22.5	549070	11.75-12.25	.169	22	42.6	14.8	19.8	9370		120		487		
NEW 425/65R22.5/20	549090		.195	23					11400		120			

The M-320Z is perfect for such applications as logging, mining, concrete mixers and refuse trucks. Features DSOC II Technology.

TOYO M-503Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
TUBELESS														
11R22.5/16	549100	8.25	.127	26	42.0	11.1	19.5	6610	6005	120	120	494		\$

The M-503Z is perfect for short and medium on/off-road applications. The 26/32" deep tread makes this lug radial an aggressively effective tire on muddy and slippery road conditions. Features DSOC II Technology.

TOYO M-506Z

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
11R22.5/16***	.549280	8.25	134	30	42.2	11.1	19.6	.6610	.6005	120	120	.492		\$
11R24.5/16***	.549300	8.25	146	30	44.3	11.1	20.6	.7160	.6610	120	120	.469		

***Speed restriction of 55mph for urban use only, not be used on Highway application.

Premium extra deep tread drive axle radial for severe on/off-road applications. The 30/32" deep, cut resistant tread makes it the ideal tire for logging, construction or other severe service where muddy, slippery and abrasive surfaces are common. Features DSOC II Technology.

TOYO M154

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
NEW 245/75R22.5/14	.548770		89.29	18.8	36.96			.4675		.110				\$
NEW 265/75R22.5/14	.548760		99.21	18.8	36.4			.5205		.110				
295/75R22.5/14	.548700	8.25-9.00	118	22	40.4	11.1	18.8	.6175	.5675	110	110	.514		
295/75R22.5/16	.548780													
11R22.5/14	.548720	7.50-8.25	122	22	41.5	11.1	19.3	.6175	.5840	105	105	.500		
11R22.5/16	.548730	7.50-8.25	123	22	41.5	11.1	19.3	.6610	.6005	120	120	.500		
285/75R24.5/14	.548710	8.25	120	22	41.5	10.8	19.3	.6175	.5675	110	110	.501		
11R24.5/14	.548740	7.50-8.25	131	22	43.5	11.1	20.2	.6610	.6005	105	105	.477		
11R24.5/16	.548750	7.50-8.25	132	22	43.5	11.1	20.2	.7160	.6610	120	120	.477		



e-balance profile minimizes growth of the tread profile and maintains uniform and flatter tread radius for the entire life of the casing. e-balance design provides even contact pressure distribution across the tread surface resulting in smooth wear and long life.

TOYO M647 PREM DVR CLSD SHLD

Medium Truck Radial



Tire Size	Code #	Rim Width	Tire Weight	Tread Depth	Overall Diameter	Overall Width	Loaded Radius	MAX LOAD		MAX PSI		Rev Mile	PRICE	F.E.T.
								Single	Dual	Single	Dual			
295/75R22.5/14 G	65434		120	29.7				.6175	.5675	110	110			\$

WE ARE YOUR SUPPLIER

NOT YOUR COMPETITOR