



# YOKOHAMA

## ADVAN

### YOKOHAMA ADVAN S.T. High Performance Radial



#### UTQG 320 AA A

The fastest SUV tires

- Aggressive unidirectional tread design for exceptional acceleration and braking.
- Large shoulder blocks for ultra-high performance handling.
- Race-bred technology provides outstanding cornering.
- Load-rated and available in W- and V-speed ratings.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
225/55R17 101W	80203	28.90	7.0	6.0 - 8.0	9.1	26.7	7.7	10	1819@50	\$
235/55R17 103W	80233	31.10	7.5	6.5 - 8.5	9.5	27.2	8.0	10	1929@50	
235/65R17 108W	80201	32.90	7.0	6.5 - 8.5	9.4	29.0	7.1	10	2205@50	
255/50R17 101W	80205	31.90	8.0	7.0 - 9.0	10.3	27.1	8.9	10	1819@51	
255/60R17 100W	80202	35.75	7.5	7.0 - 9.0	10.2	29.0	8.1	10	2337@50	
275/55R17 109W	80204	38.50	8.5	7.5 - 9.5	11.1	28.9	9.4	11	2271@51	
235/50R18 101W	80210	31.20	7.5	6.5 - 8.5	9.6	27.4	8.2	10	1819@50	
235/55R18 100W	80207	31.80	7.5	6.5 - 8.5	9.6	28.1	8.0	10	1764@51	
235/60R18 107W	80206	33.20	7.5	6.5 - 8.5	9.8	29.1	7.5	10	2149@50	
255/45R18 103W	80234	32.60	8.5	8.0 - 9.5	10.0	27.1	9.4	10	1929@50	
255/55R18 109W	80208	34.76	8.0	7.0 - 9.0	10.6	28.9	8.7	10	2271@50	
285/50R18 109W	80211	39.90	9.0	8.0 - 10.0	11.6	29.2	10.0	11	2271@51	
285/55R18 113W	80209	40.60	9.0	8.0 - 10.0	11.7	30.3	9.7	11	2535@51	
245/50R19 105W	80212	32.15	8.0	7.0 - 8.5	10.1	28.7	8.6	10	2039@50	
255/50R19 107W	80213	36.86	8.0	7.0 - 9.0	10.4	29.1	8.9	10	2149@50	
255/55R19 107Y*	80238	37.40	8.0	7.0 - 9.0	10.4	30.1	8.7	10	2149@51	
275/45R19 108Y	80231	35.90	9.0	8.5 - 10.5	10.8	28.8	10.3	10	2205@50	
285/45R19 107W	80214	39.60	9.5	9.0 - 10.5	11.4	29.1	10.5	11	2149@51	
295/45R19 109W	80215	40.80	10.0	9.5 - 11.0	12.0	29.6	10.8	10	2271@51	
245/45R20 99Y***	80236	31.40	8.0	7.5 - 9.0	9.6	28.6	10.0	13.3	1709@51	
255/50R20 109Y***	80237	37.20	8.0	7.0 - 9.0	10.3	30.1	8.9	10	2271@50	
265/45R20 108Y**	80235	36.20	9.0	8.5 - 10.0	10.6	29.3	9.8	13.6	2205@50	
265/50R20 111W	80216	38.80	8.5	7.5 - 9.5	10.9	30.5	9.3	11	2403@50	
275/40R20 106Y	80221	35.70	9.5	9.0 - 11.0	10.9	28.7	10.3	10	2094@50	
275/45R20 110Y***	80240	37.50	9.0	8.5 - 10.5	10.9	29.7	10.3	10	2337@50	
275/50R20 113W	80217	40.80	8.5	7.5 - 9.5	11.2	30.9	9.6	11	2535@50	
285/45R20 112Y	80218	39.80	9.5	9.0 - 10.5	11.3	30.2	10.5	10	2469@50	
295/40R20 106Y	80222	40.80	10.5	10.0 - 11.5	12.2	29.4	10.9	10	2094@51	
295/45R20 114W	80219	42.70	10.0	9.5 - 11.0	11.9	30.4	10.9	11	2601@50	
305/45R20 116W	80220	43.10	10.0	9.5 - 11.5	12.2	30.8	11.3	11	2756@50	
315/35R20 110Y	80223	40.60	11.0	10.5 - 12.5	12.6	28.7	12.0	10	2337@50	
265/35R22 102Y***	80239	32.30	9.5	9.0 - 10.5	10.9	29.4	9.3	10	1874@50	
275/30R22 99Y	80226	35.50	10.0	9.0 - 10.0	11.3	28.6	10.4	10	1709@50	
295/30R22 103Y	80227	38.76	10.5	10.0 - 11.0	11.9	29.1	11.3	10	1929@50	
295/35R22 108Y	80225	40.50	10.5	10.0 - 11.5	11.8	30.1	11.2	10	2205@50	
305/40R22 114W	80224	46.20	11.0	10.0 - 12.0	12.3	31.5	11.4	11	2601@50	
315/30R22 107Y	80228	42.78	11.0	10.5 - 11.5	12.2	29.5	11.8	10	2149@50	
305/35R24 112W	80230	46.50	11.0	10.0 - 12.0	12.3	32.4	11.4	11	2469@50	

\*Available 1st Qtr    \*\*Available 2nd Qtr    \*\*\*Available 3rd Qtr

visit us at:



# TDW ONLINE.NET

OPEN 24 HRS / 7 DAYS A WEEK



## UTQG 180 AA A

Yokohama's flagship ultra-high performance tire.

- New tread compound maximizes wet and dry grip.
- Block and groove configuration of the asymmetric tread pattern enables unsurpassed handling in wet and dry conditions.
- Introduced 4th quarter 2005.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
205/50ZR17 93Y	10102	22.53	6.5	5.5 - 7.5	8.4	25.1	7.0	10	1433@50	\$
205/55ZR17 91Y	10101	23.42	6.5	5.5 - 7.5	8.4	25.8	7.0	10	1356@51	
215/45ZR17 91Y	10170	22.5	7.0	7.0 - 8.0	8.5	24.5	7.7	10	1356@50	
225/45ZR17 94Y	10104	24.03	7.5	7.0 - 8.5	9.1	24.9	8.0	10	1477@50	
225/50ZR17 98Y	10172	24.9	7	6.0-8.0	9.3	25.8	7.8	10	1653@50	
<b>NEW</b> 225/55R17 101Y	10176	25.9	7	6.0-8.0	9.2	26.7	7.9	10	1819@50	
235/45ZR17 97Y	10106	24.25	8.0	7.5 - 9.0	9.5	25.3	8.4	10	1609@50	
235/50ZR17 96Y	10103	25.79	7.5	6.5 - 8.5	9.6	26.3	8.2	10	1565@51	
235/55ZR17 103Y	10175	27.0	7.5	6.5 - 8.5	9.8	27.1	8.2	10	1929@50	
245/40ZR17 91Y	10107	24.25	8.5	8.0 - 9.5	9.9	24.6	8.7	10	1356@51	
<b>NEW</b> 245/45ZR17 99Y	10173	22.5	8	7.5-9.0	9.6	25.5	8.4	10	1709@50	
255/40ZR17 94Y	10108	24.91	9.0	8.5 - 10.0	10.4	24.9	9.1	10	1477@51	
215/45ZR18 89Y	10109	21.61	7.0	7.0 - 8.0	8.5	25.6	7.7	10	1279@51	
225/40ZR18 92Y	10113	22.05	8.0	7.5 - 9.0	9.1	25.1	8.0	10	1389@50	
235/40ZR18 95Y	10114	23.38	8.5	8.5 - 9.5	9.9	25.4	8.1	10	1521@50	
<b>NEW</b> 235/45R18 98Y	10394									
245/35ZR18 92Y	10119	22.93	8.5	8.0 - 9.5	9.8	24.7	8.9	10	1389@50	
245/40ZR18 97Y	10127	23.09	8.5	8.0 - 9.5	9.7	25.6	8.7	10	1609@50	
245/45ZR18 (100Y)	10111	26.01	8.0	7.5 - 9.0	9.7	26.7	8.7	10	1929@50	
255/35ZR18 94Y	10120	23.81	9.0	8.5 - 10.0	10.3	24.9	9.2	10	1477@50	
255/40ZR18 (99Y)	10115	25.35	9.0	8.5 - 10.0	10.3	26.0	9.1	10	1709@50	
255/45ZR18 (103Y)	10112	27.56	8.5	8.0 - 9.5	9.1	27.0	9.1	10	1929@50	
255/55R18 109Y	10177	34.8	8.0	7.0 - 8.0	10.6	28.9	8.3	11	2271@50	
265/35ZR18 97Y	10121	24.25	9.5	9.0 - 10.5	10.7	25.4	9.7	10	1609@50	
265/40ZR18 (101Y)	10116	27.56	9.50	9.0 - 10.5	10.9	26.3	10.0	10	1819@50	
275/35ZR18 95Y	10122	26.34	9.5	9.0 - 11.0	11.0	25.5	10.0	10	1521@51	
275/40ZR18 (103Y)	10117	28.00	9.5	9.0 - 11.0	11.0	26.7	9.8	10	1929@50	
285/30ZR18 (97Y)	10124	26.24	10.0	9.5 - 10.5	11.4	24.8	10.3	10	1609@50	
285/35ZR18 (101Y)	10123	27.56	10.0	9.5 - 11.0	11.4	25.9	10.3	10	1819@50	
285/40ZR18 (101Y)	10118	29.32	10.0	9.5 - 11.0	11.6	26.9	10.1	10	1819@51	
295/30ZR18 (98Y)	10125	28.00	10.5	10.0 - 11.0	11.7	25.0	10.7	10	1653@50	
315/30ZR18 (98Y)	10126	30.26	11.0	10.5 - 11.5	12.5	25.4	11.5	10	1653@51	
225/35ZR19 (88Y)	10169	23.1	8.0	7.5 - 9.0	9.2	25.2	8.1	10	1235@50	
225/40ZR19 (93Y)	10130	24.47	8.0	7.5 - 9.0	9.2	26.1	8.0	10	1433@50	
235/35ZR19 (91Y)	10134	23.59	8.5	8.0 - 9.5	9.5	25.5	8.5	10	1356@50	
235/40ZR19 (92Y)	10174	25.63	8.5	8.0 - 9.5	9.6	26.3	8.3	10	1389@51	
235/45ZR19 (95Y)	10128	26.90	8.0	7.5 - 9.0	9.4	27.3	8.4	10	1521@51	
245/30ZR19 (89Y)	10140	23.15	8.5	8.0 - 9.0	9.8	24.8	8.9	10	1279@50	
245/35ZR19 (93Y)	10135	24.47	8.5	8.0 - 9.5	9.8	25.8	8.9	10	1433@50	
245/40ZR19 (98Y)	10131	26.46	8.5	8.0 - 9.5	9.8	26.7	8.7	10	1653@50	
245/45ZR19 (98Y)	10129	27.56	8.0	7.5 - 9.0	9.6	27.7	8.7	10	1653@51	
255/30ZR19 (91Y)	10145	24.25	9.0	8.5 - 9.5	10.2	25.1	9.2	10	1356@50	
255/35ZR19 (96Y)	10136	26.46	9.0	8.5 - 10	10.1	26.1	9.3	10	1565@50	
255/40ZR19 (100Y)	10132	27.78	9.0	8.5 - 10.0	10.2	27.2	9.1	10	1764@50	
265/30ZR19 (93Y)	10141	25.13	9.5	9.0 - 10.0	10.7	25.4	9.6	10	1433@50	
265/35ZR19 (94Y)	10137	27.78	9.5	9.0 - 10.5	10.7	26.3	9.6	10	1477@51	
275/30ZR19 (96Y)	10143	26.68	9.5	9.0 - 10.0	10.8	25.6	10.0	10	1565@50	
275/35ZR19 (100Y)	10138	29.19	9.5	9.0 - 11.0	11.0	26.5	10.1	10	1764@50	
275/40ZR19 (105Y)	10133	30.86	9.5	9.0 - 11.0	11.2	27.7	9.8	10	2039@50	
285/30ZR19 (98Y)	10144	27.78	10	9.5 - 10.5	11.4	25.8	10.3	10	1653@50	
285/35ZR19 (99Y)	10139	29.10	9.5	9.0 - 11.0	11.0	26.5	10.1	10	1764@50	
295/30ZR19 (100Y)	10142	29.54	10.5	10.0 - 11.0	11.6	26.0	10.9	10	1764@50	
305/30ZR19 (102Y)	10146	30.64	11.50	10.5 - 11.5	12.7	26.1	11.4	10	1874@50	
315/25ZR19 (94Y)	10147	28.66	11.5	11.0 - 12.0	12.6	25.2	11.6	10	1477@51	
235/30ZR20 (88Y)	10171									
245/30ZR20 (90Y)	10149	24.25	8.5	8.0 - 9.0	9.6	25.9	9.0	10	1323@50	
245/35ZR20 (95Y)	10150	26.01	8.5	8.0 - 9.5	9.9	26.8	8.9	10	1521@50	
245/40ZR20 (99Y)	10148	28.07	8.5	8.0 - 9.5	9.8	27.8	8.7	10	1709@50	
255/30ZR20 (92Y)	10153	25.79	9.0	8.5 - 9.5	10.2	26.1	9.2	10	1389@50	
255/35ZR20 (97Y)	10151	27.78	9.0	8.5 - 10.0	10.3	27.0	9.3	10	1609@50	
275/30ZR20 (97Y)	10154	28.22	9.5	9.0 - 10.0	10.9	26.5	10.0	10	1609@50	
275/35ZR20 (102Y)	10152	30.86	9.5	9.0 - 11.0	11.2	27.6	10.0	10	1874@50	
285/25ZR20 (93Y)	10157	27.12	10.5	10.5 ONLY	11.4	25.6	10.5	10	1433@50	
285/30ZR20 (99Y)	10155	29.36	10.0	9.5 - 10.5	11.3	26.8	10.5	10	1709@50	
295/25ZR20 (95Y)	10158	28.22	10.5	10.0 - 11.0	11.5	25.9	10.9	10	1521@50	
305/25ZR20 (97Y)	10159	29.25	11.0	10.5 - 11.5	12.2	26.1	11.2	10	1609@50	
245/35ZR21 (96Y)	10160	24.82	8.5	8.0 - 9.5	9.8	27.9	8.9	10	1565@50	
255/30ZR21 (93Y)	10162	27.07	9.0	8.5 - 9.5	10.2	27.2	9.2	10	1433@50	
255/35ZR21 (98Y)	10161	28.88	9.0	8.5 - 10.0	10.2	28.2	9.2	10	1653@50	
285/30ZR21 (100Y)	10163	31.09	10	9.5 - 10.5	11.3	27.9	10.3	10	1764@50	
295/25ZR21 (96Y)	10165	29.54	10.0	10.0 - 11.0	11.6	26.9	10.9	10	1565@50	
295/30ZR21 (102Y)	10164	31.52	10.5	10.0 - 11.0	11.9	28.1	10.7	10	1874@50	
255/30ZR22 (95Y)	10166	28.22	9.0	8.5 - 9.5	10.2	28.1	9.2	10	1521@50	
265/30ZR22 (97Y)	10167	28.88	9.0	9.0 - 10.0	11.1	28.4	9.6	10	1609@50	
295/25ZR22 (97Y)	10168	30.64	10.5	10.0 - 11.0	11.7	27.9	10.9	10	1609@50	
<b>O.E. Fitment on: AUDI S8 '07-'08, BENTLEY CONTINENTAL GT '05-'07, BENTLEY CONTINENTAL FLYING SPUR '05-'07, MERCEDES BENZ AMG C 63 '08, MERCEDES BENZ AMG CL 63/65 '08, MERCEDES BENZ AMG ML 63 '08, PORSCHE 911 CARRERA 4 '06-'08, PORSCHE CAYENNE '07-'08, VOLKSWAGEN TOUAREG '08</b>										
<b>NEW</b> 225/50R18 95W	10337	28.6	7	6.0-8.0	9.1	26.8	7.4	10	1521@51	
<b>NEW</b> 245/45R18 96W	10338	29.5	8	7.5-9.0	9.8	26.7	8.5	10	1565@51	
235/40ZR18 (91Y)	10322	24.91	8.5	8.0 - 9.5	9.8	25.3	8.1	10	1356@51	
295/35ZR18 (99Y)	10324	31.99	10.5	10.0 - 11.5	12.2	26.1	11.0	10	1709@51	
<b>NEW</b> 235/40R18 91Y	10333									
<b>NEW</b> 295/35R18 99Y	10334									
<b>NEW</b> 235/35ZR19 (91Y)	10134	23.59	8.5	8.0-9.5	9.5	25.5	8.5	10	1356@50	
<b>NEW</b> 255/30ZR19 (91Y)	10145	24.25	9.0	8.5-9.5	10.2	25.1	9.2	10	1356@50	
275/45ZR19 108Y XL	10191	35.05	9.0	8.5-10.5	10.8	28.8	10.2	10	2205@50	
265/35ZR20 99Y	10321	29.54	9.5	9.0 - 10.5	10.9	27.4	10.0	10	1709@50	
<b>NEW</b> 275/35ZR20	10330	29.94	9.5	9.0-11.0	10.9	27.6	10.1	10	2039@50	
275/40R20 106Y XL	10192	35.71	9.5	9.0-11.0	11	28.7	10.3	11	2094@50	
<b>NEW</b> 295/40ZR20 106Y	93214	37.7	10.5	10.0-11.5	11.9	29.4	10.3	10	2094@51	
295/35R21 107Y XL	10193	32.63	10.5	10.0-11.5	11.7	29	10.6	11	2149@50	

# YOKOHAMA ADVAN S.4.

# High Performance Radial



## UTQG 400 AA A

The ultimate balance of performance and all-season capabilities.

- Three circumferential grooves provides excellent water evacuation.
- Large shoulder blocks enhance cornering stability.
- Aqua cut tusk grooves remove water for all-season performance.
- The inside edge of the shoulder blocks form a wavy pattern to minimize uneven wear and tire noise.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
205/55R16 91W	.40310	22.05	6.5	5.5 - 7.5	8.3	25.0	7.2	10	1356 @ 51	\$
215/55R16 93W	.40317	23.37	7.0	6.0 - 7.5	8.9	25.4	7.6	10	1433 @ 51	
P215/60R16 94V	.40331	23.15	6.5	6.0 - 7.5	8.7	26.2	6.9	10	1477 @ 51	
225/50R16 92W	.40332	23.81	7.0	6.0 - 8.0	8.9	25.0	7.9	10	1389 @ 51	
225/55R16 95W	.40333	25.13	7.0	6.0 - 8.0	9.2	25.8	7.7	10	1521 @ 51	
225/60R16 98W	.40314	24.91	6.5	6.0 - 8.0	9.1	26.6	7.2	10	1653 @ 51	
205/50R17 93W	.40319	23.37	6.5	5.0 - 7.5	8.2	25.2	7.2	10	1433 @ 50	
215/45R17 87W	.40311	23.15	7.0	7.0 - 8.0	8.4	24.7	7.6	10	1201 @ 51	
225/45R17 94W	.40334	24.03	7.5	7.0 - 8.5	8.9	25.0	7.9	10	1477 @ 50	
225/50R17 94W	.40315	26.01	7.0	6.0 - 8.0	9.0	26.0	7.9	10	1477 @ 51	
225/55R17 97W	.40318	27.34	7.0	6.0 - 8.0	9.1	26.9	7.9	10	1609 @ 51	
235/45R17 94W	.40312	25.57	8.0	7.5 - 9.0	9.4	25.5	8.3	10	1477 @ 51	
235/50R17 96W	.40320	27.12	7.5	6.5 - 8.5	9.5	26.4	8.0	10	1565 @ 51	
245/40R17 91W	.40322	25.79	8.5	8.0 - 9.5	9.7	24.8	8.7	11	1356 @ 51	
245/45R17 95W	.40335	26.78	8.0	7.5 - 9.0	9.6	25.7	8.7	10	1521 @ 51	
255/40R17 94W	.40336	26.01	9.0	8.5 - 10.0	10.2	25.1	9.0	11	1477 @ 51	
225/40R18 92W	.40323	23.81	8.0	7.5 - 9.0	9.1	25.2	7.9	10	1389 @ 50	
235/40R18 91W	.40337	24.69	8.5	8.0 - 9.5	9.6	25.4	8.3	10	1356 @ 51	
245/40R18 93W	.40313	26.46	8.5	8.0 - 9.5	9.7	25.8	8.7	11	1433 @ 51	
245/45R18 96W	.40316	27.78	8.0	7.5 - 9.0	9.6	26.8	8.7	11	1565 @ 51	
245/50R18 100V	.40324	29.98	7.5	7.0 - 8.5	9.8	27.8	8.7	11	1764 @ 51	
255/35R18 90W	.40326	25.57	9.0	8.5 - 10.0	10.2	25.1	9.3	11	1323 @ 51	
255/45R18 99W	.40338	28.10	8.5	7.0 - 8.5	10.1	27.1	9.0	11	1709 @ 51	
265/35R18 93W	.40321	27.56	9.5	9.0 - 10.5	10.6	25.4	9.7	11	1433 @ 51	
265/40R18 101W	.40325	27.34	9.5	9.0 - 10.5	10.4	25.1	9.3	11	1819 @ 50	
275/35R18 99W	.40339	29.54	9.5	9.0 - 11.0	10.8	25.6	10.1	11	1709 @ 50	
245/45R19 98Y	.40327	28.88	8.0	7.5 - 9.0	9.7	27.6	8.7	11	1653 @ 51	
NEW 245/45R19 98W	.40340	28.60	8.0	7.5 - 9.0	9.7	27.6	8.7	11	1653 @ 51	
255/35R19 96Y	.40330	27.78	9.0	8.5 - 10.0	9.9	24.8	9.3	11	1565 @ 50	
255/40R19 100Y	.40328	28.66	9.0	8.5 - 10.0	10.3	27.0	9.0	10	1764 @ 50	
275/40R19 105Y	.40329	31.53	9.5	9.0 - 11.0	11.1	27.6	9.7	10	2039 @ 50	
NEW 275/40R19 105W	.40341	31.53	9.5	9.0 - 11.0	11.1	27.6	9.7	10	2039 @ 50	

# YOKOHAMA ADVAN A048

# D.O.T. Approved Racing Radial



The new level in DOT-approved race tire performance.

- Single block design ensures constant road contact.
- Rounded casing design provides predictable handling from straight-line sprints to high-speed cornering.
- State-of-the-art, race-ready compound delivers phenomenal grip under a broad temperature range.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
<b>M-COMPOUND</b>										
205/50R15 86V	.04807	18.78	6.5	5.5 - 7.5	8.5	23.0	8.2	6	1168 @ 51	\$
225/50R15 91V	.04808	22.03	7.0	6.0 - 8.0	9.3	23.7	9.1	6	1356 @ 51	
205/60R15 91H	.04806	20.87	6.0	5.5 - 7.5	8.2	24.6	8.1	6	1365 @ 51	
195/50R16 84W	.04840	19.71	6.0	5.5 - 7.0	8.0	23.7	7.8	6	1102 @ 51	
205/55R16 91W	.04839	22.53	6.5	5.5 - 7.5	8.4	24.9	8.2	6	1356 @ 51	
225/45R16 89W	.04842	21.62	7.5	7.0 - 8.5	8.9	23.8	8.8	6	1279 @ 51	
225/50R16 92W	.04841	24.04	7.0	6.0 - 8.0	9.1	24.9	9.0	6	1389 @ 51	
215/45R17 87W	.04843	22.79	7.0	7.0 - 8.0	8.5	24.6	8.3	6	1201 @ 51	
225/45R17 90W	.04844	23.36	7.5	7.0 - 8.5	9.0	24.8	8.8	6	1323 @ 51	
235/45R17 93W	.04845	24.82	8.0	7.5 - 9.0	9.3	25.2	9.0	6	1433 @ 51	
<b>MH-COMPOUND</b>										
195/50R16 84W	.04810	19.79	6.0	5.5 - 7.0	8.0	23.7	7.8	6	1102 @ 51	
205/55R16 91W	.04809	22.62	6.5	5.5 - 7.5	8.4	24.9	8.2	6	1356 @ 51	
225/50R16 92W	.04811	24.09	7.0	6.0 - 8.0	9.1	24.9	9.0	6	1389 @ 51	
225/45R16 89W	.04812	21.47	7.5	7.0 - 8.5	8.9	23.8	8.8	6	1279 @ 51	
215/45R17 87W	.04813	22.88	7.0	7.0 - 8.0	8.5	24.6	8.3	6	1201 @ 51	
225/45R17 90W	.04814	23.20	7.5	7.0 - 8.5	8.9	24.9	8.8	6	1323 @ 51	
235/45R17 93W	.04815	25.04	8.0	7.5 - 9.0	9.3	25.2	9.0	6	1433 @ 51	
245/40R17 91W	.04816	25.31	8.5	8.0 - 9.5	9.8	24.8	9.7	6	1356 @ 51	
255/40R17 94W	.04817	26.48	9.0	8.5 - 10.0	10.3	25.0	10.0	6	1477 @ 51	
225/40R18 88Y	.04801	22.88	8.0	7.5 - 9.0	9.1	25.0	8.5	6	1235 @ 51	
235/40R18 91Y	.04818	24.54	8.5	8.0 - 9.5	9.6	25.4	8.9	6	1356 @ 51	
265/35R18 93Y	.04802	25.95	9.5	9.0 - 10.5	10.7	25.2	10.3	6	1433 @ 51	
285/30R18 93Y	.04803	26.55	10.0	9.5 - 10.5	11.1	24.8	10.9	6	1433 @ 51	
295/30R18 94Y	.04819	27.01	10.5	10.0 - 11.0	11.6	24.9	11.1	6	1477 @ 51	
315/30R18 98Y	.04820	29.64	11.0	10.5 - 11.5	12.3	25.4	11.8	6	1653 @ 51	
<b>O.E. Fitment on: LOTUS ELISE SPORT 04-05</b>										
195/50R16 84W	.04804	18.66	6.0	5.5 - 7.0	8.0	23.6	7.8	6	1102 @ 51	
225/45R17 90W	.04805	21.09	7.5	7.0 - 8.5	8.9	24.9	8.8	6	1323 @ 51	



## UTQG 300 AA A

Introducing the S.drive, a bold new addition to the YOKOHAMA performance lineup. Packed with the latest technological advancements, the S.drive delivers extraordinary grip and handling. With 70 different sizes, the broadest range of sport sedans and coupes can experience the latest performance upgrade from YOKOHAMA.

### • Advanced Micro-Flexible Compound

Using nanotechnology, Yokohama engineers have developed a revolutionary silica-based compound that conforms to surface irregularities. By maximizing contact between the tire and road, enhanced grip in wet and dry conditions is achieved.

### • Variable Angled Grooves

Angled groove walls optimize contact with the road and provide enhanced traction when cornering.

### • Four Wide Circumferential Grooves

Quickly and efficiently evacuate water for enhanced wet traction.

### • Groove-in-Groove Technology

Tiny scores within the tire groove walls help to more effectively distribute stress loads and reduce uneven tire wear.

Tire Size	Code No.	Unit Weight (lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PSI	PRICE
NEW 185/55R14 80V	.01048	17.4	6	5.0-6.5	7.7	22	6.7	10	992	51	\$
NEW 185/55R15 82V	.1053	18.4	6	5.0-6.5	7.6	23	6.7	10	1047	51	
195/50R15 82V	.01044	18.7	6	5.5-7.0	7.8	22.7	7	10	1047	51	
195/55R15 85V	.01047	19.2	6	5.5-7.0	8	23.3	7	10	1135	51	
205/50R15 86V	.01056	20.9	6.5	5.5-7.5	8.4	23.1	7.4	10	1168	51	
205/55R15 88W	.01051	22.55	6.5	5.5-7.5	8.6	23.9	7.4	10	1235	51	
NEW 215/35R16 81W	.01073	18.7	7.5	7.0-8.5	8.6	21.9	7.7	10	1019	50	
195/40R16 80W	.01071	18.1	7	6.5-7.5	8.1	22.1	7	10	992	50	
195/45R16 84W	.01050	18.5	6.5	6.0-7.5	7.8	22.8	7	10	1102	50	
205/45R16 87W	.01046	18.5	6.5	6.0-7.5	7.8	22.8	7	10	1102	50	
205/50R16 87W	.01042	21.4	6.5	5.5-7.5	8.4	24	7.4	10	1201	51	
205/55R16 91W	.01041	23.96	6.5	5.5-7.5	8.6	24.8	7.4	10	1356	51	
215/40R16 86W	.01064	19.6	7.5	7.0-8.5	8.7	22.7	7.7	10	1168	50	
215/55R16 93W	.01083	25.13	7	6.0-7.5	9.1	25.2	7.7	10	1433	51	
NEW 175/50R16 77T	.01172	16.2	5.5	5.0-6.0	7	22.9	6.3	10	908	51	
225/50R16 92W	.01034	25.15	7	6.0-8.0	9.3	24.8	8.1	25.15	1389	51	
225/55R16 95W	.01033	25.95	7	6.0-8.0	9.3	25.7	8.1	10	1521	51	
195/40R17 81W	.01070	19.2	7	6.5-7.5	8.1	23.2	7	10	1019	50	
195/45R17 85W	.01063	20.1	6.5	6.0-7.5	7.8	23.9	7	10	1135	50	
205/40R17 84W	.01045	21.45	7.5	7.0-8.0	8.5	23.5	7.4	10	1102	50	
205/45R17 88W	.01131	22.05	7	6.5-7.5	8.2	24.3	7.4	10	1235	50	
205/50R17 93W	.01132	24.34	6.5	5.5-7.5	8.5	25.1	7.4	10	1433	50	
215/35R17 83W	.01072	19.6	7.5	7.0-8.5	8.6	22.9	7.7	10	1074	50	
215/40R17 87W	.01133	23.32	7.5	7.0-8.5	8.7	23.8	7.7	10	1201	50	
215/45R17 91W	.01134	24.56	7	7.0-8.0	8.5	24.7	7.7	10	1356	50	
215/50R17 95W	.01135	25.18	7	6.0-7.5	8.9	25.5	7.7	10	1521	50	
215/55R17 98W	.01136	26.79	7	6.0-7.5	9.1	26.3	7.7	10	1653	50	
225/35R17 86Y	.01067	20.5	8	7.5-9.0	9	23.1	8.1	10	1168	50	
225/45R17 91Y	.01040	22.5	7.5	7.0-8.5	9.1	24.8	8.1	10	1356	51	
225/50R17 98W	.01137	27.6	7	6.0-8.0	9.2	25.8	8.1	10	1653	50	
225/55R17 97Y	.01169	25.3	7	6.0-8.0	9.4	26.7	8.1	10	1609	51	
235/40R17 90Y	.01062	22.5	8.5	8.0-9.5	9.7	24.3	8.4	10	1323	51	
235/45R17 97W	.01138	26.37	8	7.5-9.0	9.4	25.3	8.4	10	1609	50	
235/50R17 100W	.01161	28.18	7.5	6.5-8.5	9.7	26.4	8.4	10	1764	50	
235/55R17 103W	.01162	29.98	7.5	6.5-8.5	9.8	27.1	8.4	10	1929	50	
245/40R17 91Y	.01170	24	8.5	8.0-9.5	9.9	24.6	8.8	10	1356	50	
245/45R17 99W	.01163	27.32	8	7.5-9.0	9.7	25.6	8.8	10	1709	50	
275/40R17 98W	.01164	29.72	9.5	9.0-11.0	11.1	25.7	9.8	10	1653	51	
205/40R18 86Y	.01061	20.5	7.5	7.0-8.0	8.5	24.4	7.4	10	1168	50	
215/35R18 84Y	.01057	20.4	7.5	7.0-8.5	8.5	23.9	7.7	10	1102	50	
215/40R18 89Y	.01065	21.6	7.5	7.0-8.5	8.7	24.7	7.7	10	1279	50	
225/35R18 87Y	.01068	21.4	8	7.5-9.0	9	24.2	8.1	10	1201	50	
225/40R18 92Y	.01055	22.5	8	7.5-9.0	9.2	25.1	8.1	10	1389	50	
225/45R18 95Y	.01087	23	7.5	7.0-8.5	9.1	25.8	8.1	10	1521	50	
235/40R18 95Y	.01032	22.9	8.5	8.0-9.5	9.7	25.3	8.4	10	1521	50	
245/35R18 92Y	.01069	23.1	8.5	8.0-9.5	9.7	24.7	8.8	10	1389	50	
245/40R18 97Y	.01077	24.1	8.5	8.0-9.5	9.9	25.7	8.8	10	1609	50	
245/45R18 100Y	.01086										
255/35R18 94Y	.01058	24.5	9	8.5-10.0	10.2	24.9	9.1	10	1477	50	
265/35R18 97Y	.01089	25.3	9.5	9.0-10.5	10.7	25.2	9.5	10	1609	50	
275/35R18 99Y	.01088	25.9	9.5	9.0-11.0	10.9	25.5	9.8	10	1709	50	
275/40R18 99Y	.01168	28	9.5	9.0-11.0	11.1	26.5	9.5	10	1709	51	
215/35R19 85Y	.01066	21.4	7.5	7.0-8.5	8.5	24.9	7.7	10	1135	50	
225/35R19 88Y	.01060	22.5	8	7.5-9.0	8.9	25.2	8.1	10	1235	50	
235/35R19 91Y	.01059	23.4	8.5	8.0-9.5	9.4	25.5	8.4	10	1356	50	
245/30R19 89Y	.01127	23.1	8.5	8.0-9.0	9.7	24.8	8.8	10	1279	50	
245/35R19 93Y	.01080	24.3	8.5	8.0-9.5	9.7	25.7	8.8	10	1433	50	
245/40R19 94Y	.01165	25.8	8.5	8.0-9.5	9.9	26.7	8.8	10	1477	51	
255/30R19 91Y	.01100										
255/40R19 96Y	.01166	27.4	9	8.5-10.0	10.4	26.9	9.1	10	1565	51	
265/30R19 93Y	.01078										
275/30R19 96Y	.01081										
275/35R19 96Y	.01167	27.9	9.5	9.0-11.0	10.9	26.5	9.8	10	1565	51	
225/35R20 90Y	.01074	23.6	8	7.5-9.0	8.9	26.3	8.1	10	1323	50	
245/35R20 95Y	.01039	25.8	8.5	8.0-9.5	9.8	26.7	8.8	10	1521	50	
245/40R20 99Y	.01038	27.7	8.5	8.0-9.5	8.5	27.7	8.8	10	1709	50	
255/30R20 92Y	.01085	26.1	9	8.5-9.5	10.1	26.1	9.1	10	1389	50	
255/35R20 97Y	.01036	28.4	9	8.5-10.0	10.2	27	9.1	10	1609	50	
275/30R20 97Y	.01075	27.4	9.5	9.0-10.0	10.7	26.5	9.8	10	1609	50	
275/35R20 102Y	.01076	29.4	9.5	9.0-11.0	10.9	27.5	9.8	10	1874	50	
285/30R20 99Y	.01037	29.8	10	9.5-10.5	11.2	26.8	10.2	10	1709	50	

# SUPER E-SPEC

# Ultra High Performance Radial



**UTQG 460 A A**

Tire Size	Code No.	Load ID	Unit Weight	Rim Width		Inflated Dimensions		Tread Width	Loaded Dimensions		Cold Inflation Pressure (lbs@psi)	Max. Load at Single	PRICE
				Meas.	Appr.	Overall Width	Overall Diameter		Tread	Static Radius			
185/65R15 88H	50112	SL	17.5	5.5	5.0-6.5	7.6	24.5	6	10	11.2	.848	1235@44	\$
195/65R15 91H	50115	SL	18.6	.6	5.5-7.0	.8	.25	6.3	10	11.4	.831	1356@44	
195/55R16 87V	50114	SL	19.1	.6	5.5-7.0	.7.9	24.4	6.8	10	11.3	.850	1201@44	
215/60R16 95V	50113												

- Advanced Construction & Compound Technology**  
 Orange Oil and other natural elements have combined to create an 80% petroleum free tire.
- Superior Wet/Dry Traction**  
 During Straight driving: special properties of Orange Oil work to ensure lower rolling resistance. During cornering and braking: compound generates heat quickly to deliver better grip.
- Advanced Inner Liner**  
 Lightweight liner that impedes escaping air molecules and contributes to reduced rolling resistance.
- 5-pitch Tread Variation & Variable Tread Sipes**  
 Break up pattern noise for extremely quiet ride and increased surface contact.
- Sound Deflection Sidewall**  
 Special sidewall grooves decrease road noise.

# YOKOHAMA ADVANS SPORT Z.P.S.

# Radial



**UTQG 180 AA A**

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
195/55RF16 87V	10182	24.53	.6	5.5-7.0	.8	24.4	6.5	10	1201@51	\$
205/55RF16 91W	10183	26.76	.6.5	5.5-7.5	.8.3	24.9	6.9	10	1356@51	
225/50RF16 92W	10186	28.33	.7	6.0-8.0	.9.1	24.9	7.8	10	1389@51	
205/45RF17 84V	10185	24.25	.7	6.5-7.5	.8.3	24.3	6.9	10	1102@51	
225/45RF17 91Y	10178	27.79	.7.5	7.0-8.5	.9	24.9	7.8	10	1356@51	
225/50RF17 94Y	10179	29.95	.7	6.0-8.0	.9.3	25.8	7.8	10	1477@51	
245/45RF17 95Y	10181	30.5	.8	7.5-9.0	.9.6	25.6	8.4	10	1521@51	
255/40RF17 94Y	10188	29.83	.9	8.5-10.0	10.3	24.9	8.4	10	1477@51	
225/40RF18 88Y	10184	26.67	.8	7.5-9.0	.9.3	25	7.8	10	1235@51	
245/40RF18 93Y	10180	30.87	.8.5	8.0-9.5	10	25.6	8.4	10	1433@51	
245/50RF18 100W	10187	36.32	.7.5	7.0-8.5	10	27.6	8.4	10	1764@51	
255/35RF18 90Y	10189	29.91	.9	8.5-10.0	10.4	24.9	8.4	10	1323@51	
275/35RF18 95Y	10190	32.52	.9.5	9.0-11.0	10.8	25.5	9	10	1521@51	

- Advan Sport Z.P.S. represents the ADVAN line's first runflat capable tire and follows the lead of the line's flagship, The ADVAN Sport.
- Rigid Sidewall Reinforcement**  
 Original low heat generating compound is designed to support your vehicle's weight during runflat operation.
  - Supportive Bead-Filler**  
 Exclusive bead filler delivers a comfortable ride at normal operation, and high rigidity under zero pressure conditions.
  - Durable Bead Wire**  
 Extra thick bead wire is placed in a hexagonal arrangement which allows for easier fitting to the rim and reduces the risk of bead unseating after loss of air pressure.
  - Nanotechnology Tread Compound**  
 Newest nanotechnology tread compound bonds super-fine, high-grade silica and polymers at the molecular level to increase flexibility, durability and contact area by approximately 10% for better wet and dry traction through a variety of temperature ranges.
  - Variable Round Grooves**  
 Are cut in round shape at different widths and angles, to prevent one-sided abrasion and maximize performance on wet surfaces.
  - Four Wide Circumferential Grooves**  
 Quickly and efficiently evacuate water for enhanced wet traction.
  - Groove In Groove Configuration**  
 Controls stress to improve handling and promotes even wear.

# YOKOHAMA AVS SPORT

# Radial



**UTQG 180 AA/A**

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
O.E. Fitment on: ASTON MARTIN VANQUISH '02-'08										
255/40R19 96Y	10253	28.79	.9	8.5-10.0	10.3	27	9.1	10	1565@51	\$
285/40R19 103Y	10254	32.43	1.0	9.5-11.0	11.5	27.9	10.2	10	1929@51	

- Y-shaped Tread Design**  
 Even groove distribution improves water drainage and increases rubber to road contact area.
- Zig-Zag Center Rib**  
 Increased rigidity or the center rib improves steering response and high speed stability.
- Shoulder Sub-Groove**  
 Improves water drainage while cornering.
- Super Silica Compound**  
 Yokohama compound technology improves wet grip without giving up wear or dry grip.
- New Casing Design**  
 Reduces "twisting" of the tread while cornering, improving comfort at the same time.

# PARADA

## YOKOHAMA PARADA SPEC-X

## High Performance Radial



### UTQG 420 A A

Aggressive design meets responsive control for SUVs.

- Reinforced shoulder blocks enhance cornering stability.
- Solid center ribs provide lateral stability for better handling.
- Deep central circumferential groove quickly expels water.
- Variable pitch technology reduces pattern noise and uneven wear.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
NEW 225/65R17 102H	.00251	29.00	6.5	6.0 - 8.0	8.9	28.6	6.9	11	1874@51	\$
NEW 225/60R18 100H	.00248	28.6	6.5	6.0 - 8.0	8.9	28.5	6.9	11	1764@51	
NEW 235/55R18 100V	.00250	28.66	7.5	6.5-8.5	9.6	28.1	7.6	11	1764@51	
NEW 235/60R18 103V	.00252	30.4	7	6.5 - 8.5	9.6	29.0	7.5	11	1929@51	
NEW 235/65R18 106H	.00256									
NEW 245/60R18 105V	.00253	32.88	7	7.0 - 8.5	9.8	29.5	7.8	11	2039@51	
235/55R19 101V	.00254	31.27	7.5	6.5 - 8.5	9.6	29.1	7.6	11	1819@51	
NEW 235/55R20 102V	.00257	32	7.5		9.6	30.2		11		
275/55R20 117V	.00231	39.90	8.5	7.5 - 9.5	10.9	31.9	9.0	11	2833@50	
265/50R20 111V	.00228	36.38	8.5	7.5 - 9.5	10.7	30.6	8.9	11	2403@50	
285/50R20 112V	.00229	40.37	9.0	8.0 - 10.0	11.5	31.3	9.5	11	2469@51	
305/50R20 120V	.00230	44.97	9.5	8.5 - 11.0	12.4	32.2	10.2	11	3086@50	
NEW 245/45R20 99V	.00247	29.9	8	7.5 - 9.0	9.5	28.7	8.4	11	1709@51	
NEW 245/50R20 102V	.00249	31.8	7.5	7.0-8.5	9.8	29.8	8.2	11	1874@51	
255/45R20 105V	.00225	32.19	8.5	8.0 - 9.5	9.9	29.1	8.8	11	2039@50	
NEW 255/50R20 109V	.00235	34.13	8	7.0 - 9.0	10.2	30.1	8.5	11	2271@50	
275/45R20 110V	.00226	34.83	9.0	8.5 - 10.5	10.6	29.9	9.4	11	2337@50	
295/45R20 114V	.00227	40.79	10.0	9.5 - 11.0	11.6	30.6	10.2	11	2601@50	
255/40R20 101V	.00224	31.09	9.0	8.5 - 10.0	10.1	28.1	8.9	11	1819@50	
NEW 275/40R20 106V	.00236	33.9	9.5	9.0 - 11.0	10.8	28.6	9.6	11	2094@50	
285/45R22 114V	.00222	39.72	9.5	9.0 - 10.5	10.9	32.2	9.8	11	2601@50	
305/45R22 118V	.00223	44.09	10.0	9.5 - 11.5	11.5	32.9	10.5	11	2910@50	
265/40R22 106V	.00220	35.94	10.0	9.0 - 10.5	10.6	30.5	9.3	11	2094@50	
NEW 285/40R22 110V	.00240	37.6	10	9.5 - 11.0	11.2	31.1	10	12	2337@50	
305/40R22 114V	.00221	41.67	11.0	10.0 - 12.0	12.2	31.7	10.7	11	2601@50	
NEW 255/30R22 95V	.00237	29.8	9	8.5-9.5	9.9	28.3	9.1	11	1524@50	
NEW 255/35R22 99V	.00238	30.5	9	8.5 - 10.0	10.2	29.1	8.9	11	1709@50	
265/35R22 102V	.00218	32.41	9.5	9.0 - 10.5	10.4	29.5	9.3	11	1874@50	
285/35R22 106V	.00219	36.6	10	9.5 - 11.0	11.0	30.1	10.0	11	2094@50	
265/30R22 97V	.00217	31.31	9.5	9.0 - 10.0	10.2	28.6	9.6	11	1609@50	
NEW 285/30R22 101V	.00239	33.1	10	9.5 - 10.5	11.1	28.9	10.3	11	1819@50	
NEW 325/50R22 116V	.00241									
285/40R23 111V	.00215	40.34	11.0	9.5 - 11.0	12.0	32.0	10.0	11	2403@50	
305/40R23 115V	.00216	44.09	11.0	10.0 - 12.0	12.2	32.7	10.7	11	2679@50	
285/35R23 107V	.00214	38.58	11.0	9.5 - 11.0	11.7	31.1	10.0	11	2149@50	
NEW 325/45R24 116V	.00243	51.4	11	10.0 - 12.0	12.8	35.4	11.2	12	275@50	
NEW 285/40R24 112V	.00242	40.39	10	9.5 - 11.0	11.7	33	10.0	12	2469@50	
295/35R24 110V	.00210	43.21	11.0	10.0 - 11.5	11.9	32.3	10.3	11	2337@50	
305/35R24 112V	.00211	43.87	11.0	10.0 - 12.0	12.1	32.7	10.7	11	2469@50	
315/35R24 114V	.00212	45.64	11.0	10.5 - 12.5	12.4	32.9	11.0	11	2601@50	
NEW 255/30R24 97V	.00244									
NEW 285/25R24 97V	.00245									
315/40R26 120V	.00234	52.25	11	10.5 - 12.5	12.5	35.8	11	12	3086@50	
325/35R28 120V	.00232	56.2	11.5	11.0 - 13.0	12.8	37	11.4	12	3086@50	
315/30R30 116V	.00233	57	11	10.5 - 12.5	12.3	38.7	11	12	2756@51	

## YOKOHAMA PARADA SPEC-2

## High Performance Radial



Bigger, badder, better street-tuner performance.

- Silica compound increases grip without sacrificing durability.
- Increased load capacity for more plus-size capabilities.
- 19" sizes take you to Plus Five fitments.
- Highest wet traction rating available: 300/AA/A UTQG.

Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
205/40R16 83V	.01211Y	19.87	7.0	7.0 - 8.0	8.3	22.4	7.7	10	1074@50	\$
205/45R16 83V	.01212Y	20.14	7.0	6.5 - 7.5	8.2	23.3	7.6	10	1074@44	
205/40ZR17 84W	.01213Y	20.25	7.5	7.0 - 8.0	8.4	23.5	7.7	10	1102@50	
205/45ZR17 84W	.01214Y	20.90	7.0	6.5 - 7.5	8.3	24.3	7.6	10	1102@44	
215/40ZR17 83W	.01215Y	21.71	7.5	7.0 - 8.5	8.7	23.9	8.1	10	1074@44	
215/35ZR18 84W	.01216Y	20.62	7.5	7.0 - 8.5	8.5	24.0	7.6	10	1102@50	
215/40ZR18 85W	.01217Y	22.20	7.5	7.0 - 8.5	8.7	24.9	8.1	10	1135@44	
225/35ZR18 83W	.01218Y	20.88	8.0	7.5 - 9.0	8.9	24.3	7.7	10	1074@44	
225/40ZR18 92W	.01219Y	22.63	8.0	7.5 - 9.0	9.1	25.1	8.3	10	1389@50	
215/35ZR19 85Y	.01220Y	21.70	7.5	7.0 - 8.5	8.5	25.0	7.6	10	1135@50	
225/35ZR19 88Y	.01221Y	22.77	8.0	7.5 - 9.0	9.2	25.3	7.8	10	1235@50	



## UTQG 560 A A

### 60,000 MILE WARRANTY

**Confident All-Season Performance**  
**Unibloc Shoulder & Tapered Center Rib** - Provide Enhanced stiffness for improved handling on wet and dry roads

**Angled Groove Walls & Adaptive 3D Sipes** - Help resist hydroplaning and maintain winter and water traction over the life of the tire.

**Long Treadlife**  
**Optimized Contact Patch** - Maximizes road contact for long, even wear while minimizing rolling resistance by reducing the friction of the cap compound

**Groove-In-Groove Technology** - Creates tiny slits inside groove walls to help distribute stress loads to reduce uneven wear and enhance stiffness

**Excellent Fuel Efficiency**  
**All-New Silica Compound** - Delivers Ultra-low rolling resistance for increased fuel efficiency, without sacrificing treadlife, comfort or grip on dry, wet or snow-covered roads

**Enhanced Comfort**  
**Six Pitch Tread Variation** - Separates the tread blocks into six size and shape variations, which are strategically staggered around the tire to reduce pattern noise

**Unique, All-New Profile** - is engineered to deliver a smooth, comfortable ride

Tire Size	Code No.	Load ID	Unit Weight	Rim Width		Inflated Dimensions			Loaded Dimensions		Max. Load at Cold Inflation Pressure		PRICE
				Meas.	Appr.	Overall Width	Overall Diameter	Tread Width	Tread Static Radius (inches)	Rev/Mile	Single (lbs@psi)		
<b>BLACKWALL</b>													
175/65R15 84H	32110	SL	17.73	5.0	5.0-6.0	6.9	24	5.1	10	11.0	865	1102@51	.. \$
185/65R15 88H	32111	SL	19.16	5.5	5.0-6.5	7.5	24.4	5.5	10	11.2	850	1235@51	
195/55R15 85V	32112	SL	18.81	6.0	5.5-7.0	7.9	23.5	6.2	10	10.8	884	1135@51	
195/60R15 88H	32113	SL	19.51	6.0	5.5-7.0	7.9	24.2	5.9	10	11.1	858	1235@51	
195/65R15 91H	32114	SL	20.19	6.0	5.5-7.0	7.8	25	5.8	10	11.4	831	1356@51	
205/60R15 91H	32115	SL	20.50	6.0	5.5-7.5	8.2	24.7	6.1	10	11.3	840	1356@51	
205/65R15 94H	32116	SL	21.39	6.0	5.5-7.5	8.2	25.5	6	10	11.6	815	1477@51	
195/55R16 87V	32117	SL	20.90	6.0	5.5-7.0	7.8	24.4	6.2	10	11.3	851	1201@51	
205/50R16 87V	32118	SL	21.21	6.5	5.5-7.5	8.4	24.1	6.9	10	11.2	861	1201@51	
205/55R16 91H	32119	SL	21.98	6.5	5.5-7.5	8.3	24.9	6.5	10	11.5	833	1356@51	
205/55R16 91V	32120	SL	21.98	6.5	5.5-7.5	8.3	24.9	6.5	10	11.5	835	1356@51	
205/60R16 92H	32121	SL	21.72	6.0	5.5-7.5	8.2	25.6	6.2	10	11.8	810	1389@51	
205/60R16 92V	32122	SL	21.74	6.0	5.5-7.5	8.3	25.7	6.2	10	11.8	808	1389@51	
215/55R16 97H	32123	XL	23.88	7.0	6.0-7.5	8.9	25.3	6.9	10	11.6	820	1609@51	
215/60R16 95H	32124	SL	22.66	6.5	6.0-7.5	8.6	26.1	6.2	10	12.0	794	1521@51	
215/60R16 95V	32125	SL	22.64	6.5	6.0-7.5	8.6	26.1	6.2	10	11.9	796	1521@51	
215/65R16 98H	32126	SL	24.25	6.5	6.0-7.5	8.7	27.1	6.3	10	12.3	767	1653@51	
225/50R16 92V	32127	SL	24.98	7.0	6.0-8.0	9.1	24.8	7.5	10	11.4	836	1389@51	
225/55R16 99V	32128	XL	24.87	7.0	6.0-8.0	9.1	25.7	7.1	10	11.8	808	1709@50	
225/60R16 98H	32129	SL	25.68	6.5	6.0-8.0	9	26.7	6.7	10	12.2	778	1653@51	
235/60R16 100H	32130	SL	26.79	7.0	6.5-8.5	9.4	27.1	7.1	10	12.3	766	1764@51	
205/45R17 84V	32131	SL	22.02	7.0	6.5-7.5	8.2	24.3	7	10	11.3	855	1102@51	
205/50R17 93V	32132	XL	24.19	6.5	5.5-7.5	8.3	25.1	6.9	10	11.7	828	1433@50	
215/45R17 87W	32133	SL	23.55	7.0	7.0-8.0	8.5	24.6	7.3	10	11.5	844	1201@51	
215/50R17 95V	32134	XL	25.51	7.0	6.0-7.5	8.9	25.5	7.2	10	11.8	815	1521@50	
215/55R17 94V	32135	SL	26.26	7.0	6.0-7.5	8.9	26.3	6.9	10	12.1	790	1477@51	
225/45R17 94H	32136	XL	25.31	7.5	7.0-8.5	8.8	25.1	7.7	10	11.7	828	1477@50	
225/45R17 94W	32137	XL	25.49	7.5	7.0-8.5	8.9	25	7.7	10	11.6	829	1477@50	
225/50R17 94V	32138	SL	26.61	7.0	6.0-8.0	9.2	26	7.5	10	12.0	799	1477@51	
225/55R17 97H	32139	SL	27.67	7.0	6.0-8.0	9.1	26.9	7.2	10	12.4	772	1609@51	
225/55R17 97V	32140	SL	27.82	7.0	6.0-8.0	9.1	26.8	7.2	10	12.3	775	1609@51	
225/60R17 99V	32141	SL	28.04	6.5	6.0-8.0	9	27.7	6.7	10	12.7	750	1709@51	
225/65R17 102H	32142	SL	28.20	6.5	6.0-8.0	8.9	28.5	6.5	10	13.0	729	1874@51	
235/45R17 97W	32143	XL	25.86	8.0	7.5-9.0	9.4	25.4	8	10	11.8	819	1609@50	
235/45R17 97H	32144	XL	25.82	8.0	7.5-9.0	9.3	25.5	8	10	11.8	815	1609@50	
235/50R17 96V	32145	SL	27.87	7.5	6.5-8.5	9.6	26.4	7.8	10	12.2	787	1565@51	
235/55R17 99W	32146	SL	29.17	7.5	6.5-8.5	9.6	27.2	7.5	10	12.5	763	1709@51	
235/55R17 99H	32147	SL	29.23	7.5	6.5-8.5	9.6	27.2	7.5	10	12.5	763	1709@51	
235/65R17 108H	32148	XL	30.78	7.0	6.5-8.5	9.4	29.1	6.9	10	13.2	715	2205@50	
245/40R17 95W	32149	XL	26.04	8.5	8.0-9.5	9.8	24.7	8.6	11	11.5	841	1521@50	
245/45R17 99W	32150	XL	27.38	8.0	7.5-9.0	9.6	25.7	8.3	11	11.9	809	1709@50	
215/45R18 89W	32151	SL	23.40	7.0	7.0-8.0	8.4	25.6	7.6	11	12.0	812	1279@51	
225/40R18 92W	32152	XL	25.35	8.0	7.5-9.0	9	25.1	8	10	11.8	828	1389@50	
225/45R18 95W	32153	XL	25.95	7.5	7.0-8.5	8.9	25.9	7.7	10	12.1	801	1521@50	
225/50R18 95W	32154	SL	26.00	7.0	6.0-8.0	9.2	26.9	7.5	11	12.4	774	1521@51	
225/55R18 98V	32155	SL	29.52	7.0	6.0-8.0	9.2	27.8	7.2	10	12.8	748	1653@51	
225/60R18 100H	32156	SL	29.61	6.5	6.0-8.0	8.9	28.7	6.7	10	13.2	725	1764@51	
235/40R18 95W	32157	XL	26.48	8.5	8.0-9.5	9.6	25.4	8.4	10	11.9	819	1521@50	
235/45R18 94W	32158	SL	27.25	8.0	7.5-9.0	9.3	26.4	8	10	12.3	787	1477@51	
235/50R18 97W	32159	SL	29.19	7.5	7.0-8.5	9.2	27.2	7.5	10	12.5	763	1709@51	
235/55R18 100V	32160	SL	30.62	7.5	6.5-8.5	9.6	28.2	7.5	10	13.0	736	1764@51	
235/60R18 107H	32161	XL	30.80	7.0	6.5-8.5	9.4	29.1	7.5	11	13.3	713	2149@50	
235/65R18 106H	32162	SL	32.43	7.0	6.5-8.5	9.4	30	7	10	13.7	692	2094@51	
245/40R18 97W	32163	XL	27.67	8.5	8.0-9.5	9.8	25.7	8.6	11	12.0	808	1609@50	
245/45R18 96W	32164	XL	28.90	8.0	7.5-9.0	9.6	26.7	8.3	11	12.4	779	1565@51	
245/60R18 105H	32165	SL	32.00	7.0	7.0-8.5	9.7	29.6	7.8	11	13.5	702	2039@51	
255/35R18 94W	32166	SL	26.90	9.0	8.5-10.0	10.2	26	9.1	11	12.1	799	1521@51	
255/40R18 95W	32167	SL	29.00	8.5	8.0-9.5	10	27	9	11	12.5	768	1929@50	
255/55R18 109V	32169	SL	27.10	9.5	9.0-10.5	10.5	25.4	9.4	11	11.9	819	1609@50	
265/35R18 97W	32170	XL	28.40	9.5	9.0-11.0	10.8	25.6	9.8	11	11.9	813	1521@51	
275/35R18 95W	32171	SL	24.30	8.0	7.5-9.0	9	26.1	8	11	12.2	797	1279@51	
225/40R19 89W	32172	SL	24.30	8.0	7.5-9.0	9	26.1	8	11	12.2	797	1279@51	
225/45R19 92W	32173	SL	25.80	7.5	7.0-8.5	8.7	27	7.9	11	12.6	770	1389@51	
245/40R19 94W	32174	SL	27.00	8.5	8.0-9.5	9.8	26.6	8.7	11	12.5	780	1477@51	
245/45R19 98W	32175	SL	28.20	8.0	7.5-9.0	9.6	27.6	8.6	11	12.9	751	1653@51	
245/45R20 99W	32176	SL	30.70	8.0	7.5-9.0	9.5	28.6	8.6	11	13.3	726	1709@51	
245/50R20 102V	32177	SL	33.10	7.5	7.0-8.5	10	29.6	8.2	11	13.8	701	1874@51	
265/50R20 107V	32178	SL	37.70	8.5	7.5-9.5	10.9	30.4	8.8	11	14.1	682	2149@51	

# AVID TOURING S

# Passenger Radial



## UTQG 620 A/B 65,000 LIMITED TREADWEAR WARRANTY

Built to deliver exceptional ride quality and stability, the AVID Touring-S affords a new level of confidence for the daily drive. Outfit your car or minivan with a set of the AVID Touring-S-Series. It's a decision you'll be more than comfortable with.

**Twin Rail Stability Rim** offers confident maneuverability and minimizes pattern noise.

**Silent Shoulder** uses extra sipes and variable tread block size to keep road noise low for a quiet, comfortable size.

**Cross Traction Sipes** create biting edges for better handling in wet or wintry conditions.

Tire Size	Code No.	Unit Weight(lb.)	Rim Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
P175/65R14 81S	31801	15.84	5.0	5.0-6.0	7	23.1	5.3	10	1019@51	\$
P185/65R14 85S	31802	17.82	5.5	5.0-6.5	7.4	23.5	5.6	10	1124@51	
<b>NEW</b> P235/75R15 105S	31821	30.64	6.5	6.0-8.0	9.2	28.9	6.2	11	2028@51	
P185/70R14 87S	31803	18.04	5.5	4.5-6.0	7.5	24.3	5.7	10	1201@51	
P195/70R14 90S	31804	18.7	6.0	5.0-6.5	8	24.8	6	10	1312@51	
P185/60R15 84T	31805	17.82	5.5	5.0-6.5	7.4	23.7	5.9	10	1102@51	
P185/65R15 86S	31806	18.26	5.5	5.0-6.5	7.4	24.4	5.6	10	1168@51	
P195/60R15 87T	31807	19.14	6.0	5.5-7.0	7.8	24.3	6.2	10	1190@51	
<b>NEW</b> P205/60R15 90T	31820	20.29	6.0	5.5-7.5	8.1	24.7	6.1	10	1301@51	
P195/65R15 89S	31808	19.63	6.0	5.5-7.0	8	25	5.9	10	1279@51	
P205/65R15 92S	31809	20.68	6.0	5.5-7.5	8.3	25.4	6.2	10	1400@51	
P205/70R15 95S	31810	22	6.0	5.0-7.0	8.2	26.4	6.5	10	1499@51	
P215/60R15 93T	31811	21.12	6.5	6.0-7.5	8.7	25.1	6.9	10	1411@51	
P215/65R15 95S	31812	21.78	6.5	6.0-7.5	8.9	25.9	6.7	10	1510@51	
215/70R15 98S	31813	23.76	6.5	5.5-7.0	8.9	26.9	6.9	10	1653@51	
P205/55R16 89T	31814	21.34	6.5	5.5-7.5	8.5	24.9	7	10	1279@51	
P205/60R16 91T	31815	21.34	6.0	5.5-7.5	8.2	25.6	6.5	10	1356@51	
P215/60R16 94T	31816	22.22	6.5	6.0-7.5	8.8	26.1	6.9	10	1477@51	
215/65R16 98T	31817	24.2	6.5	6.0-7.5	8.7	27	6.9	10	1653@51	
<b>NEW</b> 235/65R16 103T	31824	27.91	7.0	6.5-8.5	9.4	27.9	9.4	10	1929@51	
P225/60R16 97S	31818	24.64	6.5	6.0-8.0	9	26.6	7.2	10	1609@51	
<b>NEW</b> P215/70R16 99T	31822	25.96	6.5	5.5-7.0	8.7	27.8	6.1	10	1709@51	
<b>NEW</b> P235/70R16 104T	31823	29.6	7.0	6.0-8.0	9.3	28.9	9.3	11	1984@51	
<b>NEW</b> 225/55R17 97T	31827	27.29	7.0	6.0-8.0	9.1	26.8	7.2	10	1609@51	
<b>NEW</b> 215/60R17 96T	31825	25.88	6.5	6.0-7.5	8.6	27.2	6.5	10	1565@51	
P225/60R17 98T	31819	27.72	6.5	6.0-8.0	8.9	27.7	7.2	10	1653@51	
<b>NEW</b> 215/65R17 99T	31826	26.32	6.5	6.0-7.5	8.6	28.1	6.3	10	1709@51	
<b>NEW</b> 225/65R17 102T	31828	27.95	6.5	6.0-8.0	8.9	28.5	6.5	10	1874@51	
<b>NEW</b> 235/65R17 104T	31829	29.28	7.0	6.5-8.5	9.4	29	6.9	10	1984@51	

**Tapered Rain Channels** work in tandem with circumferential grooves to accelerate water evacuation for optional wet traction.

**Tri Plex Tread Compound** provides increased tread life and improved traction through a combination of advanced cap, base and butress compounds.

# YOKOHAMA AVID TRZ

# Passenger Radial



## 80,000 MILE LIMITED TREADWEAR WARRANTY

Pure Yokohama - asymmetrical all-season touring tire that delivers confidence.

- Three Ride Zones provide superior capabilities in all weather conditions.
- Four deep circumferential grooves work with sipes and grooves to quickly expel water.
- Adaptive sipes reduce block deformation and increase in length as tread wears for added dry and snow performance.

Tire Size	Code No.	Unit Weight(lb.)	Rim Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>BLACKWALL</b>										
P185/60R14 82T	31601	17.17	5.5	5.0-6.5	7.4	22.8	6.1	11	1047@44	\$
P185/65R14 85T	31603	17.86	5.5	5.0-6.5	7.4	23.5	6.0	11	1124@44	
P195/70R14 90T	31606	20.13	6.0	5.0-6.5	8.2	24.8	6.3	12	1312@44	
P185/60R15 84T	31602	18.53	5.5	5.0-6.5	7.4	23.8	6.1	11	1102@44	
P195/60R15 87T	31604	20.22	6.0	5.5-7.0	8.0	24.3	6.5	11	1190@44	
<b>NEW</b> P185/65R15 86T	31628	19.18	5.5	5.0-6.5	7.5	24.4	6.0	11	1168@51	
<b>NEW</b> P195/60R15 87H	31633	20.87	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P195/65R15 89T	31605	20.83	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
<b>NEW</b> 195/65R15 91H	31634	21.19	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
<b>NEW</b> 205/60R15 91H	31635	21.7	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P205/60R15 90T	31608	21.66	6.0	5.5-7.5	8.3	24.8	6.7	11	1301@44	
P205/65R15 92T	31610	22.48	6.0	5.5-7.5	8.3	25.5	6.6	11	1400@44	
<b>NEW</b> P205/65R15 92H	31636	22.49	6.0	5.5-7.5	8.3	25.5	6.6	11	1400@44	
P205/70R15 95T	31612	23.79	6.0	5.0-7.0	8.2	26.4	6.5	12	1499@44	
P215/60R15 93T	31614	23.70	6.5	6.0-7.5	8.7	25.2	7.1	12	1411@44	
P215/65R15 95T	31616	25.34	6.5	6.0-7.5	8.7	26.1	6.9	12	1510@44	
P215/70R15 98T	31618	25.73	6.5	5.5-7.0	8.8	27.0	6.9	12	1653@44	
<b>NEW</b> 205/60R16 91	31637	22.84	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P205/55R16 89T	31607	24.08	6.5	5.5-7.5	8.3	25.0	7.2	11	1279@44	
<b>NEW</b> P205/60R16 91H	31638	22.71	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P205/60R16 91T	31609	24.06	6.0	5.5-7.5	8.2	25.8	6.7	11	1356@44	
P205/65R16 94T	31611	24.27	6.0	5.5-7.5	8.3	26.6	6.6	11	1477@44	
<b>NEW</b> 215/55R16 93H	31639	23.38	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P215/55R16 91T	31613	24.93	7.0	6.0-7.5	8.9	25.4	7.5	12	1356@44	
<b>NEW</b> P215/60R16 94H	31640	24.89	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P215/60R16 94T	31615	25.49	6.5	6.0-7.5	8.7	26.2	7.1	12	1477@44	
P215/65R16 98T	31617	26.72	6.5	6.0-7.5	8.7	27.1	6.9	12	1653@44	
<b>NEW</b> 225/55R16 95H	31641	25.43	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P225/55R16 94T	31619	25.70	7.0	6.0-8.0	9.1	25.9	7.7	12	1477@44	
<b>NEW</b> 225/60R16 98H	31642	26.12	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
P225/60R16 98T	31621	27.03	6.5	6.0-8.0	9.0	26.7	7.3	12	1653@44	
P235/60R16 99T	31623	28.26	7.0	6.5-8.5	9.4	27.2	7.6	12	1709@44	
<b>NEW</b> P225/65R16 99H	31643	26.12	6.0	5.5-7.0	8.0	25.0	6.4	11	1279@44	
<b>NEW</b> P225/70R16 101T	31629	29.76	7	6.0-7.5	9.1	28.4	7	12	1819@51	
235/65R16 103T	31624	29.2	7.0	6.5-8.5	9.6	28.1	7.6	12	1929@51	
P215/60R17 95T	31625	27.23	6.5	6.0-7.5	8.7	27.3	7.1	12	1521@51	
P215/65R17 98T	31626	28.31	6.5	6.0-7.5	8.9	28.1	6.9	12	1653@51	
P225/55R17 95T	31620	27.72	7.0	6.0-8.0	9.1	26.9	7.7	12	1521@44	
P225/60R17 98T	31622	29.04	6.5	6.0-8.0	9.0	27.8	7.3	12	1653@44	
<b>NEW</b> P215/55R18 94T	31630	28	6.5	6.0-7.5	8.8	27.4	7.5	12	1477@51	
<b>NEW</b> P225/50R18 94T	31632	28.22	6.5	6.0-7.5	9.1	27	7.7	12	1744@51	
<b>NEW</b> P225/55R18 97T	31631	28.66	6.5	6.0-8.0	9	27.8	7.7	12	1609@51	

# GEOLANDAR

## GEOLANDAR A/T-S

## Light Truck Radial



**50,000 MILE WARRANTY  
ALL SIZES UNDER 20"  
EXCLUDING LOAD RANGE E**

**40,000 MILE WARRANTY  
ON SIZES 20" AND ABOVE  
AND LOAD RANGE E**

Featuring the newest technology for rugged all terrain performance, the Geolandar A/T-S is the right tire to fit your customers' on-and-offroad needs. Its new, long-lasting tread compound is engineered to deliver high mileage, promote even wear and reduce cutting and chipping without sacrificing wet or dry traction. When your customers demand a tire with superior on-and-offroad capabilities, look no further than the Geolandar A/T-S.

Tire Size	Code No.	Unit Weight(lb.)	Rim Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
205/70R15 96S	.01229	24.69	6.00	5.0 - 7.0	8.3	26.5	6.4	12	1565@51	\$
215/70R15 98S	.01261	26.24	6.5	5.5-7.0	8.8	26.9	6.7	12	165 @51	
P225/70R15 100S	.01258	29.10	6.5	6.0 - 7.5	9.1	27.6	7.0	12	1753@51	
P235/70R15 102S	.01245	31.09	7.0	6.0 - 8.0	9.6	28.0	7.3	13	1896@51	
P235/75R15 108S	.01235	34.17	6.5	6.0 - 8.0	9.3	28.9	7.3	13	2183@50	
265/70R15 112S	.01228	38.14	8.0	7.0 - 9.0	10.9	29.7	8.3	13	2469@51	
215/60R16 95H	.01259	25.13	6.5	6.0 - 7.5	8.7	26.1	6.7	12	1521@51	
215/65R16 98H	.01260	26.24	6.5	6.0 - 7.5	8.7	27.0	6.7	12	1653@51	
215/70R16 100S	.01224	28.00	6.5	5.5 - 7.0	8.6	28.0	6.7	12	1764@51	
225/70R16 102H	.01262	30.40	6.5	6.0-7.5	9.1	28.3	7	12	1874@51	
235/60R16 100H	.01253	28.22	7.0	6.5 - 8.5	9.4	27.0	7.3	12	1764@51	
P235/70R16 107S	.01239	33.73	7.0	6.0 - 8.0	9.5	29.2	7.3	13	2149@50	
P245/70R16 106S	.01236	34.83	7.0	6.5 - 8.0	9.8	29.7	7.6	13	2094@51	
255/65R16 109H	.01241	35.24	7.5	7.0 - 9.0	10.4	29.1	8.0	13	2271@51	
P255/70R16 109S	.01238	37.04	7.5	6.5 - 8.5	10.2	30.3	8.0	13	2271@51	
P265/70R16 111S	.01233	39.24	8.0	7.0 - 9.0	10.9	30.7	8.3	13	2403@51	
275/70R16 114S	.01240	42.67	8.0	7.0 - 9.0	10.9	31.4	8.6	13	2601@51	
225/60R17 99H	.01263	29.72	6.5	6.0-8.0	9.1	27.6	7	12	1709@51	
225/65R17 102H	.01266	31.09	6.5	6.0-7.5	9.1	28.5	7	12	1874@51	
225/70R17 108T	.01267	33.20	6.5	6.0-7.5	9.1	29.6	7	13	2205@50	
235/65R17 108H	.01247	33.73	7.0	6.5 - 8.5	9.4	29.2	7.3	13	2205@50	
P235/70R17 108S	.01268	36.20	7	6.0-8.0	9.5	30.3	7.3	13	2205@50	
245/65R17 107H	.01252	34.83	7.0	7.0 - 8.5	9.6	29.6	7.6	13	2149@51	
255/65R17 110H	.01250	36.60	7.5	7.0 - 9.0	10.2	30.3	8.0	13	2337@51	
P255/70R17 110S	.01269	40.10	7.5	6.5-8.5	10.2	31.3	8	13	2337@51	
265/65R17 112H	.01246	38.14	8.0	7.5 - 9.5	10.7	30.7	8.3	13	2469@51	
P265/70R17 113S	.01237	40.79	8.0	7.0 - 9.0	10.8	31.9	8.3	13	2535@51	
275/65R17 115H	.01248	41.45	8.0	7.5 - 9.5	11.0	31.3	8.6	13	2679@51	
<b>NEW</b> 285/65R17 116H BE	.01298	42.6	8.5	8.0-10.0	11.6	31.6	9.3	14	2756@51	
<b>NEW</b> 225/55R18 98H	.01300	28.50	7.00	6.0-8.0	9.10	27.80	7.30	12.00	1653@51	
P275/60R17 110S	.01264	43.70	8	7.5-9.5	11.1	30.1	8.6	13	2337@51	
265/60R18 110H	.01270	41.01	8	7.5-9.5	10.8	30.5	8.3	13	2337@51	
P265/70R18 114S	.01272	41.40	8	7.0-9.0	10.8	32.8	8.3	14	2601@51	
275/60R18 112H	.01271	41.90	8	7.5-9.5	11.1	31	8.6	12	2469@51	
<b>NEW</b> 285/60R18 116H BW	.01297	43	8.5	8.0-10.0	11.5	31.6	8.9	13	2756@51	
<b>NEW</b> 275/55R20 117S	.01278	41.25	8.50	7.5-9.5	11.00	32.00	9.00	13.00	2833@50	
<b>NEW</b> 275/60R20 115S	.01279	43.80	8.00	7.5-9.5	11.10	33.50	8.60	13.00	2679@51	
<b>NEW</b> 305/45R20 112H	.01242	44.97	10.00	9.5-11.5	11.70	31.10	10.90	13.00	2469@51	
<b>NEW</b> 305/50R20 120S	.01280	48.50	9.50	8.5-11.0	12.60	32.40	10.90	14.00	3086@50	
30X9.50R15/6	.01231	37.26	7.5	6.5 - 8.5	9.7	29.6	7.6	16	1985@50	
31X10.50R15/6	.01223	43.65	8.5	7.0 - 9.0	10.7	30.6	8.3	17	2270@50	
32X11.50R15/6	.01255	51.59	9	8.0-11.0	11.5	31.5	9.1	17	2535@50	
33X12.50R15/6	.01256	54.31	10	8.0-11.0	12.8	32.5	9.8	17	2205@35	
<b>NEW</b> LT215/75R15 100/97S	.01257	32.41	6	5.5-7.0	8.3	27.9	7.3	16	1985@50	
<b>NEW</b> LT235/75R15 104/101S	.01230	36.82	6.5	6.0-7.0	9.3	29.2	7.3	16	1985@50	
LT215/85R16/8	.01244	37.92	6.0	5.5 - 7.0	8.7	30.5	6.3	16	2335@65	
LT225/75R16/8	.01243	37.70	6.0	6.0 - 7.0	8.8	29.5	7.0	16	2335@65	
LT235/85R16/10	.01232	49.60	6.5	6.0 - 7.5	9.4	31.9	7.3	16	3042@80	
LT245/75R16/10	.01222	47.62	7.0	6.5 - 8.0	9.7	30.7	7.6	16	3042@80	
LT265/75R16/8	.01226	49.60	7.5	7.0 - 8.5	10.7	31.9	8.3	17	3000@65	
LT265/75R16/10	.01254	50.93	7.5	7.0-8.0	10.6	31.9	8.3	17	3415@80	
LT285/75R16/8	.01227	55.34	8.0	7.5 - 9.0	11.5	33.1	8.9	17	3305@65	
LT315/75R16/8	.01249	61.51	8.5	8.0 - 10.0	12.6	34.5	9.8	18	3195@50	
<b>NEW</b> LT235/80R17/10 E 120/117R BW	.01293	52.0	6.5	6.0-7.5	9.1	32.0	7.3	16	3085@80	
LT245/70R17/10	.01251	46.90	7	6.5-8.0	9.6	30.8	7.6	17	3000@80	
<b>NEW</b> LT245/75R17/10 E 121/118R BW	.01295	44.80	7.0	6.5-7.5	9.6	31.8	7.6	15	3195@80	
LT265/70R17/10	.01234	52.20	8	7.0-8.5	10.5	32	8.3	17	3195@80	
<b>NEW</b> LT285/70R17/8 D 121/118R BW	.01292	56.20	8.5	7.5-9.0	11.3	33.1	8.9	18	3195@65	
LT315/70R17/8	.01225	61.51	9.5	8.5 - 10	12.5	34.6	9.8	18	3195@50	
LT275/65R18/6	.01265	52.00	8	7.5-9.0	11.1	32.3	8.6	17	2535@50	
<b>NEW</b> LT275/65R18 123/120R	.01296	57.00	8.00	7.5-9.0	11.00	32.40	8.60	18.00	3415@80	
<b>NEW</b> 37X12.50R17/8	.01273	71.6	10	8.5-11.0	12.9	36.5	9.8	17	3525@50	
<b>NEW</b> LT285/65R18 121/118R	.01301	54.60	8.50	8.0-10.0	11.10	32.60	8.90	17.00	3195@65	
<b>NEW</b> LT325/60R20 121/118	.01303	69.40	9.50	9.0-12.0	13.00	35.70	10.60	17.00	3195@50	
<b>NEW</b> 37X12.50R18 123R	.01275	73.80	10.00	8.5-11.0	12.70	36.60	9.80	18.00	3415@50	
<b>NEW</b> 37X12.50R20 120R	.01276	73.30	10.00	8.5-11.0	12.20	36.70	9.80	18.00	3085@50	

Are You An Advantage Dealer?



The Best Associate Program on the Planet

# YOKOHAMA GEOLANDAR H/T-S

## Light Truck Radial



G051



G052



G053

### 60,000 MILE WARRANTY

#### Large Shoulder Blocks

- Provide strength and stiffness for outstanding cornering.

#### All-Season Capabilities

- Circumferential grooves enhance water evacuation, while cross grooves provide more biting edges for enhanced traction on snow and ice.

#### 30-Day Free Trial

- Test drive the Geolander HT-S for 30 days. If you're not satisfied, return them for a full refund.

Tire Size	Code No.	Unit Weight(lb.)	Rim Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>Standard Fitment (G051)</b>										
P235/75R15 108S	.05114	32.90	6.5	6.0-8.0	9.3	28.9	7.2	11	2183@41	\$
P265/70R15 110S	.05121	38.50	8.0	7.0-9.0	10.8	29.7	8.1	12	2337@35	
P265/75R15 112S	.05123	40.50	7.5	7.0-9.0	10.6	30.7	8.1	12	2469@35	
P215/70R16 99S	.05110	26.50	6.5	5.5-7.0	8.7	28.0	6.5	11	1709@35	
P225/70R16 101S	.05111	31.55	6.5	6.0-7.5	8.9	28.5	6.9	11	1819@35	
P225/75R16 106S	.05112	32.50	6.0	6.0-7.5	8.7	29.3	6.9	11	2094@50	
P235/70R16 104S	.05113	33.73	7.0	6.0-8.0	9.5	29.1	7.2	11	1984@35	
P265/70R16 111S	.05122	40.11	8.0	7.0-9.0	10.9	30.7	8.1	12	2403@35	
P235/75R16 109S	.05115	34.50	6.5	6.0-8.0	9.2	29.9	7.2	11	2271@41	
P245/70R16 106S	.05116	35.40	7.0	6.5-8.0	9.8	29.6	7.5	11	2094@44	
P245/75R16 109S	.05117	36.90	7.0	6.5-8.0	10.0	30.5	7.5	11	2271@35	
P255/65R16 106S	.05118	35.10	7.5	7.0-9.0	10.3	29.0	7.8	11	2094@51	
P255/70R16 112S	.05119	36.80	7.5	6.5-8.5	10.2	30.3	7.8	12	2469@41	
NEW P265/75R16 114T	.05134	30.86	7.5	7.0-9.0	10.7	31.7	8.1	11	2601@44	
P275/70R16 114S	.05124	41.50	8.0	7.0-9.0	11.0	31.3	8.4	12	2601@35	
P235/70R17 108S	.05127	38.81	7.0	6.0-8.0	9.5	30.2	7.2	11	2205@50	
P245/65R17 105S	.05128	33.62	7.0	7.0-8.5	9.8	29.4	7.5	11	2039@51	
P245/70R17 108S	.05129	40.47	7.0	6.5-8.0	9.8	30.6	7.5	11	2205@51	
P255/65R17 108S	.05130	40.70	7.5	7.0-9.0	10.3	30.0	7.8	11	2205@51	
P265/65R17 110S	.05132	42.37	8.0	7.5-9.5	10.7	30.4	8.1	11	2337@51	
P265/70R17 113S	.05101	42.50	8.0	7.0-9.0	10.7	31.8	8.1	12	2535@35	
P275/60R17 110H	.05102	37.60	8.0	7.5-9.5	11.1	29.9	8.7	12	2337@35	
P255/70R18 112S	.05131	41.08	7.5	6.5-8.5	10.3	32.2	7.8	12	2469@51	
P275/65R18 114H	.05133	41.59	7.5	7.5-9.5	10.3	32.2	8.4	12	2601@51	
LT215/75R15 100Q	.05105	31.68	6.0	5.5-7.0	8.5	27.8	6.5	13	1765@50	
LT235/75R15 104Q	.05107	34.59	6.5	6.0-7.0	9.4	29.1	7.2	14	1985@50	
LT225/75R16 110Q	.05106	38.92	6.0	6.0-7.0	8.8	29.4	6.9	13	2335@65	
LT265/75R16 119Q	.05108	45.67	7.5	7.0-8.0	10.6	31.8	8.1	14	3000@65	
LT285/75R16 122Q	.05109	50.92	8.0	7.5-9.0	11.5	33.0	8.7	15	3305@65	
LT245/70R17 114Q	.05125	38.14	7.0	6.5-8.0	9.8	30.9	7.5	14	2600@65	
LT315/70R17 121R	.05126	58.64	9.5	8.5-10.0	12.4	34.4	9.5	16	3195@50	
30X9.50R15 104Q	.05103	36.49	7.5	6.5-8.5	9.8	29.6	7.4	15	1985@50	
31X10.50R15 109Q	.05104	41.95	8.5	7.0-9.0	10.7	30.6	8.2	15	2270@50	
<b>Inch-up Fitment (G052)</b>										
235/65R17 108H	.05201	32.80	7.0	6.5-8.5	9.4	29.1	7.2	11	2205@50	
275/55R17 109H	.05204	41.10	8.5	7.5-9.5	11.1	28.9	9.4	12	2271@44	
255/55R18 109	.05202	37.71	8.0	7.0-9.0	10.4	29.1	8.7	11	2271@50	
265/60R18 110H	.05203	41.50	8.0	7.5-9.5	10.8	30.5	8.4	11	2337@44	
285/60R18 120H	.05205	42.07	8.5	8.0-10.0	11.5	31.4	9.1	11	3086@50	
P275/45R20 106H	.05206	39.61	9.0	8.5-10.0	10.8	29.7	10.0	11	2094@44	
NEW 285/50R20 112V	.05212	42.80	9.0	8.0-10.0	11.7	31.3	9.7	12	2469@44	
305/50R20 120H	.05208	46.72	9.5	8.5-11.0	12.5	32.1	10.3	12	3086@50	
P275/55R20 111H	.05211	42.79	8.5	7.5-9.5	11.1	32.0	9.4	11	2403@51	
305/45R22 118H	.05210	45.19	10.0	9.5-11.5	11.8	32.9	10.7	11	2910@50	
NEW 305/40R22 114H	.05209	43.96	11.0	10.0-12.0	12	31.6	11.1	12	2601@50	
<b>Load Range E Fitment (G053)</b>										
LT215/85R16 115Q	.05351	41.78	6.0	5.5-7.0	8.5	30.4	6.3	13	2680@80	
LT235/85R16 120Q	.05352	48.63	6.5	6.0-7.0	9.5	31.8	7.2	14	3042@80	
LT245/75R16 120Q	.05353	46.48	7.0	6.5-7.5	9.8	30.6	7.5	14	3042@80	
LT265/75R16 123Q	.05354	50.86	7.5	7.0-8.0	10.4	31.7	8.1	14	3415@80	
LT235/80R17 120/117Q (E)	.05356	46.65	6.0	6.0-7.5	9.1	31.7	7.2	14	3085@80	
LT245/70R17 119/116Q (E)	.05358	42.11	7.0	6.5-8.0	9.4	30.6	7.5	14	3000@80	
LT265/70R17 121/118Q (E)	.05357	50.06	8.0	7.0-8.5	10.4	31.6	8.1	14	3195@80	

# YOKOHAMA GEOLANDAR M/T+

## Light Truck Radial



#### Directional Tread Pattern

- Increases traction and improves self-cleaning abilities.

#### Step Block Groove Configuration

- Increases surface area and improves drainage.

#### Extra Sidewall Ribs

- Provides added protection.

#### Advanced Durable Tread Compound

- Resists cutting and chipping.

Tire Size	Code No.	Unit Weight(lb.)	Rim Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
<b>RIGHT</b>										
35X12.50R15 113Q	.00143	58.46	10.0	8.5-11.0	13.0	34.4	9.8	19	2535@35	\$
<b>ALL POSITION</b>										
LT265/75R16 112Q	.00146	47.43	7.5	7.0-8.0	10.6	31.9	8.3	17	2470@50	
NEW LT225/75R16 103/100S	.00198	34.18	6.00	6.0-7.0	8.80	29.40	7.00	16.00	1940@50	
LT285/75R16 116Q	.00147	51.65	8.0	7.5-9.0	11.5	32.9	8.9	17	2755@50	
LT305/70R16 118Q	.00145	57.22	9.0	8.0-9.5	12.5	33.2	9.5	18	2910@50	
LT315/75R16 113Q	.00148	64.67	8.5	8.0-10.0	12.0	34.6	9.8	19	2535@35	
LT265/70R17 112Q	.00144	50.14	8.0	7.0-8.5	10.9	32.0	8.4	17	2470@50	
NEW 30X9.50R15 104Q	.01501	37.30	7.5	6.5-8.5	9.8	29.7	7.6	18	1985@50	
NEW 31X10.50R15 109Q	.01502	43	8.5	7.0-9.0	10.8	30.6	8.3	18	2270@50	
NEW 33X12.50R15 108Q	.01503	51.8	10	8.5-11.0	12.6	32.6	10.4	19	2205@35	
NEW 35X12.50R17 119Q	.00189	61.7	10	8.0-11.0	12.8	34.6	9.8	17	3000@50	
NEW 37X12.50R17 124Q	.00165	71.6	10	8.5-11.0	13	36.7	9.8	17	3525@50	
NEW 38X13.50R17/8 119Q	.00190	79.34	11	8.5-11	13	37.7	10.6	21	3000@35	
NEW 40X13.250R17/6 121Q	.00191	85.5	11	8.5-11	13.4	39.7	10.6	21	3195@35	
NEW 38X13.50R18 126Q	.00192	83.30	11.00	8.5-11.0	13.40	37.80	10.60	21.00	3750@50	
NEW 40X13.50R18 124Q	.00193	88.88	11.00	8.5-11.0	14.00	39.70	10.60	21.00	3305@35	
NEW 35X12.50R20 121Q	.00197									
NEW 37X12.50R20 120Q	.00194	77.80	10.00	8.5-11.0	12.10	36.90	9.80	21.00	3085@50	
NEW 38X15.50R20 125Q	.00195	89.10	12.00	11.0-13.0	14.80	37.90	12.20	21.00	3640@50	
NEW 40X15.50R20 130Q	.00196	93.50	12.00	11.0-13.0	15.10	39.80	12.20	21.00	4190@50	

# YOKOHAMA RY215

## Light Truck Radial



Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
7.00R15/8	.21501	.31.9	.5.5	.5.0-6.5	.7.7	.29.4	.4.9	.13	.2040@65	..\$
7.00R16/12	.21505	.44.8	.6	.6.0-7.0	.8.4	.31.5	.5.5	.13	.3175@95	..\$

- **Tapered multi-kerf shoulder**  
Prolongs tread life and improves steering stability.
- **Wide Groove and deep kerfs**  
Disperse water more efficiently for wet-weather handling.
- **High Turn-up construction and bead filler**  
Reduce beadline cracking and improve responsiveness.
- **Polyester Carcass with steel belt**  
Increases durability.

# YOKOHAMA Y788R

## Light Truck Radial



Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
LT215/85R16/10	.78812	.41.64	.6	.5.5-7.0	.8.5	.30.4	.6.1	.13	.2680@80	..\$
LT235/85R16/10	.78809	.49.27	.6.5	.6.0-7.0	.9.3	.31.7	.7	.14	.3042@80	..\$

- Five-Rib tread design with wide shoulder grooves.
- High Density kerfs at center ribs.
- Wide shoulder ribs.
- Special Tread compound.
- Polyester carcass construction.
- Sturdy two-ply steel-belted construction.

# YOKOHAMA Y703B

## Light Truck Radial



Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
8R17.5/10	.70301	.42.42	.6	.5.25-6.75	.8.2	.31.3	.5.7	.18	.2790@80	..\$

- **Steel belted construction**  
Delivers versatile performance for motor homes or commercial vehicles.
- **Unique Tread design**  
Delivers outstanding mileage and excellent fuel economy.
- **Optimized All weather tread**  
Provides sure-footed mud and snow gripping traction.

# YOKOHAMA TY025

## Light Truck Radial



Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
7.50R16/14	.2501	.58.22	.6	.6	.8.2	.32	.5.5	.19	.3330@100	..\$

- **Wide shoulder Ribs**  
Add miles to tread life.
- **Straight five-rib tread design**  
Improves handling and ride comfort.
- **Computer - designed uniform profile**  
Maintains balanced dispersion of stress for easy rolling, longer life, and enhanced fuel economy.
- **Heavy duty two-ply steel belts**  
Deliver longer mileage and handling stability.
- **All-Steel construction**  
Improves original tread durability, and guards against punctures.

# YOKOHAMA Y356

## Light Truck Radial



Tire Size	Code No.	Unit Weight(lb.)	Rim Width Meas.	Width Approved	Overall Wd (In.)	Overall Dia. (In.)	Tread Wid. (In.)	Tread Depth (32/In)	Max Load (Lbs. @ psi)	PRICE
LT195/75R14/8	.35602	.23.27	.5.5	.5.0-6.0	.7.4	.25.8	.5.2	.11	.1710@65	..\$
LT185R14/6	.35601	.22.79	.5.5	.5.0-6.0	.7.3	.25.7	.5.3	.11	.1600@50	..\$
LT85R14/8	.35603	.24.28	.5.5	.5.0-6.0	.7.1	.25.7	.5.2	.11	.1850@65	..\$

- **Heavy-duty, Two Steel plus nylon belt edge construction**  
Delivers durability and a stable ride.
- **Three-groove tread block pattern**  
Produces a comfortable ride.
- **New Light truck tread compound**  
Prevents steel belt edge rise during high speeds.
- **Zig-Zag groove and three pitch variation block pattern**  
Reduces hydroplaning in rain for better high-speed traction.
- **Two-ply polyester carcass body construction**  
Reduces tire pattern noise during highway driving.

# YOKOHAMA RY587

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	58711	75	14G	11.4	39.8	13	18.5	6175@110	5675@110	101	\$	
11R22.5	58702	75	14G	10.9	41.0	13	12.0	6175@105	5840@105	107		
285/75R24.5	58703	75	14G	10.9	41.0	13	11.8	6175@110	5675@110	107		
11R24.5	58704	75	14G	10.9	43.0	13	12.0	6610@105	6005@105	115		



Highway Line Haul, Trailer Position

# YOKOHAMA RY103

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
NEW 215/75R17.5	10376		12F	8.1	30.2	16	8.8	3530@100	3420@100	55	\$	
NEW 215/75R17.5	10308		14	8.1	30.2	16	8.1	3750@105	3530@105	55		
245/75R22.5	10302	75	14G	9.7	37.3	17	10.4	4675@110	4300@110	85		
265/75R22.5	10304	75	14G	10.0	38.4	17	10.8	5205@110	4805@110	98		
275/70R22.5	10382	75	16H	10.8	37.7	17	11.6	6610@125	6175@125	108		

On-Highway/In-City, Low Profile, All Position

- Straight five-rib tread design with four grooves.
- Wide shoulder ribs reduce shoulder step wear.
- The 315/80R22.5ZDPR is specially designed for sanitation vehicle operations that require a high load carrying capacity per tire.

# 501ZA

## Medium Truck Radial



Tire Size	Code No.	Max Speed	Ply Rating	Overall Width	Inflated Dimensions			Max Load		Weight	PRICE
					Overall Diameter	Tread Depth	Section Width	Single	Dual		
11R22.5/16	75722		16		42.0	26	10.9	6610	6005	125.20	\$
11R24.5/14	75724		16		44.1	26	10.9	7160	6610	136.60	

On-and Off Highway Tire

# 104ZR

## Medium Truck Radial



Tire Size	Code No.	Max Speed	Ply Rating	Overall Width	Inflated Dimensions			Max Load		Weight	PRICE
					Overall Diameter	Tread Depth	Section Width	Single	Dual		
9R22.5/14	74731		14		38.1	17	9.1				\$
10R22.5/14	74732		14		40.1	18	10.0				
12R22/16	74733		16		42.7	20	11.8				
295/80R22.5/16	74734Y		16		41.6	20	11.9				

# 103ZR

## Medium Truck Radial



Tire Size	Code No.	Max Speed	Ply Rating	Overall Width	Inflated Dimensions			Max Load		Weight	PRICE
					Overall Diameter	Tread Depth	Section Width	Single	Dual		
295/75R22.5 14	73701		14	9.00	40.4	23	12.8	6175	5675	117.50	\$
295/75R22.5 16	73721		16	9.00	40.4	23	12.8	6610	6005	117.50	
11R22.5 14	73702		14	8.25	41.7	23	10.9	6175	5840	122.80	
11R22.5 16	73722		16	8.25	41.7	23	10.9	6610	6005	122.80	
285/75R24.5 14	73703		14	8.25	41.7	23	10.9	6175	5675	123.90	
11R24.5 14	68670		14	8.25	43.8	23	10.9	6610	6005	131.40	
11R24.5 16	73704		16	8.25	43.8	23	10.9	7160	6610	131.40	

Regional Steer Tire

# YOKOHAMA RY617

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	61701	75	14G	10.9	40.1	18	12.0	6175@110	5675@110	109	\$	
11R22.5	61702	75	14G	11.1	41.3	18	12.0	6175@105	5840@105	114		
285/75R24.5	61703	75	14G	10.8	41.3	18	11.8	6175@110	5675@110	112		
11R24.5	61704	75	14G	11.1	43.3	18	12.0	6610@105	6005@105	122		



- Highway line haul, all position tire.
- Five-rib tread design provides superior water channel dispersion and long tread life.
- 18/32" tread depth delivers extended removal mileage.

# YOKOHAMA RY023

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
NEW 215/75R17.5	02385	75	16H	8.5	30.6	16	9.1	4805@125	4540@125	63	\$	
NEW 235/75R17.5	02386	75	16H	9.4	31.7	16	10.0	6005@125	5675@125	71		
225/70R19.5	02389	75	12F	8.7	31.8	16	9.4	3640@95	3415@95	68		
245/70R19.5	02399	75	14G	9.7	33.3	16	10.4	4540@110	4300@110	80		
265/70R19.5	02398	75	14G	10.3	34.3	17	11.1	5070@110	4675@110	87		
285/70R19.5	02397	75	16H	11.1	35.1	17	12.1	6395@120	6005@120	96		
255/70R22.5	02387	75	16H	10.1	36.6	18	10.7	5510@120	5070@120	91		
295/75R22.5	02396	75	14G	11.1	40.2	19	12.1	6175@110	5675@100	114		
295/75R22.5	02391	75	16H	11.1	40.2	19	12.1	6610@120	6005@120	115		
11R22.5	02395	75	14G	10.8	41.4	19	12.0	6175@105	5840@105	117		
11R22.5	02392	75	16H	10.8	41.4	19	12.0	6610@120	6005@120	118		
285/75R24.5	02390	75	14G	10.9	41.4	19	11.8	6175@110	5675@100	117		
11R24.5	02393	75	14G	10.7	43.4	19	11.9	6610@105	6005@105	125		
11R24.5	02394	75	16H	10.7	43.4	19	11.9	7160@120	6610@120	125		
12R22.5	02388	75	16H	11.5	42.7	20	12.8	7390@120	6780@120	137		

Regional Highway, All Position

# YOKOHAMA TY527

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	52701	75	14G	11.1	41.0	32	12.1	6175@110	5675@110	131	\$	
11R22.5	52702	75	14G	10.9	42.4	32	12.0	6175@105	5840@105	136		
285/75R24.5	52703	75	14G	10.8	42.3	32	11.8	6175@110	5675@110	133		
11R24.5	52704	75	14G	11.0	44.4	32	12.0	6610@105	6005@105	142		

On-Highway, Line Haul, Drive-Axle

# YOKOHAMA TY577

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	57701	75	14G	11.4	40.9	30	12.4	6175@110	5675@110	129	\$	
11R22.5	57702	75	14G	10.9	42.3	30	12.0	6175@105	5840@105	135		
285/75R24.5	57703	75	14G	10.9	42.2	30	12.0	6175@110	5675@110	134		
11R24.5	57704	75	14G	10.9	44.3	30	12.0	6610@105	6005@105	144		

On-Highway, Line Haul, Drive-Axle

- Drive-axle radial for on-highway line haul operations.
- 30/32" deep groove depth provides extremely long wear.
- Funnel shaped groove wall provides enhanced traction while reducing stone retention.

# YOKOHAMA TY517

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	51701	75	14G	11.4	40.7	28	12.4	6175@110	5675@110	122	\$	
295/75R22.5	51721	75	16H	11.4	40.7	28	12.4	6610@120	6005@120	118		
11R22.5	51702	75	14G	11.1	42.0	28	12.0	6175@105	5840@105	126		
11R22.5	51722	75	16H	11.1	42.0	28	12.0	6610@120	6005@120	125		
285/75R24.5	51703	75	14G	10.9	42.0	28	11.9	6175@110	5675@110	126		
11R24.5	51704	75	14G	11.1	44.0	28	12.2	6610@105	6005@105	135		
11R24.5	51724	75	16H	11.1	44.0	28	12.2	7160@120	6610@120	133		

On-Highway, Line Haul, Drive-Axle

# YOKOHAMA TY303

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
225/70R19.5	30319	75	12F	8.7	32.0	20	9.4	3640@95	3415@95	72	\$	
265/70R19.5	30315	75	14G	10.3	34.4	21	11.2	5070@110	4675@110	90		
285/70R19.5	30316	75	16H	11.1	35.4	21	12.1	6395@120	6005@120	99		
255/70R22.5	30312	75	16H	10.0	37.0	24	10.8	5510@120	5070@120	98		

- Special tread compound generates fuel efficiency and long tread life.
- Advanced arrangement of shoulder lug grooves promotes flat, even treadwear.
- Mud and snow rated.

On-Highway, Drive-Axle

# YOKOHAMA 703ZL

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	77101	75	14G	11.4	40.9	32	12.5	6175@110	5675@110	130.19	\$	
11R22.5	77102	75	14G	11.0	42.3	32	12.1	6175@105	5849@105	134.04		
NEW 285/75R24.5	77103		14			32				134.37		
NEW 11R24.5	77104		14			32				142.22		

# YOKOHAMA TY287

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
225/70R19.5	28701	75	12F	8.7	32.9	19		3640@95	3415@95	72	\$	

- Original equipment tire for Isuzu NQR '03-04.
- Open shoulder block design provides increased wet and dry traction.
- Provides long, even wear over the life of the tire.

# YOKOHAMA LY053

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
11R22.5	05305	65	16H	10.7	42.2	31	11.6	6610@120	6005@120	140	\$	
11R24.5	05306	65	16H	10.9	44.2	31	11.7	7160@120	6610@120	150		

- Aggressive lug design with large blocks at tread center provides excellent traction and braking.
- Thick groove undertread protects against cuts for excellent retreadability.

On And Off-Highway, All Position

# YOKOHAMA MY507

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
255/70R22.5	50705	75	16H	10.0	36.8	20	10.8	5510@120	5070@120	94	\$	
275/70R22.5	50710	75	16H	10.9	38.1	22	10.8	6940@130	6395@130	118		
11R22.5	50702	65	16H	10.8	42.1	26	12.0	6610@120	6005@120	129		
11R24.5	50704	65	16H	10.9	44.1	26	12.1	7160@120	6610@120	138		



On And Off-Highway, All Position

# YOKOHAMA Y785R

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
NEW 8R17.5	78547		10E	8.4	31.3	13	9.0	2790@80	2460@80	40	\$	
9R17.5	78507	65	16H	9.1	33.0	15	9.8	4410@110	3970@110	68		
11R17.5	78526	65	16H	10.7	36.3	18	11.7	5675@120	5355@120	95		
9R22.5	78512	65	12F	8.9	38.1	15	9.7	4540@105	4300@105	84		
10R22.5	78525	75	14G	9.9	40.0	16	10.8	5675@115	5355@115	97		
8.25R15	78503	65	18J	9.1	33.0	15	10.0	4970@125	4830@125	70		
10.00R15	78551	60	18J	10.7	36.3	18	11.8	5905@125	5435@125	103		
NEW 7.50R16	78546		14G	8.2	31.5	14	8.9	3330@100	3175@100	52		

- Straight five-rib tread design with four wide grooves.
- Wide shoulder ribs reduce shoulder step wear.
- Extremely fuel-efficient.

On-Highway/In-City, Low Profile, All Position

# YOKOHAMA MY627W

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
315/80R22.5/20	62701		20	12.3	42.8	23	13.7	10000@130	8255@130	152.8	\$	

All Position

# YOKOHAMA RY083A

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
295/75R22.5	08307	75	14 G.	11.4	40.2	19	12.3	6175@110	5675@110	117	\$	
11R22.5	08333	75	14 G.	11.1	41.4	19	12.2	6175@105	5840@105	124		
285/75R24.5	08331	75	14 G.	10.9	41.4	19	11.7	6175@110	5675@110	121		
<b>NEW</b> 11R24.5	08332	75	14 G.	11.1	43.4	19	12.2	6610@105	6005@105	138		

# YOKOHAMA RY253

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
385/65R22.5	25301	65	18J	14.8	42.3	19	15.7	9370@120		171	\$	
425/65R22.5	25304	65	20L	16.5	44.3	19	17.6	11400@120		198		
445/65R22.5	25302	65	20L	17.7	45.7	20	18.9	12300@120		220		

- Heat resistant tread compounds produce a cool-running tire.
- Six-rib tread design provides superior traction on wet roads, a smooth ride and even wear.

**Wide Base, Off-Highway, All Position**

# YOKOHAMA MY507A

## Medium Truck Radial



Tire Size	Code #	Max Speed (mph)	Ply Rating	Overall Width	Inflated Dimen.			Max Load		Tire Weight	PRICE	FET
					Overall Diameter	Tread Depth	Section Width	Single	Dual			
385/65R22.5	50751	65	18J	14.9	42.6	23	16.0	9370@120		178	\$	
425/65R22.5	50752	65	20L	16.5	44.6	23	17.9	11400@120		203		
445/65R22.5	50753	65	20L	17.7	45.7	24	18.9	12300@120		220		

**Wide Base, Off-Highway, All Position**

# YOKOHAMA TECHNICAL BREAKTHROUGHS GIVE YOU THE ADVANTAGE

Truckers today need more miles, greater retreadability, longer even wear and less maintenance cost per mile from their tires. Yokohama technology helps truckers get the most out of their tire investments.



### STRAIN ENERGY MINIMIZATION TECHNOLOGY EXTENDS CASING LIFE

As a tire rotates under load, thousands and thousands of times, the demands on the casing steel and rubber compounds are incredibly stressful. This strain energy can take the life out of tires, prematurely. Built into our newest generation of radial truck tires, our STEM-2 technology brings you more durability than you've ever experience.

STEM-2 redirects normally destructive straining and flexing forces to deliver extended performance to the life of every STEM-2 enhanced Yokohama steel radial tire.



### MAINTENANCE SAVING CONCEPT

The latest innovation in Yokohama technical leadership is an exciting concept we call MSC (Maintenance Saving Concept). MSC brings together six unique design element to make up a system of performance characteristics that significantly reduce tire maintenance time and costs, as well as truck downtime.

1. Stress Control Ribs: Decrease pressure on rib edges to greatly reduce river wear.
2. Stress Control Groove Shape: Works to reduce stone retention.
3. Stress Control Groove Sipes: Work to reduce river wear.
4. Stress Wear Control Groove: Redistributes the load on the outside rib to greatly reduce shoulder step down wear.
5. Contoured Bead Shape: Allows the tire to seat evenly against the rim for extremely high uniformity levels around the entire circumference for better tire-to-rim fit, reduced friction, smoother ride, and long, even wear.
6. Ultra-Wide Top Belt: Increases rigidity across the entire tread surface to increase the effectiveness of the stress control elements to enable them to provide long, even wear.



### MAXIMIZED CONSERVATION CONCEPT

For Fuel Savings and Heat Reduction

Yokohama leads the way in the development of new advancements in compounding technologies that now allow the tires to run longer, cooler and best of all, smoother for maximum fuel savings and reduced rolling resistance. The MC2 concept allows the modern trucker to save valuable tire resources, and to use them more efficiently.