



SOLIDEAL[®]
"THE NATURAL CHOICE"

SOLIDEAL HAULER XD44 **Industrial**



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10-16.5	10	57536	8.25	75	4718	.5	.31	.44	.86.0	\$
12-16.5	12	57537	9.75	80	6349	.5	.33	.44	107.0	

SOLIDEAL LIFEMASTER SKZ **Industrial**



Compactor Pneumatic

Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10-16.5	8	20687	8.25	60	4134	.5	.31	.37	.72.0	\$
10-16.5	10	20696	8.25	75	4718	.5	.31	.37	.73.0	
12-16.5	10	20697	9.75	64	5611	.5	.33	.37	.89.0	
12-16.5	12	20698	9.75	80	6349	.5	.33	.38	.97.0	
31X15.5-15	8	57538							.78.0	
33X15.5-16.5	14	57540	12.00	70	6944	.5		.38		
14-17.5	14	57542	10.5	80	8543	.5	.37	.48	144.0	

SOLIDEAL HAULER LOADER SKS **Industrial**



Hauler Skid Steer Loader SKS

Still the best skid steer tire made today. All natural rubber compounding along with heavy duty construction makes. Hauler sks the best performing skid tire available. Wide wall - rim guard - extra deep tread - less void to lug ratio - 3 step tread - tubeless.

Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
23X8.5-12	6	4881	7.00	50	1819	.5	.23	.16	25.0	
27X8.5-15	6	4882	7JA	44	2480	.5	.27	.12	32.0	
27X10.5-15	8	57546	8.50	59	3064	.5	.28	.20	46.0	
31X15.5-15	8	17954	13.00	44	3726	.5	.31	.28	82.0	
10-16.5(30)	8		8.25	60	4134	.5	.30	.17	52.0	
10-16.5(30)	10		8.25	75	.0	.5	.30	.17	0.0	
10-16.5	8	4883	8.25	55	3924	.5	.31	.17	54.0	
10-16.5	10	45623	8.25	75	4718	.5	.31	.17	54.0	
31.5X13-16.5	10	57551	9.75	70	5368	.5	.31	.17	67.0	
12-16.5	10		9.75	60	5357	.5	.32	.20	78.0	
12-16.5	10	4884	9.75	64	5611	.5	.32	.20	78.3	
33X15.5-16.5	14	34708	12.00	70	6944	.5	.33	.22	108.0	
14-17.5	10		10.5	55	6845	.5	.0	.48	0.0	
14-17.5	14	4885	10.5	80	8543	.5	.37	.30	115.0	
380/65-19.5(14.5-19.5) 12°			11.75	60	9193	.5	.39	.31	0.0	
15-19.5	8		11.75	40	7176	.5	.0	.31	0.0	
15-19.5	14	4886	11.75	80	11177	.5	.40	.31	146.0	
385/65-22.5(15-22.5)	12		11.75	72	12676	.5	.43	.31	170.0	
385/65-22.5(15-22.5)	16	57560	11.75	100	15520	.5	.437	.31	181.0	

SOLIDEAL SKS XTRA WALL

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
23X8.5-12	.4		7.001	.32	.1411	.5	.0	.18	.00	..\$
26X12-12	.10	.7454	10.50	.64	.3593	.5	.26	.30	.43	
10-16.5	.8	.20188	8.25	.60	.4134	.5	.30	.20	.64	
10-16.5	.10	.57565	8.25	.75	.4718	.5	.31	.20	.50.71	
12-16.5	.8	.20186	9.75	.50	.4806	.5	.33	.20	.64	
12-16.5	.10	.20185	9.75	.64	.5611	.5	.32	.20	.64	
14-17.5	.12	.57569	10.50	.69	.7826	.5	.36	.35	.116.84	

SOLIDEAL SKID STEER SKS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
5.70-12	.6	.17950	4.501	.60	.1455	.5	.22	.10	.16.0	..\$
23X8.5-12	.6	.4855	7.001	.50	.1819	.5	.22	.18	.22.0	
27X8.5-15	.6	.4856	7JA	.44	.2480	.5	.27	.17	.30.0	
10-16.5	.8	.4857	8.25	.60	.4134	.5	.30	.20	.48.0	
14-17.5	.12	.25489	10.50	.69	.7826	.5	.36	.35	.109.8	

**Skid Steer Loader
SKS**

Extra wide profile for bigger footprint and higher flotation. Extra thick sidewall gives added protection against damage and penetration. Extra deep tread makes for better traction and longer tread life. Extra thick under-tread protects against flats. Extra wide lug and less void to lug ratio - tubeless these have 100% natural rubber compounds for greater tear and cut resistance.

SOLIDEAL GRIPPER

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
12-16.5	.10	.58856	12.5	.65	.5599	.5MPH	.32.5	.23/32	.55.1	..\$

Innovative compounding and tread design technology in our ultra competitive skid steer line. Designed and manufactured according to the highest OEM standards with full North American ply ratings. Premium natural rubber compounds for enhanced cut resistance. A proven, durable tread design for long life and extra traction.

SOLIDEAL MPT / TRACTIONMATER R1 / DUMPER PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
I3										
10.5-18	.8		9 x 18	.43	.3704	.31	.0	.31	.0.0	..\$
10.5-18	.10	.57578	9 x 18	.54	.4200	.31	.35	.31	.77.0	
12.5-18	.12	.57580	11x18	.50	.4817	.31	.39	.28	.105.0	
10.5 - 20	.10	.53413	9 x 20	.54	.4442	.31	.37	.28	.72.0	
12.5 - 20	.12	.41114	11 x 20	.50	.4938	.31	.41	.30	.127.0	
14.5 - 20	.14	.57584	11 x 20	.50	.5831	.31	.44	.34	.143.0	
405/70-20	.14	.57586	13 x 20	.50	.8267	.25	.43	.34	.132.0	
405/70-24	.14	.57587	13 x 24	.50	.8818	.25	.47	.37	.154.0	
R1										
29x12.5-15	.8	.57598	10LB	.44	.0	.0	.0	.0	.0.0	
31x15.5-15	.8	.57599	13.00	.44	.3726	.5	.32	.26	.61.0	
10.0/75-15.3	.8		9 x 15.3	.44	.0	.0	.0	.28	.0.0	
11.5/80-15.3	.8		9 x 15.3	.39	.3748	.25	.34	.29	.56.0	
33X15.5-16.5	.10	.57601	12.00	.49	.6008	.5	.0	.29	.0.0	
405/70-20	.12	.57590	13 x 20	.43	.7606	.25	.0	.38	.0.0	
15.5/80-24	.14	.57593	13 x 24	.50	.9921	.25	.51	.45	.157.0	
R4										
10.0/75-15.3	.8	.20703	9 x 15.3	.44	.0	.0	.0	.28	.51.0	
11.5/80-15.3	.10	.20705	9 x 15.3	.49	.0	.0	.0	.31	.68.0	



SOLIDEAL HAULER PNEUMATIC FORKLIFT

Industrial



Hauler LT

Hauler Lt, with its natural rubber compounds, is acknowledged as the finest quality, highest performance industrial tire on the market. Hauler Lt's massive tread and wide wall rim guard give all-around protection. Hauler Lt "the original". The one every-body tries to copy is de-signed to give the longest service possible with less void to lug ratio and extra deep tread.



Portmaster



Halftrac

Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load Steer	Max Load Drive	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
LT											
5.00-8	10	4860	3.00D	143	2403	3120	6	19	11	19.0	\$
18X7-8	18	4863	4.33R	150	4079	5302	6	19	13	26.0	
6.00-9	10	4864	4.00E	122	2910	3781	6	21	14	28.0	
6.50-10	10	4865	5.00F	111	3307	4299	6	23	14	26.0	
7.00-12	14	4867	5.00S	129	4674	6074	6	27	14	40.0	
27X10-12	24	4868	8.00G	143	9370	12180	6	27	14	71.0	
7.00-15	14	4870	5.50	129	5677	7385	6	29	16	45.0	
7.50-15	14	4871	6.00	132	6173	8025	6	0	16	45.0	
8.25-15	14	4873	6.50	114	7165	9314	6	33	9	78.0	
28X9-15(8.15-15)	14	4872	7.00	129	6393	8311	6	28	16	55.0	
2.50-15	20	4875	7.50	150	8818	11464	6	29	16	77.0	
3.00-15	20	4877	8.00	136	10747	13977	6	33	20	106.0	
28X12.5-15	24	4874	9.75	143	10196	13261	6	27	16	96.0	
32X12.1-15	24	4878	9.75	143	13228	17196	6	32	20	130.0	
10.00-20	16	4879	7.50	129	11023	13228	6	43	23	177.0	
12.00-20	20	4880	8.50	143	15102	18122	6	46	23	203.0	
PORTMASTER											
12.00-20	20	37915	8.50	143	15102	18122	6	45	72	222	
12.00-20	28	57609	8.50	143	15102	18122	6	45	72	224.87	
SMOOTH											
10.00-20	16	57611	7.50	129	11023	13228	6	43		186.0	
12.00-20	20	57612	8.50	143	15102	18122	6	45		213.0	
HALFTRAC											
10.00-20	16	57614	7.50	129	11023	13228	6	43	23	183.0	
12.00-20	20	57615	8.50	143	15102	18122	6	45	23	229.0	

SOLIDEAL EXTRA DEEP PNEUMATIC FORKLIFT

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load Steer	Max Load Drive	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
5.00-8	8	4842	3.00D	118	2094	2723	6	18	9	13.0	\$
18X7-8	14	4851	4.33R	129	3197	4156	6	18	9	19.0	
18X7-8	16	57648	4.33R	143	3638	4729	6	18	9	18.0	
6.00-9	10	4843	4.00E	122	2910	3781	6	21	10	21.0	
21X8-9	14	4852	6.00E	129	4299	5589	6	21	14	29.0	
6.50-10	10	4844	5.00F	111	3307	4299	6	23	12	26.0	
6.50-10	12	57634	5.00F	129	3638	4729	6	23	12	28.0	
23X9-10	16	57652	6.50F	114	5071	6592	6	23	10	42.0	
7.00-12	12	4845	5.00S	122	4541	5908	6	27	11	37.0	
7.00-12	14	17943	5.00S	129	4674	6074	6	27	11	36.0	
23X10-12	14	17948	8.00G	118	5512	7165	6	23	10	42.0	
27X10-12	16	57654	8.00G	114	6614	8598	6	0	14	60.0	
7.00-15	14	4846	5.50	129	5677	7385	6	30	11	49.0	
7.50-15	14	4847	6.00	132	6173	8025	6	31	25	0.0	
8.25-15	12	17946	6.50	100	6614	8598	6	34	23	72.0	
8.25-15	14	4849	6.50	114	7165	9314	6	33	25	72.0	
28X9-15(8.15-15)	14	4848	7.00	129	6393	8311	6	28	24	57.0	
2.50-15	16	4853	7.50	118	7385	9601	6	29	28	74.0	
3.00-15	18	4854	8.00	114	10196	13261	6	32	30	105.0	
7.50-16	12	20682	6.00	114	6393	8311	6	32	27	57.0	
9.00-20	14	38949	7.00	129	9810	11773	6	41	25	103.0	
10.00-20	16	4850	7.50	129	11023	13228	6	42	25	117.0	

SOLIDEAL GRADER G2/L2 PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
NEW 13.00-24 TL	.12	.65451								..\$
13.00-24 TG	.12	.9554	.8.00TGx24	.43	.6008	.25	.50	.33	.161.0
14.00-24 TG	.12	.9555	.8.00TGx24	.36	.6779	.25	.52	.33	.183.0
14.00-24 TG	.16	.57662	.8.00TGx24	.79			.52	.33	.183.0

Industrial grade compounding - extra tear resistant - outstanding casing protection from thick undertreads. Full dimension sizing - excellent bruise resistance - long wearing properties.

SOLIDEAL BACKHOE PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
F3										
11L-15SL	.10	.17957	.8LBx15	.51	.2337	.31	.30	.16	.47.0\$
11L-16SL	.10	.4887	.8LBx16	.51	.2469	.31	.32	.16	.50.0
11L-16SL	.12	.57666	.8LBx16	.51	.3428	.31	.32	.16	.52.0
14.5/75-16.1SL	.10	.17958	.W11Cx16.1	.40	.4795	.9	.37	.21	.94.0
R4										
10.5/80-18	.10	.7455	.W9x18	.53	.2998	.19	.34	.26	.61.0
12.5/80-18	.12	.7456	.W9x18	.53	.5842	.19	.38	.38	.89.0
14.9-24	.8	.20702	.W13x24	.30	.0	.0	.50	.38	.0.0
14.9-24	.12	.21548	.W13x24	.41	.6393	.25	.49	.38	.151.0
16.9-24	.12	.21549	.W15Lx24	.37	.7165	.25	.51	.33	.189.0
17.5L-24	.6	.21550	.W15Lx24	.20	.0	.0	.50	.38	.0.0
17.5L-24	.10	.16769	.W15Lx24	.31	.6173	.25	.50	.38	.183.0
19.5L-24	.10	.17960	.W16Lx24	.27	.6779	.25	.52	.35	.212.0
19.5L-24	.12	.18943	.DW16Ax24	.33	.7606	.25	.52	.35	.230.0
21L-24	.12	.31137	.DW18Ax24	.31	.8543	.25	.55	.48	.260.0
16.9-28	.12	.21551	.W15Lx28	.37	.7826	.25	.56	.42	.220.0
18.4-28	.12	.21552	.W16Lx28	.36	.0	.0	.59	.49	.0.0



SOLIDEAL SLA R4

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
16.9-24	.12	.61223	.W14Lx24			A8	.50.4	.17.7	\$
17.5L-24	.12	.61236	.W14Lx24			A8	.48.9	.17.5	
19.5L-24	.10	.61237	.DW16A,W15Lx24			A8	.52.3	.19.6	
19.5L-24	.12	.61238	.W16Lx24			A8	.52.3	.19.6	
21L-24	.10	.61239	.DW18Ax24			A8	.54.4	.21	
21L-24	.12	.61240	.W18Lx24			A8	.54.4	.21	

Extremely low tread related vibrations. More Flexible carcass. Triple angle lugs. Rim Guard and sidewall protection. Unique Solideal three-stepped tread which breaks and removes mud.

SOLIDEAL COMPACTOR PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
7.50-15 NHS	.14	.4859	.6.00-15	.122	.6250	.6	.31		.56.0
8.50/90-15K	.6	.20701	.6.00G-15	.50			.30		.41.0

SOLIDEAL WHEEL LOADER PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
L2										
15.5-25	.12	.54122	12.00/1.3	.57	12346	.6	.50	.31	160.0	..\$
			12.00/1.3	.32	5842	.25	.0	.31	0.0	
			12.00/1.3	.36	7165	.31	.0	.31	0.0	
17.5-25	.12	.54123	14.00/1.5	.50	13558	.6	.53	.33	192.0	
			14.00/1.5	.29	6393	.25	.0	.33	0.0	
			14.00/1.5	.32	8047	.31	.0	.33	0.0	
17.5-25	.16	.37329	14.00/1.5	.68	16094	.6	.0	.33	223.0	
			14.00/1.5	.39	7385	.25	.0	.33	0.0	
			14.00/1.5	.43	9370	.31	.0	.33	0.0	
20.5-25	.16	.37333	17.00/2.0	.50	18188	.6	.59	.38	293.0	
			17.00/2.0	.32	8818	.25	.0	.38	0.0	
			17.00/2.0	.39	12015	.31	.0	.38	0.0	
L3										
15.5-25	.12	.54125	12.00/1.3	.57	12346	.6	.0	.33	163.0	
			12.00/1.3	.32	5842	.25	.0	.33	0.0	
			12.00/1.3	.36	7165	.31	.0	.33	0.0	
15.5-25	.16	.54126	12.00/1.3	.79	15212	.6	.0	.33	172.0	
			12.00/1.3	.39	6614	.25	.0	.33	0.0	
			12.00/1.3	.43	8818	.31	.0	.33	0.0	
17.5-25	.12	.37330	14.00/1.5	.50	13561	.6	.0	.35	262.0	
			14.00/1.5	.29	6393	.25	.0	.35	0.0	
			14.00/1.5	.32	8047	.31	.0	.35	0.0	
17.5-25	.16	.37331	14.00/1.5	.68	16094	.6	.0	.35	0.0	
			14.00/1.5	.39	7385	.25	.0	.35	0.0	
			14.00/1.5	.43	9370	.31	.0	.35	0.0	
20.5-25	.16	.37334	17.00/2.0	.50	18188	.6	.59	.40	348.0	
			17.00/2.0	.32	8818	.25	.0	.40	0.0	
			17.00/2.0	.39	12015	.31	.0	.40	0.0	
20.5-25	.20	.54128	17.00/2.0	.64	20944	.6	.60	.40	351.0	
			17.00/2.0	.46	13228	.31	.0	.40	0.0	
23.5-25	.16	.54129	19.5/2.5	.43	20944	.6	.64	.47	529.0	
			19.5/2.5	.29	10472	.25	.0	.47	0.0	
			19.5/2.5	.32	13558	.31	.0	.47	0.0	
23.5-25	.20	.54130	19.5/2.5	.54	24030	.6	.62	.47	483.0	
			19.5/2.5	.43	16094	.31	.0	.47	0.0	
26.5-25	.20	.54132	22.00/3.0	.50	29101	.6	.69	.50	617.0	
26.5-25	.20		22.00/3.0	.36	18188	.31	.0	.50	0.0	
26.5-25	.28		22.00/3.0	.68	34171	.6	.70	.50	0.0	
26.5-25	.28		22.00/3.0	.50	22046	.31	.0	.50	0.0	

SOLIDEAL EXCAVATOR PNEUMATICS

Industrial



Tire Size	Ply	Code #	Rim Width	Max PSI	Max Load	Speed	Overall Diameter	Tread Depth	Tire Weight	PRICE
10.00-20	.16	.20700	7.50-20	.122	9348	.6	.42	.33	103.0	
11.00-20	.16	.30256	8.00-20	.122			.43	.33	132.0	



COMPTON

1714 Anderson Ave.
Compton, CA 90220
Local 310-631-8200 • Fax 310-631-2503
Toll Free: 1-800-962-5222

HOUSTON

3635 Willowbend Blvd.
Houston, TX 77054
Local 713-660-6600 • Fax 713-660-9633
Toll Free: 1-800-711-3919

MIAMI

9800 NW 100 Road
Medley, FL 33178
Local 305-887-8876 • Fax 305-470-9967
Toll Free: 1-888-833-3953

PORTLAND

7515 N. Leadbetter Dr.
Portland, Oregon 97203
Local 503-285-5422 • Fax 503-240-3342
Toll Free: 1-866-977-8473

BAKERSFIELD

7600 District Blvd., Suite B
Bakersfield, CA 93313
Local 661-831-5600 • Fax 661-831-5641
Toll Free: 1-888-414-8473

SAN ANTONIO

4530 Tejasco Dr.
San Antonio, TX 78212
Local 210-212-8866 • Fax 210-212-8815
Toll Free: 1-800-666-8840

TAMPA

9110 King Palm Drive, Suite 106
Tampa FL 33619
Local 813-626-0866 • Fax 813-626-0977
Toll Free: 1-800-483-2099

CHICAGO

3710 N River Road, Suite 400
Franklin Park, IL 60131
Local 708-450-7000 • Fax 708-450-7001
Toll Free: 1-866-220-8439

UNION CITY

33375 Central Ave.
Union City, CA 94587
Local 510-489-7600 • Fax 510-489-0494
Toll Free: 1-800-447-8473

DALLAS

9500 Royal Lane, Suite 160
Irving, Texas 75063
Local 972-484-6900 • Fax 972-484-7742
Toll Free: 1-888-455-2234

ORLANDO

2222 Diversified Way
Orlando, FL 32804
Local 407-218-4600 • Fax 407-218-4601
Toll Free: 1-800-903-0014

OHIO

14801 CR 212
Findlay, OH 45840
Local 419-425-6512 • Fax 419-425-6521
Toll Free: 1-877-309-1972